

TEST CERTIFICATE

NMD61DPB048BK

PRODUCT DESCRIPTION: 48f, Direct buried, Non-metallic armoured

CONSTRUCTION: 6 position Stranded, 12f/tube, 2.0/1.4mm gel-filled tubes, Polyethylene/Nylon/ Non-metallic armoured /Polyethylene

DATE: 11 OCT 2019

TEST PROPERTY/ METHOD	SPECIFIED VALUE	AFL ACCEPTANCE CRITERIA	ACHIEVED	RESULT
Tensile Performance IEC 60794-1-21 (E1) (incl. Static Bend under tension)	5kN $r_b = 20 \times OD$	Loss variation ($\Delta\alpha$) < 0.1dB at 1550nm 0.6% fibre strain $r_b = 20 \times OD$ (296mm)	Load = 5kN $\Delta\alpha \leq 0.08dB$ <0.07% fibre strain $r_b = 230mm$	Pass
Crush (short term) IEC 60794-1-21 (E3)	2.5kN/100mm/10min $\Delta\alpha < 0.05dB$ at 1550nm	No Sheath/tube cracking $\Delta\alpha < 0.1dB$ at 1550nm	2.5kN/100mm/10min $\Delta\alpha < 0.01dB$ No damage	Pass
Crush (long term) IEC 60794-1-21 (E3)	2.5kN/100mm/120min $\Delta\alpha < 0.05dB$ at 1550nm	No Sheath/tube cracking $\Delta\alpha < 0.1dB$ at 1550nm	2.5kN/100mm/120min $\Delta\alpha < 0.01dB$ No damage	Pass
Impact IEC 60794-1-21 (E4)	1.5kg.m, 12.5mm rad anvil	No Sheath/tube cracking $\Delta\alpha < 0.1dB$ at 1550nm	1.5kg.m $\Delta\alpha < 0.07dB$ No damage	Pass
Bend IEC 60794-1-21 (E11)	$r_b = 10 \times OD$, 360° loop	No Sheath/tube cracking $\Delta\alpha < 0.1dB$ at 1550nm $r_b = 10 \times OD$ (148mm)	$r_b = 10 \times OD$ $\Delta\alpha < 0.03dB$ No damage	Pass
Water Penetration IEC 60794-1-22 (F5B)	1m head of water, 3m sample, 24hrs exposure	No water detected at sample end.	No water	Pass
Temperature Cycle IEC 60794-1-22 (F1)	2 cycles: Amb. , -40, +70, Amb.	$\Delta\alpha < 0.1dB$ average at 1550nm	$\Delta\alpha < 0.05dB/km$	Pass

Design No.	068/07	NMD6**PB0 ⁷² BK; Where ** is the fibre code and ⁷² No. of fibres up to 72
Cable No.	12565	NMD61DPB048BK

Tested By:	Attila Nagy
Verified By:	Shashini Subasinghe
Approved By:	Jim Boukouvalas