


OSP Cable Storage and Handling Guide




When storing OSP cable drums for short/long periods, please take the following guidelines into consideration:

- Select a site for storage that is level and dry, preferably indoors with a concrete surface, with no risk of falling objects, chemical spills (oil, grease, etc.) open flames and excessive heat.
- Ideally, cable drums should be stored indoors on a hard, dry surface to prevent deterioration of the drums and possible moisture damage. If Outdoor storage is necessary, the drums must be supported off the ground and covered with a suitable weatherproof material. The drum supports should be long enough to have both drum flanges supported and adequate to prevent sinking and high enough to prevent the drum from sitting in free standing water in any circumstance.
- For all OSP 'LSZH' jacketed cables storage shall be indoors. If an indoor storage facility is not available select a stable, flat surface that will be free draining. The drum must be supported off the ground and prevent the reel flanges sinking into it. It MUST be a covered space providing full protection from direct UV and rain.
- The drums must always be stored with their flanges vertical.
- All drums should be stored in such a manner to allow easy access for safe lifting and moving.
- Leave enough space between stored drums for air circulation.
- If drums are stored in a high traffic area (fork lifts frequent transit) suitable barriers should be erected to prevent damage from moving equipment.
- The bolts should be tightened at regular intervals.
- During storage, the drums should be rolled to an angle of 90° every three months.
- Drums should always be rolled in the direction indicated by the arrow(s) on the drum flanges, preventing the cable from loosening on the reel potentially causing problems during installation.
- Under no circumstance should cable drums be dropped from any height or allowed to roll uncontrolled.
- Ensure that a protective layer of UV stabilised Coreflute completely covers the entire cable when in storage.
- When only a portion of the cable is used, the open end of the cable remaining on the drum should immediately be re-sealed to prevent the entrance of moisture. Once it has been resealed, the cut end should be fixed to the inside edge of the drum flange to prevent the end from extending beyond the flanges during drum movement.
- For short term storage (Up to 4 months) timber and or steel drums are suitable. Site / customer dependant.
- For long term storage (> 4 months) steel reels should be used. To be determined by the customer placing the PO.
- When considering the drum suitability, local conditions such as humidity, temperature fluctuations, flooding etc should be considered by the customer.
- When it is required to rewind the cable on to another drum, always consider that the diameter of the new drum barrel should be at least the same size of the original drum barrel diameter.











OSP Cable Storage and Handling Guide



- Do not use the fork lift tynes to push cable drums sideways on a truck tray or the ground as damage to the flanges can result in the drum being unacceptable to customers. This could result in damage to drum flange deeming it unacceptable.
- Do not attempt to lift drums of cable without inserting the fork lift tynes fully under both flanges as the tynes can damage the cable, making it unserviceable. Do not attempt to lift drums by the flange or to lift drums into the upright (correct) position by lifting the top flanges as it may break the flange from the drum barrel. The drum will then be undeliverable. Use a length of steel pipe through the centre of the drum to provide leverage and control.

This cable has been rendered unserviceable through fork lift tyne damage.







	Lower drums gently onto the ground or transport.		Avoid impact force loadings. Never drop drums.
	Always protect cable from rubbing or damage. Adjust load or use separators.		Never let drum flanges contact cable on adjacent drums.
	Heavy drums should be chained appropriately for transit, with protection from the chain rubbers for the spindle hole in the centre of the drum. Under no circumstances are drums to be transported on their side.		Never lay drums on their side, even on top of pallets, as protruding bolts damage spools and cable.
	Always protect product, especially spools, against rope damage during tying down of load.		Never use rope directly over shrinkwrapped cable.

NOTE: When de-reeling cable ensure that the inner end of the cable is released from all attachments to the flange. Ensure the excess length on the inner end is safely managed. Secure the inner end and ensure cable end is sealed when the cable is not being de-reeled.

CAUTION

CAUTION

OSP Cable Storage and Handling Guide

	Ensure drums are restrained to restrict movement during sudden stop/starts.		When securing drums for transit, do not place ropes or chains over cable as damage can occur to the outer insulation rendering the cable unserviceable.
	Ensure cable sealing is intact so moisture cannot seep into cable. Report damage.		Avoid use of additional nails on drums or cable. Flange thicknesses vary and some customers prohibit their use.
	When placing drums on an uneven surface be prepared to check drums against rolling and chock if required.		Do not roll cable drums from the back of a delivery truck to the ground as the resulting flange damage will be unacceptable to the customer as the cable will not be able to be rolled off the drum and the drum will need to be returned.

NOTE: When de-reeling cable ensure that the inner end of the cable is released from all attachments to the flange. Ensure the excess length on the inner end is safely managed. Secure the inner end and ensure cable end is sealed when the cable is not being de-reeled.

CAUTION

CAUTION