

INDUSTRIAL & SPORTS LIGHTING

RIDE / STADIUM



TECHNICAL DESCRIPTION

High-performance stadium floodlight, 180 lm/W, IP66 and IK08, from 250 W to 2500 W (up to 450,000 lm). The reference for stadiums, large halls and event lighting.

FEATURES

180 lm/W

IP66

IK08

250-2500W

2300-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC85–305V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD3030
DRIVER	Philips Inventronics	BEAM ANGLE	30° 60° 90° 45°
MATERIAL	Aluminium (ADC12)	WORKING TEMPERATURE	-30°C ~ 50°C
IP RATING	IP66	IK RATING	IK08
LUMEN MAINTENANCE	> 90%		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Dimensions
62 00 25	projecteur Stades-180lm/w-IK08-IP66	250 W	45000	180	2300-6500K	507 × 183 × 150 mm
62 00 50	projecteur Stades-180lm/w-IK08-IP66	500 W	90000	180	2300-6500K	507 × 183 × 320 mm
62 00 75	projecteur Stades-180lm/w-IK08-IP66	750 W	135000	180	2300-6500K	507 × 183 × 490 mm

Technical data is subject to change without prior notice.

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Dimensions
62 01 00	projecteur Stades-180lm/w-IK08-IP66	1000 W	180000	180	2300-6500K	507 × 183 × 660 mm
62 01 50	projecteur Stades-180lm/w-IK08-IP66	1500 W	270000	180	2300-6500K	983 × 251 × 490 mm
62 20 00	projecteur Stades-180lm/w-IK08-IP66	2000 W	360000	180	2300-6500K	983 × 251 × 660 mm
62 25 00	projecteur Stades-180lm/w-IK08-IP66	2500 W	450000	180	2300-6500K	983 × 251 × 830 mm

Technical data is subject to change without prior notice.