

STREET & AREA LIGHTING

AZUR



TECHNICAL DESCRIPTION

Azur residential luminaire, 160 lm/W, available in five mountings: lantern, cross, bracket, lantern D and pendant. Two wattages (40 W and 100 W) for squares, residential areas and town centres. Dedicated power supply unit available.

FEATURES

160 lm/W IP66 IK08 40-100W 2300-6500K 5 mountings

TECHNICAL SPECIFICATIONS

VOLTAGE	AC85–305V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD2835 SMD3030 SMD5050
DRIVER	Philips Inventronics	BEAM ANGLE	Type I / II / III
MATERIAL	Aluminium (ADC12) + tempered glass	MOUNTING DIAMETER	60 mm
WORKING TEMPERATURE	-30°C ~ 50°C	IP RATING	IP66
IK RATING	IK10	DIMENSIONS	500 × 500 × 450 mm
LUMEN MAINTENANCE	> 90%		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
50 00 50	Lum residentie Azur Lanterne 160LM/W IP66;IK08	40 W	6400	160	2300-6500K
50 00 80	Lum residentiel Azur Lanterne 160LM/W IP66;IK08	100 W	16000	160	2300-6500K

Technical data is subject to change without prior notice.

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
50 01 50	Lum residentie Azur cross 160LM/W IP66;IK08	40 W	6400	160	2300-6500K
50 01 80	Lum residentie Azur cross 160LM/W IP66;IK08	100 W	16000	160	2300-6500K
50 02 50	Lum residentie Azur Potence 160LM/W IP66;IK08	40 W	6400	160	2300-6500K
50 02 80	Lum residentie Azur Potence 160LM/W IP66;IK08	100 W	16000	160	2300-6500K
50 03 50	Lum residentie Azur Lanterne D 160LM/W IP66;IK08	40 W	6400	160	2300-6500K
50 03 80	Lum residentie Azur Lanterne D 160LM/W IP66;IK08	100 W	16000	160	2300-6500K
50 04 50	Lum residentie Azur Suspension 160LM/W IP66;IK08	40 W	6400	160	2300-6500K
50 04 80	Lum residentie Azur Suspension 160LM/W IP66;IK08	100 W	16000	160	2300-6500K

Technical data is subject to change without prior notice.