


STREET & AREA LIGHTING

STREET PRO



TECHNICAL DESCRIPTION

SSA's flagship road luminaire: 200 lm/W, from 50 W to 200 W (up to 40,000 lm). Minimal consumption for major roads and intensive public lighting.

FEATURES

200 lm/W

50-200W

10000-40000 lm

2300-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC85–305V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD5050
DRIVER	Philips Inventronics	BEAM ANGLE	Type I / II / III
MATERIAL	Aluminium (ADC12) + tempered glass	MOUNTING DIAMETER	60 mm
WORKING TEMPERATURE	-30°C ~ 50°C	IP RATING	IP66
IK RATING	IK10	DIMENSIONS	539.7–589.7 × 205.5 × 102.8 mm
LUMEN MAINTENANCE	> 90%		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
53 00 50	Lum Routier 200lm/w	50 W	10000	200	2300-6500K
53 01 00	Lum Routier 200lm/w	100 W	20000	200	2300-6500K
53 01 50	Lum Routier 200lm/w	150 W	30000	200	2300-6500K

Technical data is subject to change without prior notice.

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
53 02 00	Lum Routier 200lm/w	200 W	40000	200	2300-6500K

Technical data is subject to change without prior notice.