

INDUSTRIAL & SPORTS LIGHTING

ROCK



TECHNICAL DESCRIPTION

Rock industrial floodlight, 170 lm/W, IP65 and IK08, from 50 W to 400 W. Versatile: facades, yards, storage areas and local sports grounds.

FEATURES

170 lm/W

IP65

IK08

50-400W

2300-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC100–265V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 50 000 h	LED CHIP TYPE	SMD3030 SMD5050
DRIVER	DOB Non-isolated	BEAM ANGLE	Type I / II / III
MATERIAL	Die-cast aluminium + glass	WORKING TEMPERATURE	-30°C ~ 50°C
IP RATING	IP65	IK RATING	IK08
LUMEN MAINTENANCE	> 90%		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Dimensions
60 00 50	projecteur Industriel 170lm/w - IK08-IP65	50 W	8500	170	2300-6500K	240 × 213 × 51.5 mm
60 00 10	projecteur Industriel 170lm/w - IK08-IP65	100 W	17000	170	2300-6500K	255 × 263 × 51.5 mm
60 00 15	projecteur Industriel 170lm/w - IK08-IP65	150 W	25500	170	2300-6500K	300 × 263 × 51.5 mm

Technical data is subject to change without prior notice.

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Dimensions
60 00 20	projecteur Industriel 170lm/w - IK08-IP65	200 W	34000	170	2300-6500K	310 × 313 × 56.5 mm
60 00 30	projecteur Industriel 170lm/w - IK08-IP65	300 W	51000	170	2300-6500K	370 × 363 × 61.5 mm
60 00 40	projecteur Industriel 170lm/w - IK08-IP65	400 W	68000	170	2300-6500K	504 × 365 × 62.9 mm

Technical data is subject to change without prior notice.