

## SOLAR LIGHTING

## RESILIGHT



## TECHNICAL DESCRIPTION

Compact residential solar garden light for gardens, driveways and estates. Integrated 25 W panel and LiFePO4 battery, adjustable warm-to-cool light.

## FEATURES

Residential

10W

1800 lm

2200-6500K

12.8V 15AH battery

## TECHNICAL SPECIFICATIONS

|                     |                             |                   |                                |
|---------------------|-----------------------------|-------------------|--------------------------------|
| LED CHIP TYPE       | SMD5054 (40 pcs)            | CRI               | ≥70                            |
| BEAM ANGLE          | 111.6°                      | LED LIFESPAN      | > 50 000 h                     |
| CHARGING TIME       | 6–10 h (sunny day)          | LIGHTING MODE     | Time + light control (100→30%) |
| MATERIAL            | Die-cast aluminium + PC     | MOUNTING DIAMETER | 76 mm                          |
| MOUNTING HEIGHT     | 3 m                         | OPTICS            | PC lens Type I/II/III/IV/V     |
| WORKING TEMPERATURE | -20°C ~ 50°C                | IP RATING         | IP65                           |
| IK RATING           | IK08                        | DIMENSIONS        | 450 × 450 × 600 mm             |
| WARRANTY            | Battery 3 yr · Product 5 yr |                   |                                |

## REFERENCES

| SSA code | Designation | Power | Flux (lm) | Efficacy (lm/W) | Colour temp. | Panel | Battery    |
|----------|-------------|-------|-----------|-----------------|--------------|-------|------------|
| 42 02 10 | Lum Solaire | 10 W  | 1800      | 180             | 2200-6500K   | 25w   | 15AH-12.8V |

Technical data is subject to change without prior notice.