

STREET & AREA LIGHTING

STREET CORE



TECHNICAL DESCRIPTION

Entry-level road luminaire at 150 lm/W, from 50 W to 200 W. The right performance/price ratio for municipal road retrofits.

FEATURES

150 lm/W

50-200W

7500-30000 lm

2300-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC100–277V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD3030
DRIVER	Philips Inventronics	BEAM ANGLE	160 × 100°
MATERIAL	Aluminium (ADC12) + PC	MOUNTING DIAMETER	60 mm
WORKING TEMPERATURE	-30°C ~ 50°C	IP RATING	IP66
IK RATING	IK08	DIMENSIONS	326 × 175 × 71 → 545 × 230 × 86 mm
LUMEN MAINTENANCE	> 90%		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
51 00 50	Lum Routier 150lm/w	50 W	7500	150	2300-6500K
51 01 00	Lum Routier 150lm/w	100 W	15000	150	2300-6500K
51 01 50	Lum Routier 150lm/w	150 W	22500	150	2300-6500K

Technical data is subject to change without prior notice.

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
51 02 00	Lum Routier 150lm/w	200 W	30000	150	2300-6500K

Technical data is subject to change without prior notice.