

INDUSTRIAL & SPORTS LIGHTING

ARÉNA



TECHNICAL DESCRIPTION

Aréna stadium floodlight, 160 lm/W, IP66 and IK08, adjustable modules from 500 W to 1500 W (up to 240,000 lm). Designed for high masts and sports venues.

FEATURES

160 lm/W

IP66

IK08

500-1500W

2200-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC85–305V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD3030 SMD5050
DRIVER	Philips Inventronics	BEAM ANGLE	30° 60° 90° 60°×120°
MATERIAL	Aluminium (ADC12) + tempered glass	WORKING TEMPERATURE	-30°C ~ 50°C
IP RATING	IP66	IK RATING	IK08
LUMEN MAINTENANCE	> 90%		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Dimensions
61 00 50	projecteur Stades-160lm/w-IK08-IP66	500 W	80000	160	2300-6500K	534 × 130 × 338 mm
61 00 10	projecteur Stades-160lm/w-IK08-IP66	1000 W	160000	160	2300-6500K	544 × 178 × 800 mm
61 00 15	projecteur Stades-160lm/w-IK08-IP66	1500 W	240000	160	2300-6500K	544 × 178 × 1179 mm

Technical data is subject to change without prior notice.