

STREET & AREA LIGHTING

MISTRAL



TECHNICAL DESCRIPTION

Mistral residential lantern, 160 lm/W, contemporary design, 50 W to 80 W. Detachable built-in driver, optional photocell and NEMA socket — designed for urban spaces and parks.

FEATURES

160 lm/W

IP66

IK08

50-80W

2300-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC90–305V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD3030 SMD5050
DRIVER	Philips Inventronics	BEAM ANGLE	Type I / II / III
MATERIAL	Aluminium (ADC12)	MOUNTING DIAMETER	60 / 76 mm
WORKING TEMPERATURE	-30°C ~ 50°C	IP RATING	IP65
IK RATING	IK08	DIMENSIONS	430 × 430 × 490.5 mm
OPTIONS	Built-in or detachable driver · NEMA · photocell		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.
50 05 50	Lum residentie Mistral Lanterne 160lm/W IP66;IK08	50 W	8000	160	2300-6500K
50 05 80	Lum residentie Mistral Lanterne 160lm/W IP66;IK08	80 W	12800	160	2300-6500K

Technical data is subject to change without prior notice.