

SOLAR LIGHTING

RESILIGHT



TECHNICAL DESCRIPTION

Compact residential solar garden light for gardens, driveways and estates. Integrated 25 W panel and LiFePO4 battery, adjustable warm-to-cool light.

FEATURES

Residential

10W

1800 lm

2200-6500K

12.8V 15AH battery

TECHNICAL SPECIFICATIONS

LED CHIP TYPE	SMD5054 (40 pcs)	CRI	≥70
BEAM ANGLE	111.6°	LED LIFESPAN	> 50 000 h
CHARGING TIME	6–10 h (sunny day)	LIGHTING MODE	Time + light control (100→30%)
MATERIAL	Die-cast aluminium + PC	MOUNTING DIAMETER	76 mm
MOUNTING HEIGHT	3 m	OPTICS	PC lens Type I/II/III/IV/V
WORKING TEMPERATURE	-20°C ~ 50°C	IP RATING	IP65
IK RATING	IK08	DIMENSIONS	450 × 450 × 600 mm
WARRANTY	Battery 3 yr · Product 5 yr		

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Panel	Battery
42 02 10	Lum Solaire	10 W	1800	180	2200-6500K	25w	15AH-12.8V

Technical data is subject to change without prior notice.