

STREET & AREA LIGHTING

STREET PLUS



TECHNICAL DESCRIPTION

Mid-range road luminaire at 170 lm/W, 50 W to 200 W. Higher efficacy and refined road optics for main thoroughfares.

FEATURES

170 lm/W

50-200W

8500-34000 lm

2300-6500K

TECHNICAL SPECIFICATIONS

VOLTAGE	AC85–305V	FREQUENCY	50/60 Hz
LED LIFESPAN	> 100 000 h	LED CHIP TYPE	SMD3030 SMD5050
DRIVER	Philips Inventronics	BEAM ANGLE	Type I / II / III
MATERIAL	Aluminium (ADC12) + tempered glass	MOUNTING DIAMETER	60 mm
WORKING TEMPERATURE	-30°C ~ 50°C	IP RATING	IP66
IK RATING	IK08	LUMEN MAINTENANCE	> 90%

REFERENCES

SSA code	Designation	Power	Flux (lm)	Efficacy (lm/W)	Colour temp.	Dimensions
52 00 50	Lum Routier 170lm/w	50 W	8500	170	2300-6500K	179 × 510 × 100 mm
52 01 00	Lum Routier 170lm/w	100 W	17000	170	2300-6500K	230 × 584 × 100 mm
52 01 50	Lum Routier 170lm/w	150 W	25500	170	2300-6500K	230 × 635 × 100 mm
52 02 00	Lum Routier 170lm/w	200 W	34000	170	2300-6500K	288 × 737 × 100 mm

Technical data is subject to change without prior notice.