

Shallow Well JET PUMPS



Applications

- Clear water supply to overhead tanks of Building, Apartments, Gardening, Hotels, Small Farms, Hospital etc.

Features And Specifications

- CED Coated Pump Components
- Powder Coated Motor Body
- High quality mechanical seal for long life
- In-Built Thermal Overload Protection
- TEFC Motor with Class-F Insulation



Cat ref	Frame	POWER		Pipe Size	Total Head in Meters									
					10	15	20	25	30	32	34	36	38	40
		kW	HP	mm	Discharge in Litre Per Hour									
CGDSW050C / CGDSW050CN	71	0.37	0.5	25 X 25	3100	3000	2400	1600	800	430				
CGDSW050S / CGDSW050SN	71	0.37	0.5	25 X 25	3100	3000	2400	1600	800	430				
CGDSW100C / CGDSW100CN	71	0.75	1	25 X 25			3000	2700	2100	1800	1450	1100	700	
CGDSW100S / CGDSW100SN	71	0.75	1	25 X 25			3000	2700	2100	1800	1450	1100	700	
CGDSW1080C / CGDSW1080CN	80	0.75	1	25 X 25			3400	2900	2200	1900	1600	1300	1000	700

Centrifugal Jet Pump



Applications

- High Rise Buildings, Small Farm House, Hospitals, Gardening &Flats etc.

Features And Specifications

- CED Coated Pump Components
- Supply 1Ph 230V, 50HZ
- High Suction Head & Ease of Installation.
- Twin Type design suitable for 4” & above bore wells.
- Provided Brass Jet Assembly.



Cat Ref	kW/HP	No. Of Stage	Operating pressure (Kg/cm2)	Pipe Connection (mm) Suction X Pressure X Delivery	Discharge (LPH)	800	600	400	280	150
CGCJV10T2	0.75 / 1.00	2	1.8	32 x 25 x 25	DLWL Head (M)	30	35	40	45	50

Registered Office:
CG Power and Industrial Solutions Limited
CG House, 6th Floor, Dr. Annie Besant Road, Worli,
Mumbai 400 030, India.
Contact: +91 22 2423 7700 | Website: www.cgglobal.com

Manufactured By:
CG Power and Industrial Solutions Limited
Commercial Motors Division, Plot No: 196-198, Kundaim Industrial Estate,
Ponda 403 115, Goa, India. | Contact: 0832-3983250
For Enquiry: cgcp.care@cgglobal.com

All India Customer Care Toll-Free No: 1800-267-0505