

HIGH FLOW

JSE/JSE1HF SERIES

SELF PRIMING SHALLOW WELL JET PUMP



JSE2, JSE1



JSE1HF

Features:

- Motor body: High quality aluminum extruded
- 50 Hz single phase AC power supply
- In-built thermal overload protector (T.O.P)
- Motor Insulation Class F
- CED coated cast iron hydraulic parts for corrosion free performance
- Pump Casing: Cast iron FG 200

| Model | Power | | Pipe Size (Suc x Del) | Total Head in metre | | | | | | | | | | | | |
|--------|---------|---------|--------------------------|-----------------------------|------|------|------|------|------|------|------|------|------|------|------|------|
| | | | | 6 m | 9 m | 12 m | 15 m | 18 m | 21 m | 24 m | 27 m | 30 m | 33 m | 36 m | 38 m | 40 m |
| | kW | HP | mm | Discharge in Litre per Hour | | | | | | | | | | | | |
| JSE2 | 0.37 kW | 0.50 HP | 25 mm x 25 mm | 3000 | 2910 | 2830 | 2750 | 2670 | 2150 | 1650 | 1090 | 500 | | | | |
| JSE1 | 0.75 kW | 1.00 HP | 25 mm x 25 mm | | | 2850 | 2770 | 2690 | 2600 | 2490 | 2150 | 1760 | 1290 | 600 | | |
| JSE1HF | 0.75 kW | 1.00 HP | 25 mm x 25 mm | | | | | 2850 | 2780 | 2700 | 2600 | 2300 | 1750 | 1150 | 750 | 400 |