

HIGH FLOW

JET PUMP

SELF PRIMING DEEP WELL JET PUMP



Features:

- Motor body: High quality aluminum extruded
- 50 Hz single phase AC power supply
- In-built thermal overload protector (T.O.P.)
- Motor Insulation Class F
- CED coated cast iron hydraulic parts for corrosion free performance
- Pump Casing: Cast iron FG 200

Model	Min. Bore-well size (mm)	Pipe Size			Minimum Operating Pressure in kg / cm ²	Power		Total Head in metre															
								9 m	12 m	15 m	18 m	21 m	24 m	27 m	30 m	33 m	36 m	39 m	40 m	42 m	45 m	48 m	51 m
		Suc.	Pres.	Dis.		Discharge in Litre per Hour																	
BWJ12T	100 mm	32 mm	25 mm	25 mm	1.8 kg / cm ²	0.75 kW	1.0 HP			1360	1330	1275	1260	1160	1035	930	810	700	660	565	470	400	230
BWJ11T	100 mm	32 mm	25 mm	25 mm	1.6 kg / cm ²	0.75 kW	1.0 HP	1800	1740	1640	1450	1265	1070	880	760	570	470	370	320				
BWJ11P	80 mm	40 mm	32 mm	25 mm	1.6 kg / cm ²	0.75 kW	1.0 HP	2100	2020	1740	1320	900	640	450	250								