REFINED FREE FLOW IODIZED SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99%
3	MOISTURE	MAX.0.5%
4	WATER INSOLUBLE	MAX. 0.5%
5	IODINE (AS I_2) AT PRODUCTION LEVEL	MIN. 20 PPM OR AS PER PARTY REQUIREMENT

MICROFINE SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 106 MICRON SIEVE	100%
2	SODIUM CHLORIDE (AS NaCl)	Min. 98%
3	MOISTURE	MAX.0.7%
4	WATER INSOLUBLE	MAX. 0.8%
5	IODINE (AS I_2) AT PRODUCTION LEVEL	MIN. 20 PPM

SUPER FINE SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 300 MICRON SIEVE	MIN.99%
2	SODIUM CHLORIDE (AS NaCl)	Min. 98.5%
3	MOISTURE	MAX.0.8%
4	WATER INSOLUBLE	MAX. 0.5%
5	IODINE (AS I_2) AT PRODUCTION LEVEL	MIN. 20 PPM

30 MESH (500 MICRON) FREE FLOW IODIZED SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 500 MICRON SIEVE	MIN. 99%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99%
3	MOISTURE	MAX.0.5%
4	WATER INSOLUBLE	MAX. 0.5%
5	IODINE (AS I_2) AT PRODUCTION LEVEL	MIN. 20 PPM

40 MESH (425 MICRON) FREE FLOW IODIZED SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 400 MICRON SIEVE	MIN. 99%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99%
3	MOISTURE	MAX.0.5%
4	WATER INSOLUBLE	MAX. 0.5%
5	IODINE (AS I_2) AT PRODUCTION LEVEL	MIN. 20 PPM

LOW HARDNESS 50 PPM SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99.65%
3	MOISTURE	MAX.0.25%
4	WATER INSOLUBLE	MAX. 0.03%

LOW HARDNESS 80 PPM SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99.6%
3	MOISTURE	MAX.0.25%
4	WATER INSOLUBLE	MAX. 0.03%

LOW HARDNESS 120 PPM SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99.55%
3	MOISTURE	MAX.0.25%
4	WATER INSOLUBLE	MAX. 0.03%

LOW HARDNESS 150 PPM SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99.5%
3	MOISTURE	MAX.0.3%
4	WATER INSOLUBLE	MAX. 0.04%

LOW HARDNESS 200 PPM SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99.4%
3	MOISTURE	MAX.0.5%
4	WATER INSOLUBLE	MAX. 0.05%

MEDIUM 1ST SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 99.0%
3	MOISTURE	MAX.1.0%
4	WATER INSOLUBLE	MAX. 0.1%

MEDIUM 2ND SALT

SR.NO.	PARAMETER	STANDARD
1	PASSING THROUGH 850 MICRON SIEVE	MIN. 98%
2	SODIUM CHLORIDE (AS NaCl)	Min. 98.0%
3	MOISTURE	MAX.1.0%
4	WATER INSOLUBLE	MAX. 0.5%