







CHAROTAR UNIVERSITY OF SCIENCE AND TECHNOLOGY (CHARUSAT)
FACULTY OF MANAGEMENT STUDIES (FMS)
INDUKAKA IPCOWALA INSTITUTE OF MANAGEMENT (I²IM)

Recording & Streaming Solution | Presentation Switching & Display Solution @ I²IM

Sr. No	PARTICULARS	QTY	Visual Image	Visual Image with Installed Location
A	RECORDING & STREAMING SOLUTION			
1	Lumens VC-B20U High Definition Pan-Tilt-Zoom Videoconference Camera <ul style="list-style-type: none"> Pan-Tilt-Zoom Camera, Easy integration with various videoconferencing software Equipped with a Sony 1/2.8 inch image sensor USB 3.0 Plug and Play and compatible with Windows, Linux, MAC OSX, Chrome OS Full HD 1080p high definition signal output format with a high frame rate of 60 Frames per second 5x Optical zoom is applicable for medium size conference rooms 	1		
2	USB & BLUETOOTH CONFERENCE PHONE YVC-1000/1000MS <ul style="list-style-type: none"> Separate microphone and speaker units for flexibility during audio, web, and video conferencing. Designed to support 2 external speakers and 5 daisy-chained microphones Scalable solution for accommodating larger meeting rooms and additional participants. Adaptive echo cancellation and human voice activity detection (HVAD) minimize background noise, facilitating natural, stress-free conversation during every call. 	1		

3	<p>Lumens VC-A50P 20x 1080p IP/SDI/HDMI PTZ Camera</p> <ul style="list-style-type: none"> • Simultaneous 1080p60 IP, SDI, HDMI Out • IP Live Broadcast with <120ms Latency • 20x Optical Zoom, 120° H/V Rotation • MJPEG/H.264 SVC Compression 	1		
4	<p>Mini Scaler Switcher with 5 video inputs MP SC 5TDS</p> <ul style="list-style-type: none"> • Compliant with HDMI1.4& HDCP2.2 • Supports video source auto-switching function. • Output resolutions selectable to assure preferred output, and supports various output resolutions. • MIC port supports balance/unbalance signal, suppress the external noise effectively. • 3-level MIC input, supports condenser microphone, dynamic microphone and wireless microphone. • Controllable via buttons, IR remote, RS232 & Web-based GUI Powerful OSD function 	1		

B	PRESENTATION SWITCHING & DISPLAY SOLUTION			
1	<p>Lumens Documens Presenter/Visualizer PC 193</p> <ul style="list-style-type: none"> • Full HD 1080p output resolution with 30fps. • 20 times variable zoom ratio (10x optical zoom with 2x sensor zoom) • VGA input/output, HDMI input/output • Built-in microphone • One-touch synchronous audio/video recording • Compatible with USB flash drives, expandable to 4TB • Jointless, highly flexible gooseneck • Plug & Play and compatible with all major whiteboard brands • Unique image optimization auto-tune button • Innovative built-in power supply • Rigid Lens provides protection from abnormal operation 	1		
2	<p>Viewsonic Multimedia Full HD Projector Model : PR08530HD 5200 ANSI Lumens</p> <ul style="list-style-type: none"> • Full HD 1080P Resolution • 5000:1 Contrast Ratio • 1.07 - 1.71 throw ratio • Unique "Flex-In" design flexible integration • Top cover design for easy dongle and lamp access • PortAll® compartment for wireless dongle 	1	