
Websource Social Login: user guide

Version 1.0.0: free PrestaShop module, AFL-3.0 licence, by Websource.

1. Overview

Websource Social Login lets your customers sign in and create their account in one click with **Google, Facebook, X (Twitter), LinkedIn, Microsoft, Apple and GitHub**.

- Sign-in **and automatic registration**: the customer account is created from the network profile (ID, first name, last name, email).
- No external library: cURL and native PHP (OAuth 2.0 / OpenID Connect, PKCE, id_token validation).
- **Account-takeover protection**: accounts are never merged automatically; an email the network has not verified is confirmed by link.
- One settings card per network with a built-in **step-by-step guide** (English and French), the callback URL to copy and a configuration test.
- Customisable buttons (3 styles, icon grid, colours, shapes) shown where you want: login, registration, checkout, header, wishlist.
- GDPR: minimal data, exported and erased with the customer account.



How a sign-in works

1. The customer clicks "Continue with Google" (or another network).
2. When returning from the network:
    - social account already linked: the customer is **signed in**;

    - **verified** email and existing customer: the customer **enters their password** to link both accounts (never merged automatically);
    - verified and unknown email: the **customer is created** (strong random password, default group, newsletter and partner offers unchecked) and signed in;
    - **unverified** email (e.g. Microsoft) or **missing** email (e.g. X): the customer enters an email and receives a **confirmation link** (valid for 1 hour, to open in the same browser).
3. In "My account > Social connections" the customer links or unlinks a network.

2. Requirements

Item	Requirement
PrestaShop	8.x (compatible from 1.7.7)
PHP	7.3 or higher (`curl` , `json` , `openssl` extensions)
HTTPS	**mandatory**: networks refuse an `http://` callback URL (Shop Parameters > Traffic & SEO > Enable SSL on all pages)
Developer accounts	a free account with each network you enable
Firewall	your server must be able to reach the networks over outbound HTTPS (cURL)

You do not have to enable all seven networks: enable those your customers use.

3. Installation

From the zip (recommended)

1. Download `websourcesociallogin-1.0.0.zip` (module page on websource.fr or the repository's "Releases" page). To check it, compare with the published SHA-256: `sha256sum websourcesociallogin-1.0.0.zip` .
2. Back office > **Modules > Module Manager > Upload a module**, pick the zip.
3. Click **Configure** when the installation is done.

From GitHub

```
 cd modules/
git clone https://github.com/Websource-fr/websourcesociallogin.git
cd ..
php bin/console prestashop:module install websourcesociallogin
```

The repository also contains `docs/` and `tests/` (not needed in production). The `vendor/` folder is included: no Composer command is required.

Updating

Replace the module folder (or upload the new zip): PrestaShop runs the upgrade scripts. Your settings are kept.

4. General configuration


Back office > Modules > Websource Social Login > **Configure**. The screen has four parts: **Networks**, **Appearance and**

locations, **Texts and GDPR**, **Help**. Settings are **per shop** (multistore: choose the shop context).

For each network (see section 5):

Field	Purpose
Enable	network switch
Client ID / Client Secret	given by the network; the secret is **encrypted** in the database and never sent back to the page ("•••• saved"); left empty, it is kept
Requested scopes	permissions requested; the default fits almost every case
Position	display order (1 = first)
Callback URL	exact address to paste at the network, with a **Copy** button
Test the configuration	checks the filled fields, the https callback URL, the scopes and the activation
Status	*Active*, *Configured*, *Incomplete*, *Not configured*

A network only shows on the storefront when it is enabled AND complete.



4 Create the OAuth client ID

▸ Menu ☰ > APIs & Services > Credentials > + Create credentials > OAuth client ID

Application type: **Web application**. In **Authorized redirect URIs**, paste the address below exactly (https, no spaces, no extra trailing "/").

Application type	Web application
Name	Store login
Authorized JavaScript origins	leave empty (not needed)
Authorized redirect URIs	`https://ma-boutique.example/fr/module/websourcesociallogin/callback` Copy

5 Copy the client ID and client secret into the module

6 Move to production

Requested scopes: `openid email profile`. The module receives: Google identifier (sub), email, email verification status, first name, last name. Nothing else.

Common errors and fixes

Error 400: redirect_uri_mismatch
The redirect URI entered in Google is not strictly identical to `https://ma-boutique.example/fr/module/websourcesociallogin/callback` Copy.
Check https, the domain name (with or without www) and any extra trailing "/". Changes may take a few minutes to take effect.

Error 403: access_denied / "App has not completed the Google verification process"
The app is still in Testing mode and your account is not among the test users: add it, or publish the app (step 6).

Error 401: invalid_client
The client ID or client secret is incorrect or has been regenerated. Paste them again from the Credentials page.

"Google hasn't verified this app"
Expected if you request sensitive scopes. Stick to the three scopes from step 3.

Error 400: invalid_request ("Google policies prohibit...")
A redirect URI is not https, or the domain is not declared in the consent screen.

Official links : Google credentials console · Google OpenID Connect documentation

5. Network guides

Common principle: (1) create an application at the network, (2) register the **callback URL** shown by the module there (it is specific to your shop; in the examples below: `https://your-shop.example/en/module/websourcesociallogin/callback`), (3) copy the ID and secret into the module, (4) enable, save, test, (5) **publish the application** at the network: while it is in test or development mode, only your test accounts can sign in.

These guides are the ones from the settings screen (Networks tab, "Step-by-step guide"), which show your own callback URL with a Copy button. Network interfaces change: if something differs, follow the step titles and the official links.

1. Google

Google uses OpenID Connect: the module validates the id_token signature and only accepts the email if it is verified by Google. Allow about 10 minutes. No cost.

- **Console** : Google Cloud Console
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Create (or select) a Google Cloud project

Where : console.cloud.google.com > project picker (top bar) > New project

Sign in with your company's Google account. Click the project picker, then **New project**. Give it your store's name and confirm.

Step 2. Configure the OAuth consent screen

Where : Menu ☰ > APIs & Services > OAuth consent screen (or "Google Auth Platform > Branding")

This is the window your customers see when signing in. Choose the **External** user type.

Fields to fill in	
App name	your store's name
User support email	an address you actually read
Authorized domains	your-shop.example
Application privacy policy link	https://your-shop.example/ (your "privacy policy" page)
Developer contact information	your email

Step 3. Declare the permissions (scopes)

Where : Consent screen > Data Access (Scopes) > Add or remove scopes

Add only the three "non-sensitive" scopes: `openid`, `.../auth/userinfo.email` and `.../auth/userinfo.profile`. They do not trigger an in-depth review by Google.

Step 4. Create the OAuth client ID

Where : Menu ☰ > APIs & Services > Credentials > + Create credentials > OAuth client ID

Application type: **Web application**. In **Authorized redirect URIs**, paste the address below exactly (https, no spaces, no extra trailing "/").

Fields to fill in	
Application type	Web application
Name	Store login
Authorized JavaScript origins	leave empty (not needed)
Authorized redirect URIs	`https://your-shop.example/en/module/websourcesociallogin/callback`

Step 5. Copy the client ID and client secret into the module

Where : "OAuth client created" dialog > Client ID + Client secret

Copy the **Client ID** (ends with `.apps.googleusercontent.com`) and the **Client secret**, paste them into this module's fields, enable Google, then save. The secret is never displayed in clear text afterwards.

Step 6. Move to production

Where : Consent screen > Publishing status > Publish app

While the app is in **Testing**, only the "test users" you list (100 maximum) can sign in, and their authorization expires after 7 days. Click **Publish app** (status "In production"). With only the non-sensitive scopes above, no verification by Google is required.

Permissions (scopes) : Requested scopes: `. The module receives: Google identifier (sub), email, email verification status, first name, last name. Nothing else.

Common errors

- **Error 400: redirect_uri_mismatch** : The redirect URI entered in Google is not strictly identical to `https://your-shop.example/`

`en/module/websourcesociallogin/callback`. Check https, the domain name (with or without www) and any extra trailing "/". Changes may take a few minutes to take effect.

- **Error 403: access_denied** / **"App has not completed the Google verification process"** : The app is still in Testing mode and your account is not among the test users: add it, or publish the app (step 6).
- **Error 401: invalid_client** : The client ID or client secret is incorrect or has been regenerated. Paste them again from the Credentials page.
- **"Google hasn't verified this app"** : Expected if you request sensitive scopes. Stick to the three scopes from step 3.
- **Error 400: invalid_request ("Google policies prohibit...")** : A redirect URI is not https, or the domain is not declared in the consent screen.

Official links : Google credentials console · Google OpenID Connect documentation

2. Facebook

Facebook Login (Meta). The `public_profile` and `email` permissions are granted by default, without app review. Allow about 15 minutes. Free.

- **Console** : Meta for Developers
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Create a Meta app

Where : developers.facebook.com > My Apps > Create App

Sign in with a Facebook account (which becomes a "developer account"). Click **Create App**, enter your store's name and your email. For the use case, choose **Authenticate and request data from users with Facebook Login**. App type: "Consumer" or "Other", depending on the wizard.

Step 2. Fill in the basic information

Where : App settings > Basic

Fill in what is required to go Live, then copy the **App ID** and the **App secret** ("Show" button, your Facebook password is requested).

Fields to fill in	
App domains	your-shop.example
Privacy Policy URL	your privacy policy page (required)
Terms of Service URL	your terms and conditions page (recommended)
App icon (1024 x 1024)	your logo
Category	Shopping / Commerce

Step 3. Configure Facebook Login

Where : Dashboard > Use cases > Facebook Login > Customize > Settings (or Products > Facebook Login > Settings)

Enable **Client OAuth login** and **Web OAuth login**, **Enforce HTTPS** and **Strict Mode** for redirect URIs, then paste the address below.

Fields to fill in	
Valid OAuth Redirect URIs	`https://your-shop.example/en/module/websourcesociallogin/callback`

Step 4. Check the permissions

Where : Use cases > Facebook Login > Permissions and features

Make sure `public_profile` and `email` are set to "Standard access" (they are by default). No app review is needed for these two.

Step 5. Paste the ID and secret into the module

Where : This module > Facebook

App ID = "Client ID", App secret = "Client Secret". Enable Facebook and save.

Step 6. Switch the app to Live mode

Where : Banner at the top of the dashboard > "App Mode": Development → Live

In **Development** mode, only the app's administrators, developers and testers can sign in. Switch to**Live** once the privacy policy and category are filled in. "Business verification" is only required for advanced access, not for public_profile + email.

Permissions (scopes) : Requested permissions: `. The module receives: Facebook identifier (id), first name, last name and email if there is one. Facebook only returns confirmed emails.

Common errors

- **"URL Blocked: This redirect failed"** / **redirect_uri is not whitelisted**: The URI entered in "Valid OAuth Redirect URIs" differs from `https://your-shop.example/en/module/websourcesociallogin/callback` . Copy it with the button, enable Strict Mode and try again.
- **"Feature Unavailable"** / **"App not active"** : The app is in Development mode and your account has no role on it. Add it under App roles, or switch to Live (step 6).
- **"Can't load URL: The domain of this URL isn't included in the app's domains"** : Add your-shop.example under Settings > Basic > App domains.
- **No email received** : The customer has no confirmed email on Facebook, or they unchecked the permission. The module then asks them to enter their email, which they confirm via a link.
- **Invalid client_secret** / **Error validating client secret** : The app secret was regenerated or copied incorrectly: paste it again.

Official links : My Meta apps · Facebook Login documentation

3. X (Twitter)

X (formerly Twitter): OAuth 2.0 with PKCE, "confidential client" application type. The email is only provided if your app is allowed to access it (scope `users.email`); otherwise the module will ask the customer for it. X API plans and quotas change over time: check them on the portal.

- **Console** : X Developer Portal
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Open an X developer account

Where : developer.x.com > Developer Portal

Sign in with your company's X account and accept the developer agreement (describe the use: "signing in my store's customers with their X account").

Step 2. Create a Project and an App

Where : Developer Portal > Projects & Apps > + Add Project (then Add App)

The app must be attached to a**Project** (otherwise the API responds "client-not-enrolled").

Step 3. Enable user authentication (OAuth 2.0)

Where : Your App > Settings > User authentication settings > Set up

This is where sign-in is configured.

Fields to fill in	
App permissions	Read (read-only is enough)
Request email from users	tick if available (requires the two URLs below)
Type of App	Web App, Automated App or Bot (= Confidential client)
Callback URI / Redirect URL	`https://your-shop.example/en/module/websourcesociallogin/callback`
Website URL	https://your-shop.example
Terms of service / Privacy policy	URLs of your terms and conditions and your privacy policy

Step 4. Retrieve the Client ID and Client Secret

Where : Your App > Keys and tokens > OAuth 2.0 Client ID and Client Secret

Click **Generate** (or Regenerate). The **Client Secret is only displayed once**: copy it immediately. Do not use "API Key / API Secret" or the "Bearer Token": those are other mechanisms (OAuth 1.0a).

Step 5. Choose the scopes

Where : This module > X > Scopes

Default: `users.read tweet.read users.email`. If X responds "invalid_scope", remove `users.email`: sign-in will work, and the module will ask the customer for their email.

Step 6. Paste the credentials into the module

Where : This module > X

Client ID, Client Secret, enable X, then save.

Step 7. Going live

Where : Developer Portal > your App > Settings

X has no "development / live" mode: the app is usable as soon as it is created. Do check the access level (Free, Basic...) and its request quotas, though: a high-traffic store may exceed the limits of a free tier.

Permissions (scopes) : Requested scopes: `. The module receives: X identifier (id), display name and, if allowed, the confirmed email (confirmed_email).

Common errors

- **"Something went wrong. You weren't able to give access to the App"** : The callback URL registered in X differs from `https://your-shop.example/en/module/websourcesociallogin/callback` (https, domain, trailing "/"). Fix it in User authentication settings.
- **invalid_scope** : The `users.email` scope is not allowed for your app: remove it from the module's scopes.
- **client-not-enrolled** / **403** : The App is not in a Project, or your access level does not include the /2/users/me endpoint.
- **429 Too Many Requests** : X plan quota exceeded: wait or change plan.
- **No email received** : Expected if the email is not allowed or is not confirmed on X: the customer enters their email and confirms it via a link.

Official links : X Developer Portal · OAuth 2.0 documentation (X)

4. LinkedIn

LinkedIn via the "Sign In with LinkedIn using OpenID Connect" product (standard OpenID Connect). A LinkedIn company Page is required to create the app. Allow about 10 minutes. Free.

- **Console** : LinkedIn Developer Portal
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Create the app

Where : linkedin.com/developers/apps > Create app

Fill in the fields; the LinkedIn Page must belong to your company (you must be an administrator of it).

Fields to fill in	
App name	your store's name
LinkedIn Page	your company's LinkedIn Page
Privacy policy URL	your privacy policy
App logo	your logo (minimum 100×100 px)

Step 2. Add the "Sign In with LinkedIn using OpenID Connect" product

Where : Your app > Products tab

Click **Request access** next to "Sign In with LinkedIn using OpenID Connect" (access is granted immediately). Without this product, LinkedIn responds "unauthorized_scope_error".

Step 3. Declare the redirect URL

Where : Your app > Auth tab > OAuth 2.0 settings > Authorized redirect URLs for your app

Click the pencil, **Add redirect URL**, paste the address below, then Update.

Fields to fill in	
Authorized redirect URLs	`https://your-shop.example/en/module/websourcesociallogin/callback`

Step 4. Copy the Client ID and Client Secret

Where : Your app > Auth tab > Application credentials

Copy the **Client ID** and the **Primary Client Secret**, paste them into this module, enable LinkedIn, then save.

Step 5. Verify the app

Where : Your app > Settings tab > Verify

Click **Verify**: LinkedIn generates a link that the Page administrator must approve. An unverified app may display a warning to customers. There is no separate "live" mode: the app works as soon as the product is added.

Permissions (scopes) : Requested scopes: ` (openid, profile, email). The module receives: LinkedIn identifier (sub), first name, last name, email and its verification status.

Common errors

- **redirect_uri doesn't match** / **Bummer, something went wrong** : The URL registered in the Auth tab differs from `https://your-shop.example/en/module/websourcesociallogin/callback` . It must be identical character for character.
- **unauthorized_scope_error** / **scope not authorized** : The "Sign In with LinkedIn using OpenID Connect" product has not been added (Products tab): add it.

- **invalid_client_id** / **invalid_client_secret** : Copy the Client ID and the Primary Client Secret again from the Auth tab (not the Page identifier).
- **No email (or unverified email)** : The member has no confirmed email: the module asks for their email and confirms it via a link.

Official links : My LinkedIn apps · Sign In with LinkedIn documentation (OpenID Connect)

5. Microsoft

Microsoft Entra ID (work or school accounts, and personal Outlook, Hotmail and Xbox accounts). Important: Microsoft does not guarantee that the email of a work account belongs to its holder; the module therefore only treats it as verified if Microsoft attests it (`xms_edov` claim) and otherwise asks for an email confirmation.

- **Console** : Microsoft Entra admin center
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Register an application

Where : entra.microsoft.com > Identity > Applications > App registrations > + New registration

You need an Azure/Entra account (a free Microsoft account is enough to create the tenant).

Fields to fill in	
Name	your store's name
Supported account types	Accounts in any organizational directory (Any Microsoft Entra ID tenant - Multitenant) and personal Microsoft accounts (e.g. Skype, Xbox)
Redirect URI - platform	Web
Redirect URI	`https://your-shop.example/en/module/websourcesociallogin/callback`

Step 2. Note the Application (client) ID

Where : Your registration > Overview

Copy the **Application (client) ID**: this is the Client ID. The module's "Tenant" field stays on `common` (work and personal accounts). Use `consumers` for personal accounts only, `organizations` for work accounts only, or the Directory (tenant) ID for a single directory.

Step 3. Create a client secret

Where : Certificates & secrets > Client secrets > + New client secret

Choose a duration (24 months maximum), then immediately copy the **Value** column (not the "Secret ID"). It will not be displayed again. **Note the expiration date**: when it expires, sign-in will stop working until you create a new secret.

Step 4. Check the permissions

Where : API permissions

Microsoft Graph, delegated permissions: `openid` , `profile` , `email` (and User.Read by default). No admin consent is required for these permissions.

Step 5. Add optional claims (recommended)

Where : Token configuration > + Add optional claim > ID

Add `email` , `given_name` , `family_name` and, if offered, `xms_edov` (email domain verified). Agree to turn on the Graph "email"

permission if Entra offers it.

Step 6. Branding and going live

Where : Branding & properties

Fill in the logo, the terms of service and privacy statement URLs, and if possible**publisher verification** (removes the "unverified" label on the consent screen). There is no "test" mode to leave: the app is usable as soon as it is registered. In some organizations, an administrator must approve the app for their users.

Permissions (scopes) : Requested scopes: `. The module receives: identifier (tenant + object), name, email (preferred: email claim).

Common errors

- **AADSTS50011: The reply URL does not match** : The registration's redirect URI ("Web" platform) differs from `https://your-shop.example/en/module/websourcesociallogin/callback` . Fix it under Authentication.
- **AADSTS7000215: Invalid client secret** : You copied the "Secret ID" instead of the **Value**, or the secret has expired: create a new one.
- **AADSTS700016** / **AADSTS50020: Application not found in the tenant** : The registration's account type or the module's "Tenant" field do not match (e.g. personal account with the "organizations" tenant).
- **AADSTS65001: Consent required** : An administrator of the customer's organization must approve the app, or the customer must accept the request.
- **An email is requested again from the customer**: Expected: Microsoft does not attest ownership of the email (protection against the nOAuth attack). Adding the `xms_edov` claim (step 5) avoids this step when Microsoft provides it.

Official links : Entra app registrations · Authorization code flow documentation

6. Apple

Sign in with Apple: the most technical of the networks. It requires the Apple Developer Program (99 USD/year), a Services ID, a `.p8` private key and an HTTPS address. The module generates the "client secret" (an ES256-signed JWT) itself on each sign-in from your key: you do not have to renew it every 6 months. Apple may hide the customer's email (relay address @privaterelay.appleid.com).

- **Console** : Apple Developer
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Join the Apple Developer Program

Where : developer.apple.com/programs > Enroll

Membership is paid (99 USD/year) and can take 1 to 2 days for a company (D-U-N-S number).

Step 2. Create an App ID with "Sign in with Apple"

Where : Certificates, Identifiers & Profiles > Identifiers > + > App IDs > App

Description and Bundle ID (e.g. `com.yourstore.web`). Under Capabilities, tick **Sign in with Apple**, then Continue > Register. This App ID serves as the "Primary App ID".

Step 3. Create a Services ID (= Client ID)

Where : Identifiers > + > Services IDs

Description and Identifier (e.g. `com.yourstore.signin`): this **Identifier is the Client ID**. Tick **Sign in with Apple** then click **Configure**.

Fields to fill in	
Primary App ID	the App ID created in step 2
Domains and Subdomains	your-shop.example (without https://)
Return URLs	`https://your-shop.example/en/module/websourcesociallogin/callback`

Step 4. Create a private key

Where : Keys > + > Key Name > Sign in with Apple > Configure

Choose the Primary App ID, confirm, then **download the `AuthKey_XXXXXXXXXX.p8` file**: Apple only offers it once, keep it somewhere safe. Note the **Key ID** (10 characters).

Step 5. Find the Team ID

Where : developer.apple.com/account > Membership details > Team ID

10-character identifier.

Step 6. Fill in the module

Where : This module > Apple

Services ID, Team ID, Key ID, then paste the **entire contents** of the .p8 file (from `-----BEGIN PRIVATE KEY-----` to `-----END PRIVATE KEY-----`) into the "Private key" field. It is encrypted in the database and never sent back to the browser. Enable Apple and save.

Step 7. Going live and relay emails

Where : Certificates, Identifiers & Profiles > More > Configure Sign in with Apple for Email Communication

Apple has no "test" mode: everything works as soon as it is configured. If a customer chooses "Hide My Email", your transactional emails go through an Apple relay: register your sending domain and sender addresses there (valid SPF and DKIM), otherwise they will not be delivered. Apple may also ask you to verify the domain by placing a file in `/.well-known/`.

Permissions (scopes) : Requested scopes: `. The module receives: Apple identifier (sub), email (real or relay), verification status, and the name only on the very first authorization.

Common errors

- **invalid_client** : The Services ID, Team ID, Key ID or .p8 key do not match, or the key is not associated with the right Primary App ID. Recreate the key if needed.
- **invalid_request: Invalid web redirect url** / **redirect_uri mismatch** : The Services ID's "Return URLs" differ from `https://your-shop.example/en/module/websourcesociallogin/callback`, or the domain is not listed in "Domains and Subdomains".
- **Back on the site with "session expired" after Apple** : Apple responds with a POST from another domain: the site must be on HTTPS (SameSite=None; Secure cookie). Check the certificate and that the binding cookie is not blocked.
- **First name and last name are empty** : Apple only sends the name on the first authorization. The customer can revoke access at appleid.apple.com > Sign-In and Security > Sign in with Apple, then try again.
- **Emails not delivered to @privaterelay.appleid.com** : Register your sending domain in "Configure Sign in with Apple for Email Communication" (step 7).

Official links : Apple Developer Services IDs · Sign in with Apple documentation (web)

7. GitHub

GitHub (OAuth App). Ideal for a developer audience. The module only uses emails marked "verified" by GitHub. Allow 5 minutes. Free.

- **Console** : GitHub Developer settings
- **Callback URL to register** : `https://your-shop.example/en/module/websourcesociallogin/callback`

Step 1. Open the developer settings

Where : github.com > your avatar > Settings > Developer settings > OAuth Apps > New OAuth App

For an app owned by an organization: Organization > Settings > Developer settings > OAuth Apps.

Step 2. Fill in the form

Where : Register a new OAuth application

GitHub accepts **only one** callback URL per OAuth App: create one app per store domain.

Fields to fill in	
Application name	your store's name
Homepage URL	https://your-shop.example
Authorization callback URL	`https://your-shop.example/en/module/websourcesociallogin/callback`
Enable Device Flow	leave unchecked

Step 3. Retrieve the Client ID and generate the secret

Where : After "Register application" > Client ID, then "Generate a new client secret"

Copy the **Client ID** then click **Generate a new client secret**: it is only displayed once, copy it into this module immediately.

Step 4. Scopes

Where : This module > GitHub > Scopes

Default `read:user user:email` : `user:email` allows reading the account's emails, including the verified primary one.

Step 5. Going live

Where : Application > Advanced / logo

OAuth Apps have no review or test mode: they are immediately usable by all GitHub accounts. Add a logo (Upload new logo). If a customer's organization restricts access to third-party applications, they will see "Request": their organization's administrator has to approve it.

Permissions (scopes) : Requested scopes: `. The module receives: GitHub identifier (id), name, verified primary email.

Common errors

- **redirect_uri_mismatch** : The OAuth App's callback URL differs from `https://your-shop.example/en/module/websourcesociallogin/callback` (only one URL per app is possible, and its path must start with the registered one).
- **incorrect_client_credentials** : Wrong Client ID or secret: regenerate a secret.
- **bad_verification_code** : The code has already been used or has expired (10 minutes): start the sign-in again.
- **No email received** : The account has no verified address (or the user:email scope was removed): the customer enters their email and confirms it via a link.

Official links : GitHub OAuth Apps · GitHub OAuth documentation

Common issues (all networks)

- **No button appears** : A network is only visible if it is **enabled AND complete** (all required fields filled in) and the location is ticked in "Where to display the buttons". Incomplete networks stay invisible to your customers.




- **"Session expired" after returning from the network** : The binding cookie was blocked (browser in strict private browsing, different domain between www and non-www) or the request took more than 10 minutes. Try again; always use the same address (the callback URL above is the store's).
- **The network rejects an "http://" URL** : Switch the store to HTTPS (Shop Parameters > Traffic & SEO > Enable SSL on all pages). The callback URL is displayed in https.
- **Multilingual store or several domains** : The callback URL is the same for all languages of a domain (it uses the default language). With several domains/stores, register each store's URL with the network (displayed in each store).

6. Customising the buttons

Appearance and locations tab: the preview updates live.


Setting	Options
Style	*Outline* (white background, theme border), *Filled* (network brand colour), *Neutral* (theme colours)
Layout	full-width column, or icon grid
Shape	square, rounded (theme), pill
Icon only	hides the text (kept for screen readers)
Radius, border	in pixels (0 to 32 and 0 to 4)
Colours	background, text, border: `#rgb` , `#rrggbb` , `rgb()` , `rgba()` , `transparent` or `var(--theme-variable)` ; any other value is rejected
"or" separator	shown or not
Last used network	moved first (local cookie, no personal data)

Google and Microsoft logos keep their official colours, as their brand guidelines require.

Outline	Filled	Neutral
		


Locations

Tick where to show the buttons: **login page**, **registration page**, **checkout** (personal information), **header** ("My account" menu, visitors), **wishlist sign-in window**. Buttons are never shown to a signed-in customer.



Texts and GDPR

Texts and GDPR tab: button text (per language), separator and information notice shown under the buttons (adapt it to your privacy policy).



7. Theme compatibility

The module relies on two hooks:

- `displayCustomerLoginFormAfter` : native hook of the login form (Classic, Hummingbird and most third-party themes). Nothing to do: buttons show on the login page.
- `displayWebsourceSocialLogin` : the module's own hook, to add in your theme for the other locations, with the `place` parameter: `register` , `checkout` , `header` , `wishlist` .

If a location does not show, add the call to the theme template (copy it into your child theme if needed), then clear the Smarty cache:

```
{* Registration page: themes/<theme>/templates/customer/registration.tpl, after the form *}
{hook h='displayWebsourceSocialLogin' place='register'}

{* Checkout: templates/checkout/_partials/steps/personal-information.tpl *}
{hook h='displayWebsourceSocialLogin' place='checkout'}

{* Header "My account" menu (visitor), in your account block template *}
{hook h='displayWebsourceSocialLogin' place='header'}

{* Wishlist window (modals/login.tpl of the blockwishlist module, theme override) *}
{hook h='displayWebsourceSocialLogin' place='wishlist'}

{* Login page if your theme does not call the native hook: templates/customer/authentication.tpl *}
{hook h='displayCustomerLoginFormAfter'}
```

The "My account" page gets a **Social connections** tile through the native `displayCustomerAccount` hook.

Styling: `views/css/front.css` uses the theme's CSS variables (`--color-brand-*` , `--color-line` , `--radius-xl` ...) with fallbacks. For a third-party theme, adjust style, colours and radius in the Appearance tab, or override `.wssl` , `.wssl-btn` , `.wssl__sep` in your theme CSS.

After a template change: Advanced Parameters > Performance > Clear cache.

8. GDPR and security

Stored data

Table `ps_websourcesociallogin_link` (one row per linked network): customer, network, the customer's ID at the network, email received, consent date, creation date, last sign-in date. Table `ps_websourcesociallogin_flow` : temporary sign-in states (hashed, deleted at expiry, 10 minutes to 1 hour). **No access token is stored or logged.** The PrestaShop log only holds the network, the event and a short code (no email, token or secret); the IP address is only kept as a hash for rate limiting.

Tell your customers in your privacy policy: the module receives the ID, first name, last name and email from the network (nothing is posted to the network). A configurable notice is shown under the buttons.

Export and erasure

Links are included in the customer's GDPR export (`actionExportGDPRData`) and deleted with the account (`actionDeleteGDPRCustomer` , customer deletion). Customers can unlink a network themselves in My account > Social connections.

Protections

- **Account-takeover protection**: never merged automatically. Verified email matching an existing customer: password required (5 attempts max). Unverified or missing email: confirmation link, same browser. Microsoft: email treated as unverified unless the `xms_edov` claim is present (nOAuth protection).
- Random 256-bit `state`, single use, 10 minutes, bound to the browser by an `HttpOnly` cookie; OpenID Connect `nonce`; PKCE S256 where the network supports it.
- id_token: RS256 only (`none` and HS256 rejected), signature checked through JWKS, `iss`, `aud`, `exp`, `iat`, `nbf` verified.
- Redirects restricted to an allow-list (no open redirect).
- Secrets encrypted at rest (PrestaShop encryption), never in HTML or JavaScript.
- Rate limiting: 30 starts per 10 minutes per IP.
- Link and unlink use POST with a CSRF token.

9. Troubleshooting and FAQ

No button shows. The network must be enabled and complete, and the location ticked. Check the theme hook (section 7), clear the cache. A signed-in customer never sees the buttons.

"redirect_uri_mismatch" or similar. The URL registered at the network differs from the module's: copy it with the Copy button (https, same domain with or without www, no trailing "/"). A change may take a few minutes to apply.

Only my own accounts can sign in. The application is in test/development mode at the network: publish it (see the end of each guide).

"Session expired" on return. Blocked cookie, different domain (www or not), or more than 10 minutes elapsed: try again, always using the same address.

The customer has no email. They enter one and confirm it by link (X, Microsoft, Apple relay...).

Where are the errors? Advanced Parameters > Information > Logs: filter on `[websourcesociallogin]`.

Multilingual or multistore shop? The callback URL is the same for all languages of a domain. With several domains or shops, register each shop's URL at the network (shown in each context).

My theme is third-party and a location is missing. See section 7.

Is there a cost? The module is free; the listed networks do not charge for sign-in.

10. Uninstalling

Modules > Websource Social Login > Uninstall: removes the two module tables (links and temporary states) and all its settings. **Network-customer links are then lost**: customers created through a network keep their account but have no known password and will have to use "Forgot your password?". Export what you need first.

11. Developer FAQ: adding a network

Networks are `Websource\SocialLogin\Provider\ProviderInterface` classes (`src/Provider/` folder). For an OpenID Connect provider extend `OidcProvider`; otherwise `AbstractProvider`.

1. Create `src/Provider/MyNetworkProvider.php` implementing: `id()`, `label()`, `fields()` (settings fields: `client_id`, `client_secret` ...), `defaultScopes()`, `usesPkce()`, `usesFormPost()`, `buildAuthorizationUrl(...)` and `fetchProfile(...)` returning a `Profile` object (ID, email, email verified, first name, last name).
2. Register it in `ProviderRegistry::default()`.
3. Add its guide to `src/Guide/data_fr.php` and `data_en.php` (keys `intro`, `console`, `steps`, `scopes`, `errors`, `links`) and its logo to `src/Render/IconLibrary.php`.
4. Run the tests: `php tests/run.php` (no PrestaShop or network needed; providers are tested with a fake HTTP client).

Account-takeover protection and the linking flow live in the core (`Linking\LinkingService`, `Flow\FlowService`): a provider only has to return a trustworthy `Profile`, stating honestly whether the email is verified.

12. Changelog

See CHANGELOG.md. Version 1.0.0: first public release.

13. Licence and support

Academic Free License 3.0 (AFL-3.0), see `LICENSE.md`. Third-party libraries: see `THIRD_PARTY.md`. Report an issue on GitHub or via websource.fr.