The Memory Allocation Kinds Side Document Version 1.0

MPI Forum Hybrid Working Group (September 2023)

Acknowledgments

Authors

Rohit Zambre, James Dinan, Maria Garzaran, Daniel Holmes, Edgar Gabriel, Michael Klemm, and Pedram Alizadeh

Contents

	finitions
2.1	Kind: cuda
	Restrictors
2.2	Kind: rocm
	Restrictors
2.3	Kind: levelzero
	Restrictors

Chapter 1

Overview

memory types.

12

13

- Modern computing systems contain a variety of memory types, each closely associated with a distinct type of computing hardware. For example, compute accelerators such as GPUs typically feature their own memory that is distinct from the memory attached to the host processor. Additionally, GPUs from different vendors also differ in their memory types. The differences in memory types influence feature availability and performance behavior of an application running on such modern systems. Hence, MPI libraries need to be aware of and support additional memory types. For a given type of memory, MPI libraries need to know the associated memory allocator and the limitations on memory access. The different memory kinds capture the differentiating information needed by MPI libraries for different
 - This MPI side document defines the memory allocation kinds and their associated restrictors that users can use to query the support for different memory kinds provided by the MPI library.

Chapter 2

2 Definitions

3 This section contains definitions of memory allocation kinds and their reistrictors.

4 2.1 Kind: cuda

The cuda memory kind refers to the memory allocated by the CUDA runtime system [1].

6 Restrictors

- host: Support for memory allocations on the host system that are page-locked for direct access from the CUDA device (e.g., memory allocations from the cudaHostAlloc() function).
- device: Support for memory allocated on a CUDA device (e.g., memory allocations from the cudaMalloc() function).
 - managed: Support for memory that is managed by CUDA's Unified Memory system (e.g., memory allocations from the cudaMallocManaged() function).

14 2.2 Kind: rocm

The rocm memory kind refers to the memory allocated by the ROCm runtime system [2].

16 Restrictors

12

13

18

19

- host: Support for memory allocated on the host system that is page-locked for direct access from the ROCm device (e.g., memory allocations from the hipHostMalloc() function).
- device: Support for memory allocated on the ROCm device (e.g., memory allocations from the hipMalloc() function).
- managed: Support for memory that is managed automatically by the ROCm runtime (e.g., memory allocations from the hipMallocManaged() function).

2.3 Kind: levelzero

- 2 The levelzero memory kind refers to the memory allocated by the Level Zero runtime sys-
- з $ext{tem } [3]$.

4 Restrictors

- host: Support for memory allocated on the host that is accessible by Level Zero devices (e.g., memory allocations from the zeMemAllocHost() function).
- device: Support for memory allocated on a Level Zero device (e.g., memory allocations from the zeMemAllocDevice() function).
- shared: Support for memory allocated that will be shared between the host and one or more devices Level Zero devices (e.g., memory allocations from the zeMemAllocShared() function).

Bibliography

- 2 [1] CUDA Runtime API. https://docs.nvidia.com/cuda/cuda-runtime-api/.
- 3 [2] HIP Programming Manual. https://rocm.docs.amd.com/en/latest/reference/hip.html.
- 4 [3] Level Zero Programming Guide. https://spec.oneapi.io/level-
- 5 zero/latest/core/PROG.html.