# HFT WSTGW API Description

| Intro                               | 2 |
|-------------------------------------|---|
| Terminology                         | 2 |
| Request-Response Workflow           | 2 |
| Assumptions                         | 2 |
| Create a handshake and join channel | 3 |
| Request                             | 3 |
| Response                            | 3 |
| Success                             | 3 |
| Fail                                | 3 |
| Send an order                       | 3 |
| Request                             | 3 |
| Response                            | 3 |
| Success                             | 3 |
| Fail                                | 4 |
| Cancel an order                     | 4 |
| Request                             | 4 |
| Response                            | 5 |
| Success                             | 5 |
| Fail                                | 5 |
| Replace Order                       | 5 |
| Not supported at the moment         | 5 |
| Cancel All Orders                   | 5 |
| Not supported at the moment         | 5 |
| Place Multiple Orders               | 5 |
| Not supported at the moment         | 5 |
| Data Flow                           | 5 |
| Trades                              | 5 |
| Sample Response                     | 5 |
| Balances                            | 6 |
| Sample Response                     | 6 |

## Intro

It is to be understood that HFT WebSocket Trading GateWay (WSTGW) is working in asynchronous model. It means that GW takes a request (an order) from client and sends one to Core Trading System and does NOT wait the response from it (the System) but sends the response back to client.

Continuing the thread of thoughts it seems to be worth mentioning that failed/erroneous response from TGW does NOT mean that system cannot proceed the request, it means that TGW cannot place the request to Core Trading system

# **Terminology**

- HFT High Frequency Trading
- WSTGW WebSocket Trading GateWay
- API Application Programming Interface

# Request-Response Workflow

## **Assumptions**

- Every Request to WS TGW must have "rgst" field, supported actions
  - o "auth"
  - o "onew"
  - o "ocncl"
- Every response from WS TGW has "rspns" field
  - o In case of success: "ok"
  - if Failed: "Error string"
- In order to identify/correspond response to request every response from WS TGW has a key, that could be either:
  - o cliorderId
  - o orderId
  - apikey
- Practically, ws tgw is going to reply back original request from client injecting the response, either "ok" or "error message"

## Create a handshake and join channel

#### Send an order

#### Request

```
{
    "rqst": "onew",
    "cliOrderId": "cxc-155-test-01",
    "price": "200",
    "type": "lmt",
    "tradingPairId": 29,
    "amount": "0.00001",
    "side": "buy"
}
```

#### Response

```
Success
{
    "rqst": "onew",
    "cliOrderId": "cxc-155-test-01",
    "price": "200",
```

```
"type": "lmt",
 "tradingPairId": 29,
"amount": "0.00001",
"side": "buy",
"orderId": "1554808412.398163.wstg1@0029.1",
"ug": 10,
"action": 1,
"userId": 93356,
"rspns": "ok",
"msqtp": "rspns"
}
Fail
{
"rqst": "onew",
"cliOrderId": "cxc-155-test-01",
"price": "200",
"type": "lmt",
 "tradingPairId": 29,
"amount": "0.00001",
"side": "buy",
"orderId": "1554808412.398163.wstg1@0029.1",
"ug": 10,
"action": 1,
"userId": 93356,
"rspns":"Some error message",
"msqtp": "rspns"
}
```

#### Cancel an order

```
Request
```

```
{"rqst":"ocncl", "orderId":"1545925300.904075.tg1.062901@0029.1"}
```

#### Response

```
Success
```

```
{"rspns":"ok", "orderId":"1545925300.904075.tg1.062901@0029.1"}

Fail
{"rspns":"Some error message", "orderId":"1545925300.904075.tg1.062901@0029.1"}
```

## Replace Order

Not supported at the moment

#### Cancel All Orders

Not supported at the moment

## Place Multiple Orders

Not supported at the moment

## **Data Flow**

- In order to distinguish between
  - o response from tgw
  - o trade from ME
  - o bal update from BE
- new JSON field is to be implemented: msgtp, that could be either:
  - o rspns
  - o trd
  - o bal

#### **Trades**

Sample Response

```
"avgPrice": "0",
  "cliOrderId": "cxc-155-test-01",
  "execPrice": "200",
  "initPrice": "200",
  "message": "",
 "msgtp": "trd",
  "oqty": "0.00001",
  "orderId": "1554810944.468910.wstg1@0029.1",
  "qty": "0.00001",
  "side": "buy",
  "stat": "accepted",
  "tradingPairId": 29,
  "trdId": "1554810946.822295.3.tg14",
  "type": "lmt",
  "ug": 13,
  "userId": 51983,
 "userIdMaker": 0.
 "userIdTaker": 0
}
```

#### Balances

#### Sample Response

```
{
  "id": "1554810944.468910.wstg1@0029.1",
  "userId": 51983,
  "currencyId": 2,
  "amount": "11924.809",
  "lockedByOrder": "49.45952697216",
  "lockedByWithdrawal": "0",
  "fee": "0",
  "feetp": 1,
  "result": "1",
  "msgtp": "bal"
}
```