

Note to other teachers and users of these slides: We would be delighted if you found this our material useful in giving your own lectures. Feel free to use these slides verbatim, or to modify them to fit your own needs. If you make use of a significant portion of these slides in your own lecture, please include this message, or a link to our web site: <http://www.mmds.org>

Mining Data Streams (Part 2)

Mining of Massive Datasets

Jure Leskovec, Anand Rajaraman, Jeff Ullman

Stanford University

<http://www.mmds.org>



(1) Counting Distinct Elements

Counting Distinct Elements

■ Problem:

- Data stream consists of a universe of elements chosen from a set of size N
- Maintain a count of the number of distinct elements seen so far

■ Obvious approach:

Maintain the set of elements seen so far

- That is, keep a hash table of all the distinct elements seen so far

Applications

- **How many different words are found among the Web pages being crawled at a site?**
 - Unusually low or high numbers could indicate artificial pages (spam?)
- **How many different Web pages does each customer request in a week?**
- **How many distinct products have we sold in the last week?**

Using Small Storage

- **Real problem: What if we do not have space to maintain the set of elements seen so far?**
- **Estimate the count in an unbiased way**
- **Accept that the count may have a little error, but limit the probability that the error is large**

Flajolet-Martin Approach

- Pick a hash function h that maps each of the N elements to at least $\log_2 N$ bits
- For each stream element a , let $r(a)$ be the number of trailing 0s in $h(a)$
 - $r(a)$ = position of first 1 counting from the right
 - E.g., say $h(a) = 12$, then 12 is 1100 in binary, so $r(a) = 2$
- Record R = the maximum $r(a)$ seen
 - $R = \max_a r(a)$, over all the items a seen so far
- Estimated number of distinct elements = 2^R

Why It Works: Intuition

- Very very rough and heuristic intuition why Flajolet-Martin works:
 - $h(a)$ hashes a with equal prob. to any of N values
 - Then $h(a)$ is a sequence of $\log_2 N$ bits, where 2^{-r} fraction of all a s have a tail of r zeros
 - About 50% of a s hash to $***0$
 - About 25% of a s hash to $**00$
 - So, if we saw the longest tail of $r=2$ (i.e., item hash ending $*100$) then we have probably seen **about 4** distinct items so far
 - So, it takes to hash about 2^r items before we see one with zero-suffix of length r

Why It Works: More formally

- Now we show why Flajolet-Martin works
- Formally, we will show that **probability of finding a tail of r zeros:**
 - Goes to **1** if $m \gg 2^r$
 - Goes to **0** if $m \ll 2^r$

where m is the number of distinct elements seen so far in the stream

- **Thus, 2^R will almost always be around m !**

Why It Works: More formally

- What is the probability that a given $h(a)$ ends in at least r zeros is 2^{-r}
 - $h(a)$ hashes elements uniformly at random
 - Probability that a random number ends in at least r zeros is 2^{-r}
- Then, the probability of **NOT** seeing a tail of length r among m elements:

The diagram shows the formula $(1 - 2^{-r})^m$ enclosed in a box. An arrow points from the text 'Prob. all end in fewer than r zeros.' to the left side of the box. Another arrow points from the text 'Prob. that given $h(a)$ ends in fewer than r zeros' to the term $1 - 2^{-r}$ inside the box.

Prob. all end in fewer than r zeros.

Prob. that given $h(a)$ ends in fewer than r zeros

Why It Works: More formally

- **Note:** $(1 - 2^{-r})^m = (1 - 2^{-r})^{2^r (m2^{-r})} \approx e^{-m2^{-r}}$
- **Prob. of NOT finding a tail of length r is:**
 - If $m \ll 2^r$, then prob. tends to **1**
 - $(1 - 2^{-r})^m \approx e^{-m2^{-r}} = 1$ as $m/2^r \rightarrow 0$
 - So, the probability of finding a tail of length r tends to **0**
 - If $m \gg 2^r$, then prob. tends to **0**
 - $(1 - 2^{-r})^m \approx e^{-m2^{-r}} = 0$ as $m/2^r \rightarrow \infty$
 - So, the probability of finding a tail of length r tends to **1**
- **Thus, 2^R will almost always be around m !**

Why It Doesn't Work

- $E[2^R]$ is actually infinite
 - Probability halves when $R \rightarrow R+1$, but value doubles
- Workaround involves using many hash functions h_i and getting many samples of R_i
- How are samples R_i combined?
 - Average? What if one very large value 2^{R_i} ?
 - Median? All estimates are a power of 2
 - Solution:
 - Partition your samples into small groups
 - Take the median of groups
 - Then take the average of the medians

(2) Computing Moments

Generalization: Moments

- Suppose a stream has elements chosen from a set A of N values
- Let m_i be the number of times value i occurs in the stream
- The k^{th} *moment* is

$$\sum_{i \in A} (m_i)^k$$

Special Cases

$$\sum_{i \in A} (m_i)^k$$

- **0th moment** = number of distinct elements
 - The problem just considered
- **1st moment** = count of the numbers of elements = length of the stream
 - Easy to compute
- **2nd moment** = *surprise number S* = a measure of how uneven the distribution is

Example: Surprise Number

- Stream of length 100
- 11 distinct values
- Item counts: 10, 9, 9, 9, 9, 9, 9, 9, 9, 9, 9
Surprise $S = 910$
- Item counts: 90, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1
Surprise $S = 8,110$


AMS Method

- AMS method works for all moments
- Gives an unbiased estimate
- We will just concentrate on the 2nd moment S
- We pick and keep track of many variables X :
 - For each variable X we store $X.el$ and $X.val$
 - $X.el$ corresponds to the item i
 - $X.val$ corresponds to the **count** of item i
 - Note this requires a count in main memory, so number of X s is limited
- Our goal is to compute $S = \sum_i m_i^2$

One Random Variable (X)

- **How to set $X.val$ and $X.el$?**
 - Assume stream has length n (we relax this later)
 - Pick some random time t ($t < n$) to start, so that any time is equally likely
 - Let at time t the stream have item i . **We set $X.el = i$**
 - Then we maintain count c (**$X.val = c$**) of the number of i s in the stream starting from the chosen time t
- **Then the estimate of the 2nd moment ($\sum_i m_i^2$) is:**
$$S = f(X) = n(2 \cdot c - 1)$$
 - Note, we will keep track of multiple X s, (X_1, X_2, \dots, X_k) and our final estimate will be **$S = 1/k \sum_j^k f(X_j)$**

Expectation Analysis



- 2nd moment is $S = \sum_i m_i^2$
- c_t ... number of times item at time t appears from time t onwards ($c_1=m_a$, $c_2=m_a-1$, $c_3=m_b$)

- $E[f(X)] = \frac{1}{n} \sum_{t=1}^n n(2c_t - 1)$

$$= \frac{1}{n} \sum_i n (1 + 3 + 5 + \dots + 2m_i - 1)$$

m_i ... total count of item i in the stream (we are assuming stream has length n)


Group times by the value seen

Time t when the last i is seen ($c_t=1$)

Time t when the penultimate i is seen ($c_t=2$)

Time t when the first i is seen ($c_t=m_i$)

Expectation Analysis



- $E[f(X)] = \frac{1}{n} \sum_i n (1 + 3 + 5 + \dots + 2m_i - 1)$
 - Little side calculation: $(1 + 3 + 5 + \dots + 2m_i - 1) = \sum_{i=1}^{m_i} (2i - 1) = 2 \frac{m_i(m_i+1)}{2} - m_i = (m_i)^2$
- Then $E[f(X)] = \frac{1}{n} \sum_i n (m_i)^2$
- So, $E[f(X)] = \sum_i (m_i)^2 = S$
- We have the second moment (in expectation)!

Higher-Order Moments

- For estimating k^{th} moment we essentially use the same algorithm but change the estimate:
 - For $k=2$ we used $n (2 \cdot c - 1)$
 - For $k=3$ we use: $n (3 \cdot c^2 - 3c + 1)$ (where $c=X.val$)
- Why?
 - For $k=2$: Remember we had $(1 + 3 + 5 + \dots + 2m_i - 1)$ and we showed terms $2c-1$ (for $c=1, \dots, m$) sum to m^2
 - $\sum_{c=1}^m 2c - 1 = \sum_{c=1}^m c^2 - \sum_{c=1}^m (c - 1)^2 = m^2$
 - So: $2c - 1 = c^2 - (c - 1)^2$
 - For $k=3$: $c^3 - (c-1)^3 = 3c^2 - 3c + 1$
- Generally: Estimate = $n (c^k - (c - 1)^k)$

Combining Samples

■ In practice:

- Compute $f(X) = n(2c - 1)$ for as many variables X as you can fit in memory
- Average them in groups
- Take median of averages

■ Problem: Streams never end

- We assumed there was a number n , the number of positions in the stream
- But real streams go on forever, so n is a variable – the number of inputs seen so far

Streams Never End: Fixups

- **(1)** The variables X have n as a factor – keep n separately; just hold the count in X
- **(2)** Suppose we can only store k counts.
We must throw some X s out as time goes on:
 - **Objective:** Each starting time t is selected with probability k/n
 - **Solution: (fixed-size sampling!)**
 - Choose the first k times for k variables
 - When the n^{th} element arrives ($n > k$), choose it with probability k/n
 - If you choose it, throw one of the previously stored variables X out, with equal probability