

# Kotlin Hello World

In this tutorial, you will learn how to write and run hello world program in Kotlin. Let's see how you can achieve this by following the procedures mentioned below

## Requirement of Kotlin Hello World Example

For running any program written in Kotlin, you need the following-

1. Install the latest version of JDK from Oracle.
2. Download zip file of Kotlin compiler from Github using this [link](#).  
Once you have downloaded the zip file, unzip it into a folder. And add the bin folder to the system path.

## Example of Hello World in Kotlin

```
fun main(args: Array<String>){  
    println("My First Kotlin program")  
}
```

### Output


```
My First Kotlin Program
```

Save

this file as hello.kt. Remember one thing the file extension of a program written in Kotlin is **.kt** or **.kts**.

**To compile a program-** kotlinc sourcefile.kt -include-runtime -d jarfile.jar  
So to compile the above code, you run- kotlinc hello.kt -include-runtime -d hello.jar

**To execute-** java -jar hello.jar

A screenshot of a Windows Command Prompt window. The title bar says "Command Prompt". The command prompt shows the following sequence of commands and output:  
C:\Users\User\Desktop>kotlinc hello.kt -include-runtime -d hello.jar  
C:\Users\User\Desktop>java -jar hello.jar  
My First Kotlin program  
C:\Users\User\Desktop>  
The output "My First Kotlin program" is displayed on the line following the second command.

```
C:\Users\User\Desktop>kotlinc hello.kt -include-runtime -d hello.jar
C:\Users\User\Desktop>java -jar hello.jar
My First Kotlin program
C:\Users\User\Desktop>
```

**Note-** `kotlinc` is the Kotlin compiler. `-include-runtime` option makes jarfile.jar file runnable by including Kotlin runtime library in it. The `-d` option indicates in what form the output of the compiler to be called.


## Explanation of above program

In every Kotlin program, the main function is necessary. It is similar to `public static void main(String args[])` function in Java. It takes an array of string as an argument and returns nothing.

The `println()` function is used to display the provided message on the output stream. It is similar to `System.out.println()` function in Java.

## Build Process of Kotlin

Following diagram explains the build process of Kotlin-



You store the source code written in Kotlin in a file having extension `.kt`. When you run `kotlinc` command, Kotlin compiler generates `.class` files similar to the Java compiler. The generated `.class` files are packaged into `.jar` file. And using `java` or `kotlin` command you execute your code.

To compile, run the below command

```
kotlinc sourcefile.kt -include-runtime -d jarfile.jar
```

To execute, run the below commands

```
java -jar jarfile.jar
```