

≡ Menu



LinuxMint
The Ideal Linux Blog for Sysadmins & Geeks

≡ Menu



Neofetch – Shows Linux System Information with Distribution Logo

Aaron Kili | Last Updated: January 25, 2017 | Open Source

| [Leave a comment](#)



system information and display it on the terminal next to an image, it could be your distributions logo or any ascii art of your choice.

Recently, a new major version of **Neofetch 3.0** released with large amount of breaking changes added to this update.

Neofetch is very similar to [ScreenFetch](#) or [Linux_Logo](#) utilities, but highly customizable and comes with some extra features as discussed below.

Its main features include: it's fast, prints a full color image – your distributions logo in ASCII alongside your system information, it's highly customizable in terms of which, where and when information is printed on the terminal and it can take a screenshot of your desktop when closing the script as enabled by a special flag.

Required Dependencies:

- **Bash 3.0+** with ncurses support.
- **w3m-img** (occasionally packaged with **w3m**) or **iTerm2** or **Terminology** for printing images.
- [imagemagick](#) – for thumbnail creation.
- [Linux terminal emulator](#) should support `\033[14t [3]` or



Important: You can read more about optional dependencies from the Neofetch Github repository to check if your [Linux terminal emulator](#) actually supports \033[14t or any extra dependencies for the script to work well on your distro.

How To Install Neofetch in Linux

Neofetch can be easily installed from third-party repositories on almost all Linux distributions by following below respective installation instructions as per your distribution.

On Debian

```
$ echo "deb http://dl.bintray.com/dawidd6/neofetch" > /etc/apt/sources.list.d/neofetch.list
$ curl -L "https://bintray.com/user/download" > /etc/apt/sources.list.d/neofetch.list
$ sudo apt-get update
$ sudo apt-get install neofetch
```



```
$ sudo add-apt-repository ppa:dawidd0811/neofetch
$ sudo apt-get update
$ sudo apt-get install neofetch
```

On RHEL, CentOS and Fedora

You need to have **dnf-plugins-core** installed on your system, or else install it with the command below:

```
$ sudo yum install dnf-plugins-core
```

Enable COPR repository and install **neofetch** package.

```
$ sudo dnf copr enable konimex/neofetch
$ sudo dnf install neofetch
```

On Arch Linux

You can either install **neofetch** or **neofetch-git** from the AUR using **packer** or **Yaourt**.



```
$ packer -S neofetch
$ packer -S neofetch-git
OR
$ yaourt -S neofetch
$ yaourt -S neofetch-git
```

On Gentoo

Install **app-misc/neofetch** from Gentoo/Funtoo's official repositories. However, in case you need the git version of the package, you can install **=app-misc/neofetch-9999**.

How To Use Neofetch in Linux

Once you have installed the package, the general syntax for using it is:

```
$ neofetch
```


Note: If **w3m-img** or [imagemagick](#) is not installed on your system, [screenfetch](#) will be enabled by default and **neofetch** will display your [ASCII art logo](#) as in the image below.



Linux Mint System Information

Ubuntu Information





After running **neofetch** for the first time, it will create a configuration file with all options and settings:

```
$HOME/.config/neofetch/config .
```

This configuration file will enable you through the `printinfo ()` function to alter the system information that you want to print on the terminal. You can type in new lines of information, modify the information lineup, delete certain lines and also tweak the script it using bash code to manage the information to be printed out.

You can open the configuration file using your favorite editor as follows:



Below is an excerpt of the configuration file on my system showing the `printinfo ()` function.

Neofetch Configuration File

```
#!/usr/bin/env bash
# vim:fdm=marker
#
# Neofetch config file
# https://github.com/dylananaraps/neofetch

# Speed up script by not using unicode
export LC_ALL=C
export LANG=C

# Info Options {{{

# Info
# See this wiki page for more info:
# https://github.com/dylananaraps/neofetch/wiki
printinfo() {
    info title
    info underline

    info "Model" model
```



```
info "Packages" packages
info "Shell" shell
info "Resolution" resolution
info "DE" de
info "WM" wm
info "WM Theme" wntheme
info "Theme" theme
info "Icons" icons
info "Terminal" term
info "Terminal Font" termfont
info "CPU" cpu
info "GPU" gpu
info "Memory" memory

# info "CPU Usage" cpu_usage
# info "Disk" disk
# info "Battery" battery
# info "Font" font
# info "Song" song
# info "Local IP" localip
# info "Public IP" publicip
# info "Users" users
# info "Birthday" birthday

info linebreak
info cols
```



Type the command below to view all flags and their configuration values you can use with neofetch script:

```
$ neofetch --help
```

To launch neofetch with all functions and flags enabled, employ the `--test` flag:

```
$ neofetch --test
```

You can enable the ASCII art logo again using the `--ascii` flag:

```
$ neofetch --ascii
```

In this article, we have covered a simple and highly configuration/customizable command line script that gathers your system information and displays it on the terminal.

Remember to get in touch with us via the feedback form below to ask any questions or give us your thoughts



Last but not least, if you know of any similar scripts out there, do not hesitate to let us know, we will be pleased to hear from you.

Visit the [neofetch Github repository](#).

[Commandline Tools](#)

[< Hacking Owncloud to Improve Branding of Login Page](#)

[How to Check Timezone in Linux](#) >

If you liked this article, then do [subscribe to email alerts](#) for Linux tutorials. If you have any questions or doubts? do [ask for help in the comments](#) section.

If You Appreciate What We Do Here
On TeoMint You Should Consider



TecMint is the fastest growing and most trusted community site for any kind of Linux Articles, Guides and Books on the web. Millions of people visit TecMint! to search or browse the thousands of published articles available FREELY to all.

If you like what you are reading, please consider buying us a coffee (or 2) as a token of appreciation.




Buy me a coffee

We are thankful for your never ending support.

Related Posts





Useful PuTTY Configuration Tips and Tricks

```
M-0.10.5 jao@cheese:~/git/marcel/marcel$ ls -fr \
M +$ | map (file: (file.suffix, file.size)) \
M +$ | red . + \
M +$ | sort
('.py', 412187)
('.pyc', 670742)
('.txt', 82)
```

Marcel - A More Modern Shell for Linux

Marcel – A More Modern Shell for Linux



Setting Up Zimbra Collaboration Suite (ZCS) on RHEL/CentOS 7/8



The 8 Best Open Source Web Servers



How to Install Eclipse IDE in CentOS, RHEL and Fedora



The 5 Best Command Line Music Players for Linux

Got something to say? Join the discussion.

Have a question or suggestion? Please leave a comment to start the discussion. Please keep in mind that all comments are moderated and your email address will NOT be published.



Email *

Website

☐ Save my name, email, and website in this browser for the next time I comment.

☐ Notify me of followup comments via e-mail. You can also subscribe without commenting.

Post Comment

This site uses Akismet to reduce spam. [Learn how your comment data is processed.](#)

Over 3,500,000+ Readers





[A Beginners Guide To Learn Linux for Free \[with Examples\]](#)

[Red Hat RHCSA/RHCE 8 Certification Study Guide \[eBooks\]](#)

[Linux Foundation LFCS and LFCE Certification Study Guide \[eBooks\]](#)



Learn XZ (Lossless Data Compression Tool) in Linux with Examples

How to Use 'at' Command to Schedule a Task on Given or Later Time in Linux

How to Use 'fsck' to Repair File System Errors in Linux

20 Advanced Commands for Linux Experts

HTTPIe – A Modern HTTP Client Similar to Curl and Wget Commands

Linux sdiff Command Examples for Linux Newbies





TECMINT

#1 WORLD'S LEADING LINUX BLOG

DO YOU WANT TO LEARN LINUX?

Get weekly Linux tutorials, tricks & tips
and other useful Open Source resources
in your INBOX.

JOIN NOW ... IT'S FREE!

If You Appreciate What We Do Here On TecMint, You Should
Consider:



Buy me a coffee



[Htop – An Interactive Process Viewer for Linux](#)

[4 Useful Commandline Tools to Monitor MySQL Performance in Linux](#)

[Use Glances to Monitor Remote Linux in Web Server Mode](#)

[How to Install and Configure ‘Collectd’ and ‘Collectd-Web’ to Monitor Server Resources in Linux](#)

[A Shell Script to Send Email Alert When Memory Gets Low](#)

[How to Install and Configure Zabbix Agents on Remote Linux Systems – Part 3](#)

Learn Linux Tricks & Tips

[How to Use ‘at’ Command to Schedule a Task on Given or Later Time in Linux](#)

[How to Save Command Output to a File in Linux](#)

[How to Delete Root Mails \(Mailbox\) File in Linux](#)

[2 Ways to Re-run Last Executed Commands in Linux](#)



[How to Restore Deleted /tmp Directory in Linux](#)

Best Linux Tools

[5 Most Frequently Used Open Source Shells for Linux](#)

[Top 27 Tools for VMware Administrators](#)

[13 Best Tiling Window Managers for Linux](#)

[10 Best Free and Open Source Software \(FOSS\) Programs I Found in 2020](#)

[9 Tools to Monitor Linux Disk Partitions and Usage in Linux](#)

[27 Best IDEs for C/C++ Programming or Source Code Editors on Linux](#)

[Donate to TecMint](#)

[Contact Us](#)

[Advertise on TecMint](#)

[Linux Services](#)

[Copyright Policy](#)

[Privacy Policy](#)

[Career](#)

[Sponsored Post](#)

Tecmint: Linux Howtos, Tutorials & Guides © 2020. All Rights Reserved.

The material in this site cannot be republished either online or offline,
without our permission.

