

Bandits on stochastic block-model graphs

Arthur Mensch, Michaël Weiss

January 14, 2015

Problem definition

N arms, T steps.

- 1 The environment chooses losses for every arm noted $l_{t,i}$ for the arm i at the step t .
- 2 Following the algorithm we hope would minimize as much as possible the regret the player draws an arm I_t .
- 3 The player receives the loss l_{t,I_t} .
- 4 We define $(O_t)_{i \in [N]}$ as the indicative function of observed loss at step t . We have:

$$O_{t,I_t} = 1 \quad \forall i \neq I_t, O_{t,i} \sim B(r)$$

$(O_t)_{i \in [N]}$ corresponds to the value of the logic expression i is neighbor of I_t in the Erdős-Rényi random graph drawn at step t .

- 5 For all i such that $O_{t,i} = 1$ the player can observe the loss $l_{t,i}$.

Duplex tricks

Definition geometrical random variables

$$M_t^* = \min\{1 \leq i < N : O'_{t-1,i} = 1\} \cup \{N\}$$

$$G_{t,i} = \min(K_{t,i}, M_t)$$

Independence

$$p_{t+2,i} \propto w_{t+2,i} = \frac{1}{N} \exp\left(-\eta_{t+2} \hat{L}_{t,i}\right)$$

Generalizing

ESTIMATE_R gives a safe lower bounding on r .

If $\underline{r} = 0$, we run vanilla EXP3.

If $\underline{r} \geq \frac{\log T}{N}$, we run vanilla DUPLEX.

If $0 < \underline{r} < \frac{\log T}{N}$, $A = \left\lceil \frac{\log T}{N\underline{r}} \right\rceil$ and run DUPLEX grouping A steps.

Random graph with Stochastic Block-Model

ZE figure!

Probability of side information

n clusters. We know in which cluster is every vertex.

$R = (r_{ij})_{1 \leq i, j \leq n}$ the matrix representing the probability of having side information.

r_{ij} represents the probability that a vertex of the cluster j reveals his loss to a given vertex of the cluster i

Adapt M_t sampling

Lower bounding R

Generalized algorithm

If $\underline{R} = 0$,

we run vanilla EXP3.

If $\min_{i,j, \underline{r}_{i,j} > 0} (\underline{r}_{ij} N_j) \geq \log T$,

we run adapted DUPLEX.

Else,

$$A = \left\lceil \frac{\log T}{r_{N^*}} \right\rceil \text{ where}$$

$$r_{N^*} = \min_{i,j, \underline{r}_{i,j} > 0} (\underline{r}_{ij} N_j)$$

and run DUPLEX grouping A steps.

Heavily unbalanced graph




Figure : Outperformance of our algorithm

Graph 'close' to Erdős-Rényi




Figure : Original algorithm outperforms our algorithm