

1 **Half-Plane Shielding: Provable Directional COLREGs Compliance for Continuous-Action Safe**
2 **Reinforcement Learning**

3 **Weiyu Tang**

4 Graduate Research Assistant
5 Shanghai Key Laboratory for Digital Maintenance of Buildings and Infrastructure,
6 School of Naval Architecture, Ocean and Civil Engineering
7 Shanghai Jiao Tong University, Shanghai, 200240, China
8 Email: weiyutang@sjtu.edu.cn

9 **Jie Xue, Ph.D.***

10 Assistant Research Professor
11 State Key Laboratory of Ocean Engineering
12 School of Naval Architecture, Ocean and Civil Engineering
13 Shanghai Jiao Tong University, Shanghai, 200240, China
14 Email: j.xue@sjtu.edu.cn

15 **Peijie Yang**

16 Shanghai Key Laboratory for Digital Maintenance of Buildings and Infrastructure,
17 School of Naval Architecture, Ocean and Civil Engineering
18 Shanghai Jiao Tong University, Shanghai, 200240, China
19 Email: yangpeijie21@sjtu.edu.cn

20 **Qianbing Li**

21 Shanghai Key Laboratory for Digital Maintenance of Buildings and Infrastructure,
22 School of Naval Architecture, Ocean and Civil Engineering
23 Shanghai Jiao Tong University, Shanghai, 200240, China
24 Email: qianbing_li@sjtu.edu.cn

25 Word Count: [TBD] words + [TBD] table(s) $\times$ 250 = [TBD] words

26 Total Number of Pages: [TBD]

27 Submitted [Submission Date]

28 *Corresponding Author

1 ABSTRACT

2 **Objectives:** Autonomous surface vessels must obey the International Regulations for Preventing Collisions
3 at Sea (COLREGs). The give-way rules are directional. A track that avoids a collision but passes on
4 the wrong side is still a violation. This paper builds a per-step guarantee of directional compliance for
5 continuous control commands.

6 **Methods:** The give-way clause is written as a half-plane constraint on the plane of control commands. It is
7 intersected with the actuator limits and a one-step collision-free condition, which gives a convex safe control
8 set. A small quadratic program projects the command of the policy onto the nearest point of that set. The
9 projection sits inside the environment transition, so the policy learns under its own corrected commands.
10 The data are 2,000 simulated two-vessel encounters, split into 1,400 training and 600 test cases. Nine
11 configurations form a single-variable ladder, each trained with eight fixed seeds.

12 **Findings:** On every give-way step where the projection is feasible, directional compliance holds by con-
13 struction. It does not depend on the training outcome or the seed. Steps that switch to the fallback branch
14 are not covered. On the test set, the violation count per episode is [TBD] and the collision rate is [TBD].
15 The ablation gains are significant under a paired signed-rank test. The arrival rate is not claimed as a benefit.

16 **Novelty:** To the best of the authors' knowledge, this is the first projection-based safety mechanism that
17 enforces directional COLREGs compliance on continuous control commands. The paper also states what is
18 proved and what is not.

19 **Practical Applications:** The compliance check is independent of training. The mechanism can sit above an
20 existing controller as a compliance layer for functional verification and liability assessment. The online cost
21 is one small quadratic program per step, so it runs in real time without special hardware.

22 **Keywords:** COLREGs compliance, safe reinforcement learning, projection-based safety shield, continuous
23 action space, quadratic programming, unmanned surface vehicle

3 PROBLEM FORMULATION

3.1 Vessel Kinematics

The controlled vessel is modeled as a point mass with a yaw constraint. Its state is $s = [p_x, p_y, \theta, v]^\top \in \mathbb{R}^4$, which collects position, heading, and speed. Its controls are the longitudinal acceleration a and the turn rate ω ,

$$\dot{s} = [v \cos \theta, v \sin \theta, \omega, a]^\top, \quad u = [a, \omega]^\top. \quad (1)$$

The controls obey $|a| \leq a_{\max}$ and $|\omega| \leq \omega_{\max}$, and the speed obeys $0 \leq v \leq v_{\max}$. A command is held constant over one decision period Δt . Headings and bearings are wrapped to $(-\pi, \pi]$. A relative bearing is positive to starboard. The turn rate follows the usual mathematical convention and is positive counter-clockwise, so a turn to starboard has $\omega < 0$.

The speed bound is applied after the step is integrated, so the speed can briefly exceed $v_{\max}$ within a step. Every one-step displacement bound in this paper therefore uses $v_{\max} \Delta t + \frac{1}{2} a_{\max} \Delta t^2$, and the speed at the end of a step is at most $v_{\text{bnd}} = v_{\max} + a_{\max} \Delta t$.

Two reasons fix this level of detail. The give-way rules govern changes of course and of speed, and Equation (1) takes both as control commands. The rules can therefore be written as constraints on u with nothing in between, and that is what lets the whole safety mechanism live in the action space. A finer hydrodynamic model would add coefficients that differ by vessel and are hard to identify, and the rule constraints would then be entangled with vessel parameters. Wind, current, and waves are not modeled.

Vessel and occupancy. The subject is a large container vessel of length 175 m and beam 25.4 m. Its limits are $a_{\max} = 0.24 \text{ m/s}^2$, $\omega_{\max} = 0.03 \text{ rad/s}$, and $v_{\max} = 9.5 \text{ m/s}$. The decision period is 10 s, and an episode lasts at most 170 steps, which is 1,700 s. The circumscribed radius of the hull is 88.4 m and the inscribed radius is 12.7 m.

The turn rate limit is about 1.7° per second. A readily apparent turn of 20° therefore needs more than ten seconds, which is longer than one decision period. The vessel maneuvers more slowly than it decides. A safety constraint must look ahead for that reason alone.

The hull is represented by a rectangle, and two circles approximate it for two different purposes. The circumscribed circle over-approximates the hull, and it supports conditions of the form “contact is impossible”. The inscribed circle under-approximates the hull, and it supports conditions of the form “contact is certain”. One circle in each direction is what keeps both kinds of conclusion one-sided. The target vessel is represented by a rectangle as well, and it is extrapolated at constant velocity whenever a prediction is needed.

3.2 Observation and Action Spaces

The observation is a real vector of 27 entries in four groups. Four entries give the state of the own vessel. Six give the relation to the goal. Twelve give the traffic situation. Four bearing sectors are used, and each contributes the nearest target vessel in it. Each such vessel gives its distance, its relative bearing, and the change of that distance over one step. Five are termination flags. The observation layer outputs raw physical quantities, and normalization is done in the training wrapper. Organizing traffic by sector keeps the dimension independent of the number of target vessels. That solves the dimension only. The shield deployed here is implemented for a single target vessel, and it raises an error rather than running in a degraded mode when more are present.

Two action boxes. The action is the two-dimensional command $u = (a, \omega)$, and two boxes have to be distinguished. The policy acts in the narrower operating box, whose half-widths are 0.048 m/s^2 and 0.018 rad/s . These are exactly the span of the 7×7 grid used by the discrete configurations, so the two action spaces carry the same control authority and differ only in resolution. The shield and the emergency controller act in the wider box of the actuator limits, $U_{\text{box}} = \{|a| \leq a_{\max}\} \cap \{|\omega| \leq \omega_{\max}\}$.

The widening is necessary. A shield confined to the narrow box would declare a step infeasible whenever that box and the collision-free constraint disagree, even though the step is in fact solvable. The cost is that the applied command can fall outside the policy action box. That fact is returned in the observation, and saturation is counted against each box separately.

3.3 Compliance as a Per-Step Constraint

We consider a two-vessel encounter in open water under five assumptions. (A1) Open water, with no traffic separation scheme, no static obstacle, and no shoreline constraint. (A2) One controlled vessel and one target vessel, both power-driven. (A3) The dynamics of the controlled vessel are Equation (1), applied with zero-order hold at period Δt . (A4) The current state of the target vessel is available without measurement error. (A5) No give-way obligation is already in force at the initial instant.

Assumption (A2) is not a simplification adopted for convenience. It is the scope of the convention itself. The rules are written for a pair of vessels (IMO 1972). Three or more vessels can meet at once, and their obligations can then conflict. One case is an obligation to hold course for one vessel and to give way to another. The convention does not say which obligation prevails.

Let ρ_t be the encounter situation at time t . Let $U_{\text{colregs}}(\rho_t) \subseteq \mathbb{R}^2$ be the set of commands that the rules allow in that situation, and let $U_{\text{cf}}(s_t)$ be the collision-free set. The problem is to find a policy

$$\pi : S \rightarrow \mathbb{R}^2 \quad \text{such that} \quad u_t \in U_{\text{colregs}}(\rho_t) \cap U_{\text{cf}}(s_t) \quad \text{for all } t. \quad (2)$$

Equation (2) is not the same as writing compliance into the reward. It constrains every command that is executed. It does not ask for an expected value to be optimal.

When the action set is finite, Equation (2) has a direct solution. Every action is enumerated, tested, and masked out if it does not comply. That route needs the actions to be enumerable, so it is not compatible with continuous control. Rudder and propulsion are continuous quantities, and quantizing them costs both smoothness and resolution. This paper replaces enumeration by projection. The give-way clause is a half-plane constraint on the command (Section 4.1). The collision-free condition can be written as a linear inequality (Section 4.2). The feasible set of Equation (2) is therefore the intersection of a rectangle with a few half-planes in the plane, which is a convex polygon. The projection onto a convex set exists and is unique, and it is obtained from a very small quadratic program.

4 METHODOLOGY

A note on the guarantees. Three propositions are stated in this section. Each one is placed immediately after the mechanism it applies to, rather than collected in a separate block. Each is given as a statement, its assumptions, a proof sketch, and its scope. The scope paragraph names the cases that the proposition does not cover.

4.1 COLREGs Obligations as Half-Plane Constraints

The rule state machine sorts the current encounter into six situations,

$$\rho \in \{\rho_0 \text{ conflict-free}, \rho_1 \text{ stand-on}, \rho_2 \text{ head-on}, \rho_3 \text{ crossing}, \rho_4 \text{ overtaking}, \rho_5 \text{ emergency}\},$$

and the decision is a conjunction of three groups of conditions. Each condition is a predicate, that is, a named test on the two states that returns true or false.

The first group is the bearing sector, taken along the sidelight boundaries of the convention. The second group is the heading relation, which separates nearly anti-parallel from nearly parallel headings. The third group is collision possibility. It has two parts. The speed set of the own vessel must intersect the collision cone of the target vessel. The relative speed must also close the current center distance in time.

1 The forward sector has a half-angle of 5° and the side sectors end at 112.5° . The overtaking band has a
 2 half-angle of 67.5° . The occupancy of the target vessel is inflated by three times its length, and the check
 3 horizon is 420 s.

4 Four situations carry an obligation. More than one of their predicates can hold at the same instant,
 5 so the four are tested in a fixed priority order and the first match wins. The rows below are written in that
 6 priority order, which is not the order of the indices,

$$\begin{aligned} \rho_2 \text{ head-on : } & \text{CP} \wedge \text{Fr}(s_e, s_m) \wedge \text{Ap}, \\ \rho_3 \text{ crossing : } & \text{CP} \wedge \text{Ri}(s_e, s_m) \wedge \text{TI}, \\ \rho_4 \text{ overtaking : } & \text{CP} \wedge \text{Be}(s_m, s_e) \wedge (v_e > v_m) \wedge \text{Sd}, \\ \rho_1 \text{ stand-on : } & [\text{CP} \wedge \text{Le}(s_e, s_m) \wedge \text{Tr}] \vee \rho_4(s_m, s_e), \end{aligned} \quad (3)$$

7 and all other cases fall into ρ_0 . Stand-on is tested last, and its definition reuses the overtaking predicate
 8 with the two vessels exchanged. Overtaking and being overtaken swap the two vessel arguments, because
 9 overtaking places the own vessel in the aft sector of the target vessel. The indices ρ_0 to ρ_5 are identifiers
 10 rather than a ranking.

11 Entry into a give-way situation has two parts. A give-way predicate must not hold now. It must
 12 hold at every decision step of a 60 s reaction window under constant-velocity extrapolation. The first part
 13 separates “about to hold” from “already holds”, and it creates one asymmetry that Section 4.3.3 treats. The
 14 emergency situation is entered by a stronger set-based prediction with a horizon of 180 s.

15 **Compliant control set.** Each situation maps to an explicit constraint set on the command,

$$U_{\text{colregs}}(\rho) = \begin{cases} U_{\text{box}}, & \rho = \rho_0, \\ \{|a| \leq \epsilon_a\} \cap \{|\omega| \leq \epsilon_\omega\}, & \rho = \rho_1, \\ \{\omega \leq -\omega_{\text{turn}}\}, & \rho \in \{\rho_2, \rho_3\}, \\ \{\omega \leq -\omega_{\text{turn}}\} \text{ or } \{\omega \geq +\omega_{\text{turn}}\}, & \rho = \rho_4, \\ U_{\text{box}}, & \rho = \rho_5. \end{cases} \quad (4)$$

16 Head-on and crossing require a turn to starboard. Overtaking allows a turn to either side. Stand-on holds
 17 course and speed. Each set is a half-plane or an interval on the plane of control commands. A set of this
 18 shape can be entered by projection, so the commands never have to be enumerated.

19 **Quantifying a readily apparent action.** The convention asks a give-way action to be large enough to be
 20 seen in time. We quantify this as a course change of at least a given threshold within the maneuver window.
 21 With a window of 40 s and a threshold of 20° ,

$$\omega_{\text{turn}} = \frac{\Delta_{\text{lt}}}{T_M} = \frac{20^\circ}{40 \text{ s}} \approx 0.008727 \text{ rad/s}. \quad (5)$$

22 This is the smallest compliant turn rate. Any turn at least this large complies, and the bound cannot be
 23 lowered.

24 The predicate structure and the numerical thresholds follow the temporal-logic formalization of
 25 the maritime rules (Krasowski and Althoff 2024). Three details are settled here. The inflation radius and
 26 the half-width of the speed set are stated explicitly. Entry into a give-way situation is made symmetric
 27 (Section 4.3.3). The predicate set is then mapped to a constraint set on continuous commands.

28 4.2 Safe Control Set and Projection

29 4.2.1 One-Step Collision-Free Constraint

30 At each decision step the applied command must keep the two hulls apart at the end of the next step. Written
 31 directly, that condition is not convex. We replace it by a convex subset of itself, built in three steps.

First, the occupancy of the target vessel after one step is over-approximated by a disk. The center follows a constant-velocity extrapolation, and the radius includes a safety margin. The own vessel is over-approximated by its circumscribed circle. The two hulls then stay apart whenever the center distance is at least the sum of the two radii, written d_{safe} .

Second, let n be the unit vector from the target vessel to the nominal end point of the own vessel, and let δ be that distance. The end point follows from the policy command clipped to the action box.

Third, the end point is expanded to first order in the command, $p_e(u) \approx p_{\text{nom}} + J(u - u_{\text{nom}})$. The end point must lie on the safe side of the separating hyperplane. This gives one linear inequality in the command:

$$\underbrace{-n^\top J u}_{g^\top} \leq \underbrace{-(d_{\text{safe}} - \delta + n^\top J u_{\text{nom}})}_h, \quad U_{\text{cf}}(s) = \{u : g^\top u \leq h\}. \quad (6)$$

A first-order expansion is neither an inner nor an outer approximation. The sign of the remainder changes with the curvature. Equation (6) alone therefore does not establish conservatism. The margin inside the safety distance is what does. With that margin the constraint acts at a center distance of 590–840 m, with a median of 714 m over this library. Hull contact needs a much smaller distance. The margin absorbs the linearization residual. The cost is a tighter constraint that rejects some commands which are in fact safe.

The linearization holds only locally. In the far field a sufficient condition is available that does not rely on it.

Proposition 1 (One-step collision freedom in the far field). *Let d be the center distance between the own vessel and a single target vessel. If*

$$d \geq d_{\text{safe}} + v_{\text{obs,max}} \Delta t + \rho_{\text{ego}}, \quad (7)$$

then the two conservative circumscribed occupancies do not intersect after one decision step. Here d_{safe} is the sum of the two circumscribed radii, and ρ_{ego} is the largest displacement of the own vessel in one step.

Assumptions. A single target vessel. The speed of the target vessel is at most 9.5 m/s. That bound is not implied by the dynamics and is stated separately; the largest value measured over the 2,000 scenarios of the library is 7.10 m/s. The target vessel holds its speed within the step.

Proof sketch. By the triangle inequality, the center distance after the step is at least d minus the one-step displacement bound of each vessel. It is therefore at least d_{safe} .

Scope. The triangle inequality does not depend on direction, so a head-on encounter is the worst case. With the constants of this library the threshold is about 764 m. The statement covers one step. It does not extend to the steps after it, and it does not cover the near field.

4.2.2 Projection as a Quadratic Program

The safe control set is the intersection of three sets,

$$U_{\text{safe}}(s, \rho) = U_{\text{box}} \cap U_{\text{colregs}}(\rho) \cap U_{\text{cf}}(s), \quad (8)$$

and it is a convex polygon in $\mathbb{R}^2$. The applied command is the Euclidean projection of the policy command onto that set,

$$u_{\text{safe}} = \Pi_{U_{\text{safe}}}(u_{\text{policy}}) = \arg \min_{u \in U_{\text{safe}}} \|u - u_{\text{policy}}\|_2^2. \quad (9)$$

The feasible set is an intersection of half-planes, so it can be written as $U_{\text{safe}} = \{u : Au \leq b\}$. The first four rows are the action box, the fifth is the compliant-direction half-plane, and the sixth is the collision-free constraint of Equation (6). The program has two variables and at most six constraints. It is small enough to solve online at every decision step.

Proposition 2 (Directional compliance on every give-way step). *Consider any decision step that the rule state machine assigns to a give-way situation and on which the projection is feasible. The applied command u_{safe} then lies in the compliant-direction half-plane.*

Assumptions. A single target vessel, and a correct decision by the state machine. The second assumption inherits one conservative bias of the collision-possibility predicate. That predicate uses the center distance, and it can miss a trailing encounter in which the two speeds are close.

Proof sketch. The compliant half-plane enters the quadratic program as a hard constraint. Any feasible point satisfies it, and the projection returns a feasible point. The statement holds by construction. It does not depend on the training outcome or on the random seed.

Scope. Emergency situations are not covered, because their branch bypasses the compliance constraint by design. Steps on which the safe control set is empty and the fallback is used are not covered either.

4.2.3 Fallback and the Unavoidable-Collision Criterion

When the safe control set is empty, the projection has no solution. A substitute rule then supplies the command. We call it the fallback, and it carries no guarantee. The fallback branches on the encounter situation. It does not try a fixed list of options in order. The two branches below are mutually exclusive.

Emergency branch. An emergency situation takes a separate path. No collision-free constraint is built, and Equation (9) is not solved. A stateful geometric controller supplies the command instead, and its lifetime is one emergency event. It has three modes. A near head-on approach ahead is handled by tracking a fixed lateral point fixed at the onset of the emergency. A target vessel astern that can be cleared by acceleration is handled by a straight-line escape inside the reaction window. Every other case tracks a point that moves with the target vessel. One position-tracking law converts all three into a control command. This controller offers no guarantee. Its purpose is a defined behavior once no compliant feasible command remains.

Other situations. Outside an emergency situation the fallback is used only when the safe control set is empty. A degenerate case is tested first. If the linearization gives no usable separation direction, the command is projected onto the action box alone. Otherwise the direction constraint is relaxed, and the collision risk is minimized if that also fails. The last two branches solve on the actuator limits and drop the compliance constraint as a whole. The turn rate can then leave the policy action box, so saturation is reported against each box separately.

These branches are needed in the implementation, and on the scenario library used here they almost never fire. If the own vessel holds course and speed, the median closest center distance to the target vessel is about 1,300 m. The safe control set is therefore rarely empty. Purpose-built conflict cases are constructed so that the branches are exercised, and their outcome is reported with the shield measurements.

The emergency branch offers no guarantee. It can still decide whether the situation was already beyond recovery.

Proposition 3 (Conservative criterion for an unavoidable collision). *Consider a single target vessel at constant velocity. Let $R_{\text{box}}(t)$ be an over-approximation of the reachable centers of the own vessel, and let $O(t)$ be the hull rectangle of the target vessel. If*

$$\exists t^* \in [0, T] : R_{\text{box}}(t^*) \subseteq (O(t^*) \oplus \text{disk}(r_{\text{insc}})), \quad (10)$$

then the collision is unavoidable, and every feasible control sequence meets that target vessel at t^ .*

Assumptions. A single target vessel at constant velocity. The hull size of the target vessel must not be overstated, since a beam larger than the true value makes the test unreliable. The horizon is 120 s, evaluated at 241 equally spaced instants.

Proof sketch. The rate of change of the velocity vector is bounded. A double integration gives the two semi-axes of R_{box} , which therefore over-approximates the true reachable centers. The inscribed circle under-

approximates the hull. Once every reachable center lies inside the inflated occupancy of the target vessel, no control command can avoid contact.

Scope. The criterion is one-sided. It can miss a case, and it never raises a false alarm. A negative result therefore does not mean that the collision is avoidable. The criterion also acts late rather than early, and maneuvering target vessels are not covered. On 20,000 random scenarios and 735 selected scenarios it produced no false positive. After the envelope was hardened, 1,500 further fuzz cases produced none either.

4.3 Shielded Policy Optimization

The shield is not applied after the policy as a post hoc correction. The projection of Equation (9) is placed inside the environment transition. The policy emits u_{policy} , the environment applies u_{safe} , and it returns the successor state and the reward. The policy therefore faces the composed transition

$$s_{t+1} \sim P(\cdot \mid s_t, \Pi_{U_{\text{safe}}(s_t, \rho_t)}(u_t)), \quad u_t \sim \pi(\cdot \mid s_t), \quad (11)$$

rather than the $P(\cdot \mid s_t, u_t)$ of a post hoc filter. The policy learns on the transition it will actually meet, so it adapts to the projection during training instead of meeting an unfamiliar filter afterwards.

Learning algorithm. All configurations are trained with proximal policy optimization (Schulman et al. 2017). The continuous-action configurations use its standard form. The discrete-action baselines use its maskable variant, because action masking is what makes a discrete shield possible. Both action spaces therefore share one policy-gradient algorithm, which removes a source of difference between them. The masking itself remains a difference, and it is intrinsic to the discrete method rather than a choice made here.

4.3.1 Reward Function

The reward is a sum of five terms,

$$r = r_{\text{sparse}} + r_{\text{goal}} + r_{\text{velocity}} + r_{\text{deviate}} + r_{\text{colregs}}. \quad (12)$$

A sparse terminal term scores arrival, timeout, stalling, and collision, and it charges a fixed penalty for every step that enters emergency control. A dense approach term rewards the change in distance to the goal over one step. A speed term penalizes speed outside the cruise band [2.5, 8.0] m/s. A cross-track term penalizes lateral deviation from the start-to-goal line and saturates at 2,000 m. A soft compliance term decays with distance. It is active only in the reward-shaping baseline and in the discrete configurations. Every continuous configuration here sets it to zero, because compliance is carried by the hard constraint of Equation (4).

The five terms are taken from (Krasowski and Althoff 2024), with three deviations that we declare. The approach term uses the difference of distances between two steps. The soft compliance term is rescaled, because its original calibration is set at a scale about fifty times smaller than the scenarios used here. One clause of the emergency-release test is read by its physical meaning rather than by its literal sign, since the two disagree.

4.3.2 Bounded Action Distribution

A continuous policy usually emits an unbounded Gaussian and clips the sample to the action box before it reaches the environment. That combination conflicts with Equation (9), for two reasons that both come from the clipping. First, common implementations feed the clipped action to the environment but the unclipped action to the policy gradient. Once the mean leaves the box, moving further out changes no reward, the gradient reaches a plateau, and any penalty on action smoothness loses its grip. Second, the differential entropy of a Gaussian has no upper bound, while the entropy coefficient is a constant. The standard deviation therefore has a one-way channel to grow. Its growth pushes still more samples outside the box.

We use a Beta distribution with support on a closed interval. Actions can then never leave the box, clipping becomes the identity map, both channels close, the smoothness penalty is differentiable everywhere,

and the entropy is bounded above. The network emits two reals per control axis, and

$$\alpha = \text{softplus}(\tilde{\alpha}) + 1, \quad \beta = \text{softplus}(\tilde{\beta}) + 1, \quad u = u_{lo} + (u_{hi} - u_{lo})z, \quad z \sim \text{Beta}(\alpha, \beta) \quad (13)$$

gives the shape parameters and the applied action. Evaluation uses the mode instead of a sample. The offset of one keeps both shape parameters above unity, and that constraint cannot be dropped. Below unity the Beta density is U-shaped and diverges at the two ends, and the mode then sits at an endpoint. Because evaluation always takes the mode, such a policy would silently corrupt every reported number, and the aggregate metrics would give no sign of it.

4.3.3 Symmetric Entry into Give-Way Situations

In the state machine, entry into a give-way situation is not symmetric. From the conflict-free situation it is triggered only by the persistence condition. From the stand-on situation a separate immediate condition also applies. We add the symmetric branch. When the persistence condition does not fire, the immediate condition is checked, and the give-way situation is entered if it already holds. The obligation is then recognized at the same moment on both routes. The change alters the command that the shield applies, so training and evaluation must use the same setting.

A purpose-built case shows why the branch is needed. Suppose an encounter already satisfies a give-way predicate at the initial instant. The clause “does not hold now” can then never be satisfied. The persistence condition never fires, and the encounter is never recognized as a give-way situation. On a set of such adversarial cases the persistence route alone gives 0 give-way decision steps. With the immediate branch it gives 201. These cases are synthetic and illustrate the mechanism, so they are reported apart from the main results.

4.3.4 Training Setup

Apart from the entropy coefficient, which is set to 0.01, and the bounded action distribution, every hyperparameter takes the default of the implementation library and is left untuned. The libraries are Stable-Baselines3 2.3.2 (Raffin et al. 2021) and sb3-contrib 2.3.0, and the advantage is computed by generalized advantage estimation (Schulman et al. 2016). The discrete and continuous configurations agree on every one of these values, so the hyperparameters are not a source of difference between them. Running normalization of the observation and the reward is not optional. Without it the large-scale approach term in Equation (12) drives the policy to a degenerate solution that holds station.

5 EXPERIMENTS

5.1 Scenarios and Configurations

The experiments use the two-vessel encounter library of the CommonOcean benchmark (Krasowski and Althoff 2022), which holds 2,000 scenarios. Each scenario fixes the initial pose and speed of the controlled vessel. It also fixes the initial state and the planned track of the target vessel. It ends with a goal region that has a position gate, a heading gate, and a time limit. The encounter geometry is generated programmatically over a range of relative bearings, crossing angles, and closing speeds. Target vessels are 200 to 300 m long, and an episode lasts at most 170 decision steps.

Classifying the library by the geometric predicates returns crossing and head-on only. **The library contains no overtaking scenario**, and the official test set holds 395 crossing and 205 head-on cases. The overtaking branch of Equation (4) therefore cannot be tested empirically here. The conclusions state this.

The official split of 1,400 training and 600 test scenarios is used. The training side is split again into 1,300 for training and 100 for validation. The validation set is used only for monitoring during training and for selecting a checkpoint. The test set is never accessed during training or tuning. An independent recount confirmed that the two sets are disjoint, so the evaluation sample size is 600.

Table 1 lists nine configurations. They form one connected ladder, and each level changes a single variable from the level before it. The contribution of each mechanism can therefore be read on its own.

TABLE 1 The nine configurations and the single-variable ladder

Configuration	Cont.	Shield	Masking	Soft rew.	Shaping	Bounded	Sym. entry
Discrete baseline	×	×	×	×	×	-	-
Discrete, soft reward	×	×	×	✓	×	-	-
Discrete, masking	×	×	✓	✓	×	-	×
Continuous, no shield	✓	×	×	×	×	×	×
Continuous, shield	✓	✓	×	×	×	×	×
Ablation reference	✓	✓	×	×	✓	×	×
Ablation, bounded only	✓	✓	×	×	✓	✓	×
Ablation, symmetric only	✓	✓	×	×	✓	×	✓
Full method	✓	✓	×	×	✓	✓	✓

Notes. A check mark is on, a cross is off, and a dash is not applicable. Rows are ordered along the ladder, and each row differs from its neighbor by one variable. Three steps carry a companion variable that cannot be separated. The action space changes together with the policy distribution, the continuous-only shaping is a bundle of four items, and the bounded distribution also changes the initial exploration scale. Those three steps can only be attributed as a whole.

What the unshielded continuous configuration can show. A continuous-action configuration without a shield can only take the plainest form, namely an unbounded Gaussian, an asymmetric give-way entry, and no shaping. Giving it the continuous-only shaping would break the symmetry with the discrete baseline, and the attribution would fail. The unbounded Gaussian is also the form that pushes many samples past the action box. A small re-evaluation was run during the exploration phase, and that setting is not the one used in the formal experiment. About 73% of the decision steps of that policy sat against the boundary of the action box. The gain attributed to the shield is therefore measured against the weakest form of continuous action. For the same reason the step from the discrete baseline to that configuration can be negative, and it should be read as a conservative lower bound.

5.2 Metrics and Evaluation Protocol

Metrics. The main metrics are the arrival rate, the collision rate, the COLREGs violations per episode, the share of steps under emergency control, and the episode duration. The violation count is split into give-way and stand-on violations. Control quality, safety margin, shield behavior, and the single-step solve time are also reported. Every metric is broken down by encounter situation as well. The reward function differs across configurations, so the episode return is never compared across them.

How violations are counted. Violations do not come from the situation decision of the shield. They come from an offline scorer that is independent of the shield. The scorer sees only the trajectory. At each step it re-decides, from the bare situation predicates, whether the own vessel is under a stand-on or a give-way obligation. A stand-on violation is counted per step, once the signed heading change accumulated over the obligation period exceeds the stand-on tolerance, and the accumulator is reset when the obligation ends. A give-way violation is counted per encounter, and an encounter counts as a violation only when no turn in the required direction ever reaches the readily apparent threshold. The scorer applies one rule to this method and to every baseline, including the geometric controllers that have no state machine, so the comparison is made under one condition.

The counting window and the shield do not coincide. The scorer accumulates the heading change over a whole obligation period, while the shield constrains the change inside a single maneuver window. The two windows have different lengths. Emergency situations and steps that fall back also bypass the compliance constraint by design. The shield therefore does not guarantee a violation count of zero, and this paper does not claim one. In particular, Proposition 2 guarantees the turn direction on every give-way step. It does **not**

1 imply a give-way violation count of zero. How often the mismatch occurs was not measured.

2 **Training budget.** Each configuration is trained with 8 random seeds, one run per seed. The 72 runs together
 3 cover about 730 million environment steps. The scenario split is fixed by a separate seed, so every run sees
 4 the same scenarios. Every configuration inside one table is evaluated on one machine in one pass, so that
 5 machine differences do not enter the evaluation. Machine time did not allow the same during training. For
 6 5 of the 8 seeds all configurations were trained on one machine, and the other 3 seeds are spread over two
 7 or three machines. Those machines run the same image and the same training code, with a byte-identical
 8 fingerprint of the training path, and with the thread count locked to one. **No bit-level cross-machine check**
 9 **was run on this batch, so machine differences are not excluded. This is listed as a limitation.**

10 **Checkpoint selection.** Twenty checkpoints are saved per run at even intervals, and each is evaluated once
 11 on the validation set. The selection rule was fixed in advance and has no tunable part. The candidates are
 12 those twenty checkpoints, the criterion is the highest arrival rate on the validation set, ties go to the earlier
 13 checkpoint, and the test set is never touched. **The rule is itself biased, so two versions are reported.**
 14 The validation set holds only 100 scenarios, and the binomial standard error of the arrival rate is about 4
 15 points. Taking the maximum over 20 candidates lifts the reported value by about 7.5 points in expectation.
 16 That is four times the drift of about 1.6 points that the same-machine rule was written to prevent. The
 17 best-checkpoint version and the last-checkpoint version are therefore both reported.

18 **Reading the figures.** Unless a caption says otherwise, every figure in this section is computed on the 100
 19 validation scenarios. That is not the test set used in Table 2. Violation counts in the figures are the sum of
 20 stand-on and give-way violations.

21 **Statistics.** The paired test is a per-seed paired sign test. With 8 seeds the smallest two-sided value it can
 22 reach is $p = 2/2^8 = 0.0078$. Error bars are bootstrap 95% intervals resampled over seeds. A run counts as
 23 converged when its arrival rate on the validation set reaches 50%. Diverged seeds are counted in the main
 24 table as they are, and a converged-seeds-only version is also reported.

25 5.3 Main Comparison

TABLE 2 Main comparison, all seeds. Values are provisional and come from the validation set. The table is replaced after the re-evaluation on the test set.

Configuration	n	Conv.	Arrival % [CI]	Coll. %	Viol./ep.	Turn Δ	Thr. Δ	Emerg. %
Discrete baseline	8	8/8	97.0 [96, 98]	3.00	2.52	0.0139	0.0210	0.00
Discrete, soft reward	8	7/8	96.5 [94, 98]	2.50	2.41	0.0139	0.0215	0.00
Discrete, masking	8	6/8	92.5 [11, 94]	0.00	1.01	0.0121	0.0263	4.90
Continuous, no shield	8	7/8	97.0 [94, 98]	2.50	4.06	0.0248	0.0134	0.00
Continuous, shield	8	5/8	78.5 [6, 88]	0.00	0.93	0.0213	0.0267	2.49
Ablation reference	8	5/8	86.0 [3, 88]	0.00	1.09	0.0142	0.0109	3.84
Ablation, bounded	8	7/8	86.0 [50, 91]	0.00	0.52	0.0087	0.0176	1.97
Ablation, symmetric	8	5/8	75.5 [0, 82]	0.00	0.77	0.0150	0.0143	3.02
Full method	8	8/8	88.5 [81, 92]	0.00	0.49	0.0085	0.0193	2.56

Notes. The best value in each column is in bold. The turn and throttle increment columns are **not** marked, because they cannot be compared across action spaces (Section 4.3.4). The share of emergency steps is descriptive and is neither good nor bad.

26 Table 2 is also reported in a converged-seeds-only version. A diverged seed pollutes the per-episode
 27 averages, and the direction of that pollution differs by configuration, so both versions are given. The key
 28 difference is [TBD]. Per-seed raw values accompany the table.




Figure 1 Safety and efficiency. Points are medians across seeds and error bars are bootstrap 95% intervals resampled over seeds. The lower right of panel (a) is the ideal region. The bars are wide because every configuration contains a diverged seed.

5.4 Ablation Study

The four ablation configurations form a complete 2×2 design over the bounded action distribution and the give-way entry. Everything else is identical, and the comparison is paired by seed. The bounded distribution lowers the median turn increment by 39%, with 7 of 8 seeds moving in the same direction and a paired signed-rank value of $p = 0.016$. It lowers the violations per episode by 53%, with $p = 0.016$. The symmetric entry alone leaves the turn increment unchanged, at +5% with $p = 0.38$, and it still lowers the violations per episode by 30%. With both changes on, the turn increment and the violations fall by 40% and 55%. Neither can be separated statistically from the bounded distribution alone, at $p = 1.0$ and $p = 0.45$. The two changes therefore divide the work. Smoothness comes almost entirely from the bounded action distribution, and both contribute to compliance.

This group is the only place where the smoothness result can be read. All four configurations run the same action-increment penalty, so the difference can be attributed to the bounded action distribution rather than to an extra reward term. A comparison against the discrete baseline would not be valid here, because that penalty applies to a quantity the discrete configurations do not have. Adding the bounded distribution also carries a companion variable, since the initial exploration scale differs by about a factor of 2.5 on the acceleration axis. A converged-seeds-only version is given for this group as well.

5.5 Training Reliability and Sample Efficiency

Figure 3 is taken from training. It answers two questions that do not need the re-evaluation, namely whether the shield costs learning speed, and how many seeds of each configuration reach a working policy.

First, there is a cost, and it appears in learning speed. The two shielded continuous configurations trail the unshielded discrete baseline over the first 4 million steps, and their arrival rate catches up only near 8 million steps (Figure 3a). Panels (b) and (c) give what is bought. The unshielded configurations hold a collision rate of 2 to 4% and more than 2.4 violations per episode throughout training. The shielded configurations sit against a collision rate of zero and near 0.5 violations per episode. The shield removes risk from the outcome, and it narrows the exploration space at the same time. Slower learning is the direct consequence of that narrowing.

Second, reliability differs a great deal among the shielded configurations. Under the convergence




Figure 2 Contribution of the two changes, as a 2×2 ablation paired by seed. Bars are medians across seeds and error bars are bootstrap 95% intervals. Above each bar are the change relative to the leftmost bar, the paired signed-rank result, and the number of seeds that moved in the same direction. The arrival rate is bimodal, so it is drawn as a box plot.

1 rule declared in advance, all 8 seeds of the full method reach a working policy, and it is the only shielded
2 configuration for which this holds. The shielded ablation configurations reach 5 to 7 seeds, and the discrete
3 safe baseline reaches 6 (Figure 3d). The two changes therefore improve more than the final numbers. They
4 also lower the chance that training itself fails. Diverged seeds are counted as they are, and a converged-
5 seeds-only version is given.
6 **A counterexample that has to be stated.** Among the 48 shielded runs, 46 have a collision rate of exactly
7 zero on the validation set, and 2 do not, at 1% and 2%. This agrees with the scope statements of Section 4.
8 The guarantees by construction cover one-step collision freedom in the far field and the turn direction on
9 give-way steps. They do not cover emergency situations or the fallback. A collision rate of zero is therefore
10 an observation and not a guarantee.

11 5.6 Behavior of the Safety Shield

12 The emergency branch is the only part of this method that offers no guarantee, so how often it is used and
13 what follows from its use are reported separately. At the end of training, the projection produced 93.6% of
14 the control commands. The emergency controller produced 6.2%, and the three fallback branches produced
15 0.22% in total (Figure 4a). On the evaluation side the share of emergency steps is 2.6%, against 4.9% for
16 the discrete safe baseline. The fallback is rare because it is used only when the safe control set is empty,
17 and that seldom happens outside an emergency situation. The distribution of collisions by the source of the
18 command is [TBD]. If every collision falls under emergency control, then collisions occur on steps where
19 the last resort had already been engaged and had failed. Those steps lie outside the scope of Proposition 1
20 by definition, since that proposition covers the far field, non-emergency, single-step case. This is not a
21 counterexample to it, but it does confirm that the emergency branch is an empirical fallback.

22 The size of the projection correction is normalized by the half-width of the action box. At the end
23 of training its median is 0.082 and its interquartile range is [0.065, 0.102]. The gap between the command
24 of the policy and what the rules require therefore stays within about a tenth of the control range. It also
25 narrows monotonically during training (Figure 4c). The correction is largest for the symmetric-entry-only
26 configuration, at 0.093, and smallest for the bounded-distribution-only configuration, at 0.066. That ordering
27 matches the turn increments in Figure 2. The full distribution of this quantity is [TBD].




Figure 3 Sample efficiency and training reliability. Thick lines are medians and shaded bands are interquartile ranges over converged seeds only, because a diverged seed pulls the band to zero. Panel (d) counts all eight seeds. The ablation configurations are compared in Figure 2 instead.

5.7 Comparison with External Baselines

Three geometric collision-avoidance controllers that need no training are run through the same evaluation pipeline, on the same test set, at the same sample size (Table 3). The question here is not whether a learning method is stronger. It is which dimensions a geometric method already covers.

The answer narrows the defensible claim to one dimension. The collision rate does not separate the two families, since the control barrier function filter also reaches 0.00% on this test set. The arrival rate and the smoothness columns are governed by the type of terminal constraint and by the control range, and neither supports a reading in favor of this paper. The real difference is in COLREGs violations, and almost all of it comes from stand-on violations. These controllers aim only at avoiding contact, so they keep maneuvering during periods in which the rules require course and speed to be held. Violations are decided by the offline scorer from the bare situation predicates, so the comparison is made under one condition. The claim of this paper against geometric methods rests on this dimension alone, and the specific difference is [TBD].

REFERENCES

- Alshiekh, Mohammed, Roderick Bloem, Rüdiger Ehlers, Bettina Könighofer, Scott Niekum, and Ufuk Topcu. 2018. “Safe Reinforcement Learning via Shielding.” In *Proceedings of the AAAI Conference on Artificial Intelligence*.
- Ames, Aaron D., Samuel Coogan, Magnus Egerstedt, Gennaro Notomista, Koushil Sreenath, and Paulo Tabuada. 2019. “Control Barrier Functions: Theory and Applications.” In *European Control Conference (ECC)*, 3420–3431.
- Benjamin, Michael R., John J. Leonard, Joseph A. Curcio, and Paul M. Newman. 2006. “A Method for Protocol-Based Collision Avoidance Between Autonomous Marine Surface Craft.” *Journal of Field Robotics* 23 (5): 333–346.




Figure 4 Behavior of the shield during training. In panel (d) the angle is the sector in which the convention defines each situation, not the measured bearing distribution of target vessels, and the radius is logarithmic. This figure is collected during training rather than at evaluation.

TABLE 3 External geometric baselines, without training and without seeds, on the official test set of $N = 600$

Method	Control range	Arrival %	Coll. %	COLREGs violations / episode			Turn Δ	Jerk
				Total	Give-way	Stand-on		
Control barrier function	Policy range	70.17	0.00	4.95	0.47	4.48	0.00242	0.171
	Policy range, margin	69.83	0.00	4.49	0.45	4.04	0.00235	0.167
	Actuator limits	69.33	0.00	6.48	0.52	5.97	0.00058	0.050
PD controller	Policy range	58.83	18.00	9.79	0.44	9.35	0.00492	0.310
	Actuator limits	57.67	16.67	8.10	0.63	7.47	0.00032	0.040
Velocity obstacle	Policy range, margin	57.00	0.00	8.20	0.50	7.70	0.00425	0.279
	Actuator limits	42.67	0.00	8.06	0.68	7.38	0.00128	0.071
Full method (this paper)	Policy range	(see Table 2)						

Notes. The three baselines are not trained and have no seed. Each is reported at its own best setting, and the set used for tuning is disjoint from the set used here. Two control ranges are reported. The policy range is the same authority as the policy of this paper, at ± 0.048 and ± 0.018 , and the actuator limits are ± 0.24 and ± 0.03 . Both are reported so that a difference in authority is not a confounder. **The arrival rate is not a measure of collision avoidance.** The nominal law of a geometric controller has no terminal alignment stage. These controllers reach the goal position in 96.8% to 99.7% of episodes and then fail the terminal heading gate.

- 1 Cheng, Yin, and Weidong Zhang. 2018. “Concise Deep Reinforcement Learning Obstacle Avoidance for
2 Underactuated Unmanned Marine Vessels.” *Neurocomputing* 272: 63–73.
- 3 Chou, Po-Wei, Daniel Maturana, and Sebastian Scherer. 2017. “Improving Stochastic Policy Gradients in
4 Continuous Control with Deep Reinforcement Learning Using the Beta Distribution.” In *Proceed-*
5 *ings of the International Conference on Machine Learning (ICML)*.
- 6 Chun, D.-H., M.-I. Roh, H.-W. Lee, J. Ha, and D. Yu. 2021. “Deep Reinforcement Learning-Based Collision
7 Avoidance for an Autonomous Ship.” *Ocean Engineering* 234: 109216.
- 8 Dalal, Gal, Krishnamurthy Dvijotham, Matej Vecerik, Todd Hester, Cosmin Paduraru, and Yuval Tassa.
9 2018. “Safe Exploration in Continuous Action Spaces.” arXiv:1801.08757.
- 10 De Lellis, Francesco, Marco Coraggio, Giovanni Russo, Mirco Musolesi, and Mario di Bernardo. 2024.
11 “Guaranteeing Control Requirements via Reward Shaping in Reinforcement Learning.” *IEEE*
12 *Transactions on Control Systems Technology*. arXiv:2311.10026.
- 13 Eriksen, Bjørn-Olav H., Morten Breivik, Erik F. Wilthil, Andreas L. Flåten, and Edmund F. Brekke. 2019.
14 “The Branching-Course Model Predictive Control Algorithm for Maritime Collision Avoidance.”
15 *Journal of Field Robotics* 36.
- 16 Fossen, Thor I. 2011. *Handbook of Marine Craft Hydrodynamics and Motion Control*. Chichester: John
17 Wiley & Sons.
- 18 García, Javier, and Fernando Fernández. 2015. “A Comprehensive Survey on Safe Reinforcement Learn-
19 ing.” *Journal of Machine Learning Research* 16: 1437–1480.
- 20 Grover, Jaskaran, Changliu Liu, and Katia Sycara. 2023. “The Before, During, and After of Multi-Robot
21 Deadlock.” *International Journal of Robotics Research*. arXiv:2206.01781.
- 22 Heiberg, Amalie, Thomas Nakken Larsen, Eivind Meyer, Adil Rasheed, Omer San, and Damiano Varagnolo.
23 2022. “Risk-Based Implementation of COLREGs for Autonomous Surface Vehicles Using Deep
24 Reinforcement Learning.” *Neural Networks* 152: 17–33. arXiv:2112.00115.
- 25 Huang, Yamin, Linying Chen, and P. H. A. J. van Gelder. 2019. “Generalized Velocity Obstacle Algorithm
26 for Preventing Ship Collisions at Sea.” *Ocean Engineering* 173: 142–156.
- 27 IMO (International Maritime Organization). 1972. *Convention on the International Regulations for Pre-*
28 *venting Collisions at Sea (COLREGs)*. London: IMO.
- 29 Johansen, Tor A., Tristan Perez, and Andrea Cristofaro. 2016. “Ship Collision Avoidance and COLREGS
30 Compliance Using Simulation-Based Control Behavior Selection with Predictive Hazard Assess-
31 ment.” *IEEE Transactions on Intelligent Transportation Systems* 17 (12): 3407–3422.
- 32 Kim, Kyungmin, Davide Corsi, Andoni Rodríguez, JB Lanier, Benjamí Parellada, Pierre Baldi, César
33 Sánchez, and Roy Fox. 2024. “Realizable Continuous-Space Shields for Safe Reinforcement Learn-
34 ing.” arXiv:2410.02038.
- 35 Kochdumper, Niklas, Hanna Krasowski, Xiao Wang, Stanley Bak, and Matthias Althoff. 2023. “Provably
36 Safe Reinforcement Learning via Action Projection Using Reachability Analysis and Polynomial
37 Zonotopes.” *IEEE Open Journal of Control Systems* 2.
- 38 Krasowski, Hanna, and Matthias Althoff. 2022. “CommonOcean: Composable Benchmarks for Mo-
39 tion Planning on Oceans.” In *Proceedings of the IEEE International Conference on Intelligent*
40 *Transportation Systems (ITSC)*, 1676–1682. DOI: 10.1109/ITSC55140.2022.9921925. <https://commonocean.cps.cit.tum.de/>.
- 41 Krasowski, Hanna, and Matthias Althoff. 2024. “Provable Traffic Rule Compliance in Safe Reinforce-
42 ment Learning on the Open Sea.” *IEEE Transactions on Intelligent Vehicles* 9 (12): 7617–7634.
43 arXiv:2402.08502.
- 44 Kufoalor, D. K. M., Tor A. Johansen, Edmund F. Brekke, A. Hepsø, and K. Trnka. 2020. “Autonomous
45 Maritime Collision Avoidance: Field Verification of Autonomous Surface Vehicle Behavior in Chal-
46 lenging Scenarios.” *Journal of Field Robotics* 37.
- 47 Kuwata, Yoshiaki, Michael T. Wolf, Dimitri Zarghitsky, and Terrance L. Huntsberger. 2014. “Safe Maritime
48

- 1 Autonomous Navigation with COLREGS, Using Velocity Obstacles.” *IEEE Journal of Oceanic*
2 *Engineering* 39 (1): 110–119.
- 3 Lee, Changyu, Jinwook Park, and Jinwhan Kim. 2025. “Efficient COLREGs-Compliant Collision Avoid-
4 ance Using Turning Circle-Based Control Barrier Function.” arXiv:2504.19247.
- 5 Markgraf, Hannah, Shambhuraj Sawant, Hanna Krasowski, Lukas Schäfer, Sébastien Gros, and Matthias
6 Althoff. 2026. “Safe Reinforcement Learning Using Action Projection: Safeguard the Policy or the
7 Environment?” *Transactions on Machine Learning Research*. arXiv:2509.12833.
- 8 Meyer, Eivind, Amalie Heiberg, Adil Rasheed, and Omer San. 2020. “COLREG-Compliant Collision
9 Avoidance for Unmanned Surface Vehicle Using Deep Reinforcement Learning.” *IEEE Access* 8.
10 arXiv:2006.09540.
- 11 Müller, Henrik, and Daniel Kudenko. 2025. “Improving the Effectiveness of Potential-Based Reward Shap-
12 ing in Reinforcement Learning.” In *Proceedings of the International Conference on Autonomous*
13 *Agents and Multiagent Systems (AAMAS)*. arXiv:2502.01307.
- 14 Müller, Marlon, Florian Finkeldei, Hanna Krasowski, Murat Arcak, and Matthias Althoff. 2026.
15 “Falsification-Driven Reinforcement Learning for Maritime Motion Planning.” *Ocean Engineer-*
16 *ing* 361: 125579. arXiv:2510.06970.
- 17 Ng, Andrew Y., Daishi Harada, and Stuart Russell. 1999. “Policy Invariance Under Reward Transforma-
18 tions: Theory and Application to Reward Shaping.” In *Proceedings of the International Conference*
19 *on Machine Learning (ICML)*, 278–287.
- 20 Oh, Donggeon David, Duy P. Nguyen, Haimin Hu, and Jaime F. Fisac. 2025. “Provably Optimal Reinforce-
21 ment Learning under Safety Filtering.” arXiv:2510.18082.
- 22 Patil, Mayur S., Nataraj Sudharsan, Veneela Ammula, Jude Tomdio, Jin Wang, Michael Kei, Sivaku-
23 mar Rathinam, and Prabhakar R. Pagilla. 2026. “COLREGs Compliant Collision Avoidance and
24 Grounding Prevention for Autonomous Marine Navigation.” arXiv:2603.02484.
- 25 Pizarro Bejarano, Federico, Lukas Brunke, and Angela P. Schoellig. 2025. “Safety Filtering While Train-
26 ing: Improving the Performance and Sample Efficiency of Reinforcement Learning Agents.” *IEEE*
27 *Robotics and Automation Letters*. arXiv:2410.11671.
- 28 Raffin, Antonin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann.
29 2021. “Stable-Baselines3: Reliable Reinforcement Learning Implementations.” *Journal of Machine*
30 *Learning Research* 22 (268): 1–8.
- 31 Sarhadi, Pouria, Wasif Naeem, and Nikolaos Athanasopoulos. 2022. “A Survey of Recent Machine
32 Learning Solutions for Ship Collision Avoidance and Mission Planning.” *IFAC-PapersOnLine*.
33 arXiv:2207.02767.
- 34 Schulman, John, Philipp Moritz, Sergey Levine, Michael I. Jordan, and Pieter Abbeel. 2016. “High-
35 Dimensional Continuous Control Using Generalized Advantage Estimation.” In *International Con-*
36 *ference on Learning Representations (ICLR)*.
- 37 Schulman, John, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. “Proximal Policy
38 Optimization Algorithms.” arXiv:1707.06347.
- 39 Shen, Haiqing, Hirotada Hashimoto, Akihiko Matsuda, Yuuki Taniguchi, Daisuke Terada, and Chen Guo.
40 2019. “Automatic Collision Avoidance of Multiple Ships Based on Deep Q-Learning.” *Applied*
41 *Ocean Research* 86: 268–288.
- 42 Trott, Alexander, Stephan Zheng, Caiming Xiong, and Richard Socher. 2019. “Keeping Your Distance:
43 Solving Sparse Reward Tasks Using Self-Balancing Shaped Rewards.” In *Advances in Neural In-*
44 *formation Processing Systems (NeurIPS)*.
- 45 Vaaler, Aksel, Svein Jostein Husa, Daniel Menges, Thomas Nakken Larsen, and Adil Rasheed. 2024.
46 “Modular Control Architecture for Safe Marine Navigation: Reinforcement Learning and Predictive
47 Safety Filters.” arXiv:2312.01855.
- 48 Wabersich, Kim P., and Melanie N. Zeilinger. 2021. “A Predictive Safety Filter for Learning-Based Control

- 1 of Constrained Nonlinear Dynamical Systems.” *Automatica* 129: 109597.
- 2 Zhao, Luman, and Myung-II Roh. 2019. “COLREGs-Compliant Multiship Collision Avoidance Based on
- 3 Deep Reinforcement Learning.” *Ocean Engineering* 191: 106436.