

Tutorial 7: DCGAN




Practical Deep Learning for Science
30 May, 2023



מכון ויצמן למדע
WEIZMANN INSTITUTE OF SCIENCE

- *Nilotpal*

GAN




Loss? It's a bit tricky...

Discriminator is a regular binary classifier



Binary Cross entropy loss


Generator loss?



AutoEncoder

Loss (input image, output image)

Generator loss?





AutoEncoder

Loss (input image, output image)

Generator loss?

No input image
Can't compute loss like in AE



Adversary

- ♦ Generator and Discriminator have exact opposite goal
- ♦ Will use the discriminator loss again
 - ➔ But we will flip the label. Label the generated images as 1 (real)
 - ➔ Want to increase the likelihood of the fake image being classified as real
- ♦ From the discriminator perspective
 - ➔ Classify real images as real, fake images as fake
- ♦ From Generator's perspective
 - ➔ Generate fake images that gets classified as real

GAN recipe

- ♦ Generate fake images
- ♦ Take real images
- ♦ Compute discriminator loss; [update discriminator](#)
- ♦ Label the fake images as real
- ♦ Compute discriminator loss; [update generator](#)

.detach()

During **discriminator training**, Torch will see **(Generator + Discriminator)** as **one big network**

Losses will get back propagated to generator as well



We need to detach the image from the generator with `fake_img.detach()`