

---

Upload your assignment here: [https://quera.org/course/add\\_to\\_course/course/12516/](https://quera.org/course/add_to_course/course/12516/)

Pass: Networks

---

Q1 For a communication session between a pair of processes, which process is the client and which is the server?

Q2 For a P2P file-sharing application, do you agree with the statement, “There is no notion of client and server sides of a communication session”? Why or why not?

Q3 Suppose you wanted to do a transaction from a remote client to a server as fast as possible. Would you use UDP or TCP? Why?

Q4 Recall that TCP can be enhanced with SSL to provide process-to-process security services, including encryption. Does SSL operate at the transport layer or the application layer? If the application developer wants TCP to be enhanced with SSL, what does the developer have to do?

Q5 Why do HTTP, SMTP, and POP3 run on top of TCP rather than on UDP?

Q6 Describe how Web caching can reduce the delay in receiving a requested object. Will Web caching reduce the delay for all objects requested by a user or for only some of the objects? Why?

Q7 Suppose Alice, with a Web-based e-mail account (such as Hotmail or Gmail), sends a message to Bob, who accesses his mail from his mail server using POP3. Discuss how the

message gets from Alice's host to Bob's host. Be sure to list the series of application-layer protocols that are used to move the message between the two hosts.

Q8 From a user's perspective, what is the difference between the download-and-delete mode and the download-and-keep mode in POP3?

Q9 Obtain the HTTP/1.1 specification (RFC 2616). Answer the following questions:

- a. Explain the mechanism used for signaling between the client and server to indicate that a persistent connection is being closed. Can the client, the server, or both signal the close of a connection?
- b. What encryption services are provided by HTTP?
- c. Can a client open three or more simultaneous connections with a given server?
- d. Either a server or a client may close a transport connection between them if either one detects the connection has been idle for some time. Is it possible that one side starts closing a connection while the other side is transmitting data via this connection? Explain.