Wg Cards English API Doc V3_0_0

wg cards OpenAPI definition

Description:

> **Sand-Box environment**
>
> **HOST:http://115.29.241.36:9009/**
>
> **prod environment**
>
> **HOST**:https://api.wgcards.com
>
> Any change in the interface will add a description before the interface, please refer to Annex II for details.

- New: indicates that the interface is added
- Changed: indicates that the interface content is modified
- Deprecated: indicates that the interface is no longer recommended
- No-encrypt: indicates that the interface is not encrypted

Contacts: tech@wgcards.com

Version:v3.0.0

Summary (Important)

Request Body Description

> In this article, appId, accountId, appKey are provided by wwgcard
>
> In this paper, we provide the appId, accountId, appKey is the public information open to partners, is used in order to facilitate the caller for debugging, if you want to get their own appId, accountId, appKey, please contact wwgcard staff
>
> All requests received by wwgcard must be objects of the following form

代码块

```
{
"appId": "provided by wwgcard",
"accountId":"provided by wwgcard",
"msg": "Encrypted request body"
}
```

name	description	require	type
appId	provided by wwgcard	true	string
accountId	provided by wwgcard	true	string
msg	The content is obtained by encrypting the concrete object	true	string

> The content of the interface in this article is the request body of the original request
>
> **Note: Only addresses in the ip whitelist can be successfully accessed**

Test Account Info

> appId: `2025112058411324`
>
> accountI: `2025112058411325`
>
> appKey: `o%Cmiq52TP4o06Uok&R6tC#^#FXGNE*3`

How To Encrypt

AES Algorithm Destribution

> Our system uses the AES tool class provided by hutool as the encryption and decrypting scheme. The following is the test code of AES in hutool

- in github
- hutool/hutool-crypto/src/main/java/cn/hutool/crypto/symmetric/AES.java
- in gitee
- hutool-crypto/src/test/java/cn/hutool/crypto/symmetric/AESTest.java

> You can use the Settings belo
>
> Data format :**hex**
>
> Encryption and decryption mode :**ECB**
>
> Data filling mode :**PKCS7**
>
> or
>
> Data format :**UTF-8**
>
> Encryption and decryption mode :**ECB**
>
> Data filling mode :**PKCS7**

>

> Please note that the results of the two encryption methods are different. The cases provided in this article are only reference examples, and the content after specific encryption may not be consistent
>
> The encryption function can be detected through the following websites
>
> AES在线解密 AES在线加密 Aes online hex 十六进制密钥 - The X 在线工具 (the-x.cn)
>
> In order to ensure the security of data, we use Aes encryption to encrypt the requested content

代码块

```
package com.roushan.api.common.util;

import cn.hutool.crypto.SecureUtil;
import cn.hutool.crypto.symmetric.SymmetricAlgorithm;
import cn.hutool.crypto.symmetric.SymmetricCrypto;

/**
 * aes  util
 *
 * @author wwgcard
 */
public class AesUtil {

    /**
     * @param key     your appId
     * @param content your request body , json format
     * @return
     */
    public static String encrypt(String key, String content) {
        byte[] byteKey = SecureUtil.generateKey(SymmetricAlgorithm.AES.getValue(), key.getBytes()).getEncoded();
        SymmetricCrypto aes = SecureUtil.aes(byteKey);
        return aes.encryptBase64(content);
    }


    /**
     * @param key     your appId
     * @param content wwgcard response body , json format
     * @return
     */
    public static String decrypt(String key, String content) {
        byte[] byteKey = SecureUtil.generateKey(SymmetricAlgorithm.AES.getValue(), key.getBytes()).getEncoded();
```

```
        SymmetricCrypto aes = SecureUtil.aes(byteKey);
        return aes.decryptStr(content);
    }


}
```

encrypt demo

代码块

```
import com.alibaba.fastjson2.JSON;
import com.roushan.api.common.util.AesUtil;
import lombok.Data;

/**
 * @author wwgcard
 * @date 2023/9/5
 */
public class EncryptDemo {

    public static void main(String[] args) {
        String appId = "2025112058411324";
        String appKey = "o%Cmiq52TP4o06Uok&R6tC#^#FXGNE*3";
        String accountId = "2025112058411325";
        GetTokenVo vo = new GetTokenVo();
        vo.setAppId(appId);
        vo.setAppKey(appKey);
        System.out.println("encrypt request body :" + AesUtil.encrypt(appId, JSON.toJSONString(vo)));

        /**
         * this is response example
         */
        String responseBody = "M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CXcA4tY+xujX1AQFdcKiFuznkwrt/IR27zrHWZtITLJ8y9O0jvIfueujJ2k95ouybRmMAASGC9EE/Z/+qYbueK/V7kVM668lYXiofo3kfLDg==";
        System.out.println("decrypt response body :" + AesUtil.decrypt(appId, responseBody));


    }

    @Data
    public static class GetTokenVo {

```

```
        private String appId;

        private String appKey;
    }
}
```

Authentication Check

introduce:

> token authentication is requested. The token is valid for 2 hours and automatically becomes invalid after it expires
>
> The token is obtained by the getToken interface and is required in all interfaces except getToken

realize:

> Add the following parameters to the request header of the request

name	require	description
appId	**true**	appId
Authorization	**true**	"Bearer" and space before the temporary access token value

Request Body

introduce:

> All request bodies are in the following format. The only difference is that msg is encrypted by different request contents. For specific request contents, refer to the description of request bodies in each interface

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

Interface V 1.x

Get Token

Basic info

- **url**: `/api/getToken`
- **method**: `POST`
- **produces**: `application/x-www-form-urlencoded,application/json`
- **consumes**: `*/*`
- **Request frequency limit**: `5 times /60 seconds`
- **Note**:

Request Body

> **RequestBody**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body , Refer to **encrypt demo**

代码块

```
{
    "appId": "2025112058411324",
    "appKey": "o%Cmiq52TP4o06Uok&R6tC#^#FXGNE*3"
}
```

> **Params**:

name	description	require	type
appId	appId	**true**	string
appKey	appKey	**true**	string

Response body

> **Example**

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS5jkV4CCyfw0GfMzy3RQxzpyNroxn1xCcLXLrQ
Z2aPLTKcRwwgVwFgm47Cq2tRlstBlrDqRxHMVJjaV7zJwoLwzwpkvIzgRO2z/RmeT0W5NoA==
```

> According to the above return value, decrypt the content by appId: `2025112058411324` refer to **encrypt demo**

代码块

```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": "opyf652pctxud70wsd87nkeyww7fhfgp",
    "msg": "success"
}
```

> **Response Params**:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data	token	string

Get Account Info

Basic info

> **url**: `/api/getAccount`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Request frequency limit**: `5 times /60 seconds`

> **Note**:

Request Body

> **RequestBody**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "userId": "2025112058411324"
}
```

> **Params**:

name	description	require	type
userId	appId	**true**	string

Response body

> **Example**

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGszG8OoA+4MEHz5n7
0DdXLoX+sLc/QkK+3evQrsh5RP2DC/9dpXx1aDR5ciNxC6bMzP4shjvbEZv2AfzLWTpmke4+cEM+NlU
AidnUQa+bQgR4dyPiC0qF2aZJJI9T5BA6o2B3u2oeUie/zHshWz4XcSwL8beyMl7fAxhGyiuNf/4ilj
43ukc31YbnOvYcS/pe5W7wsVhXXO9D0xcYfz0xQmw==
```

> According to the above return value, decrypt the content by appId: `2025112058411324`
> refer to **encrypt demo**

代码块

```
{
```

```
    "appId": "2025112058411324",
    "code": 200,
    "data": {
        "accounts": [
            {
                "balance": 20000000000,
                "currency": "USD",
                "effective": true,
                "walletId": "2025112058411157"
            }
        ],
        "userId": "2025112058411324"
    },
    "msg": "success"
}
```

> **Response Params**:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer(int32)
msg	Response message success "success", Failure Others	string
data	account info	
userId	user id	string
accounts	account info ,Note that this is a collection object	array
walletId	Wallet id	string
currency	Wallet currency	string
balance	Wallet balance	number
effective	Is the wallet valid	boolean

Get Product Info

Basic info

> **url**: `/api/getItem`
> **method**: `POST`
> **produces**: `application/x-www-form-urlencoded,application/json`
> **consumes**: `*/*`
> **Request frequency limit**: `5 times /60 seconds`
> **Note**:

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "appId": "2025112058411324",
    "currencyCode": "CNY",
    "language": "en",
    "current": 1,
    "itemId": "",
    "itemName": "",
    "size": 10
}
```

> **Params**:

name	description	require	type
size	page size	true	integer(int32)
current	page number	true	integer(int32)
appId	appId	true	string

itemId	itemId	false	string
itemName	itemName	false	string
currencyCode	currency(Refer to Annex I)	false	string
language	zh:chinese,en:english; empty value or any other values will be treated as english	false	string

Response body

Example

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGsf8Vged4ls/KXDDg
P0FT75qnhDLao0LstL2P9KqpYMbRFwvz473wsaoiq26w1TlOBFE8EgNIY/GswyWdKod+d6H0mMinExJ
ZM1tb735jbyU8/rFjEMRka3Jt5fOPfr4rEFvn7Fo2+VjsRoRU/qVSCFdv29iNZASN4C8IKOpyBJrKo+
SPyykzqHDTJMEqwScS9eNxFHLy1bssS/T2ZkxT96vxK2aGMJriqm0s4BJmGlLip0sWG3OxYB350A3W2
fKpjoYt2c2iKUqUn93VVZuJ191JYJRqpPz5emzcVkaYFWNMWbxYmzxy9gQZGgbNvHSxbLXRajpqW/cE
eo5tkBQtl+CBahnIUdnqQWAyC/xrIACyFmQoQH7t6b5HnTi4wkk6B6JLvsfenScgK7mvClR/or4VNfr
k6pejVGq9OdnW5mZQXUjNA1KJU0R0xW6XvsQr/ypeHKFM1GOEDeAGZHTWLBW3dseqegS7z2Drpphl4L
che9yrKQKH28DV6M+XPt8KMI7LPzBbe+7sEOgDazaxMmLe5+YPE57pDHZgjWrpvMgTXPb2TcelAX4if
KVm2Dl8j3JwDFKWkGyHndofUhkwDrWUiYjF/7y0nJ7Uwfza7oJWWCeaKiViRRwqea4V65J2cvlM/fxz
qhVLyj01GmD/7RgXgMwrzzC3gjlneagXKyr1NnMbelpILZufPMWAfjGP3tJKLqQ7mdWWYesQBP8adGb
h43+Y9AIq4XgcWsy/1qMf/GZ8awhh+Fa6A5lUl0YjKNCGb2N3qxiuaWBolzkZK6213QKX04269zxYcB
bUYgj0+2GRmAwhNAw9Nb94XqOw28ppCkR7v5JaOB8QNsND9XoWnFsTqXnPxro7rJHmtWQv4R9kWzAN9
HxxzBF/qYU8llWH6Thrd/ORhyslukamEjxXmIZtvF8BgNp5oeXhI6F6+XCSJBPk9FPOwHxexKmAo/c9
B0K1ANVer343FTM2yliZPuLQUKhInQB9FlABuYUga2nYZhbqSVmbd04/FQGPyJYrnEgSk8XGCQ0m9ay
axN2MN/NlnG/UMoWINj05VFtxiR4DVZygZotfvkODk8TOKRsE/WpghYj9GJjcHAWc5HQlWgRMMFlIHc
PmXll1xLHVaITYQ9hlkH13B+4Nbqw0Bc4+7xoF3WeuIovLg60wok5TETCG1PesbtCDjiW/sgXmXH4Q7
j/Meywgzl3veaDS1s49qySjQm/I51uggf8JpwTm3fZ5BJiUQFYOc4LLK1NuiaX0WDQLAnkvmwlrnLCQ
GYrpqKZVmccgQeCRWHkfv7KUdhwlxPIllFlreZmz6rqkAykUuMCc68FpEnjPiPEpq2SdkncTOgTTZC5
FaVQhsgPNUPaGui37FApVeXZ/0PECncAts9KR647tDhOMN2h0DJtdTj3LrtR0HqJxH8Qm2c1NTGObSc
rCaD2xiSo+k+dfipTYps9upNiEJwRP/Z6XtYXMBDDjOwIS19wqZJUrQbppNopEGtGPkQ1RJz1/+fVYI
nU0fV7Wax8ekrajd92YfSU/OHHEaNB/ykcMEkYR/ygwjxR1xzyf6ZFHESVLa0iumqpI+VmVQAAiNn7+
CzDhd3/8l12t8L+JyzO8QzLKIQZAIRK63NmJr5ScFDpJHumW6Exy5XK1lHxKJ4lg/H30xIrTcZ8ZAFY
/2cqaw2/lHbY1yXQVs1KwQsYsjdQ/9GVtvf60duk9J5AM4aXUEavw+FOHx8J8qAobWMShuJdas9K1ur
1jMKUqrZ1jZ1x7t6UuRjeXq3ou1xSMDV746VQJbSU/OHHEaNB/ykcMEkYR/ygwjxR1xzyf6ZFHESVLa
0itur+glPnmXthViqux1ZuneOxu4TsUFUe70EPHgG2QnY5nUAz2eK/22t1RgA42oNO+7JTWRgBkv/7a
zQkh6f2cFCJ02TmW9kB7O9+G5Ezjt/HuAy5hnv7XnjGQs5lwlZldvf60duk9J5AM4aXUEavw+zh4gRe
gnGo/IpI2IxFpWDVjYBLNm+BLBC/ipHGiiA/jrQ9k/SBA+LqTMJKVjYx8oSU/OHHEaNB/ykcMEkYR/y
gwjxR1xzyf6ZFHESVLa0iufvXIFqXbEuDp8OfhWIdaBjzwOvFTKsrzcu/G0TyHYQUhsCRQb1x3S7ZKn
ykZQRP6+Uz9/HOqFUvKPTUaYP/tGcf/jPzyd7XujEyQHHIDlHtt3cFcO1t8Xvgomw6dvs5Rvf60duk9
J5AM4aXUEavw+jF9Uy3ufLi/NeP87FtnUZdSYIPJzQ6APDkqN5/sZVw1kxclciW06moLZeCWNaSMkSU
```

/OHHEaNB/ykcMEkYR/ygwjxR1xzyf6ZFHESVLa0ivnKQpHRUcDCAC2tAsIsim03KneNt2OOkCdT0obo
4fLTJYJ5oqJWJFHCp5rhXrknZwuc7egRH/BfTpUMmuRYKy8x90rqgQ4pDX+5sl1C/2BsHw2rye0qYWx
+g87JDBZArNvf60duk9J5AM4aXUEavw+baWgberJVDTixGf2Qr5xUfNDC7cbKCuriRHSb67QQw2DpRQ
AMVOVcNEOhw5/p4u9zTx01+pURiT13PQBtGwLMSKQv51X+WIzzw8jTNs1LopLHqiPACK7fRfjpGpg22
JqJcPVVF567Hs6EuPCv62/Z42erbr7nBHDK5rPyncp3/rKA4XRCxQDJQSMORQnPf6s9UJLYukDDV9Pb
iY9DkgxWyiQdCSHXxUasXdTZ0aLl3HSeRTsu9B9l4i0CcDGytKM0d/KGVAo2rzT4exMpavouw==

> According to the above return value, decrypt the content by appId: `2025112058411324`
> refer to **encrypt demo**

代码块


```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": {
        "current": 1,
        "pages": 1,
        "records": [
            {
                "currencyCode": "JPY",
                "description": "<p><br></p>",
                "howExchange": "<p><br></p>",
                "itemBrandName": "Nintendo",
                "itemId": "2025062335235114",
                "itemName": "Nintendo Japan",
                "itemTitle": "Nintendo Japan",
                "skus": [
                    {
                        "maxFaceValue": 9000,
                        "maxPrice": 490.79,
                        "minFaceValue": 9000,
                        "minPrice": 490.79,
                        "skuId": "2025062335235117",
                        "skuName": "Nintendo JP 9000 JPY",
                        "skuPrice": 490.793,
                        "skuPriceCurrency": "CNY"
                    },
                    {
                        "maxFaceValue": 5000,
                        "maxPrice": 280.45,
                        "minFaceValue": 5000,
                        "minPrice": 280.45,
                        "skuId": "2025062335235119",
                        "skuName": "Nintendo JP 5000 JPY",
                        "skuPrice": 280.449,
```

```
                "skuPriceCurrency": "CNY"
            },
            {
                "maxFaceValue": 2000,
                "maxPrice": 112.17,
                "minFaceValue": 2000,
                "minPrice": 112.17,
                "skuId": "2025062335235121",
                "skuName": "Nintendo JP 2000 JPY",
                "skuPrice": 112.169,
                "skuPriceCurrency": "CNY"
            },
            {
                "maxFaceValue": 1000,
                "maxPrice": 56.12,
                "minFaceValue": 1000,
                "minPrice": 56.12,
                "skuId": "2025062335235123",
                "skuName": "Nintendo JP 1000 JPY",
                "skuPrice": 56.12,
                "skuPriceCurrency": "CNY"
            },
            {
                "maxFaceValue": 500,
                "maxPrice": 23.64,
                "minFaceValue": 500,
                "minPrice": 23.64,
                "skuId": "2025062450882798",
                "skuName": "Nintendo JP 500 JPY(LOCAL)",
                "skuPrice": 23.64,
                "skuPriceCurrency": "CNY"
            },
            {
                "maxFaceValue": 2000,
                "maxPrice": 14358.6,
                "minFaceValue": 2000,
                "minPrice": 14358.6,
                "skuId": "2025102758237173",
                "skuName": "Nintendo JP 10 JPY",
                "skuPrice": 14358.6,
                "skuPriceCurrency": "CNY"
            },
            {
                "maxFaceValue": 3000,
                "maxPrice": 21537.9,
                "minFaceValue": 3000,
                "minPrice": 21537.9,
```

```
                        "skuId": "2025102758290183",
                        "skuName": "Nintendo JP 20 JPY",
                        "skuPrice": 21537.9,
                        "skuPriceCurrency": "CNY"
                    },
                    {
                        "maxFaceValue": 4000,
                        "maxPrice": 28717.2,
                        "minFaceValue": 4000,
                        "minPrice": 28717.2,
                        "skuId": "2025102758610916",
                        "skuName": "Nintendo JP 30 JPY",
                        "skuPrice": 28717.2,
                        "skuPriceCurrency": "CNY"
                    },
                    {
                        "maxFaceValue": 5000,
                        "maxPrice": 35896.5,
                        "minFaceValue": 5000,
                        "minPrice": 35896.5,
                        "skuId": "2025102758672928",
                        "skuName": "Nintendo JP 40 JPY",
                        "skuPrice": 35896.5,
                        "skuPriceCurrency": "CNY"
                    }
                ],
                "spuImage": "https://roushan-img.oss-cn-hongkong.aliyuncs.com/national_flag/japan.png",
                "spuType": 2
            }
        ],
        "size": 10,
        "total": 1
    },
    "msg": "success"
}
```


Response Params:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer

msg	Response message success "success", Failure Others	string
data		
current	For the current page, the default is 1	integer
size	page size	integer
total	item total size	integer
pages	page number	integer
records	item list .Note that this is a collection object	array
itemId	spu id	string
itemName	spu name	string
itemTitle	spu description	string
itemBrandName	spu brand name	string
currencyCode	transaction currency	string
description	spu detailed introduction	string
howExchange	how to exchange	string
spuType	spu type 1:game 2:giftcard 3:software 4:microsoft product	integer
skus	sku list. Note that this is a collection object	array
skuId	sku id	string
skuName	sku name	string
skuPrice	price (when purchase custom face value sku ,this param no value)	number
skuPriceCurrency	currency need to pay	string
maxFaceValue	max facevalue of sku	number
minFaceValue	min facevalue of sku	number

maxPrice	The price of the largest denomination sku	number
minPrice	The price of the smallest denomination sku	number

Get ALL Product Info

Basic info

> **url**: `/api/getAllItem`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Request frequency limit**: `2 times /1 hour`
>
> **Note**: get all product by one time

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "appId": "2025112058411324",
    "currencyCode": "CNY",
    "language": "en",
    "itemId": "",
    "itemName": ""
}
```

> **Params**:

name	description	require	type
appId	appId	true	string
itemId	itemId	false	string
itemName	itemName	false	string
currencyCode	currency(Refer to Annex I)	false	string
language	zh:chinese,en:english; empty value or any other values will be treated as english	false	string

Response body

Example

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS72uwn+AjuHH7pUrIztXY1kiZ1y7WYP/wglRzd
Az5p/iNrafgmYOVAyafgmiO5PuoPdtC3Zvraaik928HW96STXlgJFRX5X132r2NOv8oc3o32P0JXY5+
20FUNN6jT+cZuqAYATxjfJ3lRokmo/xOWwarCGBdTcGveTp/6K3tV5yHfYatdplFkE8BfXlZNWXEEAp
mXq935MODv7gv4QsxbSZtXVuQZ7Fx16U3g3kyomsqJGBTj+JnUlhd1hHTF4Os7HObdr+zo/RQnoA8xQ
oTdL4qU2KbPbqTYhCcET/2el7RSmihF8z9VsBRub5X641PC5HOEGJsU45fheSjvHybigEt+rnp1xFfs
z2OUoaBT+XRQ4inUIn5Yoax9qgDOj4bQzUL5ciMjTv/wDG+1QMN320+XWxv09R9G/KDgZbOms13LoUk
5qY1DKUWwHAQRVha9vf60duk9J5AM4aXUEavw+eWkZnSPdNuBHRkYwaZDg0Nlf6m2YTu/24iFDjYbg6
wj5wkGKGY9F4ResDCghMZFuy8bDWuKioR75yWpzmvicZlaYpthuulceoW6xPrn2shWpgkQGuO3epfZs
y3Cq3E8Dwfva68B4lDaXjfrSBX8p3tcMVMdjUteJkCx75eZQxEzN0FiSo/4nIVtFkE2fGk4iXVjVDeP
XCrWXrJ7ZJNv2YA7OO0XnztALcpw0Q7oBGD7XPb2TcelAX4ifKVm2Dl8jiVrQ+lsWqjk1aM/EjmyD6x
M4JySMTf0/hGkcncTtVcAV5iGbbxfAYDaeaHl4SOheDJz1JoFHdfmV34J2Z9oTfP3PQdCtQDVXq9+Nx
UzNspY8gV/nJ9D6wtRZrbTAIeAUNkg+EUkpTMruSgCPz+wtGKR4/X1FWa5Bd5K4m7pd5LXnQgFg/PLM
2NLHNsN7z3eK+M+hw07hrgMkBWilVsPsgVNLm/VGqMa7toSlS+5PTf8DKRxmR05cvkkQCWmZTcvcx+V
jjT1q5+H2u1brKzUqCZUFCSV2rYlU6peyJ/4WS6sSRI4PAsmP+9Ff1Ny+C4CxdEvt3LEuZ4GVYRP+Wa
GiAQwjxR1xzyf6ZFHESVLa0ivmJ/Dw/mWmQHnItuD6e3vx+EfZFswDfR8ccwRf6mFPJcFrUSZsna1sb
GuKRhC5ACSW+0J7pVKPHru9moRoGzYWavra+B5rk26v/weql72pjt/PrXbcP0mWXRG1L9zC+dmsqtcA
1tBtMmWXE1pNmSwWpR2HCXE8iWUWWt5mbPquqfBaMwG/dMq7nMp1q4Y1361Px7hfP88Mp5QL8N8TX+6
3tXyfA49m9pefGuf4xaCPBWfNZ/uWPWGhB2eMneB++VPipTYps9upNiEJwRP/Z6Xtl9d51w50pJBbd9
ZNKkZiSFC5gNRo8u+mfkk/QnLEaoL2bsxQ6CA8YPZGG98Q6/x/SICofTLMx5T6c/oqeiYYDvMC32pfk
bSBDKeJBCPbUBqwAN4TSDPZI1cRQmABT+gJcunXjpHXQOeYJRVlUSAp4LSSi6kO5nVlmHrEAT/GnRmG
gTxgPv8gAnx1mEC7rnemcs5anSHotDDOMUbeTTY/u8IaAw+lj+vst0zdWOgEGvD92uiXoo8wkCF9zAc
WSXqHyknytK09YS5thSmkrMNLsRXwIHp6eLvjfJa1MiXW2OCA3T64509XSTQg0HatOKEmUMalFyFiO3
d+7R7r3QtBgYnD26+HFoIm8tlUMXptbUZXo8nTiopfdYjUoFG3JCtlxzPsZRDG+nGc2h6wJdRElthW
4jPZOYPEONqkEyjsYAHNIzM/pYNMOSL32rw5WEK
```

> According to the above return value, decrypt the content by appId: `2025112058411324` refer to **encrypt demo**

代码块


```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": [
        {
            "currencyCode": "JPY",
            "itemBrandName": "Nintendo",
            "itemId": "2025062335235114",
            "itemName": "Nintendo Japan",
            "skuList": [
                {
                    "maxFaceValue": 9000,
                    "minFaceValue": 9000,
                    "skuId": "2025062335235117",
                    "skuName": "Nintendo JP 9000 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 5000,
                    "minFaceValue": 5000,
                    "skuId": "2025062335235119",
                    "skuName": "Nintendo JP 5000 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 2000,
                    "minFaceValue": 2000,
                    "skuId": "2025062335235121",
                    "skuName": "Nintendo JP 2000 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 1000,
                    "minFaceValue": 1000,
                    "skuId": "2025062335235123",
                    "skuName": "Nintendo JP 1000 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 500,
                    "minFaceValue": 500,
                    "skuId": "2025062450882798",
```

```
                    "skuName": "Nintendo JP 500 JPY(LOCAL)",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 2000,
                    "minFaceValue": 2000,
                    "skuId": "2025102758237173",
                    "skuName": "Nintendo JP 10 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 3000,
                    "minFaceValue": 3000,
                    "skuId": "2025102758290183",
                    "skuName": "Nintendo JP 20 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 4000,
                    "minFaceValue": 4000,
                    "skuId": "2025102758610916",
                    "skuName": "Nintendo JP 30 JPY",
                    "skuPriceCurrency": "JPY"
                },
                {
                    "maxFaceValue": 5000,
                    "minFaceValue": 5000,
                    "skuId": "2025102758672928",
                    "skuName": "Nintendo JP 40 JPY",
                    "skuPriceCurrency": "JPY"
                }
            ],
            "spuType": 2
        }
    ],
    "msg": "success"
}
```


Response Params:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer

msg	Response message success "success", Failure Others	string
data		
itemId	spu id	string
itemName	spu name	string
itemBrandName	spu brand name	string
currencyCode	transaction currency	string
spuType	spu type 1:game 2:giftcard 3:software 4:microsoft product	integer
skuList	sku list. Note that this is a collection object	array
skuId	sku id	string
skuName	sku name	string
skuPriceCurrency	currency need to pay	string
maxFaceValue	max facevalue of sku	number
minFaceValue	min facevalue of sku	number

Get Stock

Basic info

> **url**: `/api/getStock`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Request frequency limit**: `5 times /60 seconds`
>
> **Note**:

Request Body

> **Request Body**

```
代码块
```

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "skuIds": ["2025062450882798","2025062335235123"]
}
```

> **Params**:

name	description	require	type
skuIds	skuId list	true	array

Response body

> **Example**

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS72uwn+AjuHH7pUrIztXY1klgJFRX5X132r2NO
v8oc3o16qNvszGdEMZVDzNIlPjkOCCfYQMyDxVNzpZRjKzEAuZW5whgRZHZglj3MeyFz/DYiTPx4W8e
0TQwUvBwNjF8+7zfa8WRHwIwo+l5H5KYkdbIvvnj/qJbKEKDL/TOTbl6r9S/4AjfYULBf9rrm+RDJbk
byOavVCDHsNLRFz2oO70d/KGVAo2rzT4exMpavouw==
```

> According to the above return value, decrypt the content by appId: `2025112058411324`
> refer to **encrypt demo**

代码块

```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": [
        {
            "itemId": "2025062335235114",
            "number": 2,
            "skuId": "2025062450882798"
```

```
        },
        {
            "itemId": "2025062335235114",
            "number": 151,
            "skuId": "2025062335235123"
        }
    ],
    "msg": "success"
}
```


> **Response Params**:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		stock info list
number	Inventory quantity (if return -1 ,means no limit)	integer
skuId	sku id	integer

Get Product And Stock Info

Basic info

> **url**: `/api/getItemAndStock`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Request frequency limit**: `5 times /60 seconds`
>
> **Note**:

Request Body

> **Request Body**

代码块

```
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "appId": "2025112058411324",
    "currencyCode": "CNY",
    "current": 1,
    "itemId": "",
    "itemName": "",
    "size": 10
}
```

> **Params**:

name	description	require	type
size	page size	true	integer(int32)
current	page number	true	integer(int32)
appId	appId	true	string
itemId	itemId	false	string
itemName	itemName	false	string
currencyCode	currency	false	string

Response body

> **Example**

代码块


```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGsf8Vged4ls/KXDDg
P0FT75qnhDLao0LstL2P9KqpYMbRFwvz473wsaoiq26w1TlOBWurOyzdutsqhlbqLZxbB/6LKz8yrSW
2OrFxWww5dbvCAe54IQJVBCKq/+Bd592WSDddaKN7/AJFNKF4IgjvQPpq7BuQU5Yf89tPBB6WPB343u
il81hLn+VsJirETA7WNXGza64ocvbfQVpVoAUIElNVPT9Z1rVAT2wQpeUgYY6+qoZGdBmZ15oZpcdjs
ehB84Aj9TBCg2xeTc58oCsbV2+hQy/amTIz498jKKwGKSwfymkKRHu/klo4HxA2w0P1e1TWWTgkUA+2
```

Nme6KTAVRYBAdMJQM/eyddmBpdijLdSQdFIjrVeV8vzSvRVwuN5yzFeYhm28XwGA2nmh5eEjoXmukmj
LAikZnXqqC6+O/wVz9z0HQrUA1V6vfjcVMzbKWXPLnOAlg0LRH2XcjaGUUG7wnQQH7wqJbdL+ASQkRr
wsliucSBKTxcYJDSb1rJrE3v3wSlB+ZHcekA4tMbU9RE/cizHmQVAP6FPstVQhcvldWR46lGYSvdMUg
5sgWdWe0DRs4SqpkVUDfqYYc3hhJSfFjha60wFQzLLRMqbXhIaqGfW4FpnzWolUJGFeTh1wO2vZGV9F
BKZWMlm2hCEWU10TiXtdvi+2PNnfBcp7AN29sCPltDHRKfUFmRSRqQLsTXXcggE9u5H6xghD3puWlUP
l0sjwg50c4i1tQR5bJ4wpNGznGKNW2cOP6Qh7FK+2uRWuqCysHzopVIHKze3cgLwuxssVFaS++WdxqC
tOrjWd15y61rBKDpW4UNvrYSW1UTHVqgIsComoopY1M61WraCQG9DBRdrh1wqt+PbNXnajZKfqP00+d
fzD3gT0eDl2worJteuR758At1Ozq2l40wLF0ZR76p+swjWLHrFAmDYf2ABB3TkUp9CxaJTfn0TQZavr
a+B5rk26v/weql72pjoWAJek1kKClk7licW4xYRMN3S3WaH9F6pQYpeWsQR3duRzhBibFOOX4Xko7x8
m4oN/koHk2SCsNMeVys+oJat9bPxu+QDp6JCucUcMBJMjm/akM6TQQV0iKlega89fqejC2kQyaKBClM
Gu3IhBBv1vNcPW86dj+2ztT4Hxh+6tlwDJyzwUA4YbAJ9C5gRu01JzNJ49T+Xpmq3C1kIPemaAzyvlx
6QlC8Bn/K9dCb6PAx+VjjT1q5+H2u1brKzUqCT/Jy5Hcd2lflnLvGAihacPZwOem4qIk2mwn1BFylfP
JwFM3oFc92yuGgaFv3G1MIzpcFJcMMAl/Fyp/MmenKQpBgzq2/IcvY4GB3MW31kNmPEvmo1mox7T1Is
zqAmDtFwQoCQcet2aHXzzZ40zIi3kzUL5ciMjTv/wDG+1QMN32hn1uBaZ81qJVCRhXk4dcDuvEO6UZd
ArxEz1lz/tLeIZlbnCGBFkdmCWPcx7IXP8Nb3+tHbpPSeQDOGl1BGr8PsNu4JPZesta/+ydJPwimbKp
ev49gMBoDrPbWpGsKO2ivuFmhf5jg+RwV+tgbZEkrEpxxw2+6LUePM9ODLJpadXCDTlEWZ6A9yow6az
OB9HyVkQBieX0wJPS+BzCZsSwvukISl+1gLv/kpFledtpmFxa4S8Y8xcrbLPSsDHWSkK5C2I4vVscWm
iIlEY1YDNlGm59zW5iSUrJcpwfTohOrMn6jxq47cZKvmJDincbj/3LbKAvyhnEJKpDYZQQpllH2hSaW
Q7ZiO4zJKlBtg/aaiEnKf7PT/yNFevxslMQYm0J2bwwK3CXbhpvuaHRjGPehftw5ZNF1223r0dQYyJ/
eu/vybHCsY0mTI2+1cYM9YypkgyqFA5sjtuFJ6WmVggfNlO/GrxeOaBbaZ/KAaCgXz1HcBUqQGvB089
+XBSmKIQ50RWEIoekftHs7qqqwffFe1o0sC01hyVizY4CNRZCHD4VfLG52MhwDPiNAJMq5DW4kKPDki
+Jhhh8vZTi0/H3BrBSgMWHFtusSzqFb5RLpHTJcDd+XnV5WFXAHp3drHFoM2wY6yZ1g+1ZMZxYqPQmW
JNWljO5/jGuQv56Baf5y+xyzlqdIei0MM4xRt5NNj+76awJVdvtxXZYnpZm5D6+w10156V3m98k90jw
+TW7z/kmTSVVo2f0TQCJqaJpJlVw6Ov05YDiIcvXhLgxg7V0gdDODAhb6xeXLhkaFC8dqtyGfW4Fpnz
WolUJGFeTh1wOM31uq6T8qP2tdwMFv4/2AM2MN4Delo+/CV5S81kzP+TvC/vUFbpE+wd43BVOX5QXJg
fX25j/8LU4cfFsB46Tl/l0sjwg50c4i1tQR5bJ4wqlYOvdB8Ls3mfMcYHkDH/YYrpqKZVmccgQeCRWH
kfv7JbS11A1ahLQw8P+ppE6M9oAg5ddLhgbptF/ltsR1gs1656Kp6jvJHhkdr7jiRGfYKW9R90En6dg
pbEX7e4OutQUOIp1CJ+WKGsfaoAzo+G0j7abCNw2RK814UyP8shdpvHCdiK318kCv+E3IzwvTFeBy2K
+Xx8IcMAefLjJQozsx+VjjT1q5+H2u1brKzUqCWiS9vkTm6R/6/tFB0S8kqDRaAK5+LX0TD26CRBslZ
+A1TdsMGoiMV9WhxdELuZiVah4QNuSDDKJSTo0lMkY3qOLJ9TPrrjyGe80Kbd03X75k4bgMccO3nKXz
f+Pmlr3n2a9SakyGW47jkZrYxYqD0CbdA74I4xpyCr8aOAu5johOwyqA7jIbyn8WylTSxP79tEVfz1Q
ae4RoDzqhFjUnh9QqeFKWS1YFXDhwC6ZmRJDbKZ/Mwg5ar2G9Y4r8Mz2xmWsOpHEcxUmNpXvMnCgvDP
CmS8jOBE7bP9GZ5PRbk2g

> According to the above return value, decrypt the content by appId: `2025112058411324` refer to **encrypt demo**

代码块

```
1  {
2      "appId": "2025112058411324",
3      "code": 200,
4      "data": {
5          "current": 1,
6          "pages": 1,
7          "records": [
```

```
            {
                "currencyCode": "JPY",
                "howExchange": "<p><br></p>",
                "itemBrandName": "Nintendo",
                "itemId": "2025062335235114",
                "itemName": "Nintendo Japan",
                "itemTitle": "Nintendo Japan",
                "skuInfos": [
                    {
                        "maxFaceValue": 9000,
                        "maxPrice": 490.79,
                        "minFaceValue": 9000,
                        "minPrice": 490.79,
                        "skuId": "2025062335235117",
                        "skuName": "Nintendo JP 9000 JPY",
                        "skuPrice": 490.793,
                        "skuPriceCurrency": "CNY",
                        "stock": 64
                    },
                    {
                        "maxFaceValue": 5000,
                        "maxPrice": 280.45,
                        "minFaceValue": 5000,
                        "minPrice": 280.45,
                        "skuId": "2025062335235119",
                        "skuName": "Nintendo JP 5000 JPY",
                        "skuPrice": 280.449,
                        "skuPriceCurrency": "CNY",
                        "stock": 82
                    },
                    {
                        "maxFaceValue": 2000,
                        "maxPrice": 112.17,
                        "minFaceValue": 2000,
                        "minPrice": 112.17,
                        "skuId": "2025062335235121",
                        "skuName": "Nintendo JP 2000 JPY",
                        "skuPrice": 112.169,
                        "skuPriceCurrency": "CNY",
                        "stock": 94
                    },
                    {
                        "maxFaceValue": 1000,
                        "maxPrice": 56.12,
                        "minFaceValue": 1000,
                        "minPrice": 56.12,
                        "skuId": "2025062335235123",
```

```
                "skuName": "Nintendo JP 1000 JPY",
                "skuPrice": 56.12,
                "skuPriceCurrency": "CNY",
                "stock": 151
            },
            {
                "maxFaceValue": 500,
                "maxPrice": 23.64,
                "minFaceValue": 500,
                "minPrice": 23.64,
                "skuId": "2025062450882798",
                "skuName": "Nintendo JP 500 JPY(LOCAL)",
                "skuPrice": 23.64,
                "skuPriceCurrency": "CNY",
                "stock": 2
            },
            {
                "maxFaceValue": 2000,
                "maxPrice": 14358.6,
                "minFaceValue": 2000,
                "minPrice": 14358.6,
                "skuId": "2025102758237173",
                "skuName": "Nintendo JP 10 JPY",
                "skuPrice": 14358.6,
                "skuPriceCurrency": "CNY",
                "stock": 0
            },
            {
                "maxFaceValue": 3000,
                "maxPrice": 21537.9,
                "minFaceValue": 3000,
                "minPrice": 21537.9,
                "skuId": "2025102758290183",
                "skuName": "Nintendo JP 20 JPY",
                "skuPrice": 21537.9,
                "skuPriceCurrency": "CNY",
                "stock": 0
            },
            {
                "maxFaceValue": 4000,
                "maxPrice": 28717.2,
                "minFaceValue": 4000,
                "minPrice": 28717.2,
                "skuId": "2025102758610916",
                "skuName": "Nintendo JP 30 JPY",
                "skuPrice": 28717.2,
                "skuPriceCurrency": "CNY",
```

```
                        "stock": 0
                    },
                    {
                        "maxFaceValue": 5000,
                        "maxPrice": 35896.5,
                        "minFaceValue": 5000,
                        "minPrice": 35896.5,
                        "skuId": "2025102758672928",
                        "skuName": "Nintendo JP 40 JPY",
                        "skuPrice": 35896.5,
                        "skuPriceCurrency": "CNY",
                        "stock": 0
                    }
                ],
                "spuImage": "https://roushan-img.oss-cn-hongkong.aliyuncs.com/national_flag/japan.png",
                "spuType": 2
            }
        ],
        "size": 10,
        "total": 1
    },
    "msg": "success"
}
```


Response Params:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
current	For the current page, the default is 1	integer
size	page size	integer
total	item total size	integer
pages	page number	integer

records	item list .Note that this is a collection object	array
itemId	spu id	string
itemName	spu name	string
itemTitle	spu description	string
itemBrandName	spu brand name	string
currencyCode	transaction currency	string
skus	sku list. Note that this is a collection object	array
skuId	sku id	string
skuName	sku name	string
skuPrice	price (when purchase custom face value sku ,this param no value)	number
skuPriceCurrency	currency need to pay	number
maxFaceValue	max facevalue of sku	string
minFaceValue	min facevalue of sku	number
maxPrice	The price of the largest denomination sku	
minPrice	The price of the smallest denomination sku	
stock	sku stock number(-1 means no limit)	number

Place Order

Basic info

> **url**: `/api/placeOrder`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`

> **Note**: Card purchase service is available

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "userId": "2025112058411324",
    "accountId": "2025112058411325",
    "currency": "USD",
    "serviceOrder": "1caf9f17-37e-112a-1e14-3c229sdfs99",
    "detailVos": [
       {
             "skuId": "2025062450882798",
             "faceValue": 500,
             "buyNum": 2
       }
    ]
}
```

> **Params**:

name	description	require	type
userId	appId	true	string
accountId	account Id	true	string
currency	currency(The currency of payment)	true	string
serviceOrder	The service tracking number (provided by the caller)	true	string

detailVos	Goods to buy Note that this is a collection object	true	array
skuId	skuId	true	string
faceValue	sku facevalue (required ,when purchasing a custom par sku)	false	number
buyNum	buy number	true	integer

> **please ensure `serviceOrder` is unique, wwgcard will check this value, if repeated, you can not place the order**

Response body

> **Example**

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGsZVzw3TaSsemyx5b
JZGF3OWJQ7omsWLu/GLPiyQPc66hEkPVsps6YREH9EYtXSFMlW54FiFmJZxJFTrojc07auXqyxt8cGv
p+O0zOarooz+w=
```

> Decrypt the content in the following format according to the return value above，Refer to **encrypt demo**

代码块

```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": {
        "code": 200,
        "data": "2025112071040010",
        "message": "success"
    },
    "msg": "success"
}
```

> **Response Params**:

name	description	type

appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
data	order id	integer
message	Response message	integer

Get Order History

Basic info

> **url**: `/api/getOrderInfo`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**:

Request Body

> **Request Body**

代码块

```
1   {
2       "appId": "provided by wwgcard",
3       "accountId":"provided by wwgcard",
4       "msg": "Encrypted request body"
5   }
```

> msg is encrypted by the following request body

代码块

```
1   {
2       "uesrId": "2025112058411324",
3       "current": 1,
4       "size": 10
```

```
}
```

> **Params:**

name	description	require	type
uesrId	app Id	true	string
current	page number	true	integer
size	page size	true	integer

Response body

> **Example**

代码块


```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGsf8Vged4ls/KXDDg
P0FT75qnhDLao0LstL2P9KqpYMbT0pJL+yaUTmcL0Dlrdj7hckjeKez8/h8Pz/e2GVpep3w2FX7mKQ7
WVgqgFcSKPWpIIhOWdMlPKOgTGlvCe4lyOZAI2M1SSaFZ7LajF8p/24yr68w94CK471ZEufWpobBzLX
GTsLwSjpdT2jCf6+IQekFuTlT+VRe9P4kAZOw/i0KAVr/DTtKyRnhWZGsCOH6hPYh/nJvdkXJXlpSaw
zVvYqJwekN1emLCpZ8OL4Mhdcqm9eeXLCGJB1z09U0WIZa9jPMewFiPVv9bw4Yuu1uUIcgQSP3N9BVl
F1679qY2KibnrYO4XKc3ZKAMT7M6+Ue8wHG2Gj9dGAZ9FxurKy2DzguRWbRoB25tqkgnwwe6Rhe05St
2PFBHD5TVk75+yh+0Czoobu1yY4pv1iC5kAUeEFMrdG8u2U2Jt8LhOU+T5Rdh1oc5zHTBzuhtJ6L9x4
+E=
```


> According to the above return value, decrypt the content by appId: `2025112058411324` refer to **encrypt demo**

代码块


```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": {
        "current": 1,
        "pages": 1,
        "records": [
            {
                "createTime": "2025-11-20 19:44:01",
                "cur": "USD",
                "deliveryStatus": 3,
                "orderId": "2025112071040010",
                "orderStatus": 1,
```

```
                "orderWay": 105,
                "totalAmount": 3.29
            },
            {
                "createTime": "2025-11-20 17:10:25",
                "cur": "USD",
                "deliveryStatus": 1,
                "orderId": "2025112061824741",
                "orderStatus": 0,
                "orderWay": 105,
                "totalAmount": 6.58
            }
        ],
        "size": 10,
        "total": 2
    },
    "msg": "success"
}
```

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer(int32)
msg	Response message success "success" Failure Others	string
data		
current	Current page	integer(int64)
size	Gets the number of items displayed per page	integer(int64)
total	Total number of rows currently satisfying the condition	integer(int64)
pages	The total number of pages in the current paging	integer(int64)
records		array
orderId	orderId	string
orderStatus	Order status 0: Not completed, 1: Completed	integer
deliveryStatus	Status of shipment。1: to be shipped, 2: partially shipped, 3: fully shipped	integer
orderWay	order Way	integer
createTime		string
totalAmount	total amount	number
totalAmount	total amount	number
orderDirectstatus	TOP-UP result(only used for TOP-UP products) 0:processing，1:fail，2:success	number

Get Order Detail Info

Basic info

> **url**: `/api/getOrderInfoAndDetail`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`

> **consumes:** `*/*`
>
> **Note:**

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "userId":"2025112058411324",
    "orderId": "2025112071040010",
    "current":1,
    "size":200
}
```

> **Params:**

name	description	require	type
userId	appId	true	string
orderId	orderId or serviceOrder(what sent to us when placing the order)	true	string

Response body

> **Example**

代码块


```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGs/1e+o8k0KRn/Kdt
/1fIjloWO0Q+rz7llxAWEEDb1/kr+hchfYb0HFV5eaF4LAg/bp4IaI/LcTpx6U5XGZ3DgGOxhYyaf6A
```

P15A096UOB0FgMXKmyh5PpnZo7rWLJlxJIxHt+FE0xEfXVivRGZ3D8+uQuBBr/G/6HSEcb1b4NyRUBZ
549hObDL33/QZS6OVp+gxiIWhdZUeyekNPQjbdMHaR3Z8gVW/ZyOkhr44D2xt/36F/jC2Hy4WgAhMNN
ElTP49WZkmAoVNtPC9D/c8g4yPIL2qGZZKw8pxtZrd+/qUvOnw8yNU0H1blI64Rym7y3xBhF2XEfMV5
TakKLmfz85wOuYWx8xAWvSrif2Ct5uTf6xWGS0Oe1/DIT0SoEZ+19U74fbYXgS0sm0KwiCzey65ljJ5
o7ljHjj5ocfb+YV/Pl/PbaJb1mh56I7ff6tVScpTGfBwhOGGs7L20hzug1dH0zwFZTxU7zAOacGUvGb
ClfnixJ2hYl2hsU0GNKGv9j1a8R5aNXqqV83CiFTmFAMH9VLI4tiZ8iaxIkNQz/iwG9FXTSJA0n+GQv
/AXMtBJH3kTVgbbB6TUdwgzzvdWgnx6gzyL3kH/koDSo7oKsOpjipTYps9upNiEJwRP/Z6XtYYVCwi+
wFwlKQfq2Q823PQc0jMz+lg0w5IvfavDlYQo=

> According to the above return value, decrypt the content by appId refer to **encrypt demo**

代码块


```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": {
        "firstTo": {
            "createTime": "2025-11-20 17:10:25",
            "deliveryStatus": 1,
            "orderId": "2025112061824741",
            "orderStatus": 0,
            "orderWay": 105,
            "requestId": "1caf9f17-37e-112a-1e14-3c229sdfs99",
            "totalAmount": 6.58
        },
        "secondTos": [
            {
                "actualPaidPrice": 6.58,
                "actualPaidPriceCur": "USD",
                "buyNum": 2,
                "discountRatioStr": "-2.0000%",
                "faceValue": 500,
                "isEnd": 0,
                "originalPrice": 1000,
                "originalPriceCur": "JPY",
                "sendOutNum": 0,
                "skuId": "2025062450882798",
                "skuName": "Nintendo JP 500 JPY(LOCAL)",
                "spuName": "Nintendo Japan"
            }
        ]
    },
    "msg": "success"
}
```

Response Params:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer(int32)
msg	Response message success "success" Failure Others	string
data		OrderInfoAndDetailOutTo
firstTo		
orderId	orderId	string
requestId	what sent to us when placing the order	string
orderStatus	Order status 0: Not completed, 1: Completed	integer
deliveryStatus	Status of shipment 1: to be shipped, 2: partially shipped, 3: fully shipped	integer
orderWay	order way	integer
createTime	Time of order	string
totalAmount	Total price	number
cur	currency	string
orderDirectstatus	TOP-UP result(only used for TOP-UP products) 0:processing，1:fail，2:success	number
secondTos		array
skuId	Sku id	string
skuName	sku name	string
spuName	item name	string
isEnd		integer

	Finished or not 0: Not finished, 1: finished	
buyNum	Quantity purchased	integer
faceValue	purchased sku facevalue	number
sendOutNum	The quantity shipped	integer
originalPrice	Original price	number
originalPriceCur	Original currency	string
actualPaidPrice	Actual price paid	number
actualPaidPriceCur	Actual payment currency	string
discountRatioStr	Percentage discount	string

Get Order Code

Basic info

> **url**: `/api/getBuyCard`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**:

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
```

```
    "userId":"appId",
    "orderId": "2024010955690833",
    "current": 1,
    "size": 10
}
```

> **Params**:

name	description	require	type
userId	appId	true	string
orderId	order Id	true	string
current	page number	true	Integer
size	page size (max:2000)	true	Integer

Response body

> **Example**

代码块

```
ec+4BHivsxlcY4z0N3+tQLyDRjhFjARYsP0u1vTzSS6UE7ooeD5zNOTLPYdQgTGsf8Vged4ls/KXDDg
P0FT75qnhDLao0LstL2P9KqpYMbTRpTOXyqzqd9GG+tR+Opm4wFpXOYcDazPj+YA0eXAKKwMwl61N52
sF8E0LLoCuC+EGa2SIi2WV8b4Wp+JHYNjetVcqN7nJagZ3v4+YxJXtowI9eRKFk+rKbZSfWRWz+i6BP
MaJc7qiMXmxK9wwxivyGY86TUV+hYMRc6SpddlQQ0Q0nRCkUgMHgAlO7rGOasrDLfS/fzw2dgPt4vNw
RmlvaMsBe15ZdGtXWeNCyh57k5NJoAxGafGJJveOzGy+wZCSwmC9qd8qoTBab4Jfzz0vrUlExDqWY30
SNCWLXfqhqQ2MeOvm897VAjNTJP4owR96ssbfHBr6fjtMzmq6KM/s
```

> According to the above return value, decrypt the content by appId: `2025112058411324` refer to **encrypt demo**

代码块

```
{
    "appId": "2025112058411324",
    "code": 200,
    "data": {
        "current": 1,
        "pages": 1,
        "records": [
            {
```

```
                "card": "48781C24-ECDF-D037-E4D0-BBF00D003C34    48781C24-ECDF-D037-E4D0-BBF00D003C34",
                "pinCode": "48781C24-ECDF-D037-E4D0-BBF00D003C34",
                "skuId": "2025062450882798",
                "snCode": "48781C24-ECDF-D037-E4D0-BBF00D003C34"
            }
        ],
        "size": 200,
        "total": 1
    },
    "msg": "success"
}
```


Response Params:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
current	page number	integer
pages	The total number of pages in the current paging	integer
size	Gets the number of items displayed per page	integer
total	Total number of rows currently satisfying the condition	integer
records	code list	array
skuId	purchase skuId	string
card	code	string
pinCode	pinCode	string
snCode	snCode	string

Get direct top-up Param

Basic info

> **url**: `/api/getDirectParam`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**:

Request Body

> **Request Body**:

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
  "userId": "2025112058411324",
  "skuId": "2024032040589254"
}
```

> **Params**:

name	description	require	type
userId	appId	true	string
skuId	skuId	true	string

Response body

> **Example**

```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CkWqKmp+TuP5KHO5ereiaSvGRRM7cetnVxLte
6rVr7Z25FtgupfJd6oQn+JFdyueWXXhKs1PRXEYSZ+wLYhMf5I9sWVo54TeAlNReEDYyulrezffns4S
Y+NIM9dMYQAMbDNg+Cr0y3skoy1OyVwNLfBR9IeUuIAVgd6Uxkh4hc1gwALnGvcITuOkZuh4VzzML2Z
ysn1F3cYINfc9J2MsUn4zrStg2NP/Wcf71JliW6AjGoUU+n7rCsxp1+joklKifJkog6yAY2OrXKolOM
f8nO2uUF5AQPEEK3LM6uP52/zKKL1ZLHGd/qH6AKDi8/Ib9aNpbcbd0oYBiWbsLl+uDf5+CtMUPjA2v
ZzTLQd0P3zIqoPBS2lBIQmZy0YNLK/4ir1WeH+3MJWJZnrBVJNs/7
```


> According to the above return value, decrypt the content by appId: `2025112058411324`
> refer to **encrypt demo**

代码块

```
{
  "appId": "",
  "code": 0,
  "msg": "",
  "data": {
    "code": 0,
    "msg": "",
    "paramInfos": [
      {
        "name": "",
        "type": "",
        "label": "",
        "placeholder": "",
        "values": [
          {
            "value": "",
            "label": ""
          }
        ]
      }
    ]
  }
}
```

> **Response Params**:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer

msg	Response message success "success", Failure Others	string
data	Response data	
code	Response status	integer
msg	Response message	string
paramInfos	Direct Top-up parameter list .Note that this is a collection object	array
name	parameter name	string
type	parameter type . input/select	string
label	parameter label	string
placeholder	placeholder	string
values	List of enumerated values if parameter type is select. Note that this is a collection object	array
value	The enum value	string
label	The enum label	string

Place Order (Direct Top-up)

Basic Info

> **url**: `/api/placeDirectOrder`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**: Please obtain the direct top-up parameters before placing an order

Request Body

> **Request Body**:

代码块

```
{
    "appId": "provided by wwgcard",
```

```
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
  "userId": "2025112058411324",
  "accountId": "2023072638647824",
  "currency": "EUR",
  "serviceOrder": "1caf9f17-370e-112a-1e14-3c229sdfs99",
  "skuId": "2023111340882805",
  "faceValue": 500,
  "attributeValues": [
    {
      "name": "player ID",
      "value": "1234",
      "label": "Player ID"
    }
  ]
}
```

> **Params**:

name	description	require	type
userId	appId	true	string
accountId	account Id	true	string
currency	currency(The currency of payment)	true	string
serviceOrder	The service tracking number (provided by the caller)	true	string
skuId	skuId	true	string
faceValue	sku facevalue (required ,when purchasing a custom par sku)	false	number
attributeValues	parameter list	false	array

name	parameter name	true	string
value	parameter value	true	string
label	parameter label	false	string

> **please ensure `serviceOrder` is unique, wwgcard will check this value, if repeated, you can not place the order**

Response Body

> **Example**

代码块

```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CkWqKmp+TuP5KHO5ereiaSvGRRM7cetnVxLte
6rVr7Z25FtgupfJd6oQn+JFdyueWXXhKs1PRXEYSZ+wLYhMf5I9sWVo54TeAlNReEDYyulrezffns4S
Y+NIM9dMYQAMbDNg+Cr0y3skoy1OyVwNLfBR9IeUuIAVgd6Uxkh4hc1gwALnGvcITuOkZuh4VzzML2Z
ysn1F3cYINfc9J2MsUn4zrStg2NP/Wcf71JliW6AjGoUU+n7rCsxp1+joklKifJkog6yAY2OrXKolOM
f8nO2uUF5AQPEEK3LM6uP52/zKKL1ZLHGd/qH6AKDi8/Ib9aNpbcbd0oYBiWbsLl+uDf5+CtMUPjA2v
ZzTLQd0P3zIqoPBS2lBIQmZy0YNLK/4ir1WeH+3MJWJZnrBVJNs/7
```

> Decrypt the content in the following format according to the return value above，Refer to **encrypt demo**

代码块

```
{
        "appId": "2025112058411324",
        "code": 200,
        "data": {
            "code": 200,
            "data": "2024011148886234",
            "message": "success"
        },
        "msg": "success"
}
```

> **Response Params**:

name	description	type
appId	appId	string

code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
data	order id	integer
message	Response message	integer

Interface V 2.x

Place Order V2

Basic info

> **url**: `/api/v2/placeOrder`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**: Provide card purchase service and card activation service

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "userId": "2025112058411324",
    "accountId": "2023072638647824",
    "currency": "USD",
```

```
    "serviceOrder": "{your serice order }",
    "chargeAccountType": 1,
    "chargeAccountName": "{your charge account}",
    "returnUrl": "{your return url}",
    "detailVos": [
        {
        "skuId": "2024032040589254",
        "faceValue": 30,
        "buyNum": 1
        }
    ]
}
```

> **Params**:

name	description	require	type
userId	appId	**true**	string
accountId	account Id	**true**	string
currency	currency(The currency of payment)	**true**	string
serviceOrder	The service tracking number (provided by the caller)	**true**	string
chargeAccountType	Whether to activate the service. 1 indicates yes, 0 indicates no	**true**	integer
chargeAccountName	Activate the account with the recharge code. If chargeAccountType is 1, it is required	false	string
returnUrl	Recharge code Callback address of the activation result	false	string
detailVos	Goods to buy Note that this is a collection object	**true**	array
skuId	skuId	**true**	string

faceValue	sku facevalue (required ,when purchasing a custom par sku)	false	number
buyNum	buy number	**true**	integer

1. **please ensure `serviceOrder` is unique, wwgcard will check this value, if repeated, you can not place the order**
2. **We will notify the caller immediately after the end of the recharge, and if the caller does not return the successful content, we will notify the caller at 1 second, 5 seconds, 20 seconds, 1 minute, 2 minutes, 5 minutes, 10 minutes after the result is obtained**

Response body

> **Example**

代码块

```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CkWqKmp+TuP5KHO5ereiaSBRtCTze5E/eppEin4WQp6KaAQDIoImWeiHBmgA/Y5WPGMWhlbyCS4fhfLr9aPfrK65V+zgqdW8MV7bk09ksdtavVZ4f7cwlYlmesFUk2z/s=
```

> Decrypt the content in the following format according to the return value above，Refer to **encrypt demo**

代码块

```
{
        "appId": "2025112058411324",
        "code": 200,
        "data": {
              "code": 200,
             "data": "2024032240914951",
              "message": "success"
        },
        "msg": "success"
}
```

> **Response Params**:

name	description	type
appId	appId	string

code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
data	order id (you can query charge service status by this)	string
message	Response message	string

Code Activate

Basic info

> **url**: `/api/v2/codeActivate`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**: Provide card activation service

Request Body

> **Request Body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
"userId": "2025112058411324",
"carryPinCodes": [
"{carryPin code}"
],
```

```
"chargeAccount": "{your charge account}",
"notifyUrl": "{your return url}"
}
```

> **Params**:

name	description	require	type
userId	appId	**true**	string
carryPinCodes	carryPinCodes	**true**	list
chargeAccount	Activat account (like steam account name)	**true**	string
returnUrl	The return interface provided by the caller, if it exists, we will notify the caller after the recharge is finished	false	string

代码块

```
1. **We will do it at 1 second, 5 seconds, 20 seconds, 1 minute, 2 minutes, 5 minutes, 10 minutes after the end of the recharge until we get a success message from the caller**
```

Response body

> **Example**

代码块


```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CkWqKmp+TuP5KHO5ereiaS5ZZxQD4GjaxsWpubXYZwt9bmBjIKswwsneCvZPyuo4E4LHf4490FULOOuWbX41sKq98IaoC0vKjcJHb/VSqA29NSPNt8EK5UQIhvrhMgKb0=
```


> Decrypt the content in the following format according to the return value above，Refer to **encrypt demo**

代码块

```
{
    "appId": "2025112058411324",
```

```
    "code": 200,
    "data": {
        "code": 200,
        "msg": "Success",
        "orderServiceId": "2024032251303686"
    },
    "msg": "success"
}
```

> **Response Params**:

name	description	type
appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
orderServiceId	charge service order id , by this can check charge status	string
message	Response message	string

Query Activate status

Basic Info

> **url**: `/api/v2/queryCodeActivate`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**: query card activate status

Request Body

> **Request Body**

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg is encrypted by the following request body

代码块

```
{
    "userId": "2025112058411324",
    "orderServiceId": "{wwgcardOrderId} or {orderServiceId}"
}
```

> **Params**:

name	description	require	type
userId	appId	**true**	string
orderServiceId	Order number (palce order interface return) or service order number (code activate interface return)	**true**	string

Response body

> **Example**

代码块


```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CkWqKmp+TuP5KHO5ereiaSb75t9twl+jmqxRy
7yYxO1vK9MoavFlr7PlmKe0AgQ9b+gItHTeAxMwT8XeSINMahy1mro0dGsPy4dq8u5bT3YLNrJUaWmE
1nRKaOKV8n/EPipx1s7SLbfzOuPk0neljr2mG7PWeaHx869cgH8q9luDgsd/jj3QVQs465ZtfjWwoCP
59i38eOOFxhYg1iyz5VjNtLFmEQ52YKfoQg+dHAQZf8zy24Dj/UTW2KHTMwoRUC1vuwDGFC34Q3lzfq
ShnWXZExdN9+Me4OVNAAkyzYaQ==
```


> Decrypt the content in the following format according to the return value above，Refer to **encrypt demo**

代码块

```
{
    "code": 200,
    "msg": "成功",
    "stateCode": null,
    "data": {
       "orderServiceId": "2024032251303686",
       "rechargeMoney": 30,
       "finishMoney": 0,
       "serviceStatus": 1,
       "codesList": [
         {
           "carryPinCode": "920e9df7-**********-c16679b59071",
           "status": "PROCESSING",
           "failMessage": null
         }
       ]
    }
}
```

Response Params:

param	desc	type
appId	appId	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
orderServiceId	charge service order id	string
rechargeMoney	expecte recharge money	string
finishMoney	finish recharge money	string
serviceStatus	Recharge status (1 recharge 2 recharge completed 3 recharge abnormal (partially successful) 4 recharge failed)	string
codesList	carryPinCodes	list
carryPinCode	carryPinCode	string

status	code status	string
failMessage	error msg	string

(No-encrypt)Notify recharge result

Basic Info

> **url**: `{your callback url}`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consumes**: `*/*`
>
> **Note**: Notify the recharge result， ==encryption measures are not adopted on this interface==

Reuqest Body

> **Request Body**

代码块

```
{
  "orderServiceId": "2024032251303686",
  "rechargeMoney": 30,
  "finishMoney": 0,
  "serviceStatus": 1,
  "codesList": [
    {
      "carryPinCode": "920e9df7-**********-c16679b59071",
      "status": "PROCESSING",
      "failMessage": null
    }
  ]
}
```

> **params**:

param	desc	type
orderServiceId	charge service order id	string
rechargeMoney	expecte recharge money	string
finishMoney	finish recharge money	string

serviceStatus	Recharge status (1 recharge 2 recharge completed 3 recharge abnormal (partially successful) 4 recharge failed)	string
codesList	carryPin codes	list
carryPinCode	carryPin code	string
status	code status	string
failMessage	error msg	string

Response Body

> **response body**

```
代码块
1   success
```

- success
- Back to success, we assume you have received the notification and will not continue to notify you
- Any other string or content
- We will do it at 1 second, 5 seconds, 20 seconds, 1 minute, 2 minutes, 5 minutes, 10 minutes after the end of the recharge until we get a success message from the caller

Interface V 3.x

Topup parameter fetching

Basic Info

> **url**: `/api/v3/getCodeParamInfo`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consume**: `*/*`
>
> **Note**:

Request body

> **Request body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg:encrypted by the request body below

代码块

```
{
"userId": "2025112058411324",
 "carryPinCodes": [
        "{carryPinCode}"
 ]
}
```

> **parameter**:

parameter	description	mandatory	type
userId	appId	**true**	string
carryPinCodes	carryPinCodes	**true**	list

response body

> **example**

代码块

```
f5x9jj+QWl9RqWJm5Epx+x0dGUL5RLHtAgkdQt3PfxmXt2Pmbrpb9WWliG8/I2a+ezRKsOD03hrf7ni
4MuKYjdoOyrfpu9t300l9WkUelKz0uBRiUXFJtoXE37jabHlmiEcloNUoQB6a+W06B2AEoj7YYQU6+G
DpQ+oIQ6vmf17sfHm+U3Vx61og56k2uOUWEhIOov6am8bgXdr1I2uYyZtObDa5W9fHMP8ZTePA9fubJ
OQF8jfRKPE/NKWFo9BHRe8lwF5+dovdiS67Vwtq7avVZ4f7cwlYlmesFUk2z/s=
```

> decrypt the response body by your AppId， refer to **encryption demo**

代码块

```
{
 "appId": "2025112058411324",
```

```
  "code": 200,
  "data": {
     "code": 200,
     "msg": "成功",
     "codeParamInfos":  [
             {
                "carryPinCode": "{carryPinCode}",
                "paramInfos": [
                    {
                        "name": "{name}",
                        "type": "{type}",
                        "values": [
                            {
                                "value": "{value}",
                                "label": "{label}"
                            }
                        ],
                        "label": "{label}",
                        "placeholder": "{placeholder}"
                    }
                ],
              "verifyRole": "{verifyRole}"
             }
       ]
   },
   "msg": "success"
  }
```

> *response parameter*:

name	description	type
appId	appId	string
code	200 equals to success，else fail	integer
msg	success or others	string
data		
code	status	integer
msg	msg	string
codeParamInfos	topup parameter information	array
carryPinCode	carryPinCode	string

paramInfos	topup parammeter	array
name	Attribute names	string
type	type	string
label	label	string
placeholder	placeholder	string
values	enumeration	array
value	value	string
label	label	string
verifyRole	Whether to retrieve roles. Default is false. If the return value is true, the Get Role List interface needs to be called.	boolean

Topup activiation

Basic Info

> **url**: `/api/v3/codeActivate`
>
> **method**: `POST`
>
> **produces**: `application/x-www-form-urlencoded,application/json`
>
> **consume**: `*/*`
>
> **note**:

Request body

> **Request body**

代码块

```
{
    "appId": "provided by wwgcard",
    "accountId":"provided by wwgcard",
    "msg": "Encrypted request body"
}
```

> msg:encrypted by the request body below

代码块

```
{
  "userId": "2025112058411324",
   "codeParams": [
          {
             "carryPinCode": "{carryPinCode}",
             "paramValues": [
                 {
                     "name": "{name}",
                     "value": "{value}"
                 }
             ]
         }
   ],
  "notifyUrl": "{notifyUrl}"
  }
```

> **Parameter**:

Parameter	description	Mandatory	type
userId	appId	**true**	string
codeParams	code list	**true**	list
carryPinCode	carryPinCode	**true**	string
paramValues	topup parameters	**true**	list
name	name	**true**	string
value	value	**true**	string
notifyUrl	notification address	**false**	string

Response body

> **example**

代码块

```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CkWqKmp+TuP5KHO5ereiaS5ZZxQD4GjaxsWpubXYZwt9bmBjIKswwsneCvZPyuo4E4LHf4490FULOOuWbX41sKq98IaoC0vKjcJHb/VSqA29NSPNt8EK5UQIhvrhMgKb0=
```

> decrypt the response body by your AppId， refer to **encryption demo**

```
代码块
  "appId": "2025112058411324",
  "code": 200,
  "data": {
     "code": 200,
     "msg": "Success",
     "orderServiceId": "2024032251303686"
  },
  "msg": "success"
}
```

> **Response parameter**:

Parameter	Description	Type
appId	appId	string
code	200 equals to success，else fail	integer
msg	success or others	string
data		
code	status	integer
orderServiceId	topup orderId used to query topup status	string
message	message	string

Get Role List

Basic Information

> **Endpoint**: `/api/v3/getCodeRoleParam`
>
> **Request**: `POST`
>
> **Request Data Type**: `application/x-www-form-urlencoded,application/json`
>
> **Response Data Type**: `*/*`
>
> **Notes**: `getCodeParamInfo` When the `verifyRole` parameter returned by the recharge parameter acquisition interface is `true`, use this interface to query and obtain role parameters.

Request Body

> **Request Body

Code block

```
{
   "appId": "provided by wwgcard",
   "accountId":"provided by wwgcard",
   "msg": "Encrypted request body"
 }
```

> msg is encrypted from the request body below.

Code block

```
{
"userId": "2025112058411324",
"codeParams": [
     {
        "carryPinCode": "{carryPinCode}",
        "paramValues": [
            {
                "name": "{name}",
                "value": "{value}"
            }
        ]
     }
  ],
}
```

> **Parameters

Parameters	Introduction	Required	Parameter Type
userId	appId	**true**	string
codeParams	Code List	**true**	list
carryPinCode	Recharge Code	**true**	string
paramValues	Recharge Parameters	**true**	list
name	Parameter Name (must have a value when used as input)	**true**	string
value	Parameter Value	**true**	string

Response Body

> **Example

Code block

```
1
```

> Decrypt the response body using your AppId. Refer to the encryption demo.

Code block

```
1  {
2  "appId": "2025112058411324",
3  "code": 200,
4  "data": {
5   "code": 200,
6   "msg": "success",
7   "codeParamInfos":  [
8           {
9              "carryPinCode": "{carryPinCode}",
10             "paramInfos": [
11                 {
12                     "name": "{name}",
13                     "type": "{type}",
14                     "values": [
15                         {
16                             "value": "{value}",
17                             "label": "{label}"
18                         }
19                     ],
20                     "label": "{label}",
21                     "placeholder": "{placeholder}"
22                 }
23             ],
24          }
25    ]
26 },
27 "msg": "success"
28 }
```

> **Response Parameters:**

Parameters	Introduction	Parameter Type

appId	appId	string
code	Response status code: 200 for success, others for failure	integer
msg	Response message: "Success" for success, "Other" for failure	string
data		
code	Status	integer
msg	Message	string
codeParamInfos	Recharge parameter information	array
carryPinCode	Recharge code	string
paramInfos	Recharge parameters	array
name	Attribute name	string
type	Category	string
label	Label	string
placeholder	Placeholder	string
values	Enum	array
value	Value	string
label	Label	string

Annex Ⅰ 《wg cards Currency Directory》

Country	Currency
Thailand	THB
China	CNY
Saudi Arabia	SAR
Hong Kong (China)	HKD
South Africa	ZAR

United States	USD
Indonesia	IDR
Vietnam	VND
Ukraine	UAH
European Union	EUR
India	INR
Malaysia	MYR
Turkey	TRY
Japan	JPY
Taiwan (China)	TWD
South Korea	KRW
Brazil	BRL
Australia	AUD
Poland	PLN
Britain	GBP
The United Arab Emirates	AED
Qatar	QAR
Columbia	COP
New Zealand	NZD
Chile	CLP
Romania	RON
Sweden	SEK
Norway	NOK
Denmark	DKK
Kuwait	KWD
Canada	CAD

Mexico	MXN
Russia	RUB
Singapore	SGD
Argentina	ARS
Philippines	PHP
Switzerland	CHF
Czech Republic	CZK
Hungary	HUF
Peru	PEN
Morocco	MAD
Jordan	JOD

Annex II 《wg cards Version Logs》

> This section records the changes of all version updates since V1.2.0

V 1.2.1 2023-09-12

- Summary
  a. Request body add prod environment
- Place Order
  a. Request body add parameter **userId**
- Get Order History
  a. Request body change parameter from **accountId** to **userId**
  b. Request body change parameter from **pageSie** to **size**
  c. Request body change parameter from **pageNum** to **current**
- Get Order Detail Info
  a. Request body add parameter **userId**
- Get Order Code
  a. Request body add parameter **userId**
  b. Response body modify **data** from an array object to an entity object

V 1.2.2 2023-09-13

- Place Order
  a. Delete the parameter **itemId** from the **detailVos** object
  b. Delete the parameter **itemName** from the **detailVos** object
  c. Delete the parameter **skuName** from the **detailVos** object

V 1.2.3 2023-09-14

- Get Stock
  a. Response body modify **data** from an entity object object to an array
  b. Request body change parameter from **skuId** to **skuIds**
  c. Request body modify **skuIds** from an string object object to an array
- Get Order Code
  a. Response body modify **records**， change from an array of strings to an array of objects

V 1.2.4 2023-09-21

- How To Encrypt
  a. add aes destribution

V 1.2.5 2023-10-16

- Added interfaces for obtaining commodity information and inventory information

V 1.2.6 2023-10-25

- Fix some documentation errors
- **Increased call interface frequency limit**

V 1.2.7 2023-12-03

- **Add ip address whitelist**

V 1.2.8 2024-01-11

- ==Increased supply of custom denominations==
- Modify the return parameter of the `getItemAndStock` interface
- Modify the return parameter of the `getItem` interface
- Modify the `placeOrder` interface request parameters
- Modify the return parameter of the `getOrderInfoAndDetail` interface

- Modify the Get Stock interface return. If -1 is returned, there is no limit
- Add annex `Supported Currency Catalog`

V 1.2.9 2024-01-16

- change dev ip

V 2.1.0 2024-03-21

- Provides a new ordering interface to support the code activation service for your account while placing an order for a card
- Provide code activation service
- Provides an interface for querying activation code results
- Provides an asynchronous notification activation result interface
- Change getCode interface , in response body ,add `pinCode` and `snCode`

V 2.1.1 2024-07-02

- change dev ip address

V 2.1.2 2024-07-23

- add new interfance `getAllItem`

V 2.1.3 2024-09-11

- `Get Product Info` add return param `spuImage` , `howExchange`
- `Get Product And Stock Info` add return param `spuImage` , `howExchange`

V 2.1.4 2024-11-15

- `Get Product Info` add return param `spuType`
- `Get Product And Stock Info` add return param `spuType`
- `Get All Product` add return param `spuType`

V 2.1.5 2025-03-19

- `Topup parameter fetching`
- `Topup activiation`

V 2.1.6 2025-04-18

- add new interface `getDirectParam`
- add new interface `placeDirectOrder`

V 2.1.7 2025-04-28

- add TOP-UP status `orderDirectStatus`

V 2.1.8 2025-06-12

- `Get Product Info` add request param 'language'
- `Get Product Info` add return param `description`
- `Get All Product` add request param `language`

V 2.1.9 2025-09-04

- `Get Order Detail Info` supports querying through `serviceOrder( what sent to us when placing the order)`
- `Get Order Detail Info` add return param `requestId`

V 2.2.0 2025-09-10

- Interface V 3.x
- `getCodeParamInfo` add return param `verifyRole`
- add new interface `getCodeRoleParam`

V 3.0.0 2025-11-20

- change dev ip address
- Provide new account for test