TABLE III

DAR BENCHMARKS WITHOUT DRIFTSLICE; HWA + GDC-SAFE REMAINS THE BASELINE

Model	Training	Compensation	Test Accuracy (%)				Gain vs HWA + GDC-safe (pp)			
			Final Test	Initial 20s	Final 5Y	Max-drop	1h	1d	6M	5Y
ResNet-32	HWA	GDC-safe (baseline)	—	89.91	84.14	5.78	—	—	—	—
ResNet-32	HWA	DriftSlice B=1	—	**89.96**	85.11	4.85	+0.20	+0.30	+0.70	+0.97
ResNet-32	HWA	DriftSlice selected B	—	89.96	85.07	4.88	+0.20	+0.28	+0.67	+0.94
ResNet-32	DAR-HWA	None (pure DAR)	—	89.93	10.06	79.88	-71.84	-77.73	-75.82	-74.07
ResNet-32	DAR-HWA	GDC-safe	—	89.85	84.46	5.38	+0.02	+0.01	+0.22	+0.33
ResNet-32	NSR-HWA	GDC-safe	—	89.81	74.22	16.05	-2.19	-7.54	-11.36	-9.92
ResNet-32	NSR-HWA	DriftSlice B=1	—	89.88	**85.30**	**4.58**	+0.16	+0.20	+0.73	+1.17
ResNet-32	NSR-HWA	DriftSlice selected B	—	89.87	85.25	4.63	+0.16	+0.17	+0.69	+1.11

All gains use HWA + GDC-safe as the baseline. Means across 3 repetitions, each with 30 device realizations.

Training and compensation vary across rows; matched-training comparisons isolate compensation.

Max-drop = initial 20s accuracy minus the minimum over 12 timestamps. Final Test before PCM is unavailable.