

# High-Power DC Power Supply

## MPS-15000S Series



Standard RS-232 RS-485 SENSE

### Features

- Simultaneous five digit display of voltage and current, precise and easy to use
- Adopting PWM modulation and high gain amplification circuit design, stable and reliable
- The panel has preset buttons that can preset voltage and current values
- Complete protection functions: OVP、OCP、OTP、Short circuit protection
- Key lock function
- Key components are imported to ensure long-term full load operation
- Remote voltage compensation function ensures usage accuracy

| Model                                |                | Voltage                                             | Current          | Power  |
|--------------------------------------|----------------|-----------------------------------------------------|------------------|--------|
| MPS-15000S-30-500                    |                | 0-30.000V                                           | 0-500.00A        | 15000W |
| MPS-15000S-60-250                    |                | 0-60.000V                                           | 0-250.00A        | 15000W |
| MPS-15000S-100-150                   |                | 0-100.00V                                           | 0-150.00A        | 15000W |
| MPS-15000S-150-100                   |                | 0-150.00V                                           | 0-100.00A        | 15000W |
| MPS-15000S-200-75                    |                | 0-200.00V                                           | 0-75.000A        | 15000W |
| MPS-15000S-300-50                    |                | 0-300.00V                                           | 0-50.000A        | 15000W |
| MPS-15000S-600-25                    |                | 0-600.00V                                           | 0-25.000A        | 15000W |
| MPS-15000S-1000-15                   |                | 0-1000.0V                                           | 0-15.000A        | 15000W |
| MPS-15000S-1500-10                   |                | 0-1500.0V                                           | 0-10.000A        | 15000W |
| AC input                             | Three-phase    |                                                     | AC380V±10%, 50Hz |        |
| DC output                            | Output voltage | 0V - rating                                         |                  |        |
|                                      | Output current | 0A - rating                                         |                  |        |
|                                      | Output power   | 0W - rating                                         |                  |        |
| Load regulation                      | Voltage        | ≤0.1%F.S+0.1%F.S                                    |                  |        |
|                                      | Current        | ≤0.1%F.S+0.1%F.S                                    |                  |        |
| Setting value accuracy               | Voltage        | ≤0.1%F.S+0.1%F.S                                    |                  |        |
|                                      | Current        | ≤0.1%F.S+0.1%F.S                                    |                  |        |
| Readback value accuracy              | Voltage        | ≤0.1%F.S+0.1%F.S                                    |                  |        |
|                                      | Current        | ≤0.1%F.S+0.1%F.S                                    |                  |        |
| Ripple(20Hz-20MHz)                   | Voltage        | Vrms≤0.2%F.S+50mV                                   |                  |        |
| Dynamic response time(10% -90% load) |                | ≤5mS                                                |                  |        |
| Display method                       |                | 4 and a half digit meter (LED digital tube display) |                  |        |
| Display resolution                   |                | Voltage0.001V/0.01V/0.1V,Current0.001A/0.01A/0.1A   |                  |        |
| Interface                            |                | RS232/RS485                                         |                  |        |
| Functional protection                |                | OVP, OCP, OTP, Short circuit protection             |                  |        |
| Heat dissipation method              |                | Adopting PWM speed regulating fan, air-cooled       |                  |        |
| Operating environment                |                | Temperature 0 °C -40 °C; Humidity 10% -85% RH       |                  |        |
| Environment                          |                | Temperature -20 °C -70 °C; Humidity 10% -90% RH     |                  |        |
| Size (mm)                            |                | 430×560×132 (W*D*H mm)                              |                  |        |
| Weight (kg)                          |                | 26KG                                                |                  |        |
| Note                                 |                | The power cord and output cables are optional       |                  |        |