

High-Power DC Power Supply

MPS-7500S Series



Standard RS-232 RS-485 SENSE

Features

- Simultaneous five digit display of voltage and current, precise and easy to use
- Adopting PWM modulation and high gain amplification circuit design, stable and reliable
- The panel has preset buttons that can preset voltage and current values
- Complete protection functions: OVP、OCP、OTP、Short circuit protection
- Key lock function
- Key components are imported to ensure long-term full load operation
- Remote voltage compensation function ensures usage accuracy

Model		Voltage	Current	Power
MPS-7500S-30-250		0-30.000V	0-250.00A	7500W
MPS-7500S-60-125		0-60.000V	0-125.00A	7500W
MPS-7500S-100-75		0-100.00V	0-75.000A	7500W
MPS-7500S-150-50		0-150.00V	0-50.000A	7500W
MPS-7500S-200-36		0-200.00V	0-36.000A	7200W
MPS-7500S-300-25		0-300.00V	0-25.000A	7500W
MPS-7500S-600-12		0-600.00V	0-12.000A	7200W
MPS-7500S-1500-5		0-1500.0V	0-5.0000A	7500W
AC input	Three-phase		AC380V±10%, 50Hz	
DC output	Output voltage		0V - rating	
	Output current		0A - rating	
	Output power		0W - rating	
Load regulation	Voltage		≤0.1%F.S+0.1%F.S	
	Current		≤0.1%F.S+0.1%F.S	
Setting value accuracy	Voltage		≤0.1%F.S+0.1%F.S	
	Current		≤0.1%F.S+0.1%F.S	
Readback value accuracy	Voltage		≤0.1%F.S+0.1%F.S	
	Current		≤0.1%F.S+0.1%F.S	
Ripple(20Hz-20MHz)	Voltage		Vrms≤0.2%F.S+50mV	
Dynamic response time(10% -90% load)			≤5mS	
Display method			4 and a half digit meter (LED digital tube display)	
Display resolution			Voltage0.001V/0.01V/0.1V,Current0.001A/0.01A/0.1A	
Interface			RS232/RS485	
Functional protection			OVP, OCP, OTP, Short circuit protection	
Heat dissipation method			Adopting PWM speed regulating fan, air-cooled	
Operating environment			Temperature 0 °C -40 °C; Humidity 10% -85% RH	
Environment			Temperature -20 °C -70 °C; Humidity 10% -90% RH	
Size (mm)			430×500×88 (W*D*H mm)	
Weight (kg)			16KG	
Note			The power cord and output cables are optional	