

Triple Channel DC Power Supply

MPS-S-3 Series



- One click series and parallel settings, convenient and easy to use
- Input voltage 110V/220V switching, globally applicable
- Power on state memory setting
- The buzzer can be turned off and on
- One click factory reset function

Features

- High precision display with a resolution of 10mV voltage and 1mA current
- CH1 and CH2 independent output switch control, convenient and practical
- Easily preset current without short circuit, disrupting your use
- OVP/OCP settings, fully functional
- The knob adopts an encoded switch, which is convenient and fast to use, and has anti misoperation function
- The design of the startup slow start circuit has low surge current and high practicality
- V/A can be adjusted within a range to prevent accidental operation and damage to the measured object

Model		MPS-3206S-3		MPS-3210S-3		MPS-6005S-3		MPS-8003S-3		MPS-15H02S-3	
Rated input voltage		AC 220V/110V±10% 50Hz/60Hz									
Channel		CH1/CH2	CH3	CH1/CH2	CH3	CH1/CH2	CH3	CH1/CH2	CH3	CH1/CH2	CH3
Rated output voltage		0~32V	5V	0~32V	5V	0~60V	5V	0~80V	5V	0~150V	5V
Rated output current		0~6A	3A	0~10A	3A	0~5A	3A	0~3A	3A	0~2A	3A
Rated output power		399W		655W		615W		495W		615W	
Load regulation rate	Voltage	<0.1%+5mV		<0.1%+10mV		<0.1%+5mV		<0.1%+10mV		<0.1%+10mV	
	Current	<0.2%+3mA		<0.2%+5mA		<0.2%+3mA		<0.2%+3mA		<0.2%+3mA	
Line regulation rate	Voltage	<0.1%+5mV		<0.1%+10mV		<0.1%+5mV		<0.1%+10mV		<0.1%+10mV	
	Current	<0.2%+3mA		<0.2%+5mA		<0.2%+3mA		<0.2%+3mA		<0.2%+3mA	
Set value accuracy	Voltage	≤0.1%+1digit		≤0.1%+1digit		≤0.1%+2digits		≤0.1%+2digits		≤0.1%+2digits	
	Current	≤0.2%+3mA		≤0.2%+5mA		≤0.2%+3mA		≤0.2%+3mA		≤0.2%+3mA	
Readback value accuracy	Voltage	≤0.1%+1digit		≤0.1%+1digit		≤0.1%+2digits		≤0.1%+1digit		≤0.1%+1digit	
	Current	≤0.2%+3mA		≤0.2%+5mA		≤0.2%+3mA		≤0.2%+3mA		≤0.2%+3mA	
Readback resolution	Voltage	10mV		10mV		10mV		10mV		10mV	
	Current	1 mA		1 mA		1 mA		1 mA		1 mA	
Ripple and Noise	Voltage	≤10mVrms		≤10mVrms		≤10mVrms		≤10mVrms		≤10mVrms	
	Current	≤5mA _{rms}		≤5mA _{rms}		≤5mA _{rms}		≤5mA _{rms}		≤5mA _{rms}	
OVP		0~32V±0.2%FS		0~32V±0.2%FS		0~62V±0.2%FS		0~80V±0.2%FS		0~150V±0.2%FS	
Max voltage		32V±0.2%		32V±0.2%		62V±0.2%		80V±0.2%		150V±0.2%	
OCP		0~6.1A±0.2%FS		0~10A±0.2%FS		0~5.1A±0.2%FS		0~3.1A±0.2%FS		0~2.1A±0.2%FS	
Max current		6.1A±0.2%		10A±0.2%		5.1A±0.2%		3.1A±0.2%		2.1A±0.2%	
Temperature	Operational environment	0~40℃≤80%RH									
	Storage environment	-15~70℃≤80%RH									
Size	(W*H*D)	219*95*300 mm									
Weight	kg	4.5									