

Table 1: Firewall Performance and Capacities												
Performance and Capacities	PA-7500 ^A	PA-5580	PA-5570	PA-5560	PA-5550	PA-5540	PA-5450 ^B	PA-5445	PA-5440	PA-5430	PA-5420	PA-5410
Firewall throughput (appmix)	1.5 Tbps	375 Gbps	300 Gbps	240 Gbps	175 Gbps	150 Gbps	200 Gbps	90 Gbps	85 Gbps	80 Gbps	70 Gbps	52 Gbps
Threat Prevention throughput (appmix)	1.44 Tbps	300 Gbps	240 Gbps	180 Gbps	120 Gbps	90 Gbps	189 Gbps	76 Gbps	70 Gbps	60 Gbps	50 Gbps	35 Gbps
IPsec VPN throughput	407 Gbps	170 Gbps	150 Gbps	125 Gbps	100 Gbps	80 Gbps	85 Gbps ^C	64 Gbps	58 Gbps	42 Gbps	28 Gbps	20 Gbps
New sessions per second	7.2M	3.3M	3M	2.5M	1.67M	1.33M	3.6M ^B	449,000	390,000	380,000	370,000	270,000
Maximum sessions	440M	99M	89M	74M	49M	39M	100M ^B	48M	20M	9M	7M	5M
Virtual systems (base/max ^D)	25/225 (standalone) 25/25 (NGFW cluster)	25/225					25/225			25/125	15/65	10/20
Hardware Specifications	PA-7500	PA-5580	PA-5570	PA-5560	PA-5550	PA-5540	PA-5450	PA-5445	PA-5440	PA-5430	PA-5420	PA-5410
Interfaces supported ^E	SFP-DD (up to 84), QSFP-DD (up to 56)	10G/25G SFP28 (8), 40G/100G QSFP28 (12), and 100G/400G QSFP-DD (8)			10G/25G SFP28 (16), 40G/100G QSFP28 (16), and 100G/400G QSFP-DD (4)		100/1000/10G Cu (up to 8), 1G/10G SFP/SFP+ (up to 24), 40G/100G QSFP28 (up to 4)	1G/2.5G/5G/10G (8), 1G/10G SFP/SFP+ (12), 25G SFP28 (4), 40G/100G QSFP+/QSFP28 (4)				
Management I/O	QSFP28 logging (2), QSFP-DD HA (2), SFP28 management (2), Combo RJ-45 console (1), Micro USB console (1), USB (1)	Out-of-band management: 1G/10G SFP+ (2) Console: RJ-45 console port (1) Console: USB-C Bootstrap: USB 3.2 Gen1 Type A HSCI: 100G/400G QSFP-DD (2) Log: 10G SFP+ (2)					SFP/SFP+ MGT (2), SFP/SFP+ HA1 (2), HSCI HA2/HA3 QSFP+/QSFP28 (2), RJ-45 serial console (1), Micro USB serial console (1)	1G SFP out-of-band management (1), 1G SFP HA (2) 40G QSFP+ HA (1), RJ-45 serial console (1), Micro USB serial console (1)				
Size	14U standard rack (24.4" H x 31.0" D x 17.4" W)	3U, 19" standard rack (5.2" H x 29.8" D x 17.3" W) with power supply inserted.					5U, 19" standard rack (8.75" H x 30.25" D x 17.38" W)	2U, 19" standard rack (3.45" H x 22.5" D x 17.34" W)				
Power supply	M+N (up to 10 PSUs)	2+2 redundant for 220V and DC 3+1 redundant for 110V					2200W AC or DC (2 expandable to 4)	1200W AC or DC (1:1 fully redundant) (2)				
Redundant power supply	Yes	Yes					Yes					
Disk drives	—	Optional 3.84 TB RAID1 SSD pair for system and log storage supported as cold swap.					System: 480 GB SSD, RAID1 Log: 4 TB SSD (optional)	480 GB SSD pair, system storage				
Hot-swappable fans	Yes	Yes					Yes					
Performance and Capacities	PA-3440	PA-3430		PA-3420		PA-3410		PA-1420		PA-1410		
Firewall throughput (appmix)	35 Gbps	29 Gbps		19 Gbps		14 Gbps		9.5 Gbps		8.5 Gbps		
Threat Prevention throughput (appmix)	20 Gbps	15 Gbps		10 Gbps		7.5 Gbps		6.2 Gbps		4.5 Gbps		
IPsec VPN throughput	14.5 Gbps	12 Gbps		9.9 Gbps		6.6 Gbps		5.6 Gbps		4.1 Gbps		
New sessions per second	268K	240K		220K		145K		140K		100K		
Maximum sessions	3M	2.5M		2.2M		1.4M		1.4M		945K		
Virtual systems (base/max ^D)	1/11							1/6				
Hardware Specifications	PA-3440	PA-3430		PA-3420		PA-3410		PA-1420		PA-1410		
Interfaces supported ^D	1G/2.5G/5G/10G (12), 1G/10G SFP/SFP+ (10), 25G SFP28 (4), 40G/100G QSFP/QSFP28 (2)			1G/2.5G/5G/10G (12), 1G/10G SFP/SFP+ (10), 25G SFP28 (4)				10/100/1000 (4), 1/2.5/5G (4), 1/2.5/5G (4)/PoE, 1G SFP (2), 10G SFP+ (8)		10/100/1000 (8), 1/2.5/5G (4)/PoE, 1G SFP (6), 10G SFP+ (4)		
Management I/O	10/100/1000 out-of-band management (1), 10/100/1000 high availability (2), 10G SFP+ high availability (1), RJ-45 console port (1), Micro USB (1)							10/100/1000 out-of-band management (1), HSCI 10G high availability (1), RJ-45 console (1), USB (1), Micro USB console (1)				
Size	1U, 19" standard rack (14.15" H x 17.15" D x 1.70" W)							1U, 19" standard rack (1.70" H x 14.15" D x 17.15" W)				
Power supply	450W AC							450W AC (2; one is redundant)				
Redundant power supply	Yes							Yes				
Disk drives	480 GB SSD							240 GB SSD		120 GB SSD		
Hot-swappable fans	No							No				

Table 1: Firewall Performance and Capacities (continued)														
Performance and Capacities	PA-560	PA-555-POE		PA-550	PA-545-POE		PA-540	PA-520		PA-510		PA-505		PA-501
Firewall throughput (appmix)	8.5 Gbps	7.5 Gbps		6.5 Gbps	5.0 Gbps		3.8 Gbps	2.8 Gbps		1.8 Gbps		1.2 Gbps		800 Mbps
Threat Prevention throughput (appmix)	6.0 Gbps	5.0 Gbps		4.5 Gbps	3.0 Gbps		2.2 Gbps	1.8 Gbps		1.2 Gbps		800 Mbps		500 Mbps
IPsec VPN throughput	5.5 Gbps	4.5 Gbps		4.0 Gbps	3.0 Gbps		2.0 Gbps	1.5 Gbps		0.8 Gbps		400 Mbps		240 Mbps
New sessions per second	100K	75K		70K	55K		50K	25K		15K		9K		5K
Maximum sessions	598K	448K		398K	298K		248K	148K		98K		62K		30K
Virtual systems (base/max ⁹⁾)	1/5	1/5		1/5	1/2		1/2	—		—		—		—
Hardware Specifications	PA-560	PA-555-POE		PA-550	PA-545-POE		PA-540	PA-520		PA-510		PA-505		PA-501
Interfaces supported ^E	1G RJ-45 (16), 1G SFP (4), 1G/10G SFP/SFP+ (4)	1G RJ-45 (2), 1G RJ-45 bypass (2), 1G RJ-45 (4)/PoE, 1G/2.5G (4)/PoE, 1G SFP (2), 1G/10G SFP/SFP+ (2)		1G RJ-45 (10), 1G RJ-45 bypass (2), 1G SFP (2), 1G/10G SFP/SFP+ (2)	1G RJ-45 (6), 1G RJ-45 bypass (2), 1G/2.5G (4)/PoE, 1G SFP (4)		1G RJ-45 (8), 1G SFP (2)	1G RJ-45 (8)		1G RJ-45 (8)		1G RJ-45 (7)		1G RJ-45 (7)
Management I/O	10/100/1000 out-of-band management port (1), USB port (1), RJ-45 console port (1), and USB-C console port (1)									10/100/1000 out-of-band management port (1), USB port (2), RJ-45 console port (1), and Micro USB console port (1)		10/100/1000 out-of-band management port (1), USB port (2), and RJ-45 console port (1)		10/100/1000 out-of-band management port (1), USB port (2), and RJ-45 console port (1)
Size	1.74" H x 12.1" D x 13" W (43.9 mm H x 37 mm D x 330 mm W)	1.75" H x 12.6" D x 16.1" W (43.9 mm H x 314 mm D x 409 mm W)		1.74" H x 12.1" D x 13" W (43.9 mm H x 37 mm D x 330 mm W)	1.75" H x 12.6" D x 16.1" W (43.9 mm H x 314 mm D x 409 mm W)		1.74" H x 10.4" D x 8" W (43.9 mm H x 265 mm D x 203 mm W)		1.74" H x 8.83" D x 8.07" W (43.9 mm H x 224 mm D x 205 mm W)		1.63" H x 6.42" D x 9.53" W (43.9 mm H x 163 mm D x 242 mm W)		1.63" H x 6.42" D x 9.53" W (43.9 mm H x 163 mm D x 242 mm W)	
Power supply	150W	550W		150W	350W		150W	150W	40W		25W		25W	
Redundant power supply	Yes	Yes		Yes	Yes		Yes	Yes	Yes		Yes		Yes	
Disk drives	240 GB	120 GB		120 GB	120 GB		120 GB	120 GB	128 GB		128 GB		128 GB	
Hot-swappable fans	No	Fanless												
Performance and Capacities	PA-460	PA-455R-5G	PA-455	PA-455-5G	PA-450R-5G	PA-450R	PA-450	PA-445	PA-440	PA-415-5G	PA-415	PA-410R-5G	PA-410R	PA-410
Firewall throughput (appmix)	4.2 Gbps	3.2 Gbps	3.6 Gbps	3.2 Gbps	3.2 Gbps	3.2 Gbps	3.3 Gbps	2.7 Gbps	2.4 Gbps	1.5 Gbps	1.5 Gbps	1.4 Gbps	1.4 Gbps	1.4 Gbps
Threat Prevention throughput (appmix)	3.0 Gbps	1.8 Gbps	2.3 Gbps	1.8 Gbps	1.7 Gbps	1.7 Gbps	2.1 Gbps	1.25 Gbps	1.2 Gbps	800 Mbps	800 Mbps	650 Mbps	650 Mbps	800 Mbps
IPsec VPN throughput	2.3 Gbps	1.3 Gbps	1.8 Gbps	1.6 Gbps	1.3 Gbps	1.3 Gbps	1.7 Gbps	1.1 Gbps	1.1 Gbps	500 Mbps	500 Mbps	650 Mbps	650 Mbps	500 Mbps
New sessions per second	67K	48K	56K	48K	48K	48K	48K	34K	34K	11.4K	11K	11.4K	11.4K	11K
Maximum sessions	400K	200K	300K	300K	200K	200K	300K	200K	200K	64K	64K	64K	64K	64K
Virtual systems (base/max ⁹⁾)	1/5	1/2	1/5	1/5	1/2	1/2	1/5	1/2	1/2	1/1	1/1	1/2	1/2	1/1
Hardware Specifications	PA-460	PA-455R-5G	PA-455	PA-455-5G	PA-450R-5G	PA-450R	PA-450	PA-445	PA-440	PA-415-5G	PA-415	PA-410R-5G	PA-410R	PA-410
Interfaces supported ⁹⁾	10/100/1000 (8)	Integrated 5G (DSSS – Dual SIM Single Standby), 1G RJ-45 (6), 1G SFP/RJ-45 combo (2), 1G RJ-45 PoE (4)	1G SFP/RJ-45 combo (2), 1G RJ-45 (2), 1G RJ-45/PoE (4)	Embedded 5G cellular module, 1G SFP/RJ-45 combo (2), 1G RJ-45 (6), 1G RJ-45 PoE (4)	Integrated 5G (Dual SIM Single Standby [DSSS]), 10/100/1000 (6), 1G SFP/RJ-45 combo (2)	10/100/1000 (6), Combo [SFP or Copper 10/100/1000] (2)	10/100/1000 (8)	10/100/1000 (8), 1G SFP/RJ-45 Combo	10/100/1000 (8)	Embedded 5G Wireless WAN Module, 1G SFP/RJ-45 combo (1), 1G RJ-45 (4), 1G RJ-45/PoE (4)	10/100/1000 (8), 1G SFP/RJ-45 Combo	Integrated 5G (DSSS), 10/100/1000 (4), 1G SFP (2)	10/100/1000 (4), 1G SFP (2)	10/100/1000 (7)
Management I/O	10/100/1000 out-of-band management (1), RJ-45 console (1), USB (2), Micro USB console (1)	10/100/1000 out-of-band management (1), RJ-45 console port (1), USB port (1)	SFP/RJ-45 (1 GB) combo management (1), RJ-45 console port (1), USB port (2), Micro USB console port (1)	SFP/RJ-45 (1 GB) combo management port (1), RJ-45 console port (1), USB port (1)	10/100/1000 out-of-band management (1), RJ-45 console port (1), USB port (1)		10/100/1000 out-of-band management (1), RJ-45 console (1), USB (2), Micro USB console (1)	1G SFP/RJ-45 combo management (1), RJ-45 console (1), USB (2), Micro USB console (1)	10/100/1000 out-of-band management (1), RJ-45 console (1), USB (2), Micro USB console (1)	SFP/RJ-45 (1 GB) combo management (1), RJ-45 console port (1), USB port (2) Micro USB console port (1)	1G SFP/RJ-45 combo management (1), RJ-45 console (1), USB (2), Micro USB console (1)	10/100/1000 out-of-band management (1), RJ-45 console port (1), USB port (1)		10/100/1000 out-of-band management (1), RJ-45 console (1), USB (2)
Size	1.74" H x 8.83" D x 8.07" W	16.1" H x 7.07" D x 13.84" W	1.7" H x 9.4" D x 15.4" W	1RU H x 283 mm D x 303 mm W	1.75" H x 9.96" D x 15.35" W	1.74" H x 9.37" D x 15.35" W	1.74" H x 8.83" D x 8.07" W	1.66" H x 13" D x 8.87" W	1.74" H x 8.83" D x 8.07" W	1.73" H x 9" D x 13" W	1.73" H x 13" D x 9" W	4.13" H x 8.19" D x 10.63" W	3.78" H x 8.19" D x 10.63" W	1.63" H x 6.42" D x 9.53" W
Power supply	Dual redundant 50W	Direct AC Power	Dual redundant 150W	Dual Redundant 270W	Dual redundant 150W	Dual redundant 150W	Dual redundant 50W	Dual redundant 150W	Dual redundant 50W	Dual redundant 150W		Dual DC		25W
Redundant power supply	Yes (optional)	Dual (both required for load balancing)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	Yes (optional)	No
Disk drives	128 GB eMMC													
Hot-swappable fans	Fanless													

(A) Results measured with a configuration using 6 PA-7500-DPC-A cards and 2 PA-7500-NPC-A cards. (B) tests are performed with 2 networking cards and 4 data processing cards populated, unless otherwise noted. (C) This test is performed with 1 networking cards and 5 data processing cards populated. (D) Adding virtual systems to the base quantity requires a separately purchased license. Adding virtual systems for PA-440, PA-445, PA-450, and PA-460 requires a minimum of PAN-OS® 11.0. (E) Optical and copper transceivers are sold separately.

