

ECSE 543: Numerical Methods
Assignment 1

Wenjie Wei
260685967

October 6, 2018

Contents

1	Introduction	2
2	Choleski Decomposition	2
2.a	Choleski Implementation	2
2.b	Simple Tester Matrices	2
2.c	Linear Resistive Networks	2
2.c.1	Testing Circuit 1	3
2.c.2	Testing Circuit 2	3
2.c.3	Testing Circuit 3	3
2.c.4	Testing Circuit 4	3
	Appendix A Code Listings	5

1 Introduction

All programs in this assignment are written and compiled with Python 3.6. This report is structured so that the individual problems are answered in respective sections. The python codes used to solve the assignment problems are attached in the appendices, with the file names labeled at the top of the code segments.

2 Choleski Decomposition

2.a Choleski Implementation

The implementation of Choleski decomposition is shown in Listing 2. There are two methods defined in `choleski.py`: `check_choleski(A, b, x)` and `choleski_decomposition(A, b)`. The latter method takes two matrices **A** and **b** as arguments, and returns **x** as the computational result of the decomposition. The first method takes these three matrices as arguments, and performs matrix production to check the result of

$$Ax = b$$

The precision of the equality is set to 0.001, as the program may end up with results with uncertainties with a quantity level of 10^{-8} .

2.b Simple Tester Matrices

To examine the functionality of the implementation, some tester matrices are constructed. The first tester matrix has randomly chosen entries, under the condition that the matrix is a non-singular, symmetric, positive definite matrix:

$$\begin{bmatrix} 15 & -5 & 0 & -5 \\ -5 & 12 & -2 & 0 \\ 0 & -2 & 6 & -2 \\ -5 & 0 & -2 & 9 \end{bmatrix} x = \begin{bmatrix} 115 \\ 22 \\ -51 \\ 13 \end{bmatrix}$$

To ensure non-singularity and positiveness, the entries on the primary diagonal must be chosen to be positive, otherwise the program will raise errors, meaning that the matrix does not meet the requirement. If the Choleski Decomposition succeeds, the matrix is proven to be positive definite.

Figure 1 shows the result of the test of this certain tester matrix. This result is found to be correct by checking the dot product (which is implemented in file `matrix.py`) of matrix **A** and vector **x**. This result is also verified by MATLAB using the backslash operator.

```
choleski
E:\Documents\python_env\Scripts\python.exe "E:/Documents/Cou...
Matrix A is:
| 15.000000 -5.000000 0.000000 -5.000000 |
| -5.000000 12.000000 -2.000000 0.000000 |
| 0.000000 -2.000000 6.000000 -2.000000 |
| -5.000000 0.000000 -2.000000 9.000000 |
Vector b is:
| 115.000000 |
| 22.000000 |
| -51.000000 |
| 13.000000 |
Result vector x is:
| 12.197740 |
| 6.254237 |
| -3.968927 |
| 7.338983 |
Correct
```

Figure 1: Result of the First Choleski Decomposition Test

2.c Linear Resistive Networks

Linear resistive networks are now able to be solved by the Choleski decomposition implemented in the previous parts. Listing 3 shows the implementation of reading a circuit file with data organized in a .csv file.




Figure 2: Test Circuit 5

```
wenjie@wenjie-XPS-13-9343:~/f18/numerical_method/a1$ python linearNetwork.py
5.000000
3.750000
3.750000
```

Figure 3: Result of the Testing Circuit 5

Take the 5th circuit provided by the TA for example, the circuit is shown in Figure 2, and the result of the running of the program on this circuit is shown in Figure 3.

The data of the circuit are organized in the way shown in Figure 4. The first line shows the general information about the circuit, such as the circuit ID (the example shown in the figure is the 5th test circuit), number of branches, and number of nodes. The lines followed are the data of the branches, which contains the following data: the

1	5	B	6	N	4
2	0	1	0	20	10
3	1	2	0	10	0
4	1	3	0	10	0
5	2	0	0	30	0
6	2	3	0	30	0
7	3	0	0	30	0

Figure 4: Circuit File Organizations

starting node, the end node, the current source J , the resistance R , and the voltage source E .

The convention of the input files should be well defined. In the program used for this test circuit, define the positive current direction is flowing from the start node to the end node. Current source must deliver positive current to the start node and the voltage source should deliver positive current to the end node. Following the conventions listed above, the program should be able to output desired node voltages in matrix form.

To verify the reliability of the program, four more simple test circuits are constructed. The input file as well as the result of the calculations are attached immediately after the circuit diagrams. The test runs below are proving that the program runs correctly as long as appropriate input files are passed into.

2.c.1 Testing Circuit 1

Figures 5 and 6 show the first test circuit. The desired output at node 1 can be calculated as $V_1 = 5V$, and the program is outputting the correct result.




Figure 5: Test Circuit 1

```
wenjie@wenjie-XPS-13-9343:
| 5.000000 |
```

Figure 6: Output Result of the Testing Circuit 1

2.c.2 Testing Circuit 2

Figures 7 and 8 below show the testing circuit 2 and its result. The expected result is $V_1 = 50V$.




Figure 7: Test Circuit 2

```
wenjie@wenjie-XPS-13-9343:
| 50.000000 |
```

Figure 8: Output Result of the Testing Circuit 2

2.c.3 Testing Circuit 3

Figures 9 and 10 below show the results of the testing circuit 3. The expected result of the circuit is $V_1 = 55V$.




Figure 9: Test Circuit 3

```
wenjie@wenjie-XPS-13-9343:
| 55.000000 |
```

Figure 10: Output Result of the Testing Circuit 3

2.c.4 Testing Circuit 4

Figures 11 and 12 below show the results of the testing circuit 4. The expected results of the circuit is $V_1 = 20V$ and $V_2 = 35V$.




Figure 11: Test Circuit 4

```
wenjie@wenjie-XPS-13-9343:  
| 20.000000 |  
| 35.000000 |
```

Figure 12: Output Result of the Testing Circuit 4

A Code Listings

Listing 1: Custom matrix package (matrix.py).

```
1  import math
2
3
4  class Matrix(object):
5      def __init__(self, vec, rows, cols):
6          self._vec = vec
7          self._rows = rows
8          self._cols = cols
9
10     def set_row(self, n_rows):
11         self._rows = n_rows
12
13     def is_square(self):
14         return self._rows == self._cols
15
16     def is_symmetric(self):
17         if not self.is_square():
18             return False
19
20         else:
21             for i in range(self.rows):
22                 for j in range(self.cols):
23                     if self[i][j] != self.T[i][j]:
24                         return False
25
26         return True
27
28     def transpose(self):
29         vec_trans = [[None for _ in range(self.rows)] for _ in range(self.cols)]
30         for x in range(self.cols):
31             for y in range(self.rows):
32                 vec_trans[x][y] = self.vec[y][x]
33
34         transposed_matrix = Matrix(vec_trans, self.cols, self.rows)
35         return transposed_matrix
36
37     def minus(self, other):
38         if self.cols != other.cols or self.rows != other.rows:
39             raise ValueError("Incorrect dimension for matrix subtraction.")
40
41         result_vec = [[None for _ in range(self.cols)] for _ in range(self.rows)]
42         result = Matrix(result_vec, self.rows, self.cols)
43         for i in range(self.rows):
44             for j in range(self.cols):
45                 result[i][j] = self[i][j] - other[i][j]
46
47         return result
48
49     def dot_product(self, other):
50         if self.cols != other.rows:
51             raise ValueError("Incorrect dimension for matrix multiplication.")
52
53         result_vec = [[None for _ in range(other.cols)] for _ in range(self.rows)]
54         result = Matrix(result_vec, self.rows, other.cols)
55
56         for i in range(self.rows):
57             for j in range(other.cols):
58                 temp_sum = 0
59                 for k in range(other.rows):
60                     temp_sum += self[i][k] * other[k][j]
61                 result[i][j] = temp_sum
62
63         return result
64
65     def __getitem__(self, item_number):
```

```

66         if isinstance(item_number, int):
67             return self._vec[item_number]
68
69         if isinstance(item_number, tuple):
70             x, y = item_number
71             # use some "dummy entries" as a buffer to decrease the possibility of occurring out of
↪ boundary.
72             if x < 0 or x >= self.rows or y < 0 or y >= self.cols:
73                 return 0
74             else:
75                 return self._vec[x][y]
76
77     def clone(self):
78         cloned_matrix = Matrix(self.vec, self.rows, self.cols)
79         return cloned_matrix
80
81     def print_matrix(self):
82         for i in range(self.rows):
83             print("|", end=" ")
84             for j in range(self.cols):
85                 print("%f" % self[i][j], end=" ")
86             print("|")
87
88     @property
89     def vec(self):
90         return self._vec
91
92     @property
93     def rows(self):
94         return self._rows
95
96     @property
97     def cols(self):
98         return self._cols
99
100    @property
101    def T(self):
102        return self.transpose()

```

Listing 2: Choleski decomposition (*choleski.py*).

```

1  import math
2  from matrix import Matrix
3
4
5  def check_choleski(A, b, x):
6      """
7      This method checks if the result of the choleski decomposition is correct.
8      Precision is set to 0.001.
9
10     :param A: n by n matrix A
11     :param b: result vector, n by 1
12     :param x: x vector, n by 1
13
14     :return: True if the result is correct, other wise False
15     """
16     temp_result = A.dot_product(x)
17     print("Matrix A is:")
18     A.print_matrix()
19     print("Vector b is:")
20     b.print_matrix()
21     print("Result vector x is:")
22     x.print_matrix()
23
24     for i in range(temp_result.rows):
25         for j in range(temp_result.cols):
26             if abs(temp_result[i][j] - b[i][j]) >= 0.001:
27                 return False
28     return True

```

```

29
30
31 def choleski_decomposition(A, b):
32     """
33     This is the method implemented for solving the problem  $Ax = b$ ,
34     using Choleski Decomposition.
35
36     Arguments:
37         A: the matrix A, a real, S.P.D. (Symmetric positive definite)  $n \times n$  matrix.
38         b: Column vector with n rows.
39
40     Returns:
41         Column vector x with n rows.
42     """
43     if not A.is_symmetric():
44         raise ValueError("Matrix must be symmetric to perform Choleski Decomposition.\n")
45
46     n = A.rows
47     sparse_matrix = [[0 for _ in range(n)] for _ in range(n)]
48     L = Matrix(sparse_matrix, n, n)
49
50     for j in range(n):
51         if A[j][j] <= 0:
52             raise ValueError("Matrix is not positive definite.\n")
53
54         temp_sum = 0
55         for k in range(-1, j):
56             temp_sum += math.pow(L[j][k], 2)
57         if (A[j][j] - temp_sum) < 0:
58             raise ValueError("Operand under square root is not positive. Matrix is not positive definite,
↪ exiting.")
59         L[j][j] = math.sqrt(A[j][j] - temp_sum)
60
61         for i in range(j + 1, n):
62             temp_sum = 0
63             for k in range(-1, j):
64                 temp_sum += L[i][k] * L[j][k]
65             L[i][j] = (A[i][j] - temp_sum) / L[j][j]
66     # Now L and LT are all obtained, we can move to forward elimination
67
68     y_vec = [[None for _ in range(1)] for _ in range(n)]
69     y = Matrix(y_vec, n, 1)
70     for i in range(y.rows):
71         temp_sum = 0
72         if i > 0:
73             for j in range(i):
74                 temp_sum += L[i][j] * y[j][0]
75             y[i][0] = (b[i][0] - temp_sum) / L[i][i]
76         else:
77             y[i][0] = b[i][0] / L[i][i]
78
79     # Now perform back substitution to find x.
80     x_vec = [[None for _ in range(1)] for _ in range(n)]
81     x = Matrix(x_vec, n, 1)
82
83     for i in range(n - 1, -1, -1):
84         temp_sum = 0
85         for j in range(i + 1, n):
86             temp_sum += L[j][i] * x[j][0]
87         x[i][0] = (y[i][0] - temp_sum) / L[i][i]
88
89     return x
90
91
92 if __name__ == "__main__":
93     a_vec = [[0.1167, -0.0667, 0, -0.05, 0], [-0.0667, 0.2333, -0.1, 0, 0], [0, -0.1, 0.2667, -0.1, 0],
↪ [-0.05, 0, -0.1, 0.2, -0.05], [0, 0, 0, -0.05, 0.1167]]
94     b_vec = [[0], [0.6667], [0], [0], [0]]
95
96     A = Matrix(a_vec, 5, 5)

```



```

97     b = Matrix(b_vec, 5, 1)
98
99     x = choleski_decomposition(A, b)
100     if check_choleski(A, b, x):
101         print("Correct")
102     else:
103         print("Incorrect")

```

Listing 3: Linear resistive networks (*linear_networks.py*).

```

1  from matrix import Matrix
2  from choleski import choleski_decomposition
3  import csv, math, time
4
5
6  class LinearResistiveNetwork(object):
7      def __init__(self, num, branch, node, a, y, j, e):
8          self._num = num
9          self._branch_number = branch
10         self._node_number = node
11         self._curr_vec = j
12         self._volt_vec = e
13         self._red_ind_mat = a
14         self._rev_res_mat = y
15
16     def solve_circuit(self):
17         return choleski_decomposition(self.A, self.b)
18
19     @property
20     def J(self):
21         return self._curr_vec
22
23     @property
24     def E(self):
25         return self._volt_vec
26
27     @property
28     def Y(self):
29         return self._rev_res_mat
30
31     @property
32     def re_A(self):
33         return self._red_ind_mat
34
35     @property
36     def A(self):
37         return self.re_A.dot_product(self.Y.dot_product(self.re_A.T))
38
39     @property
40     def b(self):
41         YE = self.Y.dot_product(self.E)
42         J_YE = self.J.minus(YE)
43         result = self.re_A.dot_product(J_YE)
44         return result
45
46
47     def read_circuits(filename):
48         """
49         This is the method to read the circuit information that is contained in csv files in a directory.
50         Upon success, the method will create the required calculation information such as J, E, vectors
51         and reduced indices matrices.
52
53         :return: a LinearResistiveNetwork object containing the key matrices for calculations.
54         """
55         with open(filename) as csv_file:
56             # Use CSV reader to read from circuit files
57             # row[0] = start node ID
58             # row[1] = end node ID
59             # row[2] = J value of a branch

```

```

60     # row[3] = R value of a branch
61     # row[4] = E value of a branch
62     csv_reader = csv.reader(csv_file, delimiter=',')
63     row = next(csv_reader)
64     circuit_id = int(row[0])
65     n_branch = int(row[2])
66     n_node = int(row[4])
67
68     branch_id = 0
69     current_vec = [[0] for _ in range(n_branch)]
70     volt_vec = [[0] for _ in range(n_branch)]
71     rev_res_mat = [[0 for _ in range(n_branch)] for _ in range(n_branch)]
72     incident_mat = [[0 for _ in range(n_branch)] for _ in range(n_node)]
73
74     j_vec = Matrix(current_vec, n_branch, 1)
75     e_vec = Matrix(volt_vec, n_branch, 1)
76     y_mat = Matrix(rev_res_mat, n_branch, n_branch)
77     a_mat = Matrix(incident_mat, n_node, n_branch)
78
79     for row in csv_reader:
80         j_vec[branch_id][0] = float(row[2])
81         e_vec[branch_id][0] = float(row[4])
82         if int(row[3]) != 0:
83             y_mat[branch_id][branch_id] = 1 / float(row[3])
84         else:
85             print("The input resistance is 0.")
86
87         # create un-reduced A matrix
88         a_mat[int(row[0])][branch_id] = 1
89         a_mat[int(row[1])][branch_id] = -1
90
91         branch_id += 1
92
93     # By default, Node 0 is grounded, remove node 0
94     # and create new reduced incidence matrix
95     a_mat = Matrix(a_mat.vec[1:], n_node - 1, n_branch)
96
97     linear_network = LinearResistiveNetwork(circuit_id, n_branch, n_node, a_mat, y_mat, j_vec, e_vec)
98     return linear_network
99
100
101 def network_constructor(size):
102     """
103     This method generates a linear resistive network.
104     The size of the network is defined by the argument size, and it's an N*N square network.
105
106     This method generates a new input .csv file, for future uses.
107
108     :param size: a.k.a, N, the number of nodes in a row or in a column.
109     :return: No return value.
110     """
111     n_node = int(math.pow(size, 2))
112     n_branch = 2 * size * (size - 1) + 1
113     resistance = 1000
114     test_current = 10
115     res_branch = 1000
116
117     row_count = 0
118     node_id = 0
119
120     first_row = [str(size), 'B', str(n_branch), 'N', str(n_node)]
121     first_branch = [str(n_node - 1), '0', str(test_current), str(res_branch), '0']
122     general_branch = [None for _ in range(5)]
123
124     with open('res_mesh' + str(size) + '.csv', 'w', newline='') as csv_file:
125         row_writer = csv.writer(csv_file, delimiter=',', quoting=csv.QUOTE_NONE, escapechar = ' ')
126
127         if row_count == 0:
128             row_writer.writerow(r for r in first_row)
129             row_writer.writerow(r for r in first_branch)

```

```

130         row_count += 2
131
132     for row_count in range(row_count, n_branch):
133         if node_id == n_node - 1:
134             break
135
136         elif (node_id + 1) % size == 0:
137             general_branch[0] = str(node_id)
138             general_branch[1] = str(node_id + size)
139             general_branch[2] = '0'
140             general_branch[3] = str(resistance)
141             general_branch[4] = '0'
142             row_writer.writerow(r for r in general_branch)
143
144         elif (node_id + size) >= n_node:
145             general_branch[0] = str(node_id)
146             general_branch[1] = str(node_id + 1)
147             general_branch[2] = '0'
148             general_branch[3] = str(resistance)
149             general_branch[4] = '0'
150             row_writer.writerow(r for r in general_branch)
151
152         else:
153             general_branch[0] = str(node_id)
154             general_branch[1] = str(node_id + 1)
155             general_branch[2] = '0'
156             general_branch[3] = str(resistance)
157             general_branch[4] = '0'
158             row_writer.writerow(r for r in general_branch)
159
160             general_branch[0] = str(node_id)
161             general_branch[1] = str(node_id + size)
162             general_branch[2] = '0'
163             general_branch[3] = str(resistance)
164             general_branch[4] = '0'
165             row_writer.writerow(r for r in general_branch)
166         node_id += 1
167
168
169 if __name__ == "__main__":
170     size = 15
171     #network_constructor(size)
172     start_time = time.time()
173
174     network = read_circuits('res_mesh'+str(size)+''.csv')
175     x = network.solve_circuit()
176     x.print_matrix()
177
178     v = x[x.rows - 1][0]
179     i1 = v / 1000
180     i2 = 10 - i1
181     resistance = v / i2
182     print("Computation time = " + str(time.time() - start_time))
183     print("Resistance of Mesh = " + str(resistance) + " Omega")

```