

Chapter 5

IMPLEMENTATION AND TESTING

5.1 Introduction

This chapter presents the implementation and testing of the Marrybrown Sales and Payment Analytics Platform. Whereas Chapter 4 described the analysis and design of the platform, this chapter records how the implemented platform was developed across the reporting database and ETL layer, the FastAPI semantic/API layer, and the React-based portal layer. It also documents the validation and testing activities used to confirm report accuracy, user-facing behaviour, and internal processing reliability.

To keep the chapter academically appropriate and public-safe, implementation details are presented at technical level without exposing credentials, secret configurations, or operationally sensitive access instructions.

5.2 System Development

The implemented platform was developed as a multi-layer internal reporting system intended to reduce operational dependence on a vendor-managed reporting portal while preserving report traceability and validation discipline. The completed implementation consists of three primary layers. First, selected source-system data were replicated into a company-managed Microsoft SQL Server reporting database through controlled ETL processes. Second, report logic was reconstructed in a FastAPI backend that acted as a semantic/API layer over the replicated data. Third, a React-based reporting portal was implemented to provide authenticated report access, filtering, export functions, and selected administrative tools.

The development process followed the iterative and incremental methodology described in Chapter 3. This was necessary because several report modules could not be treated as straightforward query transcription tasks. In practice, report development involved repeated cycles of source-data tracing, semantic rule reconstruction, mismatch investigation, validation against vendor outputs, and refinement of the reporting workflow in both backend and frontend layers.

5.2.1 Reporting Database and ETL Development

The reporting-database implementation centred on a company-managed Microsoft SQL Server environment that preserved selected source tables through a 1:1 replication strategy. This replica design was chosen to retain source fidelity for parity validation and reconciliation, while allowing report logic to be rebuilt independently of the external portal. Rather than flattening all logic into the database layer, the implementation preserved transactional and reference data close to source structure and left report-specific grouping, derivation, and presentation logic to the semantic/API layer.

The ETL implementation did not rely on a single loading path. Instead, it evolved into a controlled replication model with separate but coordinated operational modes. Manual utilities were retained for broad baseline loading, historical backfill, and targeted recovery work, especially for dated tables that required replay across defined time windows. In parallel, a staged daily ETL orchestrator was implemented for routine dated-table maintenance and reference-data refreshes. This staged design used boundary-based replacement logic so that repeated execution of the same reporting window could safely refresh the replica without introducing duplicate or drifting rows.

In the final implemented state, the ETL layer also supported portal-triggered manual sync requests and scheduled automation. Portal-triggered sync allowed authorised administrators to request dated-table or reference-table refreshes from the portal without executing ETL commands directly on the database host. Scheduled ETL

automation was also implemented as an operational feature for unattended daily dated refreshes and nightly retained-reference refreshes, with administration performed through the platform's automation-management workflow. This arrangement gave the platform both controlled manual recovery capability and operational automation capability, without requiring ordinary report users to interact with the ETL layer directly.

5.2.2 Backend API Development

The backend was implemented using FastAPI and functioned as the semantic/API layer of the platform. Its principal role was to reconstruct vendor-aligned report logic over the replicated database and expose the resulting report outputs through stable, parameter-driven endpoints. This design avoided direct frontend dependence on raw database structures and made it possible to keep report logic versioned and maintainable within the backend layer.

Backend development involved several recurring tasks across report modules. These included request-parameter definition, outlet and date-range filtering, shared handling of sales-status or payment-status filters where relevant, structured row output, and export-oriented response shaping. Reports that required grouped behaviour in the portal also needed backend outputs that could be normalised reliably for frontend grouping, subtotal rendering, advanced search, and export generation. In this way, the backend was not merely a database wrapper; it became the primary location where report-specific business rules, derived fields, and stable response contracts were implemented.

The backend layer also supported non-report operational functions required by the completed system. These included authentication, admin-managed user functions, portal-triggered sync control, automation-management support, and quality-check workflows linked to selected sync operations. Although these supporting features were not the central academic contribution of the project, they were necessary to make the implemented platform operationally usable in a real company environment.

5.2.3 Frontend Portal Development

The frontend portal was implemented using React and was designed to provide authenticated internal access to reports through a workflow-oriented rather than dashboard-oriented interface. The implemented report experience followed a common pattern: users sign in, access the report catalogue, select a report, define parameters, query the report, review the resulting table and totals, and export the output where needed. This structure was intentionally aligned with the practical behaviour expected by Finance and Operations users, especially for reconciliation and operational checking tasks.

Frontend development relied on shared report architecture rather than isolated page-specific implementations. A report registry, shared page shell, shared filters panel, grouped-table component, export toolbar, and supporting hooks were reused across report modules. This reduced duplication and made it feasible to add new formal-scope reports and additional customised reports through a consistent frontend pattern. The report-list view, report-query view, grouped-table behaviour, advanced search support, and export actions were therefore developed as reusable platform capabilities rather than as unrelated page fragments.

This user-facing reporting pattern is reflected in Figure 5.1 through a sanitised composite view that combines the Reports Hub with a representative report-query page. The figure represents the actual portal flow retained in the implementation: users begin from the catalogue of available reports, move into the selected module to define the required parameters, and then review grouped output through the shared query interface. Figure 5.1 therefore shows that the portal was developed as a consistent report-execution surface rather than as a collection of unrelated dashboard screens.




Figure 5.1: Reports Hub and representative report-query interface

The implemented portal also included role-restricted supporting features beyond ordinary report retrieval. Admin-only views were developed for data sync, automation control, and user management. These pages extended the platform beyond

passive report viewing and reflected the fact that the delivered system functioned as an internal reporting platform with controlled operational administration, not only as a collection of static report pages.

5.2.4 Administrative and Operational Functions

Several administrative and operational functions were implemented to make the platform sustainable for real use after report delivery. The first was admin-managed user control under the authentication model, where normal user access to report pages was separated from admin-only access to management functions. The second was the portal-triggered manual sync workflow, through which administrators could request sales-window or reference refreshes and review request history and progress. The third was automation management, where authorised administrators could review scheduled-task status and request enable, disable, or schedule-change actions for routine ETL automation.

An additional operational enhancement was the data-quality checking layer for portal-triggered replication. This feature allowed administrators to review source-to-replica quality outcomes for selected reporting windows, perform re-check actions, and trigger repair-oriented follow-up where required. This function was relevant academically because it showed that report continuity depended not only on endpoint implementation, but also on the trustworthiness of the replicated data used by those endpoints.

The administrative layer described above was implemented as three coordinated portal surfaces, each tied to a distinct governance responsibility. Figure 5.2 corresponds to user administration, where authorised staff review accounts and maintain role-controlled access. Figure 5.3 corresponds to data-sync administration, where replication requests, execution histories, and related follow-up actions are managed from the portal. Figure 5.4 corresponds to automation administration, where scheduled ETL activity is reviewed and change requests are handled under controlled

access. Considered together, these figures reinforce that the delivered platform supported governed internal operations in addition to ordinary report retrieval.

ADMIN ACCESS

User Management

Create new normal user accounts and manage active status across the organization's enterprise identity system.

Create Normal User

Register a new **Normal User** and send an email with temporary credentials after creation.

Name

John Tan

Email Address

user@marrybrown.com

Initial Password

Enter temporary password

Confirm Initial Password

Confirm temporary password

PASSWORD REQUIREMENTS:

At least 8 characters

One special character (!@#)

Create User

Existing Users

Admin accounts stay protected. Normal users can be activated or deactivated here.

Sort by

Name	Email	Role	Status	Created	Action
		User	Active	25/05/26 11:44 am	
		User	Active	14/05/26 12:44 pm	
		Admin	Active	29/04/26 11:54 am	

Reactivation Requests

Pending requests require admin review. Reviewed rows stay in this table as permanent history.

No reactivation requests have been submitted yet.

Figure 5.2: User Management page

61

MANUAL REPLICATION CONTROL

Data Sync

Centralized ETL management console. Authorized administrators can manually trigger warehouse synchronization, refresh metadata, and audit historical pipeline execution logs across regional replicas.

SERVER LOCAL DATE

Report Index Health

All monitored report indexes are enabled across 28 report tables.

SALES DATA

REFERENCE TABLES

Sync Reference Tables

Enabled

Queues a full refresh of the retained full-refresh reference tables via the ETL VM worker.

REFRESH TYPE

Full refresh

EXECUTION PATH

Stage - Swap - Audit

Last successful reference sync

Most recent completed retained-table full refresh request.

FINISHED AT

REQUESTED BY

REFRESH TYPE

REPLICA RUN ID

Queue Reference Sync

Live Sync Progress

SYSTEM ONLINE

SALES SYNC

SUCCESS

Data quality repair

Range: 23/05/2026 - 25/05/2026

Requested At

26/05/2026, 11:54 am

Started At

26/05/2026, 11:54 am

Finished At

26/05/2026, 11:57 am

Run ID

LOADED

2

FAILED

0

PENDING

0

Current Table:

PHASE: SUCCESS (2/2 COMPLETED) | LAST UPDATE: 26/05/2026, 11:57 AM

100%

WORKER CONSOLE

13 LINES

[PREFLIGHT] Required metadata, live, and stage tables are present.
[PREFLIGHT] Local disk free space OK (54.66 GB)
[INFO] meta-related run_type=ackf211 start=2026-05-23 end_exclusive=2026-05-26 run_date=manual job_date=2026-05-26
[INFO] meta-related run_type=ackf211 start=2026-05-23 end_exclusive=2026-05-26 run_date=manual job_date=2026-05-26
[INFO] Started backfill run B16C8F9D-BE91-45F6-8298FBC45260
[STAGE] extracted 278,117 rows, staged 278,117 rows in 6 chunk(s)
[UNLOAD] extracted 48,113 rows, staged 48,113 rows in 1 chunk(s)
[SWAPPED] moved 278,117 rows into dbo.com_SML2_APP_A_STOCKCHECK
[SWAPPED] moved 48,113 rows into dbo.com_SML2_APP_A_STOCKADJUST
[DONE] Run completed successfully

Data quality repair

FULL HISTORY REQUIRED

All affected table windows from the data quality check are being replaced from source for 23/05/2026 - 25/05/2026 without changing the saved sales coverage. Stock check rows drive the Stock Variance base row set and opening behaviour.

TARGET KEY

data_quality_repair

WORKER QUEUE

Shared sales queue

WATERMARK / COVERAGE

Does not change Current Coverage.

COOLDOWN BEHAVIOR

Does not create or clear the normal sales cooldown.

RESOLVED TABLES

REQUEST REASON

Data quality repair from portal ...

Data Quality For This Request

MISMATCH

Re-check Data Quality

Repair Affected Tables

Source changed after sync. Repair recommended.
This panel shows the source-to-DW audit linked to the selected sales history request. Re-check and repair actions here apply to this same request window.

CHECKED WINDOW

23/05/2026 - 25/05/2026

AFFECTED TABLES

1

CHECKED AT

26/05/2026, 11:58 am

LINKED REQUEST

TABLES NEEDING REPAIR

Source: 278,127

DW: 278,117

Missing/Extra: 10 / 0

PER-TABLE PROGRESS

Structured table rows mirrored from the ETL worker during execution.

Table	Status	Rows Extracted	Rows Loaded	Rows Processed	Latest Message	Updated At
	SUCCESS	278,117	278,117	278,117	Atomically swapped 278,117 rows into live table	26/05/2026, 11:57 am
	SUCCESS	30,113	30,113	30,113	Atomically swapped 30,113 rows into live table	26/05/2026, 11:57 am

Recent Manual Sync Requests

29 requests

Auto-updating

Audit log of all manually triggered sync requests. Select any row to open live per-table progress and the worker summary.

SEARCH REQUESTS

Search email, request ID, run ID, ts

Search

SYNC TYPE

All sync types

REQUEST TYPE

All request types

STATUS

All statuses

Clear filters

Requested At	Sync Type	Range	Status	Timeline	Replica Run	Message
26/05/2026 11:54 am	Sales incremental	23/05/2026 - 25/05/2026	SUCCESS	STARTED26/05/2026, 11:54 am FINISHED26/05/2026, 11:57 am	B16C8F9D-...FBC45260	LATEST EVENT [DONE] Run B16C8F9D-BE91-45F6-8298FBC45260 completed successfully [SWAPPED] APP_A_STOCKADJUST.mv

Figure 5.3: Data Sync page

62

Automation Control

Manage scheduled ETL safely from the portal. This page controls Windows scheduled automation tasks, while the main history below focuses on actual automation runs instead of status refresh actions.

SERVER LOCAL DATE



ENVIRONMENT SUMMARY

Windows DB VM queue + worker control path

The Linux API only queues control requests. A dedicated Windows worker inspects Scheduled Tasks, reads the latest ETL logs, and applies enable, disable, or schedule-time changes. Actual scheduled runs are tracked separately below for operator review.

CURRENT SNAPSHOT

Server local date

Managed tasks

Active control requests

Visible run rows

Refresh All Status

MANAGED TASK

Enabled

Daily Replica ETL

Marrybrown Daily Replica ETL

LATEST STATUS SNAPSHOT

08/06/2026, 4:47 pm

Task snapshot refreshed successfully.

SCHEDULED TIME

LAST RESULT

LAST RUN

HEARTBEAT

RECENT LOG SUMMARY

LATEST 3 LINES

Refresh

Enable

Disable

Edit Time

MANAGED TASK

Enabled

Nightly Reference Refresh

Marrybrown Nightly Reference Refresh

LATEST STATUS SNAPSHOT

08/06/2026, 4:46 pm

Task snapshot refreshed successfully.

SCHEDULED TIME

LAST RESULT

LAST RUN

HEARTBEAT

RECENT LOG SUMMARY

LATEST 3 LINES

Refresh

Enable

Disable

Edit Time

VIEW ONLY

Enabled

Manual Sync Request Worker

Marrybrown Manual Sync Request Worker

LATEST STATUS SNAPSHOT

08/06/2026, 4:46 pm

Task snapshot refreshed successfully.

SCHEDULED TIME

LAST RESULT

LAST RUN

HEARTBEAT

RECENT LOG SUMMARY

LATEST 3 LINES

[IDLE] No queued manual sync or data quality requests

Refresh

Enable

Disable

Edit Time

Selected Automation Run

SUCCESS

SELECTED RUN

Nightly Reference Refresh

Run ID: 7f764458-A48E-4C8B-85CD-12C8C6885A35

STARTED AT

12/06/2026, 6:00 am

FINISHED AT

AUTOMATION LANE

Nightly Reference Refresh

WORKER HOST

WINDOW START

12/06/2026

WINDOW THROUGH

12/06/2026

PROCESSED TABLES

PROCESSED TABLE SCOPE

Control action safety note

Disabling a running task only blocks future scheduled launches. It does not stop any ETL process that is already running on the VM.

```

Pat1:
2026-06-12 07:05:36,591 | INFO | etl.stcloud | [SWAPPED] moved 383,313 rows into dbo.cdw_5013_APP_5_STOCK
2026-06-12 07:06:08,313 | INFO | etl.stcloud | [IDLE] DATE2TIME_CONVERTED Converted 3 placeholder date(s) out of DATETIME range 1753-01-01 to 9999-12-31 to MALL
2026-06-12 07:07:37,665 | INFO | etl.stcloud | [STAGE] staged 11,845 rows
2026-06-12 07:08:45,590 | INFO | etl.stcloud | [SYNC] staged 11,845 row(s), updated 12,506, inserted 495
2026-06-12 07:08:45,590 | INFO | etl.stcloud | [STAGE] extracted 6,206,535 rows, staged 6,206,535 rows in 126 chunk(s)
2026-06-12 07:11:33,862 | INFO | etl.stcloud | [SWAPPED] moved 6,206,535 rows into dbo.cdw_5013_APP_4_PUINRECORD
2026-06-12 07:11:33,258 | INFO | etl.stcloud | [SYNC] no newer rows to sync (start=0, end=none)
2026-06-12 07:11:33,576 | INFO | etl.stcloud | [STAGE] staged 582 rows
2026-06-12 07:11:33,576 | INFO | etl.stcloud | [SYNC] staged 582 row(s), updated 0, inserted 582
2026-06-12 07:11:34,468 | INFO | etl.stcloud | [STAGE] staged 1 row(s), updated 0, inserted 1
2026-06-12 07:11:34,647 | INFO | etl.stcloud | [SYNC] new rows to sync (start=0305046463, end=0305046463)
2026-06-12 07:11:34,718 | INFO | etl.stcloud | [STAGE] staged 28 rows
2026-06-12 07:11:35,137 | INFO | etl.stcloud | [SYNC] staged 28 row(s), updated 0, inserted 0
    
```

Run Context

LATEST RUN SUMMARY

Nightly Reference Refresh

Run type: reference_daily

SUCCESS

STARTED AT

FINISHED AT

LOG SUMMARY

2026-06-12 07:32:07,355 | INFO | etl.stcloud | [SWAPPED] moved 103 rows into
 2026-06-12 07:34:18,192 | INFO | etl.stcloud | [STAGE] extracted 687,846 rows, staged 687,846 rows in 14 chunk(s)
 2026-06-12 07:34:28,995 | INFO | etl.stcloud | [SWAPPED] moved 687,846 rows into

CURRENT TASK SNAPSHOT

Nightly Reference Refresh

Enabled

SCHEDULED TIME

06:00

LAST SUCCESS

Not recorded yet

Automation Run History

Review actual scheduled automation runs for daily ETL and nightly reference refresh. Select a row to inspect its run detail and log above.

FILTER BY LANE

All automation lanes

FILTER BY STATUS

All run results

Started At	Automation Lane	Window	Processed Tables	Status	Finished At
12/06/2026, 6:00 am	Nightly Reference Refresh nightly_reference_refresh	12/06/2026 - 12/06/2026	28	SUCCESS	12/06/2026, 7:34 am
12/06/2026, 1:00 am	Daily Replica ETL daily_replica_etl	11/06/2026 - 11/06/2026	18	SUCCESS	12/06/2026, 2:13 am

Figure 5.4: Automation Control page

5.2.5 Report Implementation Coverage

Within the formal implementation and business scope, the platform was developed to support 19 sales and payment reports. Of these, 16 reports were successfully implemented and retained in the delivered active reporting surface. Three reports were not fully closed within the project boundary and are documented as limitations rather than omitted outcomes. In addition to the formal 19-report scope, three additional customised reports were also developed based on company requests during implementation.

The retained formal-scope reports covered several reporting groups, including sales and exception control, payment and voucher reconciliation, delivery and ordering channels, and product-, stock-, or cost-related operational analysis. The additional customised reports extended the implemented platform beyond the original formal scope and demonstrated that the shared ETL, backend, and portal architecture could support company-requested report families without requiring a separate system. Detailed per-report specifications, statuses, and classifications are documented in Appendix A.

The three formal-scope reports that were not fully closed were Product Mix Report, Discount Remark Report, and Product Mix with modifier without ETL. These were not left unresolved due to a simple lack of page development. Rather, they remained unresolved after reverse engineering and parity validation because the remaining logic required for full closure, especially profit-related behaviour in the product-mix area, could not be isolated conclusively within the available project boundary.

5.3 Coding of the system's main functions/Process

5.3.1 Data Replication and Refresh Process

The main data-process function of the platform was the movement of selected source data into the reporting database in a form suitable for report reconstruction. This process followed a staged boundary-based refresh pattern. For dated-table maintenance, the ETL process identified a defined reporting window, extracted source rows for that window, staged the refreshed data, replaced the corresponding live rows in the reporting database, and then recorded run metadata and progress information. This approach ensured that rerunning the same reporting window remained deterministic and that failed or incomplete windows could be retried without depending on ad hoc manual cleanup.

This process was important because reporting mismatches were not caused only by query logic. In several cases, mismatches were associated with late source edits, historical incompleteness, or replica-state inconsistencies. The implemented refresh model therefore had to support not only normal data movement but also controlled replays and focused correction work. For broad historical loading, manual utilities were used for baseline and backfill operations. For routine maintenance, scheduled daily ETL and portal-triggered sync requests used the staged orchestrator path. This split between baseline loading and operational refresh was necessary to balance reliability, recoverability, and maintainability.

The implemented process also included quality-oriented follow-up for selected portal-triggered sync windows. After a successful sales-window refresh, a source-to-replica quality check could be launched for the same window. Where mismatches were identified, re-check or repair-oriented follow-up could be requested. This meant that the data process for the platform was not limited to extraction and loading alone; it also included mechanisms for checking whether the reporting replica remained trustworthy enough for subsequent report reconstruction.

This two-path refresh model is summarised in Figures 5.5 and 5.6. Figure 5.5 represents the retained reference-table refresh path, in which a full refresh request is initiated from the portal and then monitored through staged execution and per-table progress review. Figure 5.6 represents the dated sales-data refresh path, where a bounded sync request moves through queued execution, post-run data-quality review, and repair-oriented follow-up for the selected reporting window. Presented in this order, the figures support the subsection's argument that portal-triggered replication was implemented as a controlled and auditable administrative process rather than as an opaque background task.




Figure 5.5: Portal-triggered reference-table refresh and execution tracking



Figure 5.6: Portal-triggered dated sales-data replication and data-quality review

5.3.2 Report Reconstruction Process

The main report-building process began with identifying the report behaviour expected from the vendor portal, including required parameters, visible output fields, grouping behaviour, totals, and export structure. From that baseline, the contributing datasets were traced in the replicated database and the required relationships were reconstructed at query level. This process was repeated across reports, even though the exact grouping and metric logic differed from one report family to another.

Once the contributing data paths were understood, the report logic was implemented in the FastAPI semantic/API layer. This typically included parameter validation, date-window scoping, outlet filtering, sales-status or payment-status handling where relevant, grouping and aggregation rules, and output formatting suitable for frontend rendering and export. The portal did not simply render raw SQL output. Instead, the backend response contracts were shaped to support tabular display, grouped subtotal behaviour, advanced search, and export actions in a stable and repeatable way.

Although each report had unique business rules, the implemented process remained consistent at high level. All report modules followed the same core pattern of source tracing, semantic reconstruction, parameter-driven querying, structured output shaping, and parity-oriented validation. This shared process allowed the project to scale from the retained formal report set to additional customised reports without abandoning the same platform architecture.

This reconstruction pattern is summarised in Figure 5.7. The figure represents the general backend process through which a report request moves from user parameter selection to semantic validation, replicated-data retrieval, dataset joining, grouping and derived-field handling, and final response shaping for portal display and export. Although the detailed query logic differs across report modules, the same high-level reconstruction sequence was retained throughout the implementation. This consistency was important because it allowed the platform to support multiple formal-scope and

customised reports within the same semantic/API architecture while preserving traceability for parity validation.




Figure 5.7: Sanitised illustration of report reconstruction logic

5.3.3 Payment Type Report Development

The Payment Type (All Payment) report is a suitable formal-scope example because it was operationally important, highly sensitive to row-level grouping behaviour, and representative of the reverse-engineering work required by the project. The purpose of this report was to provide a detailed breakdown of payment collections by store, order source, payment method, device, card type, and reference. The challenge was not merely to total payment rows, but to reconstruct the same grouping and display behaviour expected from the vendor portal with exactness sufficient for reconciliation work.

Implementation began by identifying the required payment-, sales-, and location-level source relationships in the replicated database. The main data sources were payment rows, sales status and order-source fields, and location-name mappings. Parameter handling was then defined around the selected date range, optional outlet scope, sales-status filtering, and payment-status behaviour. Because the report was intended for parity-sensitive operational use, the backend response also had to preserve a stable flat-row structure that could later support frontend grouped rendering and export processing.

The more difficult part of the implementation lay in the reference-grouping behaviour. Payment references could appear in multiple case variants, while portal output would still present them under a single preferred display value. Additional care was also required for payment-method categorisation, exclusion of return-sales behaviour, handling of zero-time anomalies, and consistent inclusion of payment rows in the correct collection totals. These issues made the report representative of the wider project challenge: the output could not be matched reliably through naive grouping alone, and several rounds of reverse engineering and refinement were required before parity could be accepted.

5.3.4 Voucher Campaign & Reward Sales Report Development

The Voucher Campaign & Reward Sales Report is a suitable customised-report example because it demonstrates that the implemented platform supported not only vendor-aligned report reconstruction, but also additional company-requested analysis built on the same architecture. This report was developed as a dynamic report family for eligible voucher campaigns and points rewards, while keeping the earlier Roblox-specific report intact as a separate implemented report.

The implementation process began with investigation of how voucher campaign and reward data could be represented reliably using the replicated data model. Rather than anchoring the report on a fixed voucher name, the implemented design used a selectable redemption-type identity so that the report could be applied to multiple campaign or reward families. The backend then reconstructed sale-level voucher scope, basket rows, derived bundle grouping, and additional-purchase indicators. This required not only data retrieval, but also interpretation of basket structure so that the final output could distinguish between the target bundle itself, other vouchers in the same sale, and additional paid items.

On the portal side, the customised report reused the shared report architecture but introduced a selector-driven reporting flow before ordinary date and outlet filtering. This illustrates a key implementation result of the project: once the shared

ETL, semantic/API, and portal architecture was stable, it became feasible to add company-requested customised reports without changing the overall platform model. The report therefore serves as evidence that the delivered system functioned as an extensible internal reporting platform rather than only as a one-time replication exercise.

5.3.5 Query Performance Observation

During implementation, selected report modules also underwent query-shape refinement and warehouse-side tuning to improve practical response time without changing validated business output. This work was documented through before-and-after timing checks on representative report scopes and was supported by later portal-side timing observations under real usage-style parameter sets.

One of the clearest examples was the Payment Type (All Payment) report, where the implementation logs recorded both application-side query-path refinement and later warehouse-side index recovery.

Table 5.1 summarises the strongest recorded timing observations for the Payment Type (All Payment) report.

Tested scope	Before optimisation	After optimisation	Observation
Single-store, single-day, 4-row case	approximately 63s	approximately 3.3s	substantial reduction after backend query-path refinement
Single-store, single-day, 608-row case	timed out beyond 120s	approximately 8.9s	timeout path removed after backend query-path refinement

Busy single-store, one-day sample after index recovery	not restated in the later log pass	approximately 1.1s	strong practical result after rebuilding disabled sales indexes
All-store, one-day sample after index recovery	not restated in the later log pass	approximately 12.2s	acceptable all-store one-day timing after warehouse-side tuning

Table 5.1: Recorded timing observations for Payment Type (All Payment)

The Payment Type observations indicate that performance improvement was achieved not only through report-query restructuring, but also through supporting warehouse maintenance and index recovery work.

Additional implementation logs recorded similar timing checks for other report families. Table 5.2 presents a compact summary of selected supporting observations.

Report	Tested scope	Recorded timing change or practical timing	Interpretation
Mobile Ordering Sales	All stores, 2025-01-01 to 2025-01-05	approximately 4.83s to 4.38s	modest improvement after query-shape refinement
Delivery-FoodPanda,Grabfood,ShopeeFood	All stores, 2025-01-01 to 2025-01-05	approximately 29.63s to 27.39s; later portal-side timing almost 20s	moderate backend improvement with usable portal-side outcome

Foodpanda Discount	All stores, 2025-01-01 to 2025-01-05	approximately 37.91s to 25.90s; later portal-side timing around 40+s	broad-window improvement, though still relatively heavy in portal use
Sales Return Report	All stores, 2025-01-01 to 2025-01-05	approximately 5.53s to 6.04s; later portal-side timing around 10s	timing was recorded and operationally acceptable, but not a strong improvement case
Sales Cancelled Report	All stores, 2025-01-01 to 2025-01-05	approximately 9.86s to 10.56s; later portal-side timing almost 20+s	timing was recorded and operationally acceptable, but not a strong improvement case
Deleted Items	All stores, 2025-01-01 to 2025-01-05	approximately 8.21s to 7.41s; later portal-side timing almost 8s	small but measurable improvement with acceptable practical timing

Table 5.2: Selected supporting timing observations across optimised report modules

Taken together, the recorded outcomes show that some report paths improved materially, while others improved more modestly or remained relatively heavy for broad all-store reporting windows. Practical portal-side timing checks were also

recorded after optimisation to ensure that the observed improvements remained meaningful from the user perspective rather than only at backend execution level.

These observations should be interpreted as implementation evidence of operational tuning rather than as a formal benchmark against the vendor portal. Within the project boundary, the main purpose of this work was to reduce timeout risk, improve response consistency, and keep validated report modules usable in the internal reporting workflow.

5.3.6 Report Accuracy Validation

The strongest testing evidence for the project was the report-accuracy validation process. This process was distinct from UAT because its purpose was not merely to confirm that a page loaded or exported correctly, but to confirm that the rebuilt report output was sufficiently aligned with the vendor portal under the same report conditions. The general validation approach was to run the platform report and the vendor portal report using the same date range, outlet scope, and other relevant filters, then compare row-level output, grouping behaviour, totals, subtotals, and exported results.

For the Payment Type (All Payment) report, this validation process was especially important because the report was sensitive to grouping precision at payment-reference level. The validation work therefore involved repeated comparison between platform output and vendor export output, investigation of mismatched rows or totals, and refinement of the reconstructed query logic until acceptable parity was achieved. Where anomalies remained, the investigation distinguished between logic faults and data-quality issues in the replica state, so that the report logic itself was not altered incorrectly to compensate for replica-specific data problems.

The same validation pattern was applied across the wider retained report surface. For each report module, parity validation used traceable filter conditions and visible output comparison rather than unsupported assumptions about hidden vendor

Figure 5.9 records the validation of return retrieval, negative-value handling, and related report totals for the Sales Return Report.

PV02: Sales Return Report Accuracy Validation									
Report accuracy validation evidence. This layout is comparison-based and is intentionally different from the UAT test case template.									
Report / Process	Sales Return	Validation Type	Report output reconciliation						
Test Data Scope	Return transactions within selected date range	Validation Source	Platform output compared with vendor portal output						
Reviewer	Project developer and business user	Execution Date	2026-05-21						
Validation Focus: Validates return transaction retrieval, negative amount handling, return item details, and outlet/date filtering.									
Comparison Setup									
Platform Output Evidence	Vendor / Reference Output Evidence	Filter Alignment	Comparison Level	Validation Method	Reviewer Note	Result	Evidence Location	Sensitivity Check	Public-Safe Note
Portal/API generated output and export file	Vendor portal output or approved business comparison output	Same selected outlet/date/report criteria	Row, group, subtotal, total, and export level	Manual reconciliation supported by sampled row checks	Reviewed by developer and business user	Passed	Screenshot/export kept separately for final report evidence	Credentials and internal access paths excluded	Only report behaviour and validation outcome documented
Reconciliation Checklist									
Comparison Point	Expected Match / Rule	Platform Observation	Vendor / Reference Observation	Result	Notes				
Date and outlet filters	Return report should only show selected business period and outlet	Returned rows followed selected parameter values	Portal output used equivalent period and outlet	Matched	Filter controls checked before comparison				
Returned item details	Item lines should represent returned products only	Return item rows were displayed with expected quantities	Portal export contained the same return-line scope	Matched	Duplicate checking performed				
Amount sign treatment	Return amounts should be represented consistently	Platform applied the expected return amount presentation	Portal output used the same direction of amount treatment	Matched	No manual sign conversion required				
Subtotal and report total	Computed total should reconcile with portal result	Subtotal and grand total aligned	Portal total matched the same comparison amount	Matched	Rounding reviewed				
Export result	Export should preserve selected report output	Export file generated successfully	Portal comparison export was available	Matched	No field loss observed				
Variance / Exception Handling									
Data Item / Field	Variance Type	Investigation / Handling Action	Resolution Status						
None identified	N/A	No adjustment required after comparison	Closed						
Validation Conclusion									
The reconstructed output was accepted for the validated scenario because the selected rows, grouping, totals, and export behaviour reconciled with the comparison evidence.									

Figure 5.9: PV02 Sales Return Report accuracy validation

Figure 5.12 records the validation of voucher redemption rows, grouped totals, and period-based filtering for the MB Cash Voucher report.

PV05: MB Cash Voucher Report Accuracy Validation									
Report accuracy validation evidence. This layout is comparison-based and is intentionally different from the UAT test case template.									
Report / Process	MB Cash Voucher	Validation Type	Report output reconciliation		Validation Focus: Validates voucher redemption rows, voucher amounts, outlet/date filters, and grouped totals.				
Test Data Scope	Voucher redemption activity in selected period	Validation Source	Platform output compared with vendor portal output						
Reviewer	Project developer and business user	Execution Date	2026-05-22						
Comparison Setup									
Platform Output Evidence	Vendor / Reference Output Evidence	Filter Alignment	Comparison Level	Validation Method	Reviewer Note	Result	Evidence Location	Sensitivity Check	Public-Safe Note
Portal/API generated output and export file	Vendor portal output or approved business comparison output	Same selected outlet/date/report criteria	Row, group, subtotal, total, and export level	Manual reconciliation supported by sampled row checks	Reviewed by developer and business user	Passed	Screenshot/export kept separately for final report evidence	Credentials and internal access paths excluded	Only report behaviour and validation outcome documented
Reconciliation Checklist									
Comparison Point	Expected Match / Rule	Platform Observation	Vendor / Reference Observation	Result	Notes				
Voucher redemption scope	Only relevant voucher redemption rows should appear	Voucher rows were filtered to the selected redemption scope	Portal export reflected the same voucher activity	Matched	Non-voucher payment rows excluded				
Voucher amount	Voucher amount should match row-level comparison	Sampled voucher amounts aligned	Portal sampled rows showed same amounts	Matched	Sampled across more than one outlet				
Outlet/date grouping	Report grouping should follow selected outlet/date parameters	Output followed expected grouping	Portal output grouped in the same business context	Matched	Group totals checked				
Grand total	Total voucher value should reconcile	Platform total aligned with comparison total	Portal output showed same total value	Matched	Rounding reviewed				
Export result	Export should preserve voucher identifiers and values	Export file generated with visible voucher fields	Portal export used for comparison	Matched	No field omission observed				
Variance / Exception Handling									
Data Item / Field	Variance Type	Investigation / Handling Action	Resolution Status						
None identified	N/A	No adjustment required after comparison	Closed						
Validation Conclusion									
The reconstructed output was accepted for the validated scenario because the selected rows, grouping, totals, and export behaviour reconciled with the comparison evidence.									

Figure 5.12: PV05 MB Cash Voucher redemption accuracy validation

Figure 5.14 presents the validation evidence for portal-triggered data-quality checking after a manual sync window.

PV07: Portal-Triggered Data Quality Validation									
Report accuracy validation evidence. This layout is comparison-based and is intentionally different from the UAT test case template.									
Report / Process	Portal-triggered replication quality check	Validation Type	Data completeness and consistency validation						
Test Data Scope	Selected reporting period after manual sync	Validation Source	Replica status, quality-check result, and report output comparison						
Reviewer	Project developer and business user	Execution Date	2026-05-25						
Validation Focus: Validates that replicated reporting data can be checked and rechecked after a portal-triggered sync request.									
Comparison Setup									
Platform Output Evidence	Vendor / Reference Output Evidence	Filter Alignment	Comparison Level	Validation Method	Reviewer Note	Result	Evidence Location	Sensitivity Check	Public-Safe Note
Portal/API generated output and export file	Vendor portal output or approved business comparison output	Same selected outlet/date/report criteria	Row, group, subtotal, total, and export level	Manual reconciliation supported by sampled row checks	Reviewed by developer and business user	Passed	Screenshot/export kept separately for final report evidence	Credentials and internal access paths excluded	Only report behaviour and validation outcome documented
Reconciliation Checklist									
Comparison Point	Expected Match / Rule	Platform Observation	Vendor / Reference Observation	Result	Notes				
Sync request completion	Manual sync should finish before validation is performed	Sync status reached completed state	Operational status view confirmed completion	Matched	No direct server credentials documented				
Row-count reasonableness	Replica row counts should be consistent for selected period	Quality check returned expected completeness result	Operational comparison did not show missing period after refresh	Matched	Focused on reporting readiness				
Missing-period detection	System should identify incomplete data when present	Quality check exposed incomplete state before repair/recheck where applicable	Expected behaviour observed	Matched	Scenario tested using controlled period selection				
Recheck after repair/sync	Recheck should update status after data refresh	Recheck result changed to valid after refreshed data was available	Operational status reflected updated state	Matched	Closed through supported portal path				
Report readiness	Reports should be generated only against refreshed replica data	Report validation used refreshed replica period	Comparison output used equivalent business period	Matched	Supports final report accuracy validation				
Variance / Exception Handling									
Data Item / Field	Variance Type	Investigation / Handling Action	Resolution Status						
Incomplete historical periods	Operational data completeness issue	Handled through manual sync and quality recheck	Closed for validated periods						
Validation Conclusion									
The reconstructed output was accepted for the validated scenario because the selected rows, grouping, totals, and export behaviour reconciled with the comparison evidence.									

Figure 5.14: PV07 Portal-triggered data quality validation

Figure 5.15 documents the remaining profit-logic limitation that prevented final closure for Product Mix related reporting and Discount Remark reporting.

PV08: Product Mix and Discount Profit Logic Validation Limitation									
Report accuracy validation evidence. This layout is comparison-based and is intentionally different from the UAT test case template.									
Report / Process	Product Mix / Discount Remark profit-related output	Validation Type	Exception and limitation record						
	Selected report samples with profit-related fields	Validation Source	Platform reconstruction compared with vendor portal output						
Reviewer	Project developer and business user	Execution Date	2026-05-26						
Validation Focus: Documents the unresolved profit-logic limitation for Product Mix related reporting and Discount Remark reporting.									
Comparison Setup									
Platform Output Evidence	Vendor / Reference Output Evidence	Filter Alignment	Comparison Level	Validation Method	Reviewer Note	Result	Evidence Location	Sensitivity Check	Public-Safe Note
Portal/API generated output and export file	Vendor portal output or approved business comparison output	Same selected outlet/date/report criteria	Row, group, subtotal, total, and export level	Manual reconciliation supported by sampled row checks	Reviewed by developer and business user	Not Fully Closed	Screenshot/export kept separately for final report evidence	Credentials and internal access paths excluded	Only report behaviour and validation outcome documented
Reconciliation Checklist									
Comparison Point	Expected Match / Rule	Platform Observation	Vendor / Reference Observation	Result	Notes				
Basic row scope	Product/discount rows should follow selected date and outlet filters	Row scope could be reconstructed for selected samples	Portal output provided comparable row scope	Matched	Base filtering was not the blocker				
Quantity and sales values	Non-profit values should align where source logic was traceable	Quantity and sales-related fields were validated in sampled output	Portal output supported these comparisons	Matched	Validation focused on traceable fields				
Profit column logic	Profit-related value should reconcile with portal result	Remaining profit calculation could not be isolated completely	Portal output did not provide enough observable evidence to derive final logic	Not Fully Closed	Documented as external black-box logic limitation				
Report closure decision	Only fully validated reports should be included in retained active surface	Report remained documented but not treated as fully closed	Comparison limitation remained unresolved	Not Fully Closed	Avoided claiming false parity				
Academic reporting treatment	Limitation should be stated honestly	Limitation recorded in final-report evidence	N/A	Documented	No internal credentials or proprietary query text included				
Variance / Exception Handling									
Data Item / Field	Variance Type	Investigation / Handling Action	Resolution Status						
Profit column	Unresolved parity difference	Reverse engineering and validation were not sufficient to isolate final profit logic	Not fully closed						
Validation Conclusion									
The report area was documented as not fully closed because the remaining profit-related logic could not be isolated with sufficient confidence through reverse engineering and portal comparison evidence.									

Figure 5.15: PV08 Product Mix and discount profit logic validation boundary

5.3.7 Black-Box Testing and User Acceptance Testing

Black-box testing and User Acceptance Testing (UAT) were treated together because, in the context of this project, both evaluated the system from the user-facing perspective rather than from the internal code path. These tests focused on whether users could sign in, access reports, enter parameters, retrieve outputs, inspect totals, export data, and use role-restricted administrative functions appropriately. The intent was to verify that the implemented platform supported realistic operational workflows rather than merely exposing technically correct endpoints.

The test scenarios were structured as test cases using the TC prefix, such as TC01, TC02, and subsequent cases. Core user-facing scenarios included authentication, report-catalogue access, report retrieval with valid filters, export behaviour, access to customised report modules, manual sync submission, data-quality follow-up visibility, automation-control access, and role-restricted administrative behaviour. This structure provided a clear and traceable record of functional acceptance across the implemented user workflows.

The UAT and black-box testing outcomes were intended to show that the implemented platform could be used coherently by both ordinary reporting users and authorised administrative users. This was especially relevant for the data-sync and automation functions, because these features extended the platform beyond simple report viewing and into controlled reporting operations. By structuring these tests around user-observable behaviour, the testing section complements the report-accuracy validation process rather than duplicating it.

The detailed UAT and black-box test cases are shown in Figures 5.16 to 5.31.

Figure 5.16 shows the functional acceptance check for valid user login and protected portal access.

User Login with Valid Credentials						Author:	Project Developer
Description:						Reviewer:	Project Supervisor / Company User
						Priority:	High
						Test Type:	Functional / UAT
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation		
TC01	Verifies that an authorised user can log in and reach the protected portal area.	Registered active user account; login page accessible.	User email and password provided by test administrator.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation		
Test Steps							
✓	1. Navigate to the login page.						
✓	2. Enter a valid email address.						
✓	3. Enter a valid password.						
✓	4. Click the login button.						
✓	5. Observe the landing page after authentication.						
✓	6.						
✓	7.						
✓	8.						
Postconditions		System state remains available for continued testing or user work.			Execution Date		
					2026-05-28		
Expected Outcome		The user is redirected to the reporting portal after successful authentication.			Actual Outcome		
					The user logged in successfully and reached the protected portal page.		
Bugs Encountered							
✓	1. No issues encountered.						
✓	2.						
✓	3.						

Figure 5.16: TC01 user login with valid credentials

Figure 5.17 records the test confirming that an authenticated user can open the Reports Hub and review available report categories.

Reports Hub Access						Author:	Project Developer	
Description: Verifies that an authenticated user can open the reports hub and view available report categories.						Reviewer:	Project Supervisor / Company User	
						Priority:	High	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC02	Verifies that an authenticated user can open the reports hub and view available report categories.	User is logged in, report definitions are available.	Authenticated user session.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1.	Open the portal navigation menu.						
✓	2.	Select Reports.						
✓	3.	Review displayed report categories.						
✓	4.	Select one report category.						
✓	5.	Confirm that the report page opens.						
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The reports hub displays available report options and allows navigation to a report page.						Reports hub loaded successfully and report navigation worked as expected.		
Bugs Encountered								
✓	1.	No issues encountered.						
✓	2.							
✓	3.							

Figure 5.17: TC02 Reports Hub access

Figure 5.18 presents the test used to confirm that common report parameters can be entered before report generation.

Report Parameter Entry						Author:	Project Developer Project Supervisor /	
Description: Verifies that a user can enter common report filters such as date range and outlet before generating a report.						Reviewer:	Company User	
						Priority:	High	
						Test Type:	Functional / Black-box	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC03	Verifies that a user can enter common report filters such as date range and outlet before generate a report.	User has access to a report page.	Outlet/date range selected for testing.	Windows browser environment and deployed reporting portal	User non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1.	Open a report page.						
✓	2.	Select a valid start date.						
✓	3.	Select a valid end date.						
✓	4.	Select or confirm outlet/report filters.						
✓	5.	Submit the report request.						
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The system accepts valid report parameters and starts report generation.						Parameters were accepted and the report request was processed.		
Bugs Encountered								
✓	1.	No issues encountered.						
✓	2.							
✓	3.							

Figure 5.18: TC03 report parameter loading

Figure 5.19 shows the user-facing test for generating the Payment Type report through the portal workflow.

Generate Payment Type Report						Author:	Project Developer
Description:						Reviewer:	Project Supervisor / Company User
						Priority:	High
						Test Type:	Functional / UAT
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation		
TC04	Verifies that a user can generate the Payment Type (All Payment) report from the portal.	User is logged in and report data is available for selected period.	Payment Type report with selected outlet/date range.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation		
Test Steps							
✓	1. Open Payment Type report.						
✓	2. Enter required filter values.						
✓	3. Click Search or Generate.						
✓	4. Wait for table output.						
✓	5. Review the loaded result rows.						
✓	6.						
✓	7.						
✓	8.						
Postconditions				Execution Date			
System state remains available for continued testing or user work.				2026-05-28			
Expected Outcome				Actual Outcome			
The Payment Type report loads with grouped payment records and totals.				The report loaded with expected grouped rows and totals.			
Bugs Encountered							
✓	1. No issues encountered.						
✓	2.						
✓	3.						

Figure 5.19: TC04 Payment Type report query

Figure 5.20 records the review of grouped rows, subtotals, and grand totals after report generation.

Review Report Totals and Grouping						Author:	Project Developer
Description:						Reviewer:	Project Supervisor / Company User
						Priority:	Medium
						Test Type:	Functional / Black-box
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation		
TC05	Verifies that report rows, group totals, and grand totals are visible and understandable to the user.	Report output has been generated.	Generated report result table.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation		
Test Steps							
✓	1. Generate a report with valid filters.						
✓	2. Scroll through grouped report output.						
✓	3. Review subtotal rows where available.						
✓	4. Review grand total row.						
✓	5. Compare displayed values with expected validation evidence.						
✓	6.						
✓	7.						
✓	8.						
Postconditions				Execution Date			
System state remains available for continued testing or user work.				2026-05-28			
Expected Outcome				Actual Outcome			
The report table presents grouped records and totals clearly.				Grouping and totals were displayed clearly for review.			
Bugs Encountered							
✓	1. No issues encountered.						
✓	2.						
✓	3.						

Figure 5.20: TC05 report totals review

Figure 5.21 shows the test confirming that generated report output can be exported for operational use.

Export Report Output						Author:	Project Developer	
Description: Verifies that a user can export generated report data for operational use.						Reviewer:	Project Supervisor / Company User	
						Priority:	High	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC06	Verifies that a user can export generated report data for operational use.	Report output is already loaded on screen.	Generated report table.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓								
1.	Generate a report.							
✓	2. Click the export button.							
✓	3. Wait for file generation.							
✓	4. Open the exported file.							
✓	5. Compare exported columns with visible report output.							
✓								
✓								
✓								
✓								
Postconditions								
System state remains available for continued testing or user work.								
Execution Date								
2026-05-28								
Expected Outcome								
The exported file contains the displayed report fields and values.								
Actual Outcome								
Export completed successfully and contained the expected report output.								
Bugs Encountered								
✓								
1.	No issues encountered.							
✓	2.							
✓	3.							

Figure 5.21: TC06 report output export

Figure 5.22 presents the test for advanced search or table filtering over multi-row report output.

Advanced Search and Table Filtering						Author:	Project Developer	
Description: Verifies that the user can narrow report output using available table search or filtering controls.						Reviewer:	Project Supervisor / Company User	
						Priority:	Medium	
						Test Type:	Functional / Black-box	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC07	Verifies that the user can narrow report output using available table search or filtering controls.	Report output contains multiple rows.	Search keyword or filter value.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1. Generate a report with multiple rows.							
✓	2. Enter a search keyword or filter value.							
✓	3. Apply the search/filter control.							
✓	4. Review filtered rows.							
✓	5. Clear the filter and confirm full result returns.							
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The table filters results according to the entered criteria and restores full output when cleared.						Filtering behaved as expected and the result table was restored after clearing.		
Bugs Encountered								
✓	1.	No issues encountered.						
✓	2.							
✓	3.							

Figure 5.22: TC07 advanced search behaviour

Figure 5.23 records the user-facing retrieval test for the Sales Return Report under selected filters.

Generate Sales Return Report						Author:	Project Developer	
Description: Verifies that a user can retrieve a sales-return related report from the portal.						Reviewer:	Project Supervisor / Company User	
						Priority:	High	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC08	Verifies that a user can retrieve a sales-return related report from the portal.	User is logged in and return records exist for the selected period.	Sales Return report filters.	Windows browser environment and deployed reporting portal	User non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1.	Open Sales Return report.						
✓	2.	Enter selected date and outlet filters.						
✓	3.	Generate the report.						
✓	4.	Review return transaction rows.						
✓	5.	Review totals and export availability.						
✓	6.							
✓	7.							
✓	8.							
Postconditions			Execution Date					
System state remains available for continued testing or user work.			2026-05-28					
Expected Outcome			Actual Outcome					
The Sales Return report displays return transaction rows for the selected filter.			Sales Return report loaded correctly with expected rows and totals.					
Bugs Encountered								
✓	1.	No issues encountered.						
✓	2.							
✓	3.							

Figure 5.23: TC08 Sales Return Report query

Figure 5.24 shows the acceptance test for generating a customised company-requested report through the portal.

Generate Custom Voucher Campaign Report						Author: Project Developer / Project Supervisor / Company User	
Description: Verifies that a customised report requested by the company can be generated through the portal.						Reviewer: Company User	
						Priority: High	
						Test Type: Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation		
TC09	Verifies that a customised report requested by the company can be generated through the portal.	User is logged in, customised report is enabled.	Voucher campaign date/filter criteria.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation		
Test Steps							
✓							
✓	1.	Open the Voucher Campaign & Reward Sales report.					
✓	2.	Enter campaign-related filter values.					
✓	3.	Generate the report.					
✓	4.	Review campaign rows and totals.					
✓	5.	Export the result if required.					
✓	6.						
✓	7.						
✓	8.						
Postconditions		Execution Date					
System state remains available for continued testing or user work.		2026-05-28					
Expected Outcome		Actual Outcome					
The customised report displays campaign-related sales/reward output according to selected criteria.		The customised report generated successfully and output was reviewable.					
Bugs Encountered							
✓	1.	No issues encountered.					
✓	2.						
✓	3.						

Figure 5.24: TC09 customised report query

Figure 5.25 presents the access-control test confirming that normal users are restricted from admin-only pages.

Admin Page Access Restriction						Author:	Project Developer / Project Supervisor /	
Description: Verifies that administrative pages are restricted from normal report users.						Reviewer:	Company User	
						Priority:	High	
						Test Type:	Security / Black-box	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC10	Verifies that administrative pages are restricted from normal report users.	One normal user and one admin user are available for testing.	Normal user session and admin user session.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1. Log in as a normal user.							
✓	2. Attempt to access an admin-only page.							
✓	3. Observe access behaviour.							
✓	4. Log out and log in as admin user.							
✓	5. Open the same admin page.							
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
Access remains controlled based on role.						2026-05-28		
Expected Outcome						Actual Outcome		
Normal user is blocked from admin functions, while admin user can access them.						Normal user could not access admin-only page and admin user could access it.		
Bugs Encountered								
✓	1. No issues encountered.							
✓	2.							
✓	3.							

Figure 5.25: TC10 normal-user admin restriction

Figure 5.26 records the test showing that an authorised admin user can open the Data Sync page and review sync controls.

Open Data Sync Administration Page						Author: Project Developer / Project Supervisor /	
Description: Verifies that an admin user can open the data sync page and view sync-related controls/status.						Reviewer: Company User	
						Priority: High	
						Test Type: Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation		
TC11	Verifies that an admin user can open the data sync page and view sync-related controls/status.	Admin user is logged in.	Admin account and sync page route.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation		
Test Steps							
✓							
✓	1. Log in as an admin user.						
✓	2. Open the Data Sync page.						
✓	3. Review available sync controls.						
✓	4. Review latest status area.						
✓	5. Confirm no unauthorised credentials are displayed.						
✓	6.						
✓	7.						
✓	8.						
Postconditions				Execution Date			
System state remains available for continued testing or user work.				2026-05-28			
Expected Outcome				Actual Outcome			
The data sync page opens for admin users and shows appropriate controls/status information.				Data Sync page opened and displayed operational controls/status safely.			
Bugs Encountered							
✓	1. No issues encountered.						
✓	2.						
✓	3.						

Figure 5.26: TC11 admin Data Sync access

Figure 5.27 shows the workflow test for submitting a portal-triggered manual sync request.

Submit Portal-Triggered Manual Sync						Author:	Project Developer	
Description: Verifies that an admin user can submit a manual sync request through the portal.						Reviewer:	Project Supervisor / Company User	
						Priority:	High	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC12	Verifies that an admin user can submit a manual sync request through the portal.	Admin user is logged in; sync service is available.	Selected sync period or sync option.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓								
✓	1. Open Data Sync page.							
✓	2. Select the required sync option.							
✓	3. Submit manual sync request.							
✓	4. Confirm the request prompt if displayed.							
✓	5. Review initial sync status.							
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The system accepts the sync request and records it for processing.						Manual sync request was submitted and appeared in the sync status view.		
Bugs Encountered								
✓	1. No issues encountered.							
✓	2.							
✓	3.							

Figure 5.27: TC12 manual sync request submission

Figure 5.28 presents the test used to monitor sync progress after a manual request has been submitted.

Monitor Sync Progress						Author:	Project Developer	
						Reviewer:	Company User	
						Priority:	Medium	
						Test Type:	Functional / UAT	
Description:		Verifies that an admin user can monitor portal-triggered sync progress after submission.						
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC13	Verifies that an admin user can monitor portal-triggered sync progress after submission.	A manual sync request has been submitted.	Existing sync request record.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1. Open the sync status section.							
✓	2. Refresh or wait for status update.							
✓	3. Review current status.							
✓	4. Confirm completion or failure message.							
✓	5. Open related report after sync if needed.							
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The system displays an understandable sync status and completion result.						Sync progress/status was visible and understandable to the admin user.		
Bugs Encountered								
✓	1. No issues encountered.							
✓	2.							
✓	3.							

Figure 5.28: TC13 sync progress review

Figure 5.29 records the test for triggering or reviewing a post-sync data-quality re-check.

Run Data Quality Recheck						Author:	Project Developer	
Description: Verifies that an admin user can trigger or review a data quality recheck after sync.						Reviewer:	Project Supervisor / Company User	
						Priority:	High	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC14	Verifies that an admin user can trigger or review a data quality recheck after sync.	Admin user is logged in; sync has completed.	Selected reporting period for quality check.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1. Open Data Sync or quality-check area.							
✓	2. Select the reporting period.							
✓	3. Run or refresh the quality check.							
✓	4. Review completeness/status result.							
✓	5. Use result to decide whether reports are ready.							
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The system displays data quality status for the selected period.						Data quality recheck completed and showed an understandable status result.		
Bugs Encountered								
✓	1. No issues encountered.							
✓	2.							
✓	3.							

Figure 5.29: TC14 data-quality re-check workflow

Figure 5.30 shows the acceptance check for reviewing and managing ETL automation controls from the portal.

Automation Control Management						Author:	Project Developer Project Supervisor / Company User	
Description:						Reviewer:	Company User	
						Priority:	Medium	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC15	Verifies that an admin user can review and manage ETL automation controls from the portal.	Admin user is logged in; automation control page is enabled.	Automation control page and selected schedule/control option.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓	1.	Open Automation Control page.						
✓	2.	Review current automation status.						
✓	3.	Select an available management action.						
✓	4.	Submit the action.						
✓	5.	Confirm updated status/message.						
✓	6.							
✓	7.							
✓	8.							
Postconditions						Execution Date		
System state remains available for continued testing or user work.						2026-05-28		
Expected Outcome						Actual Outcome		
The automation page displays current status and records the selected management action.						Automation status and control action were displayed clearly.		
Bugs Encountered								
✓	1.	No issues encountered.						
✓	2.							
✓	3.							

Figure 5.30: TC15 Automation Control review

Figure 5.31 presents the test confirming that admin users can review and manage portal users according to role and status.

User Management Workflow						Author:	Project Developer	
Description: Verifies that an admin user can manage portal users according to assigned role and status.						Reviewer:	Company User	
						Priority:	Medium	
						Test Type:	Functional / UAT	
Test Case ID	Objective	Preconditions	Input Data	Test Environment	Data Preparation			
TC16	Verifies that an admin user can manage portal users according to assigned role and status.	Admin user is logged in.	Test user account data without real credentials.	Windows browser environment and deployed reporting portal	Use non-sensitive test account and selected report period prepared for validation			
Test Steps								
✓								
✓	1. Open User Management page.							
✓	2. Review user list.							
✓	3. Open create/edit user form.							
✓	4. Enter non-sensitive test user details.							
✓	5. Save and review the updated user list.							
✓	6.							
✓	7.							
✓	8.							
Postconditions								
System state remains available for continued testing or user work.								
Execution Date								
2026-05-28								
Expected Outcome								
The user management page allows admin users to maintain user information safely.								
Actual Outcome								
User management workflow was completed using non-sensitive test data.								
Bugs Encountered								
✓	1. No issues encountered.							
✓								
✓								

Figure 5.31: TC16 User Management workflow

5.3.8 White-Box Testing

White-box testing was used to evaluate selected internal processing logic that could not be assessed fully through user-facing behaviour alone. In this project, white-box testing did not aim to provide exhaustive code-coverage measurement. Instead, it focused on the internal logic that had direct impact on report trustworthiness and operational safety, such as request-parameter validation, boundary-based refresh handling, source-to-replica quality-check flow, grouping and aggregation logic in report reconstruction, export-structure consistency, and role-restricted access handling.

This form of testing was relevant because a report can appear correct from the interface while still containing internal weaknesses in parameter interpretation, refresh-window replacement logic, or grouped output construction. By checking selected internal logic paths explicitly, the implementation could be reviewed not only at output level but also at process level. In academic terms, this strengthened the credibility of the completed system because it demonstrated that testing attention was

given to both visible behaviour and the underlying logic that produced that behaviour. The detailed white-box test cases are shown in Figures 5.32 to 5.40.

Figure 5.32 shows the internal validation checks applied to report parameters before backend execution proceeds.

WB01: API Parameter Validation Logic									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB01	Module / Component	Backend API router and request schema	Internal Logic Under Test: Checks that backend report endpoints validate required filters before executing report logic. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.					
Test Method	Boundary and invalid-input checks	Risk Area	Checks that backend report endpoints validate required filters before executing report logic.						
Reviewer	Project developer	Execution Date	2026-05-29						
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Required date parameter	Missing date should be rejected before query execution	Validation layer returned controlled error response	Passed					
2	Date range order	Invalid start/end sequence should not produce misleading output	Invalid period was rejected or normalised by validation path	Passed					
3	Outlet/report filter	Unexpected filter value should not break report execution	Controlled validation behaviour observed	Passed					
4	Response consistency	Valid request should return structured report payload	Successful response followed expected JSON structure	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.32: WB01 API parameter validation

Figure 5.33 records the internal review of payment grouping and total-calculation logic in the Payment Type report path.

WB02: Payment Grouping and Total Calculation Logic									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB02	Module / Component	Payment Type report service/query layer Checks internal grouping and total logic for payment-oriented report reconstruction.						
Test Method	Grouping and aggregation path review	Risk Area	Internal Logic Under Test: Checks internal grouping and total logic for payment-oriented report reconstruction. It is not a user acceptance test case.						
Reviewer	Project developer	Execution Date	2026-05-29						
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Grouping key	Payment rows should be grouped by the intended payment classification	Grouped output followed expected payment categories	Passed					
2	Aggregation	Amounts should be summed at group and report-total level	Subtotal and total calculations aligned with validation evidence	Passed					
3	Null/blank handling	Blank optional fields should not break grouping	Rows with optional blanks remained processable	Passed					
4	Export mapping	Exported totals should match displayed totals	Displayed and exported totals aligned	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.33: WB02 Payment Type grouping logic

Figure 5.34 presents the rerun logic review used to confirm that repeated ETL execution does not duplicate reporting output.

WB03: ETL Re-run and Idempotency Logic									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID		WB03		Module / Component		ETL scripts and reporting replica load flow			
Test Method		Controlled rerun/checkpoint review		Risk Area		Checks that repeated ETL execution for the same reporting period does not create duplicated reporting output.			
Reviewer		Project developer		Execution Date		2026-05-29			
						Internal Logic Under Test: Checks that repeated ETL execution for the same reporting period does not create duplicated reporting output.			
						This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.			
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Existing period load	Rerun should refresh or preserve target period without duplicate rows	Repeated run did not create duplicate report rows in validated period	Passed					
2	Load boundary	ETL should apply selected period boundary consistently	Loaded records stayed within selected sync boundary	Passed					
3	Failure handling	Failed step should not be treated as successful completion	Status remained traceable for failed/incomplete cases	Passed					
4	Post-load reporting	Reports should read from refreshed replica state	Report output reflected refreshed period after completion	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.34: WB03 boundary-based ETL rerun

Figure 5.35 shows the internal checkpoint review for staged refresh windows and controlled historical completeness handling.

WB04: Staged Refresh Window Logic									
White box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB04	Module / Component	Replica refresh and backfill process Checks that controlled refresh/backfill windows support historical completeness without uncontrolled production changes.	Internal Logic Under Test: Checks that controlled refresh/backfill windows support historical completeness without uncontrolled production changes. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.					
Test Method	Refresh-boundary logic review	Risk Area							
Reviewer	Project developer	Execution Date	2026-05-29						
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Selected period	Refresh should target selected historical/current period	Refresh scope followed selected period boundary	Passed					
2	Historical gaps	Known incomplete periods should remain identifiable	Quality check highlighted incomplete state where applicable	Passed					
3	Operational control	Unattended changes should be managed through approved controls	Automation controls and manual sync path were separated clearly	Passed					
4	Report readiness	Report validation should be performed after refresh	Validation was performed after refreshed data was available	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the Implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.35: WB04 staged refresh safety

Figure 5.36 records the internal logic checks used to detect completeness or consistency issues after replication.

WB05: Data Quality Detection Logic									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB05	Module / Component	Data quality check process Checks that the platform can identify data completeness issues after replication.	Internal Logic Under Test: Checks that the platform can identify data completeness issues after replication. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.					
Test Method	Completeness and consistency checkpoints	Risk Area							
Reviewer	Project developer	Execution Date							
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Completeness check	System should detect incomplete reporting period	Incomplete state was visible through quality-check result	Passed					
2	Status display	Quality status should be understandable to admin user	Status was displayed in admin workflow	Passed					
3	No credential exposure	Quality result should not expose server credentials	Only safe status information was shown	Passed					
4	Follow-up action	Admin should know whether recheck/sync is needed	Result supported operational decision	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.36: WB05 source-to-replica data quality check

Figure 5.37 presents the internal workflow review from detected data issue through repair-related follow-up and recheck.

WB06: Data Quality Repair and Recheck Routing									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB06	Module / Component	Manual sync worker and data quality recheck flow						
Test Method	Workflow checkpoint review	Risk Area	Checks the internal process flow from detected issue to repair/sync and recheck.						
Reviewer	Project developer	Execution Date	2026-05-29						
Internal Logic Under Test: Checks the internal process flow from detected issue to repair/sync and recheck. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.									
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Issue detection	Incomplete period should trigger recheck or sync action.	Detected issue was routed to supported sync/recheck flow.	Passed					
2	Repair/sync action	Manual sync should be able to refresh selected data scope.	Sync request processed through portal-supported path.	Passed					
3	Recheck	Quality status should update after data refresh.	Recheck reflected refreshed data state.	Passed					
4	Report reuse	Reports should use updated replica data after recheck.	Report validation used refreshed output.	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.37: WB06 quality repair request flow

Figure 5.38 shows the internal review used to confirm consistency between displayed report data and exported output.

WB07: Report Export Mapping Logic									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB07	Module / Component	Internal Logic Under Test: Checks that displayed report data and exported report data remain consistent. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.						
Test Method	Display-to-export mapping review	Risk Area							
Reviewer	Project developer	Execution Date							
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Visible columns	Export should include expected visible fields	Exported file retained report columns needed for review	Passed					
2	Value consistency	Exported values should match table display	Exported values matched displayed report rows in sample checks	Passed					
3	Totals	Export should not alter report totals	Exported totals aligned with on-screen totals where included	Passed					
4	Formatting safety	Export should not include hidden credentials or internal paths	Export contained report data only	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.38: WB07 report export mapping

Figure 5.39 records the access-control logic review protecting administrative routes and backend operations.

WB08: Role-Based Access Guard Logic									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB08	Module / Component	Internal Logic Under Test: Checks that route and backend access controls protect administrative features. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.						
Test Method	Access-control path review	Risk Area							
Reviewer	Project developer	Execution Date							
			Authentication/authoritati on layer and portal routing. Checks that route and backend access controls protect administrative features.						
			2026-05-29						
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behavior	Observed Evidence	Result					
1	Normal user access	Normal user should not open admin pages	Admin-only routes were blocked for normal user scenario	Passed					
2	Admin user access	Admin user should be able to open admin pages	Admin scenario could open admin pages	Passed					
3	Backend protection	Protected operations should require authorized request	Admin operations followed protected access path	Passed					
4	Navigation visibility	UI should not encourage unauthorised use	Admin navigation followed role-aware behaviour	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.39: WB08 role-based access restriction

Figure 5.40 presents the controlled request-handling review for automation-management actions in the admin workflow.

WB09: Automation-Control Request Handling									
White-box testing evidence. This layout focuses on internal logic checkpoints instead of user-facing UAT steps.									
White-Box Test ID	WB09	Module / Component	Automation control API and admin frontend page						
Test Method	Request/status checkpoint review	Risk Area	Checks that automation management requests are handled through controlled admin workflow.						
Reviewer	Project developer	Execution Date	2026-05-29						
Internal Logic Under Test: Checks that automation management requests are handled through controlled admin workflow. This sheet records internal checkpoints, controlled conditions, and observed processing behaviour. It is not a user acceptance test case.									
Controlled Inputs and Preconditions									
Input / Condition	Expected Internal Handling	Observed Handling	Evidence Method	Result	Notes				
Validated report period, role, or request payload depending on module	Processing should follow defined validation, grouping, refresh, or access-control path	Observed behaviour followed expected internal route during test scenario	Code-path review, API response inspection, and report-output cross-check	Passed	No credentials, server addresses, or proprietary setup details documented				
Internal Checkpoint Trace									
No.	Internal Checkpoint	Expected Internal Behaviour	Observed Evidence	Result					
1	Status retrieval	Admin page should retrieve current automation status	Status was available for display	Passed					
2	Action submission	Supported action should be sent as controlled request	Action request followed admin workflow	Passed					
3	Response handling	User should receive understandable result	Success/status message shown after action	Passed					
4	Safety boundary	Automation controls should not expose implementation secrets	Only safe operational status/control information was displayed	Passed					
Boundary / Negative Case Review									
Boundary Case	Expected Protection	Observed Result	Status	Reviewer Note					
Invalid or incomplete input	System should reject or handle safely without misleading report output	Controlled handling observed	Passed	No uncontrolled failure recorded					
Unauthorised or inappropriate operation where relevant	System should restrict protected actions	Role/access guard remained effective in tested path	Passed	Applies to admin-related modules					
Empty or incomplete data state	System should display understandable status rather than false result	Status/empty-state handling remained understandable	Passed	Supports operational safety					
White-Box Test Conclusion									
The selected internal logic path behaved as expected for the tested conditions. The test supports the implementation explanation in Chapter 5 without exposing internal credentials, server access instructions, or sensitive operational details.									

Figure 5.40: WB09 automation-control request handling

5.4 Summary

This chapter documented the implementation and testing of the Marrybrown Sales and Payment Analytics Platform. It described the completed development of the reporting-database and ETL layer, the FastAPI semantic/API layer, the React portal layer, and the supporting administrative functions that made the platform operationally

usable. It also outlined the formal report implementation coverage, the selected implementation examples, the recorded query-performance observation work, and the testing approach used to evaluate report accuracy, user-facing behaviour, and selected internal logic.

Taken together, the implementation and testing outcomes show that the project moved beyond conceptual design and delivered a real internal reporting platform with validated report modules, controlled refresh capability, role-based access, and company-requested extensions. The next chapter discusses the platform's contribution, remaining constraints, and future suggestions.