Flower Flipper Test

Find the three servo positions and how fast it should shake. (decision 024, `FlowerFlipper.java`)

Names		Date	
Battery voltage at start		Battery at end	

OpMode: Flower Flipper Test (Tests group on the Driver Station). **Needs in the config:** `flowerFlipperServo` (Servo)

Hidden by default (052): delete `@Disabled` in its file, build, deploy. **Safety:** space around the robot, hands clear, one person on STOP. Nothing moves in INIT.

Controls (gamepad 1)

Button	Does
A	start shaking (between POSITION_A and POSITION_B)
B	stop: goes to REST_POSITION
Dpad UP / DOWN	move the servo by hand, 0.01 at a time (only when not shaking). Read "Hand position"

Steps, in order

#	Do this	Expected	Actual (what happened)	If wrong
1	Dpad to where the flipper should sit when not in use	clear of the ball path and the frame		that number = `REST_POSITION`
2	Dpad to one end of the shake, just before it hits anything	position: _____		`POSITION_A`
3	Dpad to the other end	position: _____		`POSITION_B`
4	A, watch it shake for 10 s	moves the flower, servo not buzzing or hot		too slow: smaller `SWITCH_SECONDS`. Not reaching the ends: bigger
5	B	back to REST, stays there		

Numbers to put into the code: `subsystems/FlowerFlipper.java`

Constant	Was	New value	Checked by
`REST_POSITION`	0.5		
`POSITION_A`	0.4		
`POSITION_B`	0.6		
`SWITCH_SECONDS`	0.15		

Not on a gamepad button yet (decision 029). Write here what the team wants: which button, driver or operator, hold or toggle?

After the test: a coder puts the new numbers into the constants and removes the matching TODO comments; the results go on GitHub issue the flower flipper issue (or #3 for the button). Photos of anything surprising!