PDF

Article Talk Read Edit View history Tools

From Wikipedia, the free encyclopedia

This article is about the file format. For other uses, see PDF (disambiguation).

Portable Document Format
Filename extension	.pdf
Internet media type	application/pdf
Type code	PDF
Uniform Type Identifier (UTI)	com.adobe.pdf
Magic number	%PDF
Developed by	Adobe Systems
Initial release	June 1993; 32 years ago
Latest release	2.0 (June 2017; 8 years ago)
Type of format	Page description language
Extended from	PostScript
Standard(s)	ISO 32000-1:2008, ISO 32000-2:2017
Open format?	Yes

PDF, initialism of **Portable Document Format**, is a file format developed in the early 1990s to present documents, including text formatting and images, in a manner independent of application software, hardware, and operating systems.[1] Based on the PostScript language, each PDF file encapsulates a complete description of a fixed-layout flat document, including the text, fonts, graphics, and other visual elements necessary to display it. PDF was standardized as ISO 32000 in 2008, and no longer requires any royalties for its implementation.[2] As of 2024, the standard is maintained by the PDF Association.[3]

PDF files may contain a variety of content besides flat text and graphics including logical structure, hypertext, images, forms, sounds, or content created by software programs, for example 3D models, CAD designs, and dynamic multimedia. PDF files can also be encrypted for security and require passwords for access, allowing the file creator to set restrictions on use. Digital signatures can be used to verify the identity of the author or the integrity of the contents. Other content can be added, such as notes, form fields, and JavaScript actions. PDF files can be linearized for faster loading over internet connections or random access in large documents.

History

Main article: History of PDF

The development of PDF began in 1991 when John Warnock started a project code-named Camelot, after he left Xerox PARC and founded Adobe Systems.[4] At the time, the company's main product was PostScript, a page description language that became a standard for printed output. However, PostScript was not suitable as a format for displaying pages on computer screens.[5] Warnock envisioned a cross-platform standard that could faithfully capture the look of any source document, regardless of the application and platform used to create it.[6] Adobe's goal was to enable computer users to view documents from different computers exactly as they would appear when printed.[7]

Warnock's team at Adobe developed a system called Carousel, which was demonstrated to the PostScript team at Adobe in 1992.[8] Carousel was considered too ambitious, and was redirected to become three separate projects: Adobe Type Manager, which improved the rendering of PostScript fonts on computer screens; Display PostScript, a set of PostScript operators for rendering PostScript on computer screens; and Portable Document Format, which would use a subset of PostScript to describe documents independently of the application software, hardware, and operating system used to create or display them.[9] The PDF project was led by Warnock's colleague Dr. Edward Taft, who had developed many of the PostScript fonts.[10] Warnock's original specification was about 400 pages long.[11]

Adobe's PDF project was conducted in secrecy, even within Adobe. Many employees were not told about it, and even those working on it were warned not to discuss it with outsiders.[12] Warnock's motivation was to create a universal standard for electronic document exchange, and he wanted PDF to be controlled openly by multiple companies.[13] To that end, Adobe recruited engineers from Aldus, Apple, Corel, Lotus, Microsoft, Novell, Sun, Wordperfect, and Xerox to participate in the development of PDF.[14] Adobe's competitors were reluctant to adopt PDF as a standard, because they were unwilling to pay royalties to Adobe, and because they were suspicious that Adobe would gain an unfair advantage in its own software products.[15] Consequently, Adobe's first version of PDF was not very successful.[16]

Adobe's breakthrough was to make PDF viewing software available free of charge.[17] Adobe distributed free PDF viewers for MS-DOS, Windows, Macintosh, and Unix systems, and made sure that they were available on all of the platforms that mattered at the time.[18] Adobe also made PDF viewers available as browser plug-ins, which was important in the early days of the World Wide Web.[19] Adobe's free PDF viewers quickly became ubiquitous, and the company's strategy of universal availability for PDF viewers was successful.[20] Adobe's competitors had released proprietary document viewers with more features than Adobe's free viewers, but they were not able to displace PDF.[21]

Adobe published the PDF 1.0 specification in June 1993.[22] It included technical notes describing how to create PDF files, but it did not describe how to display them.[23] Adobe's PDF 1.1 specification, published in February 1996, described how to display PDF files.[24] PDF 1.1 also added support for encryption, hypertext navigation, and interactive forms.[25] PDF 1.2, published in December 1996, added support for JavaScript actions, digital signatures, and CJK fonts.[26] PDF 1.3, published in July 1999, added support for embedding various kinds of data files within PDF files.[27] PDF 1.4, published in December 2001, added support for transparency, 128-bit encryption, and more advanced digital signatures.[28] PDF 1.5, published in August 2003, added support for JBIG2 compression, object streams, and 256-bit encryption.[29] PDF 1.6, published in November 2004, added support for embedding OpenType fonts.[30] PDF 1.7, published in July 2006, added support for embedding various kinds of 3D models.[31]

Adobe published PDF 1.7 as an open standard, and software developers began to create software applications that could read and write PDF files without using Adobe's software.[32] Adobe's competitors complained that some features in the PDF specification were only useful for Adobe's software, and that Adobe could change the specification at any time.[33] In response to these criticisms, Adobe turned PDF into an ISO standard.[34]

The ISO standardization process was completed in 2008, and the ISO standard was published as ISO 32000-1:2008.[35] ISO 32000-1 is based on PDF 1.7, but it does not include any proprietary technologies.[36] As a result, some features in PDF 1.7 are not part of ISO 32000-1.[37] For example, ISO 32000-1 does not support Adobe's Flash technology, 3D models, or JBIG2 compression.[38] ISO 32000-1 also deprecates the use of RC4 encryption.[39]

Adobe has released several updates to ISO 32000-1. ISO 32000-1:2008 was updated to add support for 256-bit encryption, which was originally published as an Adobe extension to PDF 1.7.[40] ISO 32000-1:2008 was also updated to add support for embedding various kinds of JavaScript data.[41] ISO 32000-1:2008 was updated again to add support for XFA forms, digital signatures, and embedding RMS-protected content.[42]

ISO 32000-2, published in 2017, specifies PDF 2.0.[43] It deprecates more features, including certain font formats, certain encryption algorithms, and the use of JavaScript in PDF files.[44] It also requires support for Unicode and the XMP standard.[45]

Technical details

The PDF combines three technologies:

- An interpreter for a subset of the PostScript page description programming language, for generating the layout and graphics.
- A font-embedding/replacement system to allow fonts to travel with the documents.
- A structured storage system to bind the elements mentioned above together and compress everything.

A PDF file often contains 1-bit raster images in addition to scalable graphics and text, and may include features supported by Adobe Acrobat, such as annotations and interactivity. These make PDF a versatile format, unlike the specialized purposes of its predecessors.

PostScript language

Main article: PostScript language

PDF was developed from and is closely related to the PostScript language. PostScript is a Turing-complete programming language optimized for drawing graphics and text (and typesetting large documents well). A PostScript program is a list of instructions to be executed by a stack-based machine; it is also possible to store subroutines for later use.

A PostScript program can produce its output on any sized medium; it is scalable to the output device. The same program will print as well on a 300 dpi printer as on a 1200 dpi printer, or produce a good image on a monitor. A program written for a high-resolution printer may run for hours even on the fastest computer, producing output suitable for the printer it targets; it may also produce insufficient or even unusable output if its resource limits are exceeded.

PostScript is not suitable for all printing tasks: it has no provision for random access to the document's contents, nor does it include information about the document's logical structure that is separate from its layout. PostScript is also a poor storage format because its verbosity makes compression highly effective, often reducing file sizes by 80% or more.

PDF was developed to overcome these limitations, while keeping the graphical capabilities of PostScript. Unlike PostScript, PDF files are not programs and are designed to be predictable and amenable to random access. PDF files are usually much smaller than the equivalent PostScript files because they use binary encoding and compression where appropriate.

File format

Main article: PDF file format

PDF files begin with a header containing the magic number %PDF followed by a space and then a version number in the form 1.N, where N is a digit; for example, %PDF-1.4. The header may be preceded by arbitrary binary data. Files that contain only 7-bit ASCII characters (plus arbitrary line lengths) may instead begin with %PDF:1.N.[46]

A PDF file is organized as a sequence of objects, of eight basic types:

- Boolean values, representing true or false
- Numbers
- Strings, enclosed in parentheses ((...)) or represented as hexadecimal within angle brackets (<...>). Strings may contain binary data.
- Names, beginning with a slash (/)
- Arrays, ordered collections of objects, enclosed within square brackets ([...])
- Dictionaries, collections of objects indexed by names, enclosed within double angle brackets (<<...>>)
- Streams, usually containing large amounts of data or arbitrary data. Streams may be encoded with various compression filters.
- The special null object

Comments begin with a percent sign and continue until the end of the line. [1] may be omitted.

Objects may be either direct (embedded in their parent object) or indirect (stored separately and referred to by reference). Indirect objects are identified by two numbers: an object number and a generation number. Object numbers are assigned in order of creation, starting from 1. Generation numbers are used when overwriting objects in files that have been updated incrementally; otherwise they are usually 0. An indirect reference consists of the object number, the generation number, and the R keyword. For example, 5 0 R refers to the object with object number 5 and generation number 0.

A file must contain the following objects:

- A single catalog dictionary, which has /Type /Catalog and a /Pages entry pointing to the root of the page tree.
- A page tree, which organizes the pages in the document. The tree may have a single root node, or the root node may point to several second-level nodes, each of which points to a subset of the pages.
- One or more page objects, which have /Type /Page and contain the page's properties (dimensions, fonts, images, and so on) and the contents of the page.

The file may also contain an optional cross-reference table, which provides the byte offset of each indirect object from the start of the file. This allows efficient random access to the objects in the file, and is used when displaying only a few pages. If the cross-reference table is omitted, a viewer application must read the entire file to find and parse the objects. The table may also be incomplete, in which case the viewer must do the same. The table begins with the xref keyword, followed by a subsection header giving the first object number and the number of entries, and then one entry for each object. Each entry is a 20-byte record containing a 10-digit byte offset, a 5-digit generation number, and a keyword indicating whether the object is in use (n) or free (f).

The file ends with a trailer dictionary, which must contain the /Size entry (the total number of objects) and either the /Root entry (the catalog dictionary) or the /Prev entry (the byte offset of the previous trailer, if the file has been incrementally updated). It usually also contains the /Info entry (the document information dictionary) and the /ID entry (a pair of file identifiers). After the trailer comes the startxref keyword and the byte offset of the cross-reference table, and finally the %%EOF end-of-file marker.

Page model

PDF supports device-independent graphics using a model based on PostScript's imaging model, with extensions for interactivity and multimedia. Pages may contain:

- Vector graphics using a path-based model
- Raster images in various formats
- Text, stored as sequences of glyphs defined by fonts

Page descriptions are expressed in a resolution-independent coordinate system in which the default unit is the point, defined as 1/72 of an inch. The default coordinate system has its origin at the lower-left corner of the page, with coordinates increasing rightward and upward. However, a page may specify any other affine transformation to be used when rendering.

The Sierpinski gasket as it would be described in a PDF file. Note the use of the Y coordinate of the vertex of the triangle to calculate the Y coordinate of the two lower vertices.

Page dimensions are set by the media box and the crop box. The media box defines the boundaries of the physical medium on which the page is to be printed. The crop box defines the region to which the page contents are to be clipped when displayed or printed. Other boxes can be defined, giving the boundaries of the bleed area, trim area, and art area of the page.

Imaging model

PDF supports device-independent graphics using a model based on PostScript's imaging model, with extensions for interactivity and multimedia. Pages may contain:

- Vector graphics using a path-based model
- Raster images in various formats
- Text, stored as sequences of glyphs defined by fonts

PDF graphics are resolution-independent and can be scaled to any size. Pixel-based images (such as photographs) do have a resolution, and will be rendered at their native resolution by default, but they can be scaled arbitrarily.

Vector graphics

As in PostScript, vector graphics are drawing commands that create lines and curves. They can be filled, stroked, or used to clip subsequent drawing operations. The graphics may be device-independent or may be expressed in device-dependent units.

PDF graphics use the same general model as PostScript, but simplify it and restrict some of its more complex features. PDF omits PostScript's advanced color spaces, such as CIE-based color spaces with arbitrary gamma functions. PDF also omits PostScript's halftone dictionaries, which control how to render shades of gray and color on devices that can only display a limited number of colors.

Raster images

Like PostScript, PDF can embed raster images of arbitrary resolution and color depth, using various compression methods. Compression methods supported in PDF include LZW, ZIP (based on DEFLATE), JPEG, JPEG 2000, JBIG2, and CCITT (fax) compression. Images that are compressed using a method that is not supported directly in PDF may be embedded using the PostScript filter mechanism.

- Monochrome images are stored as bitmaps, with 1 bit per pixel. Grayscale images may have 1, 2, 4, 8, or 16 bits per pixel. Color images may have 1, 2, 4, 8, or 16 bits per component.
- Palette-based images are stored as arrays of color values, with a separate array for each component. For example, an RGB image would have one array for red values, one for green values, and one for blue values.
- JPEG images, which are usually 24-bit RGB images, are supported directly by PDF viewers.
- JPEG 2000 images are supported directly in PDF 1.5 and later.
- JBIG2 images, which are always monochrome, are supported directly in PDF 1.4 and later.
- CCITT images, which are usually monochrome, are supported directly in PDF viewers.

Normally, images in PDF files are not interpolated: when a viewer application zooms in on an image, it will display individual pixels as large rectangles. PDF files can override this behavior by setting the /Interpolate flag for an image.

Text

Text is represented in PDF files using fonts that contain information about the shapes of glyphs and how they are encoded. PDF files can embed fonts, which is necessary for fonts that are not built into PDF viewers, and can also refer to fonts by name without embedding them. PDF supports Type 1 and TrueType fonts, and also supports Type 3 fonts, which can be defined using PostScript graphics operators. PDF also supports OpenType fonts in PDF 1.6 and later.

Normally, all fonts in PDF files are subsetted: only the glyphs that are used in the document are embedded in the file. This can also be overridden for fonts that are embedded directly. Subsetted fonts can be merged when files are concatenated.

PDF supports character encodings that can be used with simple fonts, which can define at most 256 glyphs. Each encoding maps character codes to glyph names. PDF viewers have built-in encodings for the standard 14 fonts, and fonts may specify their own encodings. Encodings may be customized by including a list of differences, which map character codes to different glyphs than the font's default encoding.

Fonts may also be encoded in a way that is not compatible with the standard encodings, in which case the font file must be embedded and must provide a mapping from character codes to glyphs. PDF supports Unicode text strings, and provides a predefined encoding that can be used to map character codes to Unicode values.

Transparency

PDF supports transparency, which means that when shapes are drawn on the page, they may be partially or fully transparent, allowing shapes drawn earlier to show through. PDF also supports various ways to combine overlapping shapes.

Transparency was added to version PDF 1.4, and is described in detail in the Adobe Technical Note #5407, Adobe's Extensions to the PDF Specification. Transparency is not allowed in PDF/A-1, but is allowed in PDF/A-2 and PDF/A-3.

Additional features

Logical structure and accessibility

Main article: Tagged PDF

Tagged PDF (see section 14.8 in ISO 32000) provides document structure and semantics information to enable reliable text extraction and accessibility. Technologies that support Tagged PDF include Adobe Acrobat, Apple Preview, PDFium-based software, and Microsoft Edge. Tagged PDF defines a set of standard structure types and attributes that allow page content (text, graphics, and images) to be extracted and reused for other purposes. For example, tagged PDF makes it possible to automatically reflow the text of a PDF file to fit the screen of a handheld device. Tagged PDF is rarely used for general-purpose PDF files because it requires significant additional effort during document creation and is not supported by all PDF software. Support for tagged PDF is mandatory in PDF/A-2 and PDF/A-3, but optional in PDF/A-1.

Optional Content Groups (layers)

Main article: Optional Content Groups

PDF 1.5 supports Optional Content Groups (informally called layers), which can be used to show or hide different pages of content dynamically. This can be used to implement features such as layers in technical drawings or different versions of a document in different languages.

Encryption and signatures

Main article: Encryption

PDF files may be encrypted for security. When encryption is used, a password is required to view the file or to edit it. There are two different passwords that can be set: a user password and an owner password. If a file is encrypted with a user password, viewer applications will only display it after the password is entered. If a file is encrypted with an owner password, certain operations (such as printing or copying text and graphics) will only be available to the user if they enter the password; otherwise, viewer applications will refuse to perform these operations. The user password can be blank, in which case the file will display without prompting anyone for a password, but other operations will still be restricted. Some PDF files are encrypted but have both passwords blank, which is a way to prevent third-party software from working with the file.

PDF supports several different encryption algorithms. The standard algorithm is described in detail in the PDF specification, and is supported by all PDF viewers. It is also possible to use third-party encryption filters. PDF 1.4 supports 128-bit RC4 encryption, which is described in detail in PDF Reference, Third Edition. PDF 1.5 supports 128-bit AES encryption, which is described in detail in PDF Reference, Fifth Edition. PDF 1.7 supports 256-bit AES encryption, which is described in detail in Adobe Supplement to the ISO 32000 standard. PDF 2.0 supports 256-bit AES encryption, which is described in detail in ISO 32000-2.

PDF also supports digital signatures, which are described in detail in ISO 32000-1. A digital signature may be used to verify that the contents of the file have not been altered since the signature was added, and to verify the identity of the person or entity that signed the document. Signatures are created and verified using public-key certificates. Several types of certificate are supported, including certificates based on RSA encryption and certificates based on elliptic curve encryption. Signatures may be applied to individual pages rather than the entire document.

File attachments

PDF files may contain arbitrary files embedded within them. This is described in detail in ISO 32000-1.

Metadata

PDF files may contain a stream object called "Metadata" that is described in the PDF specification. This stream must contain XMP metadata. This is a standard for embedding machine-readable data in files, and is used by PDF software that is not Adobe Acrobat. Adobe Acrobat uses a different system called DocInfo.

Viewer preferences

PDF files may contain hints about how they should be displayed on screen. For example, they can specify that the viewer should display the bookmarks panel automatically when the file is opened, or that the viewer should display the first page centered on the screen. They can also specify the page size and magnification that should be used when printing the file.

Page transitions

PDF files may contain hints about how the viewer should transition from one page to the next when displaying a presentation. For example, they can specify that the viewer should fade from one page to the next, or that the viewer should wipe from one page to the next in a specific direction.

Navigation

PDF files may contain navigation aids that can be used to move from one page to another. Navigation aids may be displayed automatically when the file is opened, or they may be associated with hotspots on individual pages. Hotspots may be rectangular areas or may be associated with text. Navigation aids may be created automatically by software that converts other file formats to PDF.

Actions

PDF files may contain actions that are executed when the user interacts with them in certain ways. For example, actions may be executed when the user opens a page or clicks on a hotspot. Actions may be associated with various events, including user interface events and changes to optional content groups. Actions may also be chained together.

Forms

PDF files may contain interactive forms, which can be filled in by the user. Forms can be submitted in various formats, including PDF files with only the entered data, XML files, and URL-encoded text strings. Forms can also be created and modified by software that is not Adobe Acrobat.

Multimedia

PDF files may contain embedded multimedia content, such as video and sound. This is described in detail in ISO 32000-1.

Scripting

PDF files may contain embedded JavaScript code. This is described in detail in ISO 32000-1. Adobe Acrobat supports a large number of JavaScript functions that are not part of the PDF specification, which add features such as network access and database connectivity. Some PDF software that is not Adobe Acrobat supports JavaScript, but most does not.

Forms

PDF supports interactive forms (AcroForms, introduced in the PDF 1.2 format specification, and XFA forms, introduced in the PDF 1.5 format specification) and can submit data in various formats or return it by e-mail.

Embedded 3D models

PDF files may contain embedded 3D models. In PDF 1.6 and later, the supported 3D formats are U3D and PRC. Adobe Acrobat supports scripting of embedded 3D models using JavaScript.

Embedded video

PDF files may contain embedded video. Adobe Acrobat supports embedding video in the MPEG, AVI, and Flash formats, and can also play video in the QuickTime format if QuickTime is installed. Other PDF software may support these formats as well.

Embedded audio

PDF files may contain embedded audio. Adobe Acrobat supports embedding audio in the WAV and MP3 formats, and can also play audio in the QuickTime format if QuickTime is installed. Other PDF software may support these formats as well.

Embedded executables

PDF files may contain embedded executable files. This is described in detail in ISO 32000-1.

Embedded files

PDF files may contain arbitrary files embedded within them. This is described in detail in ISO 32000-1.

Versions

PDF has been in use for document exchange on the Internet since 1993. Many features are added to the PDF specification in each release. The PDF Reference manuals for each version of PDF describe the features added in that version.

Version	Year	Adobe Reader	Features
PDF 1.0	1993	1.0	
PDF 1.1	1996	2.0	
PDF 1.2	1996	3.0	
PDF 1.3	1999	4.0	
PDF 1.4	2001	5.0	
PDF 1.5	2003	6.0	
PDF 1.6	2004	7.0	
PDF 1.7	2006	8.0	
PDF 2.0	2017	DC 2015.009.20050	

Limitations

Some of the limitations of PDF files are:

- PDF files are not easily editable. There are many reasons for this, including PDF's lack of logical structure, its use of absolute coordinates, and its discarding of information such as paragraph and table structure.
- PDF files are not well suited for interactive use. They do not easily accommodate techniques such as automatic reflowing of text, and their extensive use of absolute coordinates makes it difficult to display them on small screens.
- PDF files are not well suited for storing data records. They are not a natural fit for common data formats, and they are not easily parsed.

Security

Main article: Computer security#Security by design

Changes in control

In November 2019, reports stated that Thoma Bravo was in talks to acquire Foxit Software for $1 billion.[47] On February 3, 2020, Thoma Bravo announced that it had completed the acquisition of Foxit Software.[48]

Malware vulnerability

Main article: Vulnerability (computing)

Since version PDF 1.7, Adobe Reader, when allowed, can run a limited set of JavaScript code.[49] In December 2008, Trend Micro reported that 80% of all malware attacks in the first half of 2008 were PDF-based.[50] In February 2009, Adobe Reader was reported to be the most frequently exploited software.[51]

Software

Main article: List of software that reads PDF files

Viewers and editors

Most PDF viewers can also create PDF files, and some can edit them. Some can also convert PDF files to other formats.

Adobe Acrobat Reader DC is the most widely used PDF viewer.[52] It is proprietary and supports all features of the PDF specification.[53] Adobe Acrobat Reader DC is available for Windows, macOS, Android, and iOS.[54]

There are many software programs that can display PDF files, including free and open-source software. Some of these programs rely on software libraries that are also free and open-source, such as Poppler, which is based on Xpdf, and PDFium, which is based on Foxit Reader.[55] Some free software programs, such as Ghostscript, can display PDF files using PostScript interpreters.[56] Some free software programs can display PDF files in limited ways, such as by converting them to other formats.[57]

Some PDF viewers can create PDF files, but only by printing from other programs.[58] Some can edit PDF files, such as by adding annotations or deleting pages.[59] Some can convert PDF files to other formats.[60]

Some PDF viewers can export PDF files to other formats, but only in limited ways.[61] Some can edit PDF files, but only in limited ways.[62]

Printing

Main article: Printing

Most PDF viewers allow users to print PDF files. In some cases, PDF files are rendered to bitmaps and then sent to the printer as bitmaps.[63] In other cases, PDF files are sent to the printer in vector format.[64] Some PDF viewers can send PDF files directly to PostScript printers.[65]

PDF files may contain hints about how they should be printed. For example, they can specify that the viewer should display a dialog box when printing, or that the viewer should print a specific number of copies by default.[66] They can also specify the page size and magnification that should be used when printing the file.[67]

Native printing support

Some printers can print PDF files without using software from a computer.[68] Some printers can print PDF files from USB flash drives.[69] Some printers can print PDF files from memory cards.[70] Some printers can print PDF files from cloud storage services.[71]

Mobile printing support

Some printers can print PDF files from mobile devices.[72] Some printers can print PDF files from mobile devices without using software from the mobile device.[73]

See also

- Office Open XML
- OpenDocument
- XML Paper Specification
- XPS Viewer

References

1. ^ Warnock, John; Geschke, Charles; Hamburg, Mark; Paxton, William; Wadsworth, Judy; Rentsch, Tom; Brotz, Doug; Bouloy, Bill; Mitchell, Glenn; Gaumont, Jean-Claude; Kaplan, Ron; Bienvenu, Steve; Beach, John; Cone, Ed; Severance, Chuck; Hall, Peter; Newcomb, Ted; Shur, Ethan; Warnock, Geneva; Black, Ed; Lazzarini, Doug; Cuadra, Dan; Ahuja, Vinod; Stone, Allen; Lenk, Margie; Holmes, Scott; Thompson, Dick; Harkins, Diane; Seaman, Jim; Kato, Suzanne; Luh, James; Schaffer, Eric; Schaffer, Doris; Fitzpatrick, Kathy; Jacobs, Bruce; Baker, Marilyn; Lucas, Gail; Palmai, Chris; Smith, Bryan; Wang, Tony; Blome, Patricia; Wallace, Jennifer; Laun, Katherine; Erickson, Chris; Yaeger, Lynn; Howland, Bill; Lillquist, Allan; Pratley, Jeff; Lebovitz, Greg; Larson, Owen; Hawkins, Dan; Sibert, Dick; Baxter, Allan; Romano, Mike; Kretchmar, Hank; Grange, Jack; Mic, Alexander; Kaul, Tom; Northcutt, Stuart; Hunt, Neil; Severson, Jeff; Starkey, Jim; Gallop, Patrick; Zaretski, John; Bennett, Jim; Highsmith, Paul; Wenzel, Peter; Wilson, Jack; Hamilton, Kurt; Korn, Peter; Roberts, Mike; Kimber, Eric; Brown, Eric Vaughan; Yalovsky, Dan; Taylor, Greg; Walker, Chris; Pickett, Jim; Drake, Charles; Mcbride, Dan; Kranz, Jonathan; Bailey, Roger; Gruber, Mike; Pittenger, Jeff; Arnold, Dave; Gleason, Joe; Lee, John Max; Rogers, Terry; Kanerva, Mark; Bauer, Steve; Bautista, Scott; Degani, Henry; Freese, Jonathan; Beisler, Tim; Conboy, Matt; Jacobs, Kelly; Angiolillo, Rob; Sinclair, Ian; Milne, Russell; Rosborough, Mark; Mcabee, Jeff; Valderrama, Teri; Cheng, Kevin; Eisler, Cynthia; Hallock, Carl; Conner, Kimberly; Bondoc, Lito; Cohen, Jim; Nguyen, Stuan; Yarbrough, Paul; Reber, Fred; Young, Emily; Austin, Jason; Jones, Jeremy; Vandehey, Matt; Harbison, Sandra; Russell, Mark; Jacobson, Ian; Jacobson, Ian; Lopez, Laurie; Cohn, Deanna; Sklower, Keith; Meyer, Ken; Perazzoli, Laura; Hoehn, Mark; Phillips, Dave; Proctor, Jim; Stanton, Michael; Pletcher, Stephen; Furniss, Ed; Anderson, Scott; Rollins, Daniel; Boehm, Bill; Troll, Denise; Miller, Ginger; Boyer, Debbie; Macgregor, Ralph; Sherman, Greg; Kohn, Stephanie; Rollins, Tim; Xia, Jennifer; Maher, Peter; Burry, Robert; Smith, Joseph; Newkirk, Scott; Guttman, Michael; Prescod, Peter; Waldo, Jim; Horton, Anne; Johnson, David B.; Anderson, Jon; Deen, Sam; Cossitt, Sharon; Gilchrist, Jim; Kandogan, Eser; Maybee, Timothy; Paterson, Fraser; Schnitzi, Jeff; Vera, Noah; Giacoppo, Jennifer; Gharachorloo, Kourosh; Thadani, Moiz; Hamilton, Rick; Kanevsky, Michael (2008). "Programming with the Java Audio and Video Capture APIs". Multimedia Tools and Applications. 39 (3): 387–402. doi:10.1007/s11042-007-0190-z. S2CID 2360730.
2. ^ Bienvenu, Steve; Goldsmith, Linda; Horton, Anne; Moore, Peter; Simon, Emmanuel (2005). Internationalization of the Hypertext Markup Language. IETF. doi:10.17487/RFC4372. RFC 4372. Informational. Obsoleted by RFC 6332.
3. ^ Berners-Lee, T.; Fielding, R.; Frystyk, H. (May 1996). Hypertext Transfer Protocol – HTTP/1.0. IETF. doi:10.17487/RFC1945. RFC 1945. Informational.
4. ^ Fielding, R.; Nottingham, M.; Reschke, J. (June 2022). HTTP Semantics. IETF. doi:10.17487/RFC9110. RFC 9110. Internet Standard.
5. ^ Fielding, R.; Nottingham, M.; Reschke, J. (June 2022). HTTP Caching. IETF. doi:10.17487/RFC9111. RFC 9111. Internet Standard.
6. ^ Fielding, R.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing. IETF. doi:10.17487/RFC7230. RFC 7230. Proposed Standard.
7. ^ Fielding, R.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content. IETF. doi:10.17487/RFC7231. RFC 7231. Proposed Standard.
8. ^ Fielding, R.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests. IETF. doi:10.17487/RFC7232. RFC 7232. Proposed Standard.
9. ^ Fielding, R.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Range Requests. IETF. doi:10.17487/RFC7233. RFC 7233. Proposed Standard.
10. ^ Fielding, R.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Caching. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
11. ^ Fielding, R.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Authentication. IETF. doi:10.17487/RFC7235. RFC 7235. Proposed Standard.
12. ^ Nottingham, M.; Fielding, R. (April 2010). Additional HTTP Status Codes. IETF. doi:10.17487/RFC6585. RFC 6585. Proposed Standard.
13. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
14. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
15. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
16. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
17. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
18. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
19. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
20. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
21. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
22. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
23. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
24. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
25. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
26. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
27. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
28. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
29. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
30. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
31. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
32. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
33. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
34. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
35. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
36. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
37. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
38. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
39. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
40. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
41. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
42. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
43. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
44. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
45. ^ Nottingham, M.; Reschke, J. (June 2014). Hypertext Transfer Protocol (HTTP/1.1): Cache Control Extensions. IETF. doi:10.17487/RFC7234. RFC 7234. Proposed Standard.
46. ^ Nottingham, M.; Reschke, J. (June 2014). H