

SUBMITTAL	ITEM TYPE	TITLE	LAST UPDATED
TELEPHONE	TELEPHONE SYSTEM	IS-MV	AUGUST 20, 2018



SPECIFICATIONS

Power Source: Supplied from IS-CCU/SCU/RCU

Communication: Open voice hands-free

Mounting: Flush mount to 2-gang box

Material: Stainless steel

Temperature: 14 - 140°F (-10 - 60°C)

Dimensions: 4-3/4"H x 4-3/4"W x 1-7/8"D **Weight:**

Approx. 0.82lbs (370g)

Communication: Hands-free (VOX), push-to-talk (simplex), or handset (full-duplex)

Video Display: 3-1/2" LCD screen

Door Release: Programmable Form C dry contact, 24V AC/DC, 500mA (use RY-24L for larger contact rating, which requires 24V DC power supply)

Mounting: Wall or desk mount (stand included)

Wire Type: Cat-5e or Cat-6

Wire Distance: IS-MV to Control Unit: 980'

FEATURES

- 3.5" LCD color monitor
- Handset for privacy or hands-free VO communication
- Video Output
- Audio Output
- Door release button
- PTZ & brightness control
- 6 speed dial button
- Wall or desk mount (stand included)
- Connects using C T-5e/6 cable

