

Master Station: select up to 4 per IS-CCU



IS-MV

Video Master Station

- Hands-free communication with handset for privacy
- Wall or desk mount (*stand included*) → p. 77

Master Station: select up to 8 per IS-SCU



IS-MV

Video Master Station

- Hands-free communication with handset for privacy
- Wall or desk mount (*stand included*) → p. 77

Cat-5e/6 wire
N/A from Aiphone
(max. 980')

Audio Output
600Ω



Cat-5e/6 wire
N/A from Aiphone
(max. 980')

Audio Output
600Ω



Room/Sub Stations: mix and match up to 30 per IS-RCU



SP-2570N
8Ω, 25/70V, 5W
Ceiling Speaker
→ p. 108




IS-RS
→ p. 78



IS-SS
→ p. 78



IS-SS-2G
→ p. 78



IS-SSR-2G
→ p. 78

NOTE: All are weather and vandal resistant (excluding IS-RS).



EL-12S
Electric Door Strike
(requires PT-1210N)



PT-1210N
12V AC Transformer
(required for EL-12S)

Cat-5e/6 wire — N/A from Aiphone
(variable wiring distances, see table below)

Dimensions

	INCHES			MILLIMETERS		
	Height	Width	Depth	Height	Width	Depth
IS-CCU, IS-SCU, IS-RCU	3-7/16"	16-3/4"	11"	88	425	280
IS-DV	8-7/16"	4-1/8"	1-1/8"	215	105	28
IS-DVF	10-7/16"	5-7/8"	*	265	150	*
IS-DVF-HID, IS-DVF-RP10	12-3/8"	7"	*	315	178	*
IS-MV	7-7/16"	9-13/16"	2-5/16"	189	250	59
IS-RS	7-13/16"	4-9/16"	2-1/2"	199	116.5	64
IS-SS	10-7/16"	5-7/8"	*	265	150	*
IS-SS-2G, IS-SSR-2G	4-3/4"	4-3/4"	*	120	120	*

* Aiphone recommends a 2-1/2" minimum back box depth for all flush mount stations.

Wiring

There are many different wiring configurations possible with the IS Series.

For additional help, contact Aiphone's Technical Support.

800.692.0200



Accessories



HID-SS
Card Access Station with HID® ProxPoint® Plus Proximity Card Reader
→ p. 105



TW-SPL
Interface Plate for IS-DVF or IS-SS (adapts standard door station to an Aiphone tower or wall box)
→ p. 85



IS-MB
Mullion Mounting Bracket for IS-DV
→ p. 107




SBX-2G
Surface Mount Box for IS-SS-2G or IS-SSR-2G
→ p. 106




SBX-ISDVF
Surface Mount Box for IS-DVF or IS-SS
→ p. 106



SBX-ISDVFFP
Surface Mount Box for IS-DVF-HID or IS-DVF-RP10
→ p. 106



LB-SDVF
Security Lock Box for IS-DV, IS-DVF, or IS-SS (lock not included)
→ p. 107



IS-RACK
19" Rack Mount for up to 3 IS-PU-ULs (image shown with 1 IS-PU-UL)
→ p. 111



EL-12S
Electric Door Strike (requires PT-1210N)
→ p. 105

IS Series Wiring Distances with Cat-5e/6

IS-DV, IS-DVF, IS-DVF-HID, IS-DVF-RP10, IS-SS, IS-SS-2G, or IS-SSR-2G to IS-CCU, IS-SCU, or IS-RCU	980'
IS-MV to IS-CCU or IS-SCU	980'
IS-RS to IS-CCU, IS-SCU, or IS-RCU	490'
IS-CCU to IS-SCU (x3 wires)	650'
IS-CCU to IS-RCU (x2 wires)	650'
IS-CCU to IS-IPC (x3 wires)	33'
IS-RCU to IS-IPC (x2 wires)	33'
IS-IPC to Network Node	330'
IS-PU-UL to IS-CCU, IS-SCU, or IS-RCU	50'

Features

See p. 11

Specifications

See p. 11

Camera View Area

See p. 12

UL Listed Class 2 Power Supplies & Transformers

12V AC Transformer




PT-1210N
12V AC Transformer
for CCS-1A Set,
EL-12S, IE-8 Series,
or LEM-1DL Series

Specifications

Input 120V AC, 60Hz
Output 12V AC, 10VA, 830mA
Consumption 15W

PT-1210N



15V AC Transformer




PT-1211C
15V AC Transformer
for DA-1DS, DA-4DS,
DB Series, or IPW-1A

Specifications

Input 120V AC, 60Hz
Output 15V AC, 10VA, 700mA
Consumption 10.5W

PT-1211C



6V DC Power Supply




SKK-620C
6V DC Power Supply for
AT-406 Series, C-123L/A Set,
C-123LW Set, or LEM Series

Specifications

Cord Length 12'
Ground Wire Length 1'
Input 120V AC, 60Hz
Output 6V DC, 200mA

SKK-620C



12V DC Power Supply




PS-1225UL
12V DC, 2.5A Power Supply
for LEF Series, RY-IP44,
TD-H Series, or TL-2000

Specifications

Cord Length 6'2"
Input 100~240V AC, 50/60Hz
Output 12V DC, 2.5A
Consumption 37W, 65~82VA

PS-1225UL



18V DC Power Supply




PS-1820UL
18V DC, 2A Power Supply
for JF Series, JK Series,
or JO Series

Specifications

Cord Length 6'2"
Input 100~240V AC, 50/60Hz
Output 18V DC, 2A
Consumption 45W, 75~95VA

PS-1820UL



24V DC Power Supply




PS-2420UL
24V DC, 2A Power Supply
for AX Series, GT Series,
IM Series, JP Series, KB Series,
MC Series, NHX Series,
or the Beacon/Strobe
Light for Emergency Wall
Boxes and Towers

Specifications

Cord Length 6'2"
Input 100~240V AC, 50/60Hz
Output 24V DC, 2A
Consumption 60W, 100~125VA


PS-2420UL



48V DC Power Supply & Rack Mount

IS-PU-UL
48V DC, 2A Power Supply
for IS Series or NIM Series

IS-RACK
19" Rack Mount for
up to 3 IS-PU-ULs
(image shown with 1 IS-PU-UL –
power supply not included)



Specifications (IS-PU-UL)

Cord Length 5'10"
Input 100~240V
AC, 50/60Hz
Output 48V DC, 2.1A
Consumption 120W

IS-PU-UL

