



I.T.E. POWER SUPPLY PS-1208

INPUT/入力 100-240V ~ 50/60Hz
21-33VA 0.3-0.16A

OUTPUT/出力 12V = 0.8A (VI)

Model No. NU10-G120080-I3



This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

CAUTION:

RISK OF ELECTRIC SHOCK
DRY LOCATION USE ONLY
NO SERVICEABLE PARTS INSIDE
DOUBLE POLE FUSING

ATTENTION:

POUR UTILISATION A L'INTERIEUR
SEULEMENT
DOUBLE POLE FUSIBLE

VORSICHT:

Doppel-Pole Fusing
本製品は当社製インターホンの専用電源です。
ほかの用途には使用しないでください。

This product is designed for exclusive use of
Aiphone Intercom Systems.

Do not use for other systems.

Ce produit est conçu pour l'utilisation exclusive
de systèmes d'interphone Aiphone.

Ne pas utiliser pour d'autres systèmes.



LEI F6 MADE IN CHINA EL

See the **INSTALLATION MANUAL**
for proper selection of the power supply cord.
Voir le manuel d'installation
pour le choix du cordon d'alimentation.

DESCRIPTION:

The PS-1208UL is a DC 12V Class II power supply used for Aiphone intercom applications.

This power power supply is UL and CSA listed and is designed for indoor use only.

PRODUCT APPLICATIONS:

The PS-1208UL can be used for the following
Aiphone Communication systems:

- LEF Series without BG-10C
- TD-H/B Series
- RY-IP44
- TL-2000

SPECIFICATIONS:

Power input:	AC 100~240V 50/60Hz
Power output:	DC 12V 0.8A
Power consumption:	21~33VA
Temp. Rating:	32~104°F (0~40°C)
Wiring connection:	Screw terminals
Dimensions (HxWxD):	6-9/16" x 3-9/16" x 2"