

SUBMITTAL	ITEM TYPE	TITLE	LAST UPDATED
SPEAKERS	SOUND SYSTEM	SM12CXT-B	AUGUST 22, 2018



SPECIFICATIONS

Power Rating (Rms)

250 Watts

Frequency Response

55Hz - 15kHz (± 5 dB)

Sensitivity (1W/1M)

99dB

Power Taps

7.5, 15, 30, & 60 Watts & 8 Ω

Height

19" (483mm)

Width

14 1/2" (368mm)

Depth

14 1/8" (357mm)

Weight

39 Lbs (17.7kg)

FEATURES

- High Performance Atlas Sound Compression Driver Coaxial Loudspeaker in Versatile, Flyable, Wood Enclosure
- Multiple (12) 1/4"-20 Inserts, Providing Fly Points for a Variety of Mounting Configurations
- Includes Internal, High Efficiency 60 Watt 70.7V/100V Transformer (May Be Bypassed For 8 Ω Operation)
- Barrier Strip Input For 70.7V/100V/8 Ω or Parallel 4 Pole Speak-On Input for 8 Ω Operation Only
- Unique Input Panel Allows Use of Standard 4" Square Box Cover (Raco 753 or Eq.) For Applications Where Flex Conduit is Required for Termination
- Fuse Protection for Low and High Frequency Drivers
- Attractive, Heavy-Duty Grille Assembly
- Durable Black or White, Rough-Coat Finish
- Optional Brackets for Wall Mounting
- Pre-Drilled With T-Nut Inserts for Omnimount™ Bracket Wall Mounting

