



1802-EPD

TELEPHONE ENTRY SYSTEM



**BEST SUITED FOR APPLICATIONS OF UP TO 100
RESIDENTS AND WHERE SPACE IS LIMITED**



flush mount

surface mount

- Slim design for applications with limited space. Surface or flush mount styles available
- Visitors use the phone system to communicate with a resident who can grant or deny access via their own touch-tone telephone
- Programmable directory codes can be set from 1 to 4 digits
- Provides service for up to 100 residents
- 2 year limited factory warranty



modular design
makes installation and service easy



dtmf tone output
useable with PBX, KSU and telephone
systems with auto-attendants





built-in display
resident directory



large buttons
A to Z scroll and one touch CALL buttons for quick and easy operation

ACCESS CONTROL SOLUTIONS

1802-EPD TELEPHONE ENTRY SYSTEM



1802-EPD Surface

6.5" W x 12" H x 5" D @ top 3.25"

(16.5cm W x 30.4cm H x 12.7cm D)

1802-EPD Flush

8.375" W x 14" H x 3.25" D

(30.4cm W x 34.3cm H x 6.35cm D)

1802-EPD	PHONE # MEMORY	ENTRY CODES	DEVICE CODES	RELAYS	DIRECTORY	ELEVATOR CONTROL	PROGRAMMING OPTIONS	OPTIONS	TRANSACTION BUFFER
Surface Mount	100	100 (4-digit) 6 (5-digit)	N/A	2	Single-Line LCD Display	-	System Keypad or Touch-Tone Telephone	Handset Kit	-
Flush Mount	100	100 (4-digit) 6 (5-digit)	N/A	2	Single-Line LCD Display	-	System Keypad or Touch-Tone Telephone		-

Technical Features

Mechanical

Stainless steel faceplate
Galvanized steel sub-plate
Metal keypad
Offset speaker holes for protection
Hands free voice operation
(Optional handset available on surface mount style only)
Built-in postal lock provision
Surface and Flush mounting styles
NEMA 4x rated enclosure

Programming Methods

User programmable welcome and instruction messages.
Up to 48 characters each
All programming is from the system keypad

Electrical

Single-line 16 character LCD display
16 VAC (power transformer included)
Full Duplex voice communication
Stores up to 100 phone numbers, 15 area codes
Programmable directory codes (1 to 4 digits)
10 & 11 digit dialing capability
DTMF tone output allows for use with KSU, PBX
and auto-attendant type phone systems
Four-digit entry codes (100)
Five-digit entry codes (6)
Built-in clock/calendar
Time clock has its own backup power source
Entry code time zones
Hold open time zones (4)
Flash entry codes
LCD display for programming assistance
Two relays to control two entry points

Miscellaneous

Environmental: 10°F to 145°F (-12°C to 62°C)
LCD heater kit (P/N 2600-582) recommended when
temperatures routinely fall below 10°F (-12°C)
ADA Compliant handset kit (P/N 1807-012) available on
surface mount only
Camera Ready: Optional B&W or Color CCTV camera*
*may require additional CCTV equipment
Shipping weight approximately 15-20 Lbs (6.8-9 kg)



FCC (US) DUF6VT-12874-0T-0
DOC (CAN) 1736 4507 A



Access Control Solutions since 1948

Distributed by:

MEMBER:



DOORKING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.
Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com
© 2012 All Rights Reserved. Product specifications may change without notice.
Rev. 9/12