

SUBMITTAL	ITEM TYPE	TITLE
GATE AUTOMATION	LOOP DETECTOR	EMX ULT-PLG ULTRALOOP



FEATURES:

HI-INTENSITY RED/GREEN TRAFFIC LIGHT

- 10 LEVELS OF SENSITIVITY
- 4 LOOP FREQUENCIES
 - LOW, MED-LOW, MED-HI, HIGH
- LOOP INDUCTANCE: 20-2000 μ H (Q FACTOR > 5)
- AUTOMATIC TUNING

SPECIFICATIONS	
Sensitivity	10 levels, 0-9
UltraMETER™ display	Indicates optimum sensitivity level, 0-9 diagnostic aid
Loop frequency	4 settings (low, med-low, med-hi, high)
Loop inductance	20...2000 μ H (Q factor > 5)
Grounded loop	Isolation transformer allows operation with poor quality loops
Automatic tuning	Detector tunes to loop on power-up and following frequency count function
Environmental tracking	Automatic compensation
Surge protection	Loop circuitry protected by surge suppressors
Detect output	Solid-state (open collector)
Output B	Solid-state (open collector)
Output B inverted	Solid-state (open collector)
Power / loop fault indicator	Green LED
Detect / frequency count indicator	Red LED
Detect-on-Stop	Requires vehicle to stop for a minimum of 1 second (1-2s typical)
ASB (Automatic Sensitivity Boost)	Increases sensitivity after initial detection to prevent dropout due to high-bed vehicles
Power	12VDC...24VDC
Operating current	15 mA
Operating temperature	-40°C...82°C (-40°F...180°F) 0...95% relative humidity
Dimensions (L x W x H)	3.0"(76mm) x 0.9"(22mm) x 2.75"(70mm)
Weight	0.15 lbs. (68 g)
Connector	10-pin female



2525 NE COLUMBIA BLVD PORTLAND, OR 97211
 SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1.800.813.6772

"SERVING THE PORTLAND/ VANCOUVER METRO AREA SINCE 1984"