

SUBMITTAL	ITEM TYPE	TITLE	LAST UPDATED
SAFETY DEVICE	EDGE CONTACT SENSOR	EMX SAFETY EDGES	JULY 2024

MONITORED WIRELESS EDGE WEL-200 SERIES

UL325-2016 COMPLIANT

NC, 10K & PULSE MONITORING

200 FT. OPERATING RANGE

CONNECT UP TO 4 SAFETY TRANSMITTERS

NEMA 4X ENCLOSURE

100 MS RESPONSE TIME

OPERATING TEMPERATURE -40° ...60°C (-40° ...140°F)



WEL-200T

POWER/FAULT INDICATOR

GREEN TRANSMIT/ STATUS LED

POWER PROTECTION

THERMAL FUSE

POWER SUPPLY

3-3.6 VDC (2x AA batteries)

(ANSI 15-LF, IEC-FR14505 (FR6))

BATTERY LIFE

2 YEARS AT 25°C

DIMENSIONS (L X W X H)

180MM (7") X 32MM (1.3") X 67MM (2.6")

CONNECTIONS

2 TERMINALS (18-26AG)

CODE COMPLIANCE

GATE EDGE CONTACT SENSORS ARE REQUIRED

WHEREVER A PINCH POINT IS CREATED BY A MOVING GATE.

A PINCH POINT IS CONSIDERED TO BE ANY OBJECT BETWEEN

4" AND 16" AWAY FROM ANY MOVING PORTION OF THE

GATE.



WEL-200R

POWER/FAULT INDICATOR

RED POWER LED/ GREEN CHANNEL LED

CHANNEL STATUS INDICATOR

GREEN LED

CHANNEL MODE SELECTION SWITCH

ASSIGN EACH CHANNEL TO OPEN/ CLOSE FUNCTION

OUTPUTS

- OPEN relay: Form C contacts (NO, COM, NC)
- CLOSE relay: Form C contacts (NO, COM, NC)
- OPEN pulsed: Open collector transistor output (opto-isolated)
- CLOSE pulsed: Open collector transistor output (opto-isolated)

RESISTIVE TERMINATION

10K ohm ACROSS NO CONTACT
(JUMPER SELECTABLE)

POWER PROTECTION

THERMAL FUSE/ MOV

POWER SUPPLY

12-24 VAC/VDC

CURRENT DRAW

50 mA

DIMENSIONS (L X W X H)

140MM(5.5") x 34MM (1.3") x 90MM (3.5")

CONNECTIONS

12 TERMINALS (18-26AWG)



2525 NE COLUMBIA BLVD | PORTLAND, OR 97211
SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1-888.813.6772

"SERVING THE PORTLAND/VANCOUVER METRO AREA SINCE 1984"