

SUBMITTAL	ITEM TYPE	TITLE
GATE AUTOMATION	PHOTO EYES	FAAC 7851 XP30

SPECIFICATIONS:

- MAXIMUM DISTANCE:
 - 100 FT. (30 M)
- POWER SUPPLY VOLTAGE:
 - 24 AC OR DC
- ABSORBED CURRENT:
 - RX (30 mA), TX (20 mA)
- CONTACT RATINGS:
 - 60 VA / 24 W
- ALIGNMENT:
 - AUTOMATIC
- AUTO-ALIGNMENT ANGLE:
 - 7 DEGREES - 13.5 DEGREES
- OUTPUT TYPE:
 - RELAY - N.C./N.O.
- PROTECTION CLASS:
 - IP54
- OPERATING TEMPERATURES:
 - -4 DEGREES ~ 131 DEGREES
- DIMENSIONS (LxHxD):
 - 2.16" x 3" x 0.82"



FEATURES:

- UL 325 COMPLIANT WHEN USED WITH FAAC CONTROL BOARDS
- PLASTIC BODY WITH MOULDED FRONT SEAL COVER AND CLOSED-CELL CABLE ROUTING AREA SEAL
- PROTECTS AGAINST INTERFERENCE FROM EXTERNAL LIGHT SOURCES
- 4 CHANNEL RELAY SELECTION, ALLOWING INSTALLATION OF UP TO 4 SEPARATE PHOTOCELL PAIRS
- WALL-MOUNTED INSTALLATION OR FLUSH/COLUMN-MOUNTED INSTALLATION WITH ADAPTER



2525 NE COLUMBIA BLVD PORTLAND, OR 97211
 SERVICE 503.595.4716 | INSIDE SALES 503.946.1261 | TOLL FREE 1.800.813.6772

"SERVING THE PORTLAND/ VANCOUVER METRO AREA SINCE 1984"