



ERITECH® Galvanized Ground Rods - North & Latin America

In a grounding system, the ground electrode provides the physical connection to the earth and is the instrument used to dissipate current into it. There are two main types of electrodes.

“Natural” electrodes are intrinsic to the facility and include metal underground water pipe, the metal frame of the building (if effectively grounded), and reinforcing bar in concrete foundations.

“Made” electrodes are installed specifically to improve the performance of the grounding system and include wire meshes, metallic plates, buried copper conductor and rods or pipe driven into the ground.



The ground rod is the most widely used grounding electrode. ERICO is one of the leading manufacturers of ground rods and offers a complete line of rods and accessories to meet the needs of every user.

Features

- Meet EEC-NEMA TDJ-30 and are REA listed
- Zinc-coated exteriors are hot-dip galvanized for solid protection against corrosion in accordance with ASTM specification A153-78
- Surfaces are rigidly inspected to eliminate seams, slivers and other defects
- 15 year service life in most soils

Applications

A complete line of galvanized ground rods and accessories to meet the needs of every user.

More Information

	
Pointed Galvanized Ground Rod	Compression Coupler

Pointed Galvanized Ground Rods

--	--	--	--	--	--

Part No.	Description	Diameter (in)	Length (ft)	Standard Package	Weight per 100
811350		1/2	5	5	344
811360		1/2	6	5	413
811380		1/2	8	5	550
815860		5/8	6	5	546
815880	REA	5/8	8	5	763
815800		5/8	10	5	966
813480	REA	3/4	8	5	1092
813400		3/4	10	5	1388
814400		1	10	5	2716

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

WARRANTY

ERICO products are warranted to be free from defects in material and workmanship at the time of shipment. NO OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), SHALL EXIST IN CONNECTION WITH THE SALE OR USE OF ANY ERICO PRODUCTS. Claims for errors, shortages, defects or nonconformities ascertainable upon inspection must be made in writing within 5 days after Buyer's receipt of products. All other claims must be made in writing to ERICO within 6 months from the date of shipment or transport. Products claimed to be nonconforming or defective must, upon ERICO's prior written approval in accordance with its standard terms and procedures governing returns, promptly be returned to ERICO for inspection. Claims not made as provided above and within the applicable time period will be barred. ERICO shall in no event be responsible if the products have not been stored or used in accordance with its specifications and recommended procedures. ERICO will, at its option, either repair or replace nonconforming or defective products for which it is responsible or return the purchase price to the Buyer. THE FOREGOING STATES BUYER'S EXCLUSIVE REMEDY FOR ANY BREACH OF ERICO WARRANTY AND FOR ANY CLAIM, WHETHER SOUNDING IN CONTRACT, TORT OR NEGLIGENCE, FOR LOSS OR INJURY CAUSED BY THE SALE OR USE OF ANY PRODUCT.

LIMITATION OF LIABILITY

ERICO excludes all liability except such liability that is directly attributable to the willful or gross negligence of ERICO's employees. Should ERICO be held liable its liability shall in no event exceed the total purchase price under the contract. ERICO SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS OF BUSINESS OR PROFITS, DOWNTIME OR DELAY, LABOR, REPAIR OR MATERIAL COSTS OR ANY SIMILAR OR DISSIMILAR CONSEQUENTIAL LOSS OR DAMAGE INCURRED BY BUYER.

Due to a policy of continued product development, specifications are subject to change without notice.

Copyright © 2011 ERICO International Corporation.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.



Economy Ground Rod Clamps for Ground Rods and Rebar



TYPE CGRC

Features

- Manufactured from bronze alloy
- Supplied with stainless steel hardware
- UL 467 Listed for direct burial and CSA Certified

Benefits

- Ensures maximum strength and durability
- Suitable for direct burial in earth or concrete
- Ensures a safe and reliable grounding connection



Catalog Number	Ground Rod		Rebar		Dimensions - in. (mm)		
	Size	Wire Range	Size	Wire Range	W	H	L
CGRC-38 +	3/8	4-10	#3	4-10	0.472 (12.0)	1.025 (26.0)	0.695 (17.7)
CGRC-48	1/2	2-10	#4	2-10	0.615 (15.6)	1.220 (31.0)	0.775 (19.7)
CGRC-58	5/8	2-10	#5	4-10	0.625 (15.9)	1.370 (34.8)	0.930 (23.6)
CGRC-68	3/4	2-10	#6	4-10	0.645 (16.4)	1.543 (39.2)	1.118 (28.4)

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

+ CGRC-38 is not UL Listed

Tested to UL 467, UL File E34440