

5800MINI

Wireless Door/Window Contact

The 5800MINI provides all of the advantages of Honeywell's field-proven, quick-install 5800 Series wireless devices, with the addition of signal transmission and low-battery LED indicators. It virtually disappears when installed and blends with any décor, making it ideal for applications where aesthetics are critical such as ornate doors, casements and double-hung windows. The 5800MINI provides a single zone of protection and installs easily on doors or windows with the included double-sided adhesive tape.



FEATURES AND BENEFITS

- Signal transmission and low battery LED indicators:
 - Blue LED – Ensures optimal magnet placement
 - Green LED – Sensor is transmitting
 - Red LED – Low battery warning
- Compact and unobtrusive design—ideal when aesthetics count
- Easy-to-open case requires no special tools
- Case tamper protection
- Ideal for double-hung windows
- Available in both white and brown to match any décor

SPECIFICATIONS

Dimensions:

Sensor Dimensions: 1" W x 2.2" H x 0.25" D
(25.4mm x 55.9mm x 6.4mm)

Magnet Dimensions: 0.25" x 0.25" x 1"
(6.4mm x 6.4mm x 25.4mm)

Power Source: 3V Lithium battery (supplied)

Gap: 1" (25.4mm) max distance

Case Tamper Protection: Case

Operating Temperature: 32°F to 122°F
(0°C to 50°C)

Transmit Frequency: 345 MHz

Compatibility: Compatible with all 5800 Series Wireless devices

Agency Listings: FCC, IC

ORDERING

5800MINI	Wireless Door/Window Contact supplied with Lithium battery (White)
5800MINIBR	Wireless Door/Window Contact supplied with Lithium battery (Brown)

Honeywell Security and Fire

2 Corporate Center Dr. Suite 100

P.O. Box 9040

Melville, NY 11747

1.800.323.4576

www.honeywell.com