

SlideDriver™ II SD40

**Maximum security
combined with extreme
durability**

The most secure slide gate
operator with power to move
any gate, customizable for every
unique application.



Features:



Powerful:
Move gates up to 4,000 lb.



Tough:
Secure steel chassis and taper
resistant cover.



Reliable:
UPS models remain functional
during a power outage.



Programmable:
Configure for specific
site requirements.



Fast:
1-3 ft/s operating speed.
Emergency fast operate
at 3 ft/s.



Smart:
Integrated primary/secondary
controls and preprogrammed
relay settings.



All weather performance:
Wide temperature range
without heater.



Durable:
Decades long life and
low maintenance.



Made in USA:
Designed, tested and built
with in USA from globally
sourced materials



SlideDriver™ II SD40

Next Generation

Builds on a legacy of security and reliability with the new SmartTouch™ 725 controller



NEW!

powered by
SmartTouch 725

Technical Specifications

Model	SlideDriver II SD40
Duty Cycle	Continuous
Horsepower	1 hp; DC Option 2 hp
Drive	Hydraulic
Drive Wheels	Two 6 inch (15 cm) AdvanceDrive wheels
Rate of Travel	1 ft/s (30 cm/s)
Gate Length Max.	Limited only by weight
Gate Weight Max.	Up to 4,000 lb (1,814 kg)
Pull Force	300 lb (136 kg)
UPS Battery BackUp Cycles*	Select option SB-2-2J for DC configuration. Requires DC Power Supply DCPS-60, purchased separately.
Temperature Rating	-40° to 158° F (-40° to 70° C)
Single Phase Voltages	115/208-230V 60 Hz, 110/220V 50 Hz***
Three Phase Voltages	208-230/460V 60Hz, 220/380/440V 50Hz***
Included Accessories	One premium EMX IRB-MON photo eye, one 5-foot premium ASO edge sensor
Communication	BlueBUS, USB, Ethernet, RS-485, Bluetooth, OXI receiver
User Controls	SmartTouch 725 Controller with 70+ configurable settings. 32 character OLED display and 7 tactile buttons, or Bluetooth smartphone interface, for programming. SmartTouch 720 Available without Bluetooth or Ethernet.
Relays	8 Configurable relays: Two 250V 20A electromechanical relays and six 30VDC 2A solid state relays
Enclosure	N/A
Finish	Zinc plated with powder coating
ETL Listed (UL 325)	Usage Class I, II, III, IV
Warranty	5 year w/product registration

*The actual number of gate cycles available from battery power depends upon gate resistance to travel, cycle length, battery size, state of charge and health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.

***Refer to Installed Options on pricing for all 50Hz voltages, which are special order.



 **HySecurity**
a Nice company
support.hysecurity.com

Nice/HySecurity is an industry leader of automated gate and perimeter security solutions. The HySecurity brand provides high-quality, ultra-reliable industrial gate operators and crash-rated, Hostile Vehicle Mitigation (HVM) vehicle barriers designed to secure and protect critical infrastructure and facilities worldwide.

Nice

Niceforyou.com

©2023 Nice North America LLC. HySecurity is a registered trademark of Nice North America LLC. All rights reserved. All trademarks, logos and brand names are the property of their respective owners.

1058410786 Rev-A 04/2023 D1170

SmartTouch™ 720/725

Durable and configurable industrial controller

Designed for maximum cycles and long life,
the SmartTouch controller meets the needs
of the most secure applications.



Features:



Save operator configurations

And troubleshoot system via installer
smartphone app or USB.



Three configurable user relays

Plus SmartTouch I/O Expansion module for 5
additional relay outputs on non-VFD models or
(optional) 8 additional relay outputs on
VFD models.



OLED display

32 character OLED provides increased
readability for programming and
troubleshooting.



Hy5B 2.0 vehicle detector

4 ports for HySecurity Hy5B 2.0 vehicle
detectors, enabling advanced features like
automatic gate compensation and loop
diagnostics.



Compatible with Nice accessories

OXI receiver, ERA and INTI transmitters and
BlueBUS photo eyes.



SmartTouch 725 Installer App

For simplified setup and remote
diagnostics from your smartphone via
bluetooth connection.



Remote Monitoring

Remote monitoring and management
capability with embedded HyNet™



SmartTouch™ 720/725

For use with hydraulic operators



Additional Features

Adaptive Inherent Entrapment Sensor (IES)

Any impediment to gate travel is sensed by the system, stopping gate movement per UL 325 safety standards. The intelligent system monitors gate power then adapts the IES to trip at an adjustable threshold above normal power.

Integrated HyNet™ Technology

Provides remote management capabilities over ethernet: securely report gate system status, vehicle tailgating, gate hits, failure to operate, and more. All in real time to maintain perimeter security. Additionally, configure email alerts to communicate issues to installer, facility or security responders.

Technical Specifications

Model	SmartTouch 720	SmartTouch 725
Slide Compatible	SlideDriver™ II	
Temperature Rating	-40° to 158° F (-40° to 70° C)	
Operating Voltage	24 VDC	
Input Voltage	* See operator spec	
Maximum Current	* See operator spec	
Idle Current	* See operator spec	
Accessory Power	24VDC, 3A max total load.	
BlueBUS	Yes	
Board Dimensions	10w x 5.1h x 2.1d inches	
Communication	USB and RS-485 receiver	BlueBUS, USB, Ethernet, RS-485, Bluetooth, OXI receiver
User Controls	32 character OLED display and 7 tactile buttons	32 character OLED display and 7 tactile buttons, or Bluetooth smartphone interface, for programming.
Inputs	15 inputs including 5 control inputs, 2 dedicated entrapment sensor inputs, 3 user programmable inputs, a BlueBUS port, and 4 Hy5B vehicle detectors sockets. Optional I/O Expansion module for 8 additional user programmable inputs	
Relays	Three configurable user relays: Two 30VDC, 2A solid state. One 240VAC, 20A electromechanical; Optional I/O Expansion module for 8 additional relay outputs	
ETL Listed (UL 325)	Usage Class I, II, III, IV	
External Entrapment Sensor Options	Automatically configures to 4-wire pulsed or 10k resistive monitoring	
Warranty	5 year w/product registration	

Special Features

SmartTouch 725 Installer App

SmartTouch 725 installer app for full control from your phone

- Configure everything wirelessly from a smartphone interface.
- More than 70 user settings.
- Bluetooth and integrated HyNet Technology
- Built-in diagnostics and remote monitoring, management, and maintenance capabilities.



support.hysecurity.com

Nice/HySecurity is an industry leader of automated gate and perimeter security solutions.

The HySecurity brand provides high-quality, ultra-reliable industrial gate operators and crash-rated, Hostile Vehicle Mitigation (HVM) vehicle barriers designed to secure and protect critical infrastructure and facilities worldwide.

Niceforyou.com

©2023 Nice North America LLC. HySecurity is a registered trademark of Nice North America LLC. All rights reserved.

All trademarks, logos and brand names are the property of their respective owners.

1057910580 Rev-B 03/2023 D1167