

850LM / 860LM / 811LM / 813LM UNIVERSAL RECEIVERS AND COMMERCIAL REMOTE CONTROLS

Remote Solutions for Commercial Applications.

SMART

SECURITY+ 2.0® RECEIVER COMPATIBLE WITH COMMERCIAL REMOTE CONTROLS AS WELL AS ALL LIFTMASTER® SECURITY+ 2.0 REMOTE CONTROLS AND OPERATES ON NARROWBAND, TRI-BAND (310, 315 AND 390 MHZ) FREQUENCIES TO **VIRTUALLY ELIMINATE RF INTERFERENCE THAT CAN AFFECT PERFORMANCE.**

UNIVERSAL RECEIVERS

COMPACT DESIGN THAT FITS INTO MOST GATE AND COMMERCIAL DOOR OPERATORS.

WEATHER-RESISTANT VERSION (860LM) AVAILABLE FOR OUTDOOR MOUNTING REQUIREMENTS.

3 CHANNELS PROVIDING **EXPANDED REMOTE CONTROL CAPACITY AND/OR OPEN/CLOSE/STOP FUNCTIONALITY**

- CHANNEL 1 (50 REMOTES)
- CHANNEL 2 (20 REMOTES)
- CHANNEL 3 (20 REMOTES)

UNIVERSAL RADIO SOLUTION FOR RETROFITS OR UPDATES – WORKS WITH EXISTING GATE OPERATORS MANUFACTURED BY LIFTMASTER OR OTHERS. THIS RECEIVER IS NOT COMPATIBLE WITH MYQ® ENABLED GARAGE DOOR OPENERS.

COMMERCIAL REMOTE CONTROLS

1-BUTTON COMMERCIAL REMOTE CONTROL (811LM) AND 3-BUTTON COMMERCIAL REMOTE CONTROL (813LM)

PROVIDE CONVENIENT ACCESS TO GATED COMMUNITIES, INDUSTRIAL FACILITIES, AND COMMERCIAL SITES WITH A REMOTE CONTROL SOLUTION.


ALLOWS UP TO 4,096 CODES WITH 12-POSITION DIP PROGRAMMING.

3-BUTTON COMMERCIAL REMOTE CONTROL (813LM) DESIGNED WITH OPEN/CLOSE/STOP FUNCTIONALITY FOR COMMERCIAL DOOR OPERATOR APPLICATIONS.

KEY FEATURES

SECURITY ENCRYPTED CODE for extra dependability

MANAGE MULTIPLE ACCESS POINTS with a single receiver



TOTAL SOLUTION ACCESSORIES:

UNIVERSAL RADIO CONTROL PLUG-IN AC TRANSFORMER

Plug-in jack for easy installation.



85LM

RADIO CONTROL TRANSFORMER

24VAC transformer



95LM

REMOTE ANTENNA EXTENSION WITH MOUNTING KIT

Additional 15' and 25' coaxial cables to mount antenna away from metal for optimal range.



86LM / 86LMT

PRODUCT GUIDE

850LM / 860LM / 811LM / 813LM

UNIVERSAL RECEIVERS AND
COMMERCIAL REMOTE CONTROLS

LiftMaster®

MASTERFUL ENGINEERING.

COMPATIBILITY



- Universal Receivers are compatible with the following LiftMaster Remote Controls:

811LM 813LM 891LM 893LM
892LT 894LT 890MAX 893MAX
PPV3M | PPK3M | PPK3PHM
PPLV1-X | PPLK-X | PPLK1PH

POWER



RECEIVERS

- 12-24VDC or 12-24VAC
- Relay Outputs
- Output Channels
- 1 FORM C and 2 FORM A Relays


REMOTES

- Coin Cell 3V— CR2032 type

DIMENSIONS



- 850LM - 4.25" W x 2.9" H
- 860LM - 6.0" W x 4.2" H
- 811LM - 3.125" W x 1.75" H
- 813LM - 3.125" W x 1.75" H



STANDARD SPECS.

WARRANTY

- RECEIVERS: 1-Year Limited
- REMOTES: 1-Year Limited

RECEIVERS

OPERATING TEMPERATURE -31°F to 149°F
(-35°C to 65°C)

SHIPPING.

SHIPPING WEIGHTS (in lbs.)

850LM CARTON (1)

- Receiver
- Antenna
- (2) Velcro Strips
- Instruction Manual

0.44

860LM CARTON (1)

- Receiver
- Antenna
- (2) Screws
- Instruction Manual

0.93

811LM CARTON (1)

- Remote Control
- Visor Clip
- Instruction Manual

0.22

813LM CARTON (1)

- Remote Control
- Visor Clip
- Instruction Manual

0.13

STORAGE/SHIP TEMPERATURE RANGE

- 40°F to 185°F @ 50% Rh
- 40°C to 85°C @ 50% Rh

For Support Tools and Training Videos, Visit
LiftMasterTraining.com

For More Information, Visit
LiftMaster.com/AccessControl

Sales Support: **800.282.6225**
Technical Support Center: **800.528.2806**
LiftMasterDealer.CustHelp.com/App/Ask