


CAPXLV2

Smart Video Intercom - L
Section 28 13 00



DATA SHEET

Key Features

Unit Interface Capabilities

Scheduling Capabilities

Radio Receiver

Wireless Communication

Touchscreen/voice/mobile phone/PIN/card/transmitter/RFID tag

Yes

Built-In Security+ 2.0 Credentialed

Yes*

Specifications

Data Connectivity

Wi-Fi®/wired high-speed internet/DSL/Cellular via many 3rd party modems in the market

Voice Communication

Wi-Fi®/wired high-speed internet/DSL/Cellular via many 3rd party modems in the market

Calling Connectivity

VoIP (Phone.com)

Credential Communication

BLE myQ Mobile Credentials

Power Supply

120VAC to 24VDC transformer (included)

Programming (Database Management)

Cloud (myQ® Community)

Remote Programming (Database Management)

Yes

Realtime Event Monitoring (Email Notifications)

Yes

Software

myQ Community web portal

Wiegand Input Data Format

26 BIT, 30 BIT, 36 BIT (LiftMaster), 37 BIT (HID)

37 BIT (Transcore), 32 BIT (MiFare), and 56 BIT (LiftMaster Smart)

26 BIT

Wiegand Output Data Format

Local User Capacity Per Unit

50,000

Local Event History Per Unit

50,000

Max Number of Gates/Doors of Control (Each)

8

OSDP

4 Liftmaster Smart Readers via OSDP

Wiegand Input

4

Relay Output

8 relay mapping can be done using 'Advanced Configuration setting' on myQ Community web platform

Mounting Options

Surface/flush/gooseneck

Operating Temperature

-20°F to 130°F (-29°C to 54°C)

Display Type

10-inch full color touch screen with Picture-in-Picture

Display Resolution

720p high definition

Integrated Video Camera

Yes

Anti-Tamper Alarm

Yes

Warranty

2 years

Construction

Enclosure Material


Cast Metal, Powder Coated Black

LiftMaster

CAPXLV2

Smart Video Intercom - L
Section 28 13 00

DATA SHEET



Range

CAPXLV2 Feature	Wired	Wireless	Wire Type	Range
Power 120VAC to 24VDC transformer (from outlet to controller)	x		2 wire (14 AWG) 2 wire (16 AWG) 2 wire (18 AWG)	Up to 300 ft. Up to 200 ft. Up to 100 ft.
Wiegand accessory wiring	x		7 wire (18-22 AWG)	Up to 500 ft.
Relay output wiring	x		2 wire (18-24 AWG)	Up to 2500 ft.
Exit Request (REX)	x		2 wire (18-24 AWG)	Up to 500 ft.
Supervised Input	x		2 wire (18-24 AWG)	Up to 500 ft.
RJ-45 Internet	x		CAT5e or better 8 strand (24 AWG)	Up to 328 ft.
Wireless link to LiftMaster® Gate Operators		x	N/A	Up to 750 ft.**
Wi-Fi®		x	N/A	Up to 250 ft.

*When used with LiftMaster® Operators with Security+ 2.0® Radio

**When used with LiftMaster® Gate Operators mfg. after Nov. 2017